

CU-2Z52VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
1 room	16	1.60	-	-	-	-	1.60 (1.1-2.3)	2.0	430 (220-620)	3.72	2.60	-	-	-	-	2.60 (0.7-3.8)	3.3	730 (170-1150)	3.56
	20	2.00	-	-	-	-	2.00 (1.1-2.9)	2.5	540 (220-790)	3.70	3.20	-	-	-	-	3.20 (0.7-4.8)	4.0	890 (170-1450)	3.60
	25	2.50	-	-	-	-	2.50 (1.1-3.5)	3.1	690 (220-1020)	3.62	3.60	-	-	-	-	3.60 (0.7-5.5)	4.8	1070 (170-1740)	3.36
	35	3.50	-	-	-	-	3.50 (1.1-4.0)	4.6	1030 (220-1240)	3.40	4.50	-	-	-	-	4.50 (0.7-6.2)	5.7	1290 (170-1850)	3.49
	42	4.20	-	-	-	-	4.20 (1.1-4.5)	6.2	1380 (220-1520)	3.04	5.00	-	-	-	-	5.00 (1.1-6.4)	7.1	1590 (210-2220)	3.14
	50	5.00	-	-	-	-	5.00 (1.2-5.1)	7.6	1710 (230-1810)	2.92	5.30	-	-	-	-	5.30 (1.1-6.8)	7.5	1680 (210-2330)	3.15
2 rooms	16 + 16	1.60	1.60	-	-	-	3.20 (1.5-4.0)	3.0	680 (250-990)	4.71	2.60	2.60	-	-	-	5.20 (1.1-7.0)	5.2	1210 (210-1910)	4.30
	16 + 20	1.60	2.00	-	-	-	3.60 (1.5-4.5)	3.5	780 (250-1150)	4.62	2.40	3.00	-	-	-	5.40 (1.1-7.0)	5.4	1260 (210-1890)	4.29
	16 + 25	1.60	2.50	-	-	-	4.10 (1.5-5.2)	4.0	900 (250-1370)	4.56	2.20	3.40	-	-	-	5.60 (1.1-7.0)	5.7	1310 (210-1890)	4.27
	16 + 35	1.65	3.55	-	-	-	5.20 (1.5-6.0)	5.9	1350 (250-1620)	3.85	1.90	4.20	-	-	-	6.10 (1.1-7.0)	6.2	1430 (210-1890)	4.27
	16 + 42	1.45	3.75	-	-	-	5.20 (1.5-6.0)	5.9	1350 (250-1620)	3.85	1.70	4.40	-	-	-	6.10 (1.1-7.2)	6.2	1430 (210-1900)	4.27
	16 + 50	1.25	3.95	-	-	-	5.20 (1.5-6.0)	5.9	1350 (250-1620)	3.85	1.50	4.60	-	-	-	6.10 (1.1-7.2)	6.2	1430 (210-1900)	4.27
	20 + 20	2.00	2.00	-	-	-	4.00 (1.5-5.0)	4.0	890 (250-1310)	4.49	2.80	2.80	-	-	-	5.60 (1.1-7.0)	5.7	1310 (210-1870)	4.27
	20 + 25	2.00	2.50	-	-	-	4.50 (1.5-5.2)	4.5	1030 (250-1370)	4.37	2.60	3.20	-	-	-	5.80 (1.1-7.0)	5.9	1360 (210-1870)	4.26
	20 + 35	1.90	3.30	-	-	-	5.20 (1.5-6.0)	5.9	1350 (250-1620)	3.85	2.20	3.90	-	-	-	6.10 (1.1-7.2)	6.2	1430 (210-1900)	4.27
	20 + 42	1.70	3.50	-	-	-	5.20 (1.5-6.0)	5.9	1350 (250-1620)	3.85	1.95	4.15	-	-	-	6.10 (1.1-7.2)	6.2	1430 (210-1900)	4.27
	20 + 50	1.50	3.70	-	-	-	5.20 (1.5-6.0)	5.9	1350 (250-1620)	3.85	1.75	4.35	-	-	-	6.10 (1.1-7.2)	6.2	1430 (210-1900)	4.27
	25 + 25	2.60	2.60	-	-	-	5.20 (1.5-6.0)	5.9	1350 (250-1620)	3.85	3.05	3.05	-	-	-	6.10 (1.1-7.2)	6.2	1430 (210-1900)	4.27
	25 + 35	2.15	3.05	-	-	-	5.20 (1.5-6.0)	5.9	1350 (250-1620)	3.85	2.55	3.55	-	-	-	6.10 (1.1-7.2)	6.2	1430 (210-1900)	4.27
	25 + 42	1.95	3.25	-	-	-	5.20 (1.5-6.0)	5.9	1350 (250-1620)	3.85	2.30	3.80	-	-	-	6.10 (1.1-7.2)	6.2	1430 (210-1900)	4.27
	25 + 50	1.75	3.45	-	-	-	5.20 (1.5-6.0)	5.9	1350 (250-1620)	3.85	2.05	4.05	-	-	-	6.10 (1.1-7.2)	6.2	1430 (210-1900)	4.27
	35 + 35	2.60	2.60	-	-	-	5.20 (1.5-6.0)	5.9	1350 (250-1620)	3.85	3.05	3.05	-	-	-	6.10 (1.1-7.2)	6.2	1430 (210-1900)	4.27
35 + 42	2.35	2.85	-	-	-	5.20 (1.5-6.0)	5.9	1350 (250-1620)	3.85	2.75	3.35	-	-	-	6.10 (1.1-7.2)	6.2	1430 (210-1900)	4.27	

Note: At least two indoor units must be connected. When operating just one unit, minimum connected capacity must still be met, please refer Technical Manual for details.

CU-2Z52VBR: Free Multi Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
1 room	16	1.60	-	-	-	-	1.60 (1.1-2.3)	2.1	460 (220-650)	3.48	2.60	-	-	-	-	2.60 (0.7-3.8)	3.4	760 (170-1180)	3.42
	20	2.00	-	-	-	-	2.00 (1.1-2.9)	2.6	570 (220-820)	3.51	3.20	-	-	-	-	3.20 (0.7-4.8)	4.1	920 (170-1480)	3.48
	25	2.50	-	-	-	-	2.50 (1.1-3.5)	3.3	720 (220-1050)	3.47	3.60	-	-	-	-	3.60 (0.7-5.5)	4.9	1100 (170-1770)	3.27
	35	3.50	-	-	-	-	3.50 (1.1-4.0)	4.8	1060 (220-1270)	3.30	4.50	-	-	-	-	4.50 (0.7-6.2)	5.9	1320 (170-1880)	3.41
	42	4.20	-	-	-	-	4.20 (1.1-4.5)	6.4	1410 (220-1550)	2.98	5.00	-	-	-	-	5.00 (1.1-6.4)	7.2	1620 (210-2250)	3.09
	50	5.00	-	-	-	-	5.00 (1.2-5.1)	7.7	1740 (230-1840)	2.87	5.30	-	-	-	-	5.30 (1.1-6.8)	7.6	1710 (210-2360)	3.10
2 rooms	16 + 16	1.60	1.60	-	-	-	3.20 (1.5-4.0)	3.3	740 (250-1050)	4.32	2.60	2.60	-	-	-	5.20 (1.1-7.0)	5.5	1270 (210-1970)	4.09
	16 + 20	1.60	2.00	-	-	-	3.60 (1.5-4.5)	3.7	840 (250-1210)	4.29	2.40	3.00	-	-	-	5.40 (1.1-7.0)	5.7	1320 (210-1950)	4.09
	16 + 25	1.60	2.50	-	-	-	4.10 (1.5-5.2)	4.3	960 (250-1430)	4.27	2.20	3.40	-	-	-	5.60 (1.1-7.0)	5.9	1370 (210-1950)	4.09
	16 + 35	1.65	3.55	-	-	-	5.20 (1.5-6.0)	6.1	1410 (250-1680)	3.69	1.90	4.20	-	-	-	6.10 (1.1-7.0)	6.4	1490 (210-1950)	4.09
	16 + 42	1.45	3.75	-	-	-	5.20 (1.5-6.0)	6.1	1410 (250-1680)	3.69	1.70	4.40	-	-	-	6.10 (1.1-7.2)	6.4	1490 (210-1960)	4.09
	16 + 50	1.25	3.95	-	-	-	5.20 (1.5-6.0)	6.1	1410 (250-1680)	3.69	1.50	4.60	-	-	-	6.10 (1.1-7.2)	6.4	1490 (210-1960)	4.09
	20 + 20	2.00	2.00	-	-	-	4.00 (1.5-5.0)	4.2	950 (250-1370)	4.21	2.80	2.80	-	-	-	5.60 (1.1-7.0)	5.9	1370 (210-1930)	4.09
	20 + 25	2.00	2.50	-	-	-	4.50 (1.5-5.2)	3.5	810 (250-1430)	5.56	2.60	3.20	-	-	-	5.80 (1.1-7.0)	6.1	1420 (210-1930)	4.08
	20 + 35	1.90	3.30	-	-	-	5.20 (1.5-6.0)	6.1	1410 (250-1680)	3.69	2.20	3.90	-	-	-	6.10 (1.1-7.2)	6.4	1490 (210-1960)	4.09
	20 + 42	1.70	3.50	-	-	-	5.20 (1.5-6.0)	6.1	1410 (250-1680)	3.69	1.95	4.15	-	-	-	6.10 (1.1-7.2)	6.4	1490 (210-1960)	4.09

CU-2Z52VBR: Free Multi Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION									
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP	
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E					
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
2 rooms	20 + 50	1.50	3.70	-	-	-	5.20 (1.5-6.0)	6.1	1410 (250-1680)	3.69	1.75	4.35	-	-	-	6.10 (1.1-7.2)	6.4	1490 (210-1960)	4.09
	25 + 25	2.60	2.60	-	-	-	5.20 (1.5-6.0)	6.1	1410 (250-1680)	3.69	3.05	3.05	-	-	-	6.10 (1.1-7.2)	6.4	1490 (210-1960)	4.09
	25 + 35	2.15	3.05	-	-	-	5.20 (1.5-6.0)	6.1	1410 (250-1680)	3.69	2.55	3.55	-	-	-	6.10 (1.1-7.2)	6.4	1490 (210-1960)	4.09
	25 + 42	1.95	3.25	-	-	-	5.20 (1.5-6.0)	6.1	1410 (250-1680)	3.69	2.30	3.80	-	-	-	6.10 (1.1-7.2)	6.4	1490 (210-1960)	4.09
	25 + 50	1.75	3.45	-	-	-	5.20 (1.5-6.0)	6.1	1410 (250-1680)	3.69	2.05	4.05	-	-	-	6.10 (1.1-7.2)	6.4	1490 (210-1960)	4.09
	35 + 35	2.60	2.60	-	-	-	5.20 (1.5-6.0)	6.1	1410 (250-1680)	3.69	3.05	3.05	-	-	-	6.10 (1.1-7.2)	6.4	1490 (210-1960)	4.09
	35 + 42	2.35	2.85	-	-	-	5.20 (1.5-6.0)	6.1	1410 (250-1680)	3.69	2.75	3.35	-	-	-	6.10 (1.1-7.2)	6.4	1490 (210-1960)	4.09

Note: At least two indoor units must be connected. When operating just one unit, minimum connected capacity must still be met, please refer Technical Manual for details.

CU-3Z54VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W	
1 room	16	1.60	-	-	-	1.60 (1.3-2.3)	2.0	420 (250-660)	3.81	2.60	-	-	-	-	2.60 (1.2-3.2)	3.0	640 (290-1000)	4.06
	20	2.00	-	-	-	2.00 (1.8-2.9)	2.5	520 (340-830)	3.85	3.20	-	-	-	-	3.20 (1.2-4.1)	3.7	780 (290-1270)	4.10
	25	2.50	-	-	-	2.50 (1.8-2.9)	2.9	650 (340-830)	3.85	3.60	-	-	-	-	3.60 (1.2-4.3)	4.5	980 (290-1270)	3.67
	35	3.50	-	-	-	3.50 (1.8-3.8)	4.2	960 (340-1380)	3.65	4.50	-	-	-	-	4.50 (1.2-5.8)	5.8	1270 (290-2140)	3.54
	42	4.20	-	-	-	4.20 (1.8-4.3)	6.0	1390 (340-2010)	3.02	5.60	-	-	-	-	5.60 (1.2-6.8)	7.5	1760 (290-2970)	3.18
	50	5.00	-	-	-	5.00 (1.9-5.4)	7.3	1630 (340-2150)	3.07	6.80	-	-	-	-	6.80 (1.2-6.9)	10.4	2350 (290-2840)	2.89
2 rooms	16 + 16	1.60	1.60	-	-	3.20 (1.8-6.2)	3.0	630 (330-2130)	5.08	2.60	2.60	-	-	-	5.20 (1.4-7.0)	5.9	1340 (340-2070)	3.88
	16 + 20	1.60	2.00	-	-	3.60 (1.8-6.2)	3.5	770 (330-2090)	4.68	2.58	3.22	-	-	-	5.80 (1.4-7.0)	6.7	1520 (330-2030)	3.82
	16 + 25	1.60	2.50	-	-	4.10 (1.8-6.2)	4.1	920 (330-2090)	4.46	2.42	3.78	-	-	-	6.20 (1.4-7.0)	7.2	1650 (330-2030)	3.76
	16 + 35	1.60	3.50	-	-	5.10 (1.8-6.3)	5.9	1350 (330-2100)	3.78	2.20	4.80	-	-	-	7.00 (1.4-7.3)	8.2	1900 (290-2130)	3.68
	16 + 42	1.49	3.91	-	-	5.40 (1.9-6.4)	6.6	1500 (350-2140)	3.60	1.93	5.07	-	-	-	7.00 (1.4-7.3)	8.2	1890 (310-2120)	3.70
	16 + 50	1.31	4.09	-	-	5.40 (1.9-6.8)	5.8	1320 (340-2080)	4.09	1.70	5.30	-	-	-	7.00 (1.4-8.0)	7.5	1710 (270-2230)	4.09
	20 + 20	2.00	2.00	-	-	4.00 (1.8-6.2)	4.0	890 (330-2050)	4.49	3.20	3.20	-	-	-	6.40 (1.4-7.0)	7.5	1710 (320-2030)	3.74
	20 + 25	2.00	2.50	-	-	4.50 (1.8-6.2)	4.8	1080 (330-2050)	4.17	3.02	3.78	-	-	-	6.80 (1.4-7.0)	8.0	1840 (290-2030)	3.70
	20 + 35	1.96	3.44	-	-	5.40 (1.8-6.3)	6.4	1470 (330-2060)	3.67	2.55	4.45	-	-	-	7.00 (1.4-7.3)	8.2	1890 (280-2120)	3.70
	20 + 42	1.74	3.66	-	-	5.40 (1.9-6.4)	6.4	1470 (350-2100)	3.67	2.26	4.74	-	-	-	7.00 (1.4-7.3)	8.0	1850 (300-2080)	3.78
	20 + 50	1.54	3.86	-	-	5.40 (1.9-6.8)	5.6	1280 (340-2080)	4.22	2.00	5.00	-	-	-	7.00 (1.4-8.0)	7.4	1700 (270-2230)	4.12
	25 + 25	2.50	2.50	-	-	5.00 (1.8-6.2)	5.8	1320 (330-2050)	3.79	3.50	3.50	-	-	-	7.00 (1.4-7.2)	8.2	1900 (290-2100)	3.68
	25 + 35	2.25	3.15	-	-	5.40 (1.9-6.3)	6.4	1470 (350-2060)	3.67	2.92	4.08	-	-	-	7.00 (1.4-7.3)	8.2	1890 (280-2120)	3.70
	25 + 42	2.01	3.39	-	-	5.40 (1.9-6.4)	6.4	1470 (350-2100)	3.67	2.61	4.39	-	-	-	7.00 (1.4-7.3)	8.0	1850 (280-2080)	3.78
	25 + 50	1.80	3.60	-	-	5.40 (1.9-6.8)	5.6	1280 (340-2080)	4.22	2.33	4.67	-	-	-	7.00 (1.4-8.0)	7.4	1700 (240-2230)	4.12
	35 + 35	2.70	2.70	-	-	5.40 (1.9-6.4)	6.3	1430 (350-2060)	3.78	3.50	3.50	-	-	-	7.00 (1.4-7.5)	8.0	1840 (270-2140)	3.80
	35 + 42	2.45	2.95	-	-	5.40 (1.9-6.5)	6.3	1430 (350-2110)	3.78	3.18	3.82	-	-	-	7.00 (1.4-7.5)	7.9	1830 (260-2140)	3.83
	35 + 50	2.22	3.18	-	-	5.40 (1.9-6.9)	5.6	1280 (360-2080)	4.22	2.88	4.12	-	-	-	7.00 (1.4-8.0)	7.4	1680 (240-2160)	4.17
42 + 42	2.70	2.70	-	-	5.40 (1.9-6.5)	6.3	1430 (350-2110)	3.78	3.50	3.50	-	-	-	7.00 (1.4-7.6)	7.8	1790 (260-2170)	3.91	
42 + 50	2.47	2.93	-	-	5.40 (1.9-6.9)	5.6	1280 (360-2080)	4.22	3.20	3.80	-	-	-	7.00 (1.4-8.0)	7.4	1680 (240-2160)	4.17	
3 rooms	16 + 16 + 16	1.60	1.60	1.60	-	4.80 (1.8-7.2)	4.2	930 (360-2140)	5.16	2.33	2.33	2.33	-	-	6.99 (1.5-8.1)	6.9	1550 (290-2270)	4.51
	16 + 16 + 20	1.66	1.66	2.08	-	5.40 (1.8-7.3)	5.1	1120 (360-2180)	4.82	2.15	2.15	2.70	-	-	7.00 (1.6-9.0)	6.8	1540 (320-2630)	4.55
	16 + 16 + 25	1.52	1.52	2.36	-	5.40 (1.9-7.2)	5.1	1120 (390-2090)	4.82	1.96	1.96	3.08	-	-	7.00 (1.6-9.0)	6.8	1540 (320-2630)	4.55
	16 + 16 + 35	1.29	1.29	2.82	-	5.40 (1.9-7.2)	5.1	1120 (390-2050)	4.82	1.67	1.67	3.66	-	-	7.00 (1.6-9.0)	6.7	1520 (340-2610)	4.61
	16 + 16 + 42	1.17	1.17	3.06	-	5.40 (1.8-7.3)	5.1	1120 (390-2090)	4.82	1.51	1.51	3.98	-	-	7.00 (1.6-9.0)	6.7	1510 (310-2560)	4.64
	16 + 16 + 50	1.05	1.05	3.30	-	5.40 (1.8-7.3)	4.7	1050 (420-1920)	5.14	1.37	1.37	4.26	-	-	7.00 (1.6-9.0)	6.2	1410 (330-2410)	4.96
	16 + 20 + 20	1.54	1.93	1.93	-	5.40 (1.9-7.2)	5.1	1120 (390-2090)	4.82	2.00	2.50	2.50	-	-	7.00 (1.6-9.0)	6.8	1530 (310-2620)	4.58
	16 + 20 + 25	1.42	1.77	2.21	-	5.40 (1.9-7.2)	5.1	1120 (390-2090)	4.82	1.84	2.30	2.86	-	-	7.00 (1.6-9.0)	6.8	1530 (310-2620)	4.58
	16 + 20 + 35	1.22	1.52	2.66	-	5.40 (1.9-7.2)	5.1	1120 (390-2010)	4.82	1.58	1.97	3.45	-	-	7.00 (1.6-9.0)	6.7	1510 (340-2560)	4.64
16 + 20 + 42	1.11	1.38	2.91	-	5.40 (1.8-7.3)	5.1	1120 (390-2090)	4.82	1.44	1.79	3.77	-	-	7.00 (1.6-9.0)	6.7	1510 (310-2550)	4.64	

CU-3Z54VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
3 rooms	16 + 20 + 50	1.00	1.26	3.14	-	-	5.40 (1.8-7.3)	4.7	1050 (420-1880)	5.14	1.30	1.63	4.07	-	-	7.00 (1.6-9.0)	6.2	1410 (340-2400)	4.96
	16 + 25 + 25	1.30	2.05	2.05	-	-	5.40 (1.9-7.2)	5.1	1120 (390-2090)	4.82	1.70	2.65	2.65	-	-	7.00 (1.6-9.0)	6.8	1530 (310-2620)	4.58
	16 + 25 + 35	1.14	1.78	2.48	-	-	5.40 (1.8-7.3)	5.1	1120 (390-2090)	4.82	1.47	2.30	3.23	-	-	7.00 (1.6-9.0)	6.7	1510 (340-2560)	4.64
	16 + 25 + 42	1.04	1.63	2.73	-	-	5.40 (1.8-7.3)	5.1	1120 (390-2090)	4.82	1.35	2.11	3.54	-	-	7.00 (1.6-9.0)	6.7	1510 (310-2550)	4.64
	16 + 25 + 50	0.95	1.48	2.97	-	-	5.40 (1.8-7.3)	4.7	1050 (420-1880)	5.14	1.23	1.92	3.85	-	-	7.00 (1.6-9.0)	6.2	1410 (340-2400)	4.96
	16 + 35 + 35	1.00	2.20	2.20	-	-	5.40 (1.8-7.3)	4.9	1090 (390-2050)	4.95	1.30	2.85	2.85	-	-	7.00 (1.6-9.0)	6.6	1500 (320-2530)	4.67
	16 + 35 + 42	0.93	2.03	2.44	-	-	5.40 (1.8-7.3)	4.9	1090 (390-2050)	4.95	1.20	2.63	3.17	-	-	7.00 (1.6-9.0)	6.6	1490 (320-2520)	4.70
	20 + 20 + 20	1.80	1.80	1.80	-	-	5.40 (1.9-7.2)	5.1	1120 (390-2050)	4.82	2.33	2.33	2.33	-	-	6.99 (1.6-9.0)	6.8	1530 (310-2610)	4.57
	20 + 20 + 25	1.66	1.66	2.08	-	-	5.40 (1.9-7.2)	5.1	1120 (390-2050)	4.82	2.15	2.15	2.70	-	-	7.00 (1.6-9.0)	6.8	1530 (310-2610)	4.58
	20 + 20 + 35	1.44	1.44	2.52	-	-	5.40 (1.9-7.2)	5.1	1120 (390-2010)	4.82	1.87	1.87	3.26	-	-	7.00 (1.6-9.0)	6.7	1510 (340-2550)	4.64
	20 + 20 + 42	1.32	1.32	2.76	-	-	5.40 (1.8-7.3)	4.9	1090 (390-2050)	4.95	1.71	1.71	3.58	-	-	7.00 (1.6-9.0)	6.6	1500 (320-2540)	4.67
	20 + 20 + 50	1.20	1.20	3.00	-	-	5.40 (1.8-7.3)	4.7	1050 (420-1880)	5.14	1.56	1.56	3.88	-	-	7.00 (1.6-9.0)	6.2	1400 (340-2390)	5.00
	20 + 25 + 25	1.54	1.93	1.93	-	-	5.40 (1.9-7.2)	5.1	1120 (390-2050)	4.82	2.00	2.50	2.50	-	-	7.00 (1.6-9.0)	6.8	1530 (310-2610)	4.58
	20 + 25 + 35	1.35	1.69	2.36	-	-	5.40 (1.9-7.2)	5.1	1120 (390-2010)	4.82	1.75	2.19	3.06	-	-	7.00 (1.6-9.0)	6.7	1510 (340-2550)	4.64
	20 + 25 + 42	1.24	1.55	2.61	-	-	5.40 (1.8-7.3)	4.9	1090 (390-2050)	4.95	1.61	2.01	3.38	-	-	7.00 (1.6-9.0)	6.6	1500 (320-2540)	4.67
	20 + 25 + 50	1.14	1.42	2.84	-	-	5.40 (1.8-7.3)	4.7	1050 (420-1880)	5.14	1.47	1.84	3.69	-	-	7.00 (1.6-9.0)	6.2	1400 (340-2390)	5.00
	20 + 35 + 35	1.20	2.10	2.10	-	-	5.40 (1.8-7.3)	4.9	1090 (390-2010)	4.95	1.56	2.72	2.72	-	-	7.00 (1.6-9.0)	6.6	1490 (320-2520)	4.70
	25 + 25 + 25	1.80	1.80	1.80	-	-	5.40 (1.9-7.2)	5.1	1120 (390-2050)	4.82	2.33	2.33	2.33	-	-	6.99 (1.6-9.0)	6.8	1530 (310-2610)	4.57
	25 + 25 + 35	1.59	1.59	2.22	-	-	5.40 (1.9-7.2)	5.1	1120 (390-2010)	4.82	2.06	2.06	2.88	-	-	7.00 (1.6-9.0)	6.7	1510 (310-2550)	4.64
	25 + 25 + 42	1.47	1.47	2.46	-	-	5.40 (1.8-7.3)	4.9	1090 (390-2050)	4.95	1.90	1.90	3.20	-	-	7.00 (1.6-9.0)	6.6	1500 (680-2540)	4.67
25 + 35 + 35	1.42	1.99	1.99	-	-	5.40 (1.8-7.3)	4.9	1090 (390-2010)	4.95	1.84	2.58	2.58	-	-	7.00 (1.6-9.0)	6.6	1490 (680-2520)	4.70	

Note: At least two indoor units must be connected. When operating just one unit, minimum connected capacity must still be met, please refer Technical Manual for details.

CU-3Z54VBR: Free Multi Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
1 room	16	1.60	-	-	-	-	1.60 (1.3-2.3)	2.2	450 (250-690)	3.56	2.60	-	-	-	-	2.60 (1.2-3.2)	3.2	700 (290-1060)	3.71
	20	2.00	-	-	-	-	2.00 (1.8-2.9)	2.6	550 (340-860)	3.64	3.20	-	-	-	-	3.20 (1.2-4.1)	3.9	840 (290-1330)	3.81
	25	2.50	-	-	-	-	2.50 (1.8-2.9)	3.1	680 (340-860)	3.68	3.60	-	-	-	-	3.60 (1.2-4.3)	4.7	1040 (290-1330)	3.46
	35	3.50	-	-	-	-	3.50 (1.8-3.8)	4.3	990 (340-1410)	3.54	4.50	-	-	-	-	4.50 (1.2-5.8)	6.1	1330 (290-2200)	3.38
	42	4.20	-	-	-	-	4.20 (1.8-4.3)	6.1	1420 (340-2040)	2.96	5.60	-	-	-	-	5.60 (1.2-6.8)	7.7	1820 (290-3030)	3.08
	50	5.00	-	-	-	-	5.00 (1.9-5.4)	7.3	1630 (340-2150)	3.07	6.80	-	-	-	-	6.80 (1.2-6.9)	10.4	2350 (290-2840)	2.89
2 rooms	16 + 16	1.60	1.60	-	-	-	3.20 (1.8-6.2)	3.2	690 (330-2190)	4.64	2.60	2.60	-	-	-	5.20 (1.4-7.0)	6.4	1460 (340-2190)	3.56
	16 + 20	1.60	2.00	-	-	-	3.60 (1.8-6.2)	3.7	830 (330-2150)	4.34	2.58	3.22	-	-	-	5.80 (1.4-7.0)	7.2	1640 (330-2150)	3.54
	16 + 25	1.60	2.50	-	-	-	4.10 (1.8-6.2)	4.4	980 (330-2150)	4.18	2.42	3.78	-	-	-	6.20 (1.4-7.0)	7.7	1770 (330-2150)	3.50
	16 + 35	1.60	3.50	-	-	-	5.10 (1.8-6.3)	6.2	1410 (330-2160)	3.62	2.20	4.80	-	-	-	7.00 (1.4-7.3)	8.8	2020 (290-2250)	3.47
	16 + 42	1.49	3.91	-	-	-	5.40 (1.9-6.4)	6.8	1560 (350-2200)	3.46	1.93	5.07	-	-	-	7.00 (1.4-7.3)	8.7	2010 (310-2240)	3.48
	16 + 50	1.31	4.09	-	-	-	5.40 (1.9-6.8)	6.0	1380 (340-2140)	3.91	1.70	5.30	-	-	-	7.00 (1.4-8.0)	7.9	1830 (270-2350)	3.83
	20 + 20	2.00	2.00	-	-	-	4.00 (1.8-6.2)	4.2	950 (330-2110)	4.21	3.20	3.20	-	-	-	6.40 (1.4-7.0)	7.9	1830 (320-2150)	3.50
	20 + 25	2.00	2.50	-	-	-	4.50 (1.8-6.2)	5.0	1140 (330-2110)	3.95	3.02	3.78	-	-	-	6.80 (1.4-7.0)	8.5	1960 (290-2150)	3.47
	20 + 35	1.96	3.44	-	-	-	5.40 (1.8-6.3)	6.7	1530 (330-2120)	3.53	2.55	4.45	-	-	-	7.00 (1.4-7.3)	8.7	2010 (280-2240)	3.48
	20 + 42	1.74	3.66	-	-	-	5.40 (1.9-6.4)	6.7	1530 (350-2160)	3.53	2.26	4.74	-	-	-	7.00 (1.4-7.3)	8.5	1970 (300-2200)	3.55
	20 + 50	1.54	3.86	-	-	-	5.40 (1.9-6.8)	5.9	1340 (340-2140)	4.03	2.00	5.00	-	-	-	7.00 (1.4-8.0)	7.9	1820 (270-2350)	3.85
	25 + 25	2.50	2.50	-	-	-	5.00 (1.8-6.2)	6.0	1380 (330-2110)	3.62	3.50	3.50	-	-	-	7.00 (1.4-7.2)	8.8	2020 (290-2220)	3.47
	25 + 35	2.25	3.15	-	-	-	5.40 (1.9-6.3)	6.7	1530 (350-2120)	3.53	2.92	4.08	-	-	-	7.00 (1.4-7.3)	8.7	2010 (280-2240)	3.48
	25 + 42	2.01	3.39	-	-	-	5.40 (1.9-6.4)	6.7	1530 (350-2160)	3.53	2.61	4.39	-	-	-	7.00 (1.4-7.3)	8.5	1970 (280-2200)	3.55
25 + 50	1.80	3.60	-	-	-	5.40 (1.9-6.8)	5.9	1340 (340-2140)	4.03	2.33	4.67	-	-	-	7.00 (1.4-8.0)	7.9	1820 (240-2350)	3.85	

CU-3Z54VBR: Free Multi Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
2 rooms	35 + 35	2.70	2.70	-	-	-	5.40 (1.9-6.4)	6.5	1490 (350-2120)	3.62	3.50	3.50	-	-	-	7.00 (1.4-7.5)	8.5	1960 (270-2260)	3.57
	35 + 42	2.45	2.95	-	-	-	5.40 (1.9-6.5)	6.5	1490 (350-2170)	3.62	3.18	3.82	-	-	-	7.00 (1.4-7.5)	8.5	1950 (260-2260)	3.59
	35 + 50	2.22	3.18	-	-	-	5.40 (1.9-6.9)	5.9	1340 (360-2140)	4.03	2.88	4.12	-	-	-	7.00 (1.4-8.0)	7.8	1800 (240-2280)	3.89
	42 + 42	2.70	2.70	-	-	-	5.40 (1.9-6.5)	6.5	1490 (350-2170)	3.62	3.50	3.50	-	-	-	7.00 (1.4-7.6)	8.3	1910 (260-2290)	3.66
	42 + 50	2.47	2.93	-	-	-	5.40 (1.9-6.9)	5.9	1340 (360-2140)	4.03	3.20	3.80	-	-	-	7.00 (1.4-8.0)	7.8	1800 (240-2280)	3.89
3 rooms	16 + 16 + 16	1.60	1.60	1.60	-	-	4.80 (1.8-7.2)	4.6	1020 (360-2230)	4.71	2.33	2.33	2.33	-	-	6.99 (1.5-8.1)	7.6	1730 (290-2450)	4.04
	16 + 16 + 20	1.66	1.66	2.08	-	-	5.40 (1.8-7.3)	5.5	1210 (360-2270)	4.46	2.15	2.15	2.70	-	-	7.00 (1.6-9.0)	7.6	1720 (320-2810)	4.07
	16 + 16 + 25	1.52	1.52	2.36	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2180)	4.46	1.96	1.96	3.08	-	-	7.00 (1.6-9.0)	7.6	1720 (320-2810)	4.07
	16 + 16 + 35	1.29	1.29	2.82	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2140)	4.46	1.67	1.67	3.66	-	-	7.00 (1.6-9.0)	7.5	1700 (340-2790)	4.12
	16 + 16 + 42	1.17	1.17	3.06	-	-	5.40 (1.8-7.3)	5.5	1210 (390-2180)	4.46	1.51	1.51	3.98	-	-	7.00 (1.6-9.0)	7.5	1690 (310-2740)	4.14
	16 + 16 + 50	1.05	1.05	3.30	-	-	5.40 (1.8-7.3)	5.1	1140 (420-2010)	4.74	1.37	1.37	4.26	-	-	7.00 (1.6-9.0)	7.0	1590 (330-2590)	4.40
	16 + 20 + 20	1.54	1.93	1.93	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2180)	4.46	2.00	2.50	2.50	-	-	7.00 (1.6-9.0)	7.6	1710 (310-2800)	4.09
	16 + 20 + 25	1.42	1.77	2.21	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2180)	4.46	1.84	2.30	2.86	-	-	7.00 (1.6-9.0)	7.6	1710 (310-2800)	4.09
	16 + 20 + 35	1.22	1.52	2.66	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2100)	4.46	1.58	1.97	3.45	-	-	7.00 (1.6-9.0)	7.5	1690 (340-2740)	4.14
	16 + 20 + 42	1.11	1.38	2.91	-	-	5.40 (1.8-7.3)	5.5	1210 (390-2180)	4.46	1.44	1.79	3.77	-	-	7.00 (1.6-9.0)	7.5	1690 (310-2730)	4.14
	16 + 20 + 50	1.00	1.26	3.14	-	-	5.40 (1.8-7.3)	5.1	1140 (420-1970)	4.74	1.30	1.63	4.07	-	-	7.00 (1.6-9.0)	7.0	1590 (340-2580)	4.40
	16 + 25 + 25	1.30	2.05	2.05	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2180)	4.46	1.70	2.65	2.65	-	-	7.00 (1.6-9.0)	7.6	1710 (310-2800)	4.09
	16 + 25 + 35	1.14	1.78	2.48	-	-	5.40 (1.8-7.3)	5.5	1210 (390-2180)	4.46	1.47	2.30	3.23	-	-	7.00 (1.6-9.0)	7.5	1690 (340-2740)	4.14
	16 + 25 + 42	1.04	1.63	2.73	-	-	5.40 (1.8-7.3)	5.5	1210 (390-2180)	4.46	1.35	2.11	3.54	-	-	7.00 (1.6-9.0)	7.5	1690 (310-2730)	4.14
	16 + 25 + 50	0.95	1.48	2.97	-	-	5.40 (1.8-7.3)	5.1	1140 (420-1970)	4.74	1.23	1.92	3.85	-	-	7.00 (1.6-9.0)	7.0	1590 (340-2580)	4.40
	16 + 35 + 35	1.00	2.20	2.20	-	-	5.40 (1.8-7.3)	5.3	1180 (390-2140)	4.58	1.30	2.85	2.85	-	-	7.00 (1.6-9.0)	7.4	1680 (320-2710)	4.17
	16 + 35 + 42	0.93	2.03	2.44	-	-	5.40 (1.8-7.3)	5.3	1180 (390-2140)	4.58	1.20	2.63	3.17	-	-	7.00 (1.6-9.0)	7.4	1670 (320-2700)	4.19
	20 + 20 + 20	1.80	1.80	1.80	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2140)	4.46	2.33	2.33	2.33	-	-	6.99 (1.6-9.0)	7.6	1710 (310-2790)	4.09
	20 + 20 + 25	1.66	1.66	2.08	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2140)	4.46	2.15	2.15	2.70	-	-	7.00 (1.6-9.0)	7.6	1710 (310-2790)	4.09
	20 + 20 + 35	1.44	1.44	2.52	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2100)	4.46	1.87	1.87	3.26	-	-	7.00 (1.6-9.0)	7.5	1690 (340-2730)	4.14
	20 + 20 + 42	1.32	1.32	2.76	-	-	5.40 (1.8-7.3)	5.3	1180 (390-2140)	4.58	1.71	1.71	3.58	-	-	7.00 (1.6-9.0)	7.4	1680 (320-2720)	4.17
	20 + 20 + 50	1.20	1.20	3.00	-	-	5.40 (1.8-7.3)	5.1	1140 (420-1970)	4.74	1.56	1.56	3.88	-	-	7.00 (1.6-9.0)	7.0	1580 (340-2570)	4.43
	20 + 25 + 25	1.54	1.93	1.93	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2140)	4.46	2.00	2.50	2.50	-	-	7.00 (1.6-9.0)	7.6	1710 (310-2790)	4.09
	20 + 25 + 35	1.35	1.69	2.36	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2100)	4.46	1.75	2.19	3.06	-	-	7.00 (1.6-9.0)	7.5	1690 (340-2730)	4.14
	20 + 25 + 42	1.24	1.55	2.61	-	-	5.40 (1.8-7.3)	5.3	1180 (390-2140)	4.58	1.61	2.01	3.38	-	-	7.00 (1.6-9.0)	7.4	1680 (320-2720)	4.17
20 + 25 + 50	1.14	1.42	2.84	-	-	5.40 (1.8-7.3)	5.1	1140 (420-1970)	4.74	1.47	1.84	3.69	-	-	7.00 (1.6-9.0)	7.0	1580 (340-2570)	4.43	
20 + 35 + 35	1.20	2.10	2.10	-	-	5.40 (1.8-7.3)	5.3	1180 (390-2100)	4.58	1.56	2.72	2.72	-	-	7.00 (1.6-9.0)	7.4	1670 (320-2700)	4.19	
25 + 25 + 25	1.80	1.80	1.80	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2140)	4.46	2.33	2.33	2.33	-	-	6.99 (1.6-9.0)	7.6	1710 (310-2790)	4.09	
25 + 25 + 35	1.59	1.59	2.22	-	-	5.40 (1.9-7.2)	5.5	1210 (390-2100)	4.46	2.06	2.06	2.88	-	-	7.00 (1.6-9.0)	7.5	1690 (310-2730)	4.14	
25 + 25 + 42	1.47	1.47	2.46	-	-	5.40 (1.8-7.3)	5.3	1180 (390-2140)	4.58	1.90	1.90	3.20	-	-	7.00 (1.6-9.0)	7.4	1680 (680-2720)	4.17	
25 + 35 + 35	1.42	1.99	1.99	-	-	5.40 (1.8-7.3)	5.3	1180 (390-2100)	4.58	1.84	2.58	2.58	-	-	7.00 (1.6-9.0)	7.4	1670 (680-2700)	4.19	

Note: At least two indoor units must be connected. When operating just one unit, minimum connected capacity must still be met, please refer Technical Manual for details.

CU-4Z71VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
1 room	16	1.60	-	-	-	-	1.60 (1.3-2.3)	2.0	420 (250-660)	3.81	2.60	-	-	-	-	2.60 (1.2-3.2)	3.0	640 (290-1000)	4.06
	20	2.00	-	-	-	-	2.00 (1.8-2.9)	2.5	520 (340-830)	3.85	3.20	-	-	-	-	3.20 (1.2-4.1)	3.7	780 (290-1270)	4.10
	25	2.50	-	-	-	-	2.50 (1.8-2.9)	3.1	650 (340-830)	3.85	3.60	-	-	-	-	3.60 (1.2-4.3)	4.7	980 (290-1270)	3.67
	35	3.50	-	-	-	-	3.50 (1.8-3.8)	4.4	960 (340-1380)	3.65	4.50	-	-	-	-	4.50 (1.2-5.8)	5.9	1270 (290-2140)	3.54
	42	4.20	-	-	-	-	4.20 (1.8-4.3)	6.2	1390 (340-2010)	3.02	5.60	-	-	-	-	5.60 (1.2-6.8)	7.8	1760 (290-2970)	3.18
	50	5.00	-	-	-	-	5.00 (1.9-5.4)	7.3	1630 (340-2150)	3.07	6.80	-	-	-	-	6.80 (1.2-6.9)	10.4	2350 (290-2840)	2.89
	60	6.00	-	-	-	-	6.00 (1.9-6.2)	8.9	2050 (340-2350)	2.93	8.50	-	-	-	-	8.50 (1.3-9.0)	10.8	2440 (320-2590)	3.48

CU-4Z71VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION									
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				Total	
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W	
2 rooms	16 + 16	1.60	1.60	-	-	-	3.20 (1.9-6.4)	2.9	600 (270-2160)	5.33	2.60	2.60	-	-	-	5.20 (2.7-9.8)	6.0	1380 (660-3090)	3.77
	16 + 20	1.60	2.00	-	-	-	3.60 (1.9-6.4)	3.4	730 (270-2120)	4.93	2.58	3.22	-	-	-	5.80 (2.7-9.8)	6.8	1560 (650-3100)	3.72
	16 + 25	1.60	2.50	-	-	-	4.10 (1.9-6.4)	3.9	870 (270-2120)	4.71	2.42	3.78	-	-	-	6.20 (2.7-9.8)	7.4	1690 (650-3100)	3.67
	16 + 35	1.60	3.50	-	-	-	5.10 (1.9-6.9)	5.6	1290 (270-2520)	3.95	2.23	4.87	-	-	-	7.10 (2.7-9.9)	8.6	1940 (630-3100)	3.59
	16 + 42	1.60	4.20	-	-	-	5.80 (1.9-6.9)	7.2	1650 (270-2480)	3.52	2.26	5.94	-	-	-	8.20 (2.7-9.9)	10.4	2410 (630-3100)	3.40
	16 + 50	1.60	5.00	-	-	-	6.60 (2.0-7.5)	8.1	1860 (280-2560)	3.55	2.06	6.44	-	-	-	8.50 (2.8-10.2)	10.1	2340 (560-3070)	3.63
	16 + 60	1.49	5.61	-	-	-	7.10 (2.0-7.5)	9.8	2260 (280-2560)	3.14	1.79	6.71	-	-	-	8.50 (2.8-10.2)	10.1	2340 (560-3070)	3.63
	20 + 20	2.00	2.00	-	-	-	4.00 (1.9-6.4)	3.8	840 (270-2080)	4.76	3.20	3.20	-	-	-	6.40 (2.7-9.8)	7.6	1750 (640-3100)	3.66
	20 + 25	2.00	2.50	-	-	-	4.50 (1.9-6.4)	4.6	1020 (270-2080)	4.41	3.02	3.78	-	-	-	6.80 (2.7-9.8)	8.1	1880 (640-3100)	3.62
	20 + 35	2.00	3.50	-	-	-	5.50 (1.9-6.9)	6.4	1470 (270-2480)	3.74	2.80	4.90	-	-	-	7.70 (2.7-9.9)	9.5	2190 (630-3100)	3.52
	20 + 42	2.00	4.20	-	-	-	6.20 (1.9-6.9)	8.2	1890 (270-2440)	3.28	2.74	5.76	-	-	-	8.50 (2.7-9.9)	10.9	2520 (620-3110)	3.37
	20 + 50	2.00	5.00	-	-	-	7.00 (2.0-7.5)	9.2	2120 (280-2520)	3.30	2.43	6.07	-	-	-	8.50 (2.8-10.2)	10.1	2340 (560-3070)	3.63
	20 + 60	1.78	5.32	-	-	-	7.10 (2.0-7.5)	9.6	2210 (280-2520)	3.21	2.12	6.38	-	-	-	8.50 (2.8-10.2)	10.1	2340 (560-3070)	3.63
	25 + 25	2.50	2.50	-	-	-	5.00 (1.9-6.8)	5.5	1250 (270-2470)	4.00	3.60	3.60	-	-	-	7.20 (2.7-9.8)	8.8	2020 (640-3100)	3.56
	25 + 35	2.50	3.50	-	-	-	6.00 (1.9-6.9)	7.7	1770 (270-2480)	3.39	3.37	4.73	-	-	-	8.10 (2.7-9.9)	10.1	2340 (630-3100)	3.48
	25 + 42	2.50	4.20	-	-	-	6.70 (1.9-6.9)	10.1	2320 (270-2440)	2.89	3.17	5.33	-	-	-	8.50 (2.7-9.9)	10.9	2520 (620-3110)	3.37
	25 + 50	2.37	4.73	-	-	-	7.10 (1.9-7.5)	9.6	2210 (260-2520)	3.21	2.83	5.67	-	-	-	8.50 (2.8-10.2)	10.1	2340 (560-3070)	3.63
	25 + 60	2.09	5.01	-	-	-	7.10 (1.9-7.5)	9.6	2210 (260-2520)	3.21	2.50	6.00	-	-	-	8.50 (2.8-10.2)	10.1	2340 (560-3070)	3.63
	35 + 35	3.50	3.50	-	-	-	7.00 (1.9-7.1)	10.9	2510 (270-2580)	2.79	4.25	4.25	-	-	-	8.50 (2.8-10.0)	10.7	2470 (640-3100)	3.44
	35 + 42	3.23	3.87	-	-	-	7.10 (1.9-7.2)	11.3	2610 (270-2630)	2.72	3.86	4.64	-	-	-	8.50 (2.8-10.0)	10.7	2470 (640-3100)	3.44
	35 + 50	2.92	4.18	-	-	-	7.10 (2.0-7.6)	9.2	2130 (280-2520)	3.33	3.50	5.00	-	-	-	8.50 (2.8-10.3)	9.9	2280 (540-3050)	3.73
	35 + 60	2.62	4.48	-	-	-	7.10 (2.0-7.6)	9.2	2130 (280-2520)	3.33	3.13	5.37	-	-	-	8.50 (2.8-10.3)	9.9	2280 (540-3050)	3.73
	42 + 42	3.55	3.55	-	-	-	7.10 (1.9-7.2)	11.1	2560 (260-2630)	2.77	4.25	4.25	-	-	-	8.50 (2.8-10.0)	10.7	2460 (600-3060)	3.46
	42 + 50	3.24	3.86	-	-	-	7.10 (2.0-7.6)	9.2	2130 (280-2480)	3.33	3.88	4.62	-	-	-	8.50 (2.8-10.3)	9.8	2270 (540-3040)	3.74
	42 + 60	2.92	4.18	-	-	-	7.10 (2.0-7.6)	9.2	2130 (280-2480)	3.33	3.50	5.00	-	-	-	8.50 (2.8-10.3)	9.8	2270 (540-3040)	3.74
	50 + 50	3.55	3.55	-	-	-	7.10 (2.1-8.1)	8.1	1870 (320-2540)	3.80	4.25	4.25	-	-	-	8.50 (2.8-10.5)	9.2	2130 (510-2950)	3.99
	50 + 60	3.23	3.87	-	-	-	7.10 (2.1-8.1)	8.1	1870 (320-2540)	3.80	3.86	4.64	-	-	-	8.50 (2.8-10.5)	9.2	2130 (510-2950)	3.99
	16 + 16 + 16	1.60	1.60	1.60	-	-	4.80 (1.9-8.0)	4.6	1050 (270-2560)	4.57	2.60	2.60	2.60	-	-	7.80 (3.3-10.4)	9.0	2080 (640-3070)	3.75
	16 + 16 + 20	1.60	1.60	2.00	-	-	5.20 (1.9-8.0)	5.3	1190 (270-2520)	4.37	2.58	2.58	3.24	-	-	8.40 (3.3-10.4)	10.0	2310 (640-3060)	3.64
	16 + 16 + 25	1.60	1.60	2.50	-	-	5.70 (1.9-8.0)	6.2	1420 (270-2520)	4.01	2.39	2.39	3.72	-	-	8.50 (3.3-10.4)	10.2	2350 (640-3060)	3.62
	16 + 16 + 35	1.60	1.60	3.50	-	-	6.70 (1.9-8.0)	8.1	1880 (270-2430)	3.56	2.03	2.03	4.44	-	-	8.50 (3.3-10.4)	9.9	2280 (630-3040)	3.73
	16 + 16 + 42	1.54	1.54	4.02	-	-	7.10 (1.9-8.1)	9.1	2100 (270-2520)	3.38	1.84	1.84	4.82	-	-	8.50 (3.3-10.5)	9.8	2270 (620-3070)	3.74
	16 + 16 + 50	1.39	1.39	4.32	-	-	7.10 (2.0-8.5)	8.3	1920 (320-2480)	3.70	1.66	1.66	5.18	-	-	8.50 (3.2-10.7)	9.3	2140 (600-2970)	3.97
	16 + 16 + 60	1.23	1.23	4.64	-	-	7.10 (2.0-8.5)	8.3	1920 (320-2480)	3.70	1.48	1.48	5.54	-	-	8.50 (3.2-10.7)	9.3	2140 (600-2970)	3.97
	16 + 20 + 20	1.60	2.00	2.00	-	-	5.60 (1.9-8.0)	5.9	1340 (270-2520)	4.18	2.42	3.04	3.04	-	-	8.50 (3.3-10.4)	10.1	2340 (630-3050)	3.63
16 + 20 + 25	1.60	2.00	2.50	-	-	6.10 (1.9-8.0)	6.9	1580 (270-2520)	3.86	2.23	2.79	3.48	-	-	8.50 (3.3-10.4)	10.1	2340 (630-3050)	3.63	
16 + 20 + 35	1.60	2.00	3.50	-	-	7.10 (1.9-8.0)	9.1	2100 (270-2430)	3.38	1.92	2.39	4.19	-	-	8.50 (3.3-10.4)	9.8	2270 (620-2980)	3.74	
16 + 20 + 42	1.46	1.82	3.82	-	-	7.10 (1.9-8.1)	9.1	2100 (270-2480)	3.38	1.74	2.18	4.58	-	-	8.50 (3.3-10.5)	9.8	2270 (620-3020)	3.74	
16 + 20 + 50	1.32	1.65	4.13	-	-	7.10 (2.0-8.5)	8.3	1920 (320-2480)	3.70	1.58	1.98	4.94	-	-	8.50 (3.2-10.7)	9.2	2130 (600-2960)	3.99	
16 + 20 + 60	1.18	1.48	4.44	-	-	7.10 (2.0-8.5)	8.3	1920 (320-2480)	3.70	1.42	1.77	5.31	-	-	8.50 (3.2-10.7)	9.2	2130 (600-2960)	3.99	
16 + 25 + 25	1.60	2.50	2.50	-	-	6.60 (1.9-8.0)	7.9	1830 (270-2520)	3.61	2.06	3.22	3.22	-	-	8.50 (3.3-10.4)	10.1	2340 (630-3050)	3.63	
16 + 25 + 35	1.49	2.34	3.27	-	-	7.10 (1.9-8.0)	9.1	2100 (270-2430)	3.38	1.79	2.80	3.91	-	-	8.50 (3.3-10.4)	9.8	2270 (620-2980)	3.74	
16 + 25 + 42	1.37	2.14	3.59	-	-	7.10 (1.9-8.1)	9.1	2100 (270-2480)	3.38	1.64	2.56	4.30	-	-	8.50 (3.3-10.5)	9.8	2270 (620-3020)	3.74	
16 + 25 + 50	1.25	1.95	3.90	-	-	7.10 (2.0-8.5)	8.3	1920 (320-2480)	3.70	1.49	2.34	4.67	-	-	8.50 (3.2-10.7)	9.2	2130 (600-2960)	3.99	
16 + 25 + 60	1.12	1.76	4.22	-	-	7.10 (2.0-8.5)	8.3	1920 (320-2480)	3.70	1.35	2.10	5.05	-	-	8.50 (3.2-10.7)	9.2	2130 (600-2960)	3.99	
16 + 35 + 35	1.32	2.89	2.89	-	-	7.10 (1.9-8.1)	8.9	2060 (290-2430)	3.45	1.58	3.46	3.46	-	-	8.50 (3.3-10.5)	9.8	2250 (640-3000)	3.78	
16 + 35 + 42	1.22	2.67	3.21	-	-	7.10 (1.9-8.2)	8.9	2060 (290-2480)	3.45	1.46	3.20	3.84	-	-	8.50 (3.3-10.5)	9.7	2240 (640-2990)	3.79	
16 + 35 + 50	1.12	2.46	3.52	-	-	7.10 (2.0-8.5)	8.1	1870 (340-2440)	3.80	1.34	2.95	4.21	-	-	8.50 (3.2-10.7)	9.1	2110 (600-2930)	4.03	
16 + 35 + 60	1.02	2.24	3.84	-	-	7.10 (2.0-8.5)	8.1	1870 (340-2440)	3.80	1.23	2.68	4.59	-	-	8.50 (3.2-10.7)	9.1	2110 (600-2930)	4.03	
16 + 42 + 42	1.14	2.98	2.98	-	-	7.10 (1.9-8.2)	8.9	2060 (290-2480)	3.45	1.36	3.57	3.57	-	-	8.50 (3.3-10.5)	9.7	2230 (640-2980)	3.81	
16 + 42 + 50	1.05	2.76	3.29	-	-	7.10 (2.0-8.5)	8.1	1870 (340-2390)	3.80	1.25	3.31	3.94	-	-	8.50 (3.2-10.6)	9.1	2100 (600-2880)	4.05	
20 + 20 + 20	2.00	2.00	2.00	-	-	6.00 (1.9-8.0)	6.7	1540 (270-2470)	3.90	2.83	2.83	2.83	-	-	8.49 (3.3-10.4)	9.9	2290 (630-3040)	3.71	
20 + 20 + 25	2.00	2.00	2.50	-	-	6.50 (1.9-8.0)	7.8	1790 (270-2470)	3.63	2.62	2.62	3.26	-	-	8.50 (3.3-10.4)	9.9	2290 (630-3040)	3.71	
20 + 20 + 35	1.89	1.89	3.32	-	-	7.10 (1.9-8.0)	9.1	2100 (270-2380)	3.38	2.27	2.27	3.96	-	-	8.50 (3.3-10.4)	9.8	2270 (620-2970)	3.74	
20 + 20 + 42	1.73	1.73	3.64	-	-	7.10 (1.9-8.1)	8.9	2060 (290-2480)	3.45	2.07	2.07	4.36	-	-	8.50 (3.3-10.5)	9.8	2260 (620-3010)	3.76	
20 + 20 + 50	1.58	1.58	3.94	-	-	7.													

CU-4Z71VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
4 rooms	16 + 16 + 16 + 16	1.60	1.60	1.60	1.60	-	6.40 (1.9-8.7)	6.2	1390 (340-2370)	4.60	2.12	2.12	2.12	2.12	-	8.48 (3.0-10.7)	8.7	1960 (500-2770)	4.33
	16 + 16 + 16 + 20	1.67	1.67	1.67	2.09	-	7.10 (1.9-8.8)	7.4	1660 (340-2470)	4.28	2.00	2.00	2.00	2.50	-	8.50 (3.0-10.7)	8.6	1950 (500-2720)	4.36
	16 + 16 + 16 + 25	1.56	1.56	1.56	2.42	-	7.10 (1.9-8.8)	7.4	1660 (340-2470)	4.28	1.86	1.86	1.86	2.92	-	8.50 (3.0-10.7)	8.6	1950 (500-2720)	4.36
	16 + 16 + 16 + 35	1.37	1.37	1.37	2.99	-	7.10 (1.9-8.8)	7.4	1660 (340-2380)	4.28	1.64	1.64	1.64	3.58	-	8.50 (3.0-10.7)	8.5	1930 (500-2700)	4.40
	16 + 16 + 16 + 42	1.26	1.26	1.26	3.32	-	7.10 (1.9-8.8)	7.4	1660 (340-2380)	4.28	1.51	1.51	1.51	3.97	-	8.50 (3.0-10.7)	8.5	1930 (500-2690)	4.40
	16 + 16 + 16 + 50	1.16	1.16	1.16	3.62	-	7.10 (1.9-8.8)	7.1	1580 (400-2240)	4.49	1.39	1.39	1.39	4.33	-	8.50 (3.0-10.7)	8.4	1890 (560-2590)	4.50
	16 + 16 + 16 + 60	1.05	1.05	1.05	3.95	-	7.10 (1.9-8.8)	7.1	1580 (400-2240)	4.49	1.26	1.26	1.26	4.72	-	8.50 (3.0-10.7)	8.4	1890 (560-2590)	4.50
	16 + 16 + 20 + 20	1.58	1.58	1.97	1.97	-	7.10 (1.9-8.8)	7.4	1660 (340-2420)	4.28	1.89	1.89	2.36	2.36	-	8.50 (3.1-10.7)	8.6	1950 (520-2710)	4.36
	16 + 16 + 20 + 25	1.48	1.48	1.84	2.30	-	7.10 (1.9-8.8)	7.4	1660 (340-2420)	4.28	1.77	1.77	2.20	2.76	-	8.50 (3.1-10.7)	8.6	1950 (520-2710)	4.36
	16 + 16 + 20 + 35	1.31	1.31	1.63	2.85	-	7.10 (1.9-8.8)	7.4	1660 (340-2380)	4.28	1.56	1.56	1.95	3.43	-	8.50 (3.0-10.7)	8.5	1930 (500-2690)	4.40
	16 + 16 + 20 + 42	1.21	1.21	1.51	3.17	-	7.10 (1.9-8.8)	7.2	1620 (370-2380)	4.38	1.45	1.45	1.80	3.80	-	8.50 (3.0-10.7)	8.5	1920 (520-2680)	4.43
	16 + 16 + 20 + 50	1.11	1.11	1.39	3.49	-	7.10 (1.9-8.8)	7.1	1580 (400-2200)	4.49	1.33	1.33	1.67	4.17	-	8.50 (3.0-10.7)	8.3	1880 (570-2580)	4.52
	16 + 16 + 20 + 60	1.01	1.01	1.27	3.81	-	7.10 (1.9-8.8)	7.1	1580 (400-2200)	4.49	1.21	1.21	1.52	4.56	-	8.50 (3.0-10.7)	8.3	1880 (570-2580)	4.52
	16 + 16 + 25 + 25	1.39	1.39	2.16	2.16	-	7.10 (1.9-8.8)	7.4	1660 (340-2420)	4.28	1.66	1.66	2.59	2.59	-	8.50 (3.1-10.7)	8.6	1950 (520-2710)	4.36
	16 + 16 + 25 + 35	1.23	1.23	1.93	2.71	-	7.10 (1.9-8.8)	7.4	1660 (340-2380)	4.28	1.48	1.48	2.31	3.23	-	8.50 (3.0-10.7)	8.5	1930 (500-2690)	4.40
	16 + 16 + 25 + 42	1.15	1.15	1.79	3.01	-	7.10 (1.9-8.8)	7.2	1620 (370-2380)	4.38	1.37	1.37	2.15	3.61	-	8.50 (3.0-10.7)	8.5	1920 (520-2680)	4.43
	16 + 16 + 25 + 50	1.06	1.06	1.66	3.32	-	7.10 (1.9-8.8)	7.1	1580 (400-2200)	4.49	1.27	1.27	1.99	3.97	-	8.50 (3.0-10.7)	8.3	1880 (570-2580)	4.52
	16 + 16 + 35 + 35	1.11	1.11	2.44	2.44	-	7.10 (1.9-8.8)	7.2	1620 (370-2330)	4.38	1.33	1.33	2.92	2.92	-	8.50 (3.0-10.7)	8.4	1910 (530-2660)	4.45
	16 + 16 + 35 + 42	1.04	1.04	2.28	2.74	-	7.10 (1.9-8.8)	7.2	1620 (370-2330)	4.38	1.25	1.25	2.72	3.28	-	8.50 (3.0-10.7)	8.4	1900 (530-2650)	4.47
	16 + 20 + 20 + 20	1.49	1.87	1.87	1.87	-	7.10 (1.9-8.8)	7.4	1660 (340-2420)	4.28	1.78	2.24	2.24	2.24	-	8.50 (3.1-10.7)	8.6	1940 (520-2700)	4.38
	16 + 20 + 20 + 25	1.40	1.75	1.75	2.20	-	7.10 (1.9-8.8)	7.4	1660 (340-2420)	4.28	1.68	2.10	2.10	2.62	-	8.50 (3.1-10.7)	8.6	1940 (520-2700)	4.38
	16 + 20 + 20 + 35	1.25	1.56	1.56	2.73	-	7.10 (1.9-8.8)	7.2	1620 (370-2380)	4.38	1.49	1.87	1.87	3.27	-	8.50 (3.0-10.7)	8.5	1920 (520-2680)	4.43
	16 + 20 + 20 + 42	1.16	1.45	1.45	3.04	-	7.10 (1.9-8.8)	7.2	1620 (370-2380)	4.38	1.39	1.73	1.73	3.65	-	8.50 (3.0-10.7)	8.4	1910 (520-2670)	4.45
	16 + 20 + 20 + 50	1.07	1.34	1.34	3.35	-	7.10 (1.9-8.8)	7.1	1580 (420-2200)	4.49	1.28	1.60	1.60	4.02	-	8.50 (3.0-10.7)	8.3	1880 (590-2570)	4.52
	16 + 20 + 25 + 25	1.33	1.65	2.06	2.06	-	7.10 (1.9-8.8)	7.4	1660 (340-2420)	4.28	1.58	1.98	2.47	2.47	-	8.50 (3.1-10.7)	8.6	1940 (520-2700)	4.38
	16 + 20 + 25 + 35	1.18	1.48	1.85	2.59	-	7.10 (1.9-8.8)	7.2	1620 (370-2380)	4.38	1.42	1.77	2.21	3.10	-	8.50 (3.0-10.7)	8.5	1920 (520-2680)	4.43
	16 + 20 + 25 + 42	1.10	1.38	1.72	2.90	-	7.10 (1.9-8.8)	7.2	1620 (370-2380)	4.38	1.32	1.65	2.06	3.47	-	8.50 (3.0-10.7)	8.4	1910 (520-2670)	4.45
	16 + 20 + 25 + 50	1.02	1.28	1.60	3.20	-	7.10 (1.9-8.8)	7.1	1580 (420-2200)	4.49	1.23	1.53	1.91	3.83	-	8.50 (3.0-10.7)	8.3	1880 (590-2570)	4.52
	16 + 20 + 35 + 35	1.07	1.34	2.34	2.35	-	7.10 (1.9-8.8)	7.2	1620 (370-2330)	4.38	1.28	1.60	2.81	2.81	-	8.50 (3.0-10.7)	8.4	1900 (530-2650)	4.47
	16 + 20 + 35 + 42	1.01	1.26	2.20	2.63	-	7.10 (1.9-8.8)	7.2	1620 (370-2330)	4.38	1.20	1.50	2.63	3.17	-	8.50 (3.0-10.7)	8.4	1900 (530-2650)	4.47
	16 + 25 + 25 + 25	1.25	1.95	1.95	1.95	-	7.10 (1.9-8.8)	7.4	1660 (340-2420)	4.28	1.48	2.34	2.34	2.34	-	8.50 (3.1-10.7)	8.6	1940 (520-2700)	4.38
	16 + 25 + 25 + 35	1.12	1.76	1.76	2.46	-	7.10 (1.9-8.8)	7.2	1620 (370-2380)	4.38	1.35	2.10	2.10	2.95	-	8.50 (3.0-10.7)	8.5	1920 (520-2680)	4.43
	16 + 25 + 25 + 42	1.05	1.64	1.64	2.77	-	7.10 (1.9-8.8)	7.2	1620 (370-2380)	4.38	1.25	1.97	1.97	3.31	-	8.50 (3.0-10.7)	8.4	1910 (520-2670)	4.45
	16 + 25 + 35 + 35	1.02	1.60	2.24	2.24	-	7.10 (1.9-8.8)	7.2	1620 (370-2330)	4.38	1.23	1.91	2.68	2.68	-	8.50 (3.0-10.7)	8.4	1900 (530-2650)	4.47
	20 + 20 + 20 + 20	1.77	1.77	1.77	1.77	-	7.08 (1.9-8.8)	7.2	1620 (340-2380)	4.37	2.12	2.12	2.12	2.12	-	8.48 (3.1-10.7)	8.5	1930 (520-2690)	4.39
	20 + 20 + 20 + 25	1.67	1.67	1.67	2.09	-	7.10 (1.9-8.8)	7.4	1660 (340-2380)	4.28	2.00	2.00	2.00	2.50	-	8.50 (3.1-10.7)	8.5	1930 (520-2690)	4.40
	20 + 20 + 20 + 35	1.49	1.49	1.49	2.63	-	7.10 (1.9-8.8)	7.2	1620 (370-2330)	4.38	1.79	1.79	1.79	3.13	-	8.50 (3.0-10.7)	8.4	1910 (520-2670)	4.45
	20 + 20 + 20 + 42	1.39	1.39	1.39	2.93	-	7.10 (1.9-8.8)	7.2	1620 (370-2330)	4.38	1.67	1.67	1.67	3.49	-	8.50 (3.0-10.7)	8.4	1910 (530-2660)	4.45
	20 + 20 + 20 + 50	1.29	1.29	1.29	3.23	-	7.10 (1.9-8.8)	7.1	1580 (420-2200)	4.49	1.55	1.55	1.55	3.85	-	8.50 (3.0-10.7)	8.3	1870 (590-2570)	4.55
	20 + 20 + 25 + 25	1.58	1.58	1.97	1.97	-	7.10 (1.9-8.8)	7.4	1660 (340-2380)	4.28	1.89	1.89	2.36	2.36	-	8.50 (3.1-10.7)	8.5	1930 (520-2690)	4.40
20 + 20 + 25 + 35	1.42	1.42	1.78	2.48	-	7.10 (1.9-8.8)	7.2	1620 (370-2330)	4.38	1.70	1.70	2.12	2.98	-	8.50 (3.0-10.7)	8.4	1910 (520-2670)	4.45	
20 + 20 + 25 + 42	1.33	1.33	1.66	2.78	-	7.10 (1.9-8.8)	7.2	1620 (370-2330)	4.38	1.59	1.59	1.98	3.34	-	8.50 (3.0-10.7)	8.4	1910 (530-2660)	4.45	
20 + 20 + 25 + 50	1.23	1.23	1.54	3.10	-	7.10 (1.9-8.8)	7.1	1580 (420-2200)	4.49	1.48	1.48	1.84	3.70	-	8.50 (3.0-10.7)	8.3	1870 (590-2570)	4.55	
20 + 20 + 35 + 35	1.29	1.29	2.26	2.26	-	7.10 (1.9-8.8)	7.2	1620 (370-2330)	4.38	1.55	1.55	2.70	2.70	-	8.50 (3.0-10.7)	8.4	1900 (530-2650)	4.47	
20 + 25 + 25 + 25	1.49	1.87	1.87	1.87	-	7.10 (1.9-8.8)	7.4	1660 (340-2380)	4.28	1.78	2.24	2.24	2.24	-	8.50 (3.1-10.7)	8.5	1930 (520-2690)	4.40	
20 + 25 + 25 + 35	1.35	1.69	1.69	2.37	-	7.10 (1.9-8.8)	7.2	1620 (370-2330)	4.38	1.62	2.02	2.02	2.84	-	8.50 (3.0-10.7)	8.4	1910 (520-2670)	4.45	
20 + 25 + 25 + 42	1.27	1.58	1.58	2.67	-	7.10 (1.9-8.8)	7.2	1620 (370-2330)	4.38	1.51	1.90	1.90	3.19	-	8.50 (3.0-10.7)	8.4	1910 (530-2660)	4.45	
20 + 25 + 35 + 35	1.24	1.54	2.16	2.16	-	7.10 (1.9-8.8)	7.2	1620 (370-2330)	4.38	1.47	1.85	2.59	2.59	-	8.50 (3.0-10.7)	8.4	1900 (530-2650)	4.47	
25 + 25 + 25 + 25	1.77	1.77	1.77	1.77	-	7.08 (1.9-8.8)	7.2	1620 (340-2380)	4.37	2.12	2.12	2.12	2.12	-	8.48 (3.1-10.7)	8.5	1930 (520-2690)	4.39	
25 + 25 + 25 + 35	1.61	1.61	1.61	2.27	-	7.10 (1.9-8.8)	7.2	1620 (370-2330)	4.38	1.93	1.93	1.93	2.71	-	8.50 (3.0-10.7)	8.4	1910 (520-2670)	4.45	

Note: At least two indoor units must be connected. When operating just one unit, minimum connected capacity must still be met, please refer Technical Manual for details.

CU-4Z71VBR: Free Multi Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION									
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP	
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E					
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W	
1 room	16	1.60	-	-	-	-	1.60 (1.3-2.3)	2.2	450 (250-690)	3.56	2.60	-	-	-	-	2.60 (1.2-3.2)	3.2	700 (290-1060)	3.71	
	20	2.00	-	-	-	-	2.00 (1.8-2.9)	2.6	550 (340-860)	3.64	3.20	-	-	-	-	3.20 (1.2-4.1)	3.9	840 (290-1330)	3.81	
	25	2.50	-	-	-	-	2.50 (1.8-2.9)	3.2	680 (340-860)	3.68	3.60	-	-	-	-	3.60 (1.2-4.3)	4.9	1040 (290-1330)	3.46	
	35	3.50	-	-	-	-	3.50 (1.8-3.8)	4.5	990 (340-1410)	3.54	4.50	-	-	-	-	4.50 (1.2-5.8)	6.2	1330 (290-2220)	3.38	
	42	4.20	-	-	-	-	4.20 (1.8-4.3)	6.3	1420 (340-2040)	2.96	5.60	-	-	-	-	5.60 (1.2-6.8)	8.0	1820 (290-3030)	3.08	
	50	5.00	-	-	-	-	5.00 (1.9-5.4)	7.3	1630 (340-2150)	3.07	6.80	-	-	-	-	6.80 (1.2-6.9)	10.4	2350 (290-2840)	2.89	
2 rooms	60	6.00	-	-	-	-	6.00 (1.9-6.2)	9.0	2080 (340-2380)	2.88	8.50	-	-	-	-	8.50 (1.3-9.0)	11.0	2500 (320-2650)	3.40	
	16 + 16	1.60	1.60	-	-	-	3.20 (1.9-6.4)	3.1	660 (270-2220)	4.85	2.60	2.60	-	-	-	5.20 (2.7-9.8)	6.6	1500 (660-3210)	3.47	
	16 + 20	1.60	2.00	-	-	-	3.60 (1.9-6.4)	3.6	790 (270-2180)	4.56	2.58	3.22	-	-	-	5.80 (2.7-9.8)	7.4	1680 (650-3220)	3.45	
	16 + 25	1.60	2.50	-	-	-	4.10 (1.9-6.4)	4.2	930 (270-2180)	4.41	2.42	3.78	-	-	-	6.20 (2.7-9.8)	7.8	1810 (650-3220)	3.43	
	16 + 35	1.60	3.50	-	-	-	5.10 (1.9-6.9)	5.9	1350 (270-2580)	3.78	2.23	4.87	-	-	-	7.10 (2.7-9.9)	9.1	2100 (630-3220)	3.38	
	16 + 42	1.60	4.20	-	-	-	5.80 (1.9-6.9)	7.5	1710 (270-2540)	3.39	2.26	5.94	-	-	-	8.20 (2.7-9.9)	11.0	2530 (630-3220)	3.24	
	16 + 50	1.60	5.00	-	-	-	6.60 (2.0-7.5)	8.3	1920 (280-2620)	3.44	2.06	6.44	-	-	-	8.50 (2.8-10.2)	10.7	2460 (560-3190)	3.46	
	16 + 60	1.49	5.61	-	-	-	7.10 (2.0-7.5)	10.1	2320 (280-2620)	3.06	1.79	6.71	-	-	-	8.50 (2.8-10.2)	10.7	2460 (560-3190)	3.46	
	20 + 20	2.00	2.00	-	-	-	4.00 (1.9-6.4)	4.1	900 (270-2140)	4.44	3.20	3.20	-	-	-	6.40 (2.7-9.8)	8.1	1870 (640-3220)	3.42	
	20 + 25	2.00	2.50	-	-	-	4.50 (1.9-6.4)	4.8	1080 (270-2140)	4.17	3.02	3.78	-	-	-	6.80 (2.7-9.8)	8.7	2000 (640-3220)	3.40	
	20 + 35	2.00	3.50	-	-	-	5.50 (1.9-6.9)	6.7	1530 (270-2540)	3.59	2.80	4.90	-	-	-	7.70 (2.7-9.9)	10.0	2310 (630-3220)	3.33	
	20 + 42	2.00	4.20	-	-	-	6.20 (1.9-6.9)	8.5	1950 (270-2500)	3.18	2.74	5.76	-	-	-	8.50 (2.7-9.9)	11.4	2640 (620-3230)	3.22	
	20 + 50	2.00	5.00	-	-	-	7.00 (2.0-7.5)	9.5	2180 (280-2580)	3.21	2.43	6.07	-	-	-	8.50 (2.8-10.2)	10.7	2460 (560-3190)	3.46	
	20 + 60	1.78	5.32	-	-	-	7.10 (2.0-7.5)	9.8	2270 (280-2580)	3.13	2.12	6.38	-	-	-	8.50 (2.8-10.2)	10.7	2460 (560-3190)	3.46	
	25 + 25	2.50	2.50	-	-	-	5.00 (1.9-6.8)	5.7	1310 (270-2530)	3.82	3.60	3.60	-	-	-	7.20 (2.7-9.8)	9.3	2140 (640-3220)	3.36	
	25 + 35	2.50	3.50	-	-	-	6.00 (1.9-6.9)	7.9	1830 (270-2540)	3.28	3.37	4.73	-	-	-	8.10 (2.7-9.9)	10.6	2450 (630-3220)	3.31	
	25 + 42	2.50	4.20	-	-	-	6.70 (1.9-6.9)	10.3	2380 (270-2500)	2.82	3.17	5.33	-	-	-	8.50 (2.7-9.9)	11.4	2640 (620-3230)	3.22	
	25 + 50	2.37	4.73	-	-	-	7.10 (1.9-7.5)	9.8	2270 (260-2580)	3.13	2.83	5.67	-	-	-	8.50 (2.8-10.2)	10.7	2460 (560-3190)	3.46	
	25 + 60	2.09	5.01	-	-	-	7.10 (1.9-7.5)	9.8	2270 (260-2580)	3.13	2.50	6.00	-	-	-	8.50 (2.8-10.2)	10.7	2460 (560-3190)	3.46	
	35 + 35	3.50	3.50	-	-	-	7.00 (1.9-7.1)	11.1	2570 (270-2640)	2.72	4.25	4.25	-	-	-	8.50 (2.8-10.0)	11.2	2590 (640-3220)	3.28	
	35 + 42	3.23	3.87	-	-	-	7.10 (1.9-7.2)	11.6	2670 (270-2690)	2.66	3.86	4.64	-	-	-	8.50 (2.8-10.0)	11.2	2590 (600-3220)	3.28	
	35 + 50	2.92	4.18	-	-	-	7.10 (2.0-7.6)	9.5	2190 (280-2580)	3.24	3.50	5.00	-	-	-	8.50 (2.8-10.3)	10.4	2400 (540-3170)	3.54	
	35 + 60	2.62	4.48	-	-	-	7.10 (2.0-7.6)	9.5	2190 (280-2580)	3.24	3.13	5.37	-	-	-	8.50 (2.8-10.3)	10.4	2400 (540-3170)	3.54	
	42 + 42	3.55	3.55	-	-	-	7.10 (1.9-7.2)	11.4	2620 (260-2690)	2.71	4.25	4.25	-	-	-	8.50 (2.8-10.0)	11.2	2580 (600-3180)	3.29	
	42 + 50	3.24	3.86	-	-	-	7.10 (2.0-7.6)	9.5	2190 (280-2540)	3.24	3.88	4.62	-	-	-	8.50 (2.8-10.3)	10.4	2390 (540-3160)	3.56	
	42 + 60	2.92	4.18	-	-	-	7.10 (2.0-7.6)	9.5	2190 (280-2540)	3.24	3.50	5.00	-	-	-	8.50 (2.8-10.3)	10.4	2390 (540-3160)	3.56	
	50 + 50	3.55	3.55	-	-	-	7.10 (2.1-8.1)	8.4	1930 (320-2600)	3.68	4.25	4.25	-	-	-	8.50 (2.8-10.5)	9.8	2250 (510-3070)	3.78	
	50 + 60	3.23	3.87	-	-	-	7.10 (2.1-8.1)	8.4	1930 (320-2600)	3.68	3.86	4.64	-	-	-	8.50 (2.8-10.5)	9.8	2250 (510-3070)	3.78	
	3 rooms	16 + 16 + 16	1.60	1.60	1.60	-	-	4.80 (1.9-8.0)	5.0	1140 (270-2650)	4.21	2.60	2.60	2.60	-	-	7.80 (3.3-10.4)	9.8	2260 (640-3250)	3.45
		16 + 16 + 20	1.60	1.60	2.00	-	-	5.20 (1.9-8.0)	5.6	1280 (270-2610)	4.06	2.58	2.58	3.24	-	-	8.40 (3.3-10.4)	10.8	2490 (640-3240)	3.37
		16 + 16 + 25	1.60	1.60	2.50	-	-	5.70 (1.9-8.0)	6.6	1510 (270-2610)	3.77	2.39	2.39	3.72	-	-	8.50 (3.3-10.4)	11.0	2530 (640-3240)	3.36
		16 + 16 + 35	1.60	1.60	3.50	-	-	6.70 (1.9-8.0)	8.5	1970 (270-2520)	3.40	2.03	2.03	4.44	-	-	8.50 (3.3-10.4)	10.7	2460 (630-3220)	3.46
16 + 16 + 42		1.54	1.54	4.02	-	-	7.10 (1.9-8.1)	9.5	2190 (270-2610)	3.24	1.84	1.84	4.82	-	-	8.50 (3.3-10.5)	10.6	2450 (620-3250)	3.47	
16 + 16 + 50		1.39	1.39	4.32	-	-	7.10 (2.0-8.5)	8.7	2010 (320-2570)	3.53	1.66	1.66	5.18	-	-	8.50 (3.2-10.7)	10.1	2320 (600-3150)	3.66	
16 + 16 + 60		1.23	1.23	4.64	-	-	7.10 (2.0-8.5)	8.7	2010 (320-2570)	3.53	1.48	1.48	5.54	-	-	8.50 (3.2-10.7)	10.1	2320 (600-3150)	3.66	
16 + 20 + 20		1.60	2.00	2.00	-	-	5.60 (1.9-8.0)	6.3	1430 (270-2610)	3.92	2.42	3.04	3.04	-	-	8.50 (3.3-10.4)	10.9	2520 (630-3230)	3.37	
16 + 20 + 25		1.60	2.00	2.50	-	-	6.10 (1.9-8.0)	7.3	1670 (270-2610)	3.65	2.23	2.79	3.48	-	-	8.50 (3.3-10.4)	10.9	2520 (630-3230)	3.37	
16 + 20 + 35		1.60	2.00	3.50	-	-	7.10 (1.9-8.0)	9.5	2190 (270-2520)	3.24	1.92	2.39	4.19	-	-	8.50 (3.3-10.4)	10.6	2450 (620-3160)	3.47	
16 + 20 + 42		1.46	1.82	3.82	-	-	7.10 (1.9-8.1)	9.5	2190 (270-2570)	3.24	1.74	2.18	4.58	-	-	8.50 (3.3-10.5)	10.6	2450 (620-3200)	3.47	
16 + 20 + 50		1.32	1.65	4.13	-	-	7.10 (2.0-8.5)	8.7	2010 (320-2570)	3.53	1.58	1.98	4.94	-	-	8.50 (3.2-10.7)	10.0	2310 (600-3140)	3.68	
16 + 20 + 60		1.18	1.48	4.44	-	-	7.10 (2.0-8.5)	8.7	2010 (320-2570)	3.53	1.42	1.77	5.31	-	-	8.50 (3.2-10.7)	10.0	2310 (600-3140)	3.68	
16 + 25 + 25		1.60	2.50	2.50	-	-	6.60 (1.9-8.0)	8.3	1920 (270-2610)	3.44	2.06	3.22	3.22	-	-	8.50 (3.3-10.4)	10.9	2520 (630-3230)	3.37	
16 + 25 + 35		1.49	2.34	3.27	-	-	7.10 (1.9-8.0)	9.5	2190 (270-2520)	3.24	1.79	2.80	3.91	-	-	8.50 (3.3-10.4)	10.6	2450 (620-3160)	3.47	
16 + 25 + 42		1.37	2.14	3.59	-	-	7.10 (1.9-8.1)	9.5	2190 (270-2570)	3.24	1.64	2.56	4.30	-	-	8.50 (3.3-10.5)	10.6	2450 (620-3200)	3.47	
16 + 25 + 50		1.25	1.95	3.90	-	-	7.10 (2.0-8.5)	8.7	2010 (320-2570)	3.53	1.49	2.34	4.67	-	-	8.50 (3.2-10.7)	10.0	2310 (600-3140)	3.68	
16 + 25 + 60		1.12	1.76	4.22	-	-	7.10 (2.0-8.5)	8.7	2010 (320-2570)	3.53	1.35	2.10	5.05	-	-	8.50 (3.2-10.7)	10.0	2310 (600-3140)	3.68	
16 + 35 + 35		1.32	2.89	2.89	-	-	7.10 (1.9-8.1)	9.3	2150 (290-2520)	3.30	1.58	3.46	3.46	-	-	8.50 (3.3-10.5)	10.5	2430 (640-3180)	3.50	
16 + 35 + 42		1.22	2.67	3.21	-	-	7.10 (1.9-8.2)	9.3	2150 (290-2570)	3.30	1.46	3.20	3.84	-	-	8.50 (3.3-10.5)	10.5	2420 (640-3170)	3.51	
16 + 35 + 50		1.12	2.46	3.52	-	-	7.10 (2.0-8.5)	8.5	1960 (340-2530)	3.62	1.34	2.95	4.21	-	-	8.50 (3.2-10.7)	9.9	2290 (600-3110)	3.71	
16 + 35 + 60		1.02	2.24	3.84	-	-	7.10 (2.0-8.5)	8.5	1960 (340-2530)	3.62	1.23	2.68	4.59	-	-	8.50 (3.2-10.7)	9.9	2290 (600-3110)</		

CU-4Z71VBR: Free Multi Indoor Combination

Indoor Units Capacity	COOLING OPERATION										HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP	
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E					
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W	
3 rooms	20 + 42 + 50	1.27	2.66	3.17	-	-	7.10 (2.0-8.5)	8.5	1960 (340-2480)	3.62	1.52	3.19	3.79	-	-	8.50 (3.2-10.6)	9.8	2270 (620-3050)	3.74
	25 + 25 + 25	2.36	2.36	2.36	-	-	7.08 (1.9-8.0)	9.5	2190 (270-2560)	3.23	2.83	2.83	2.83	-	-	8.49 (3.3-10.4)	10.7	2470 (630-3220)	3.44
	25 + 25 + 35	2.09	2.09	2.92	-	-	7.10 (1.9-8.0)	9.5	2190 (270-2470)	3.24	2.50	2.50	3.50	-	-	8.50 (3.3-10.4)	10.6	2450 (620-3150)	3.47
	25 + 25 + 42	1.93	1.93	3.24	-	-	7.10 (1.9-8.1)	9.3	2150 (290-2570)	3.30	2.31	2.31	3.88	-	-	8.50 (3.3-10.5)	10.6	2440 (620-3190)	3.48
	25 + 25 + 50	1.78	1.78	3.54	-	-	7.10 (2.0-8.5)	8.7	2010 (340-2530)	3.53	2.13	2.13	4.24	-	-	8.50 (3.2-10.7)	10.0	2300 (600-3130)	3.70
	25 + 25 + 60	1.61	1.61	3.88	-	-	7.10 (2.0-8.5)	8.7	2010 (340-2530)	3.53	1.93	1.93	4.64	-	-	8.50 (3.2-10.7)	10.0	2300 (600-3130)	3.70
	25 + 35 + 35	1.86	2.62	2.62	-	-	7.10 (1.9-8.1)	9.3	2150 (290-2480)	3.30	2.24	3.13	3.13	-	-	8.50 (3.3-10.5)	10.5	2420 (640-3170)	3.51
	25 + 35 + 42	1.74	2.44	2.92	-	-	7.10 (1.9-8.2)	9.1	2100 (290-2570)	3.38	2.08	2.92	3.50	-	-	8.50 (3.3-10.5)	10.4	2410 (640-3160)	3.53
	25 + 35 + 50	1.61	2.26	3.23	-	-	7.10 (2.0-8.5)	8.5	1960 (340-2480)	3.62	1.93	2.70	3.87	-	-	8.50 (3.2-10.7)	9.9	2280 (600-3100)	3.73
	25 + 42 + 42	1.62	2.74	2.74	-	-	7.10 (1.9-8.2)	9.1	2100 (290-2520)	3.38	1.94	3.28	3.28	-	-	8.50 (3.3-10.5)	10.4	2400 (630-3160)	3.54
3 rooms	35 + 35 + 35	2.36	2.36	2.36	-	-	7.08 (1.9-8.2)	9.1	2100 (290-2480)	3.37	2.83	2.83	2.83	-	-	8.49 (3.3-10.5)	10.2	2360 (630-3150)	3.60
	35 + 35 + 42	2.22	2.22	2.66	-	-	7.10 (1.9-8.2)	9.1	2100 (290-2480)	3.38	2.66	2.66	3.18	-	-	8.50 (3.3-10.5)	10.2	2350 (630-3100)	3.62
	16 + 16 + 16 + 16	1.60	1.60	1.60	1.60	-	6.40 (1.9-8.7)	6.7	1510 (340-2490)	4.24	2.12	2.12	2.12	2.12	-	8.48 (3.0-10.7)	9.7	2200 (500-3010)	3.85
	16 + 16 + 16 + 20	1.67	1.67	1.67	2.09	-	7.10 (1.9-8.8)	7.9	1780 (340-2590)	3.99	2.00	2.00	2.00	2.50	-	8.50 (3.0-10.7)	9.7	2190 (500-2960)	3.88
	16 + 16 + 16 + 25	1.56	1.56	1.56	2.42	-	7.10 (1.9-8.8)	7.9	1780 (340-2590)	3.99	1.86	1.86	1.86	2.92	-	8.50 (3.0-10.7)	9.7	2190 (500-2960)	3.88
	16 + 16 + 16 + 35	1.37	1.37	1.37	2.99	-	7.10 (1.9-8.8)	7.9	1780 (340-2500)	3.99	1.64	1.64	1.64	3.58	-	8.50 (3.0-10.7)	9.6	2170 (500-2940)	3.92
	16 + 16 + 16 + 42	1.26	1.26	1.26	3.32	-	7.10 (1.9-8.8)	7.9	1780 (340-2500)	3.99	1.51	1.51	1.51	3.97	-	8.50 (3.0-10.7)	9.6	2170 (500-2930)	3.92
	16 + 16 + 16 + 50	1.16	1.16	1.16	3.62	-	7.10 (1.9-8.8)	7.6	1700 (400-2360)	4.18	1.39	1.39	1.39	4.33	-	8.50 (3.0-10.7)	9.4	2130 (560-2830)	3.99
	16 + 16 + 16 + 60	1.05	1.05	1.05	3.95	-	7.10 (1.9-8.8)	7.6	1700 (400-2360)	4.18	1.26	1.26	1.26	4.72	-	8.50 (3.0-10.7)	9.4	2130 (560-2830)	3.99
	16 + 16 + 20 + 20	1.58	1.58	1.97	1.97	-	7.10 (1.9-8.8)	7.9	1780 (340-2540)	3.99	1.89	1.89	2.36	2.36	-	8.50 (3.1-10.7)	9.7	2190 (520-2950)	3.88
4 rooms	16 + 16 + 20 + 25	1.48	1.48	1.84	2.30	-	7.10 (1.9-8.8)	7.9	1780 (340-2540)	3.99	1.77	1.77	2.20	2.76	-	8.50 (3.1-10.7)	9.7	2190 (520-2950)	3.88
	16 + 16 + 20 + 35	1.31	1.31	1.63	2.85	-	7.10 (1.9-8.8)	7.9	1780 (340-2500)	3.99	1.56	1.56	1.95	3.43	-	8.50 (3.0-10.7)	9.6	2170 (500-2930)	3.92
	16 + 16 + 20 + 42	1.21	1.21	1.51	3.17	-	7.10 (1.9-8.8)	7.8	1740 (370-2500)	4.08	1.45	1.45	1.80	3.80	-	8.50 (3.0-10.7)	9.5	2160 (520-2920)	3.94
	16 + 16 + 20 + 50	1.11	1.11	1.39	3.49	-	7.10 (1.9-8.8)	7.6	1700 (400-2320)	4.18	1.33	1.33	1.67	4.17	-	8.50 (3.0-10.7)	9.4	2120 (570-2820)	4.01
	16 + 16 + 20 + 60	1.01	1.01	1.27	3.81	-	7.10 (1.9-8.8)	7.6	1700 (400-2320)	4.18	1.21	1.21	1.52	4.56	-	8.50 (3.0-10.7)	9.4	2120 (570-2820)	4.01
	16 + 16 + 25 + 25	1.39	1.39	2.16	2.16	-	7.10 (1.9-8.8)	7.9	1780 (340-2540)	3.99	1.66	1.66	2.59	2.59	-	8.50 (3.1-10.7)	9.7	2190 (520-2950)	3.88
	16 + 16 + 25 + 35	1.23	1.23	1.93	2.71	-	7.10 (1.9-8.8)	7.9	1780 (340-2500)	3.99	1.48	1.48	2.31	3.23	-	8.50 (3.0-10.7)	9.6	2170 (500-2930)	3.92
	16 + 16 + 25 + 42	1.15	1.15	1.79	3.01	-	7.10 (1.9-8.8)	7.8	1740 (370-2500)	4.08	1.37	1.37	2.15	3.61	-	8.50 (3.0-10.7)	9.5	2160 (520-2920)	3.94
	16 + 16 + 25 + 50	1.06	1.06	1.66	3.32	-	7.10 (1.9-8.8)	7.6	1700 (400-2320)	4.18	1.27	1.27	1.99	3.97	-	8.50 (3.0-10.7)	9.4	2120 (570-2820)	4.01
	16 + 16 + 35 + 35	1.11	1.11	2.44	2.44	-	7.10 (1.9-8.8)	7.8	1740 (370-2450)	4.08	1.33	1.33	2.92	2.92	-	8.50 (3.0-10.7)	9.5	2150 (530-2900)	3.95
4 rooms	16 + 16 + 35 + 42	1.04	1.04	2.28	2.74	-	7.10 (1.9-8.8)	7.8	1740 (370-2450)	4.08	1.25	1.25	2.72	3.28	-	8.50 (3.0-10.7)	9.5	2140 (530-2890)	3.97
	16 + 20 + 20 + 20	1.49	1.87	1.87	1.87	-	7.10 (1.9-8.8)	7.9	1780 (340-2540)	3.99	1.78	2.24	2.24	2.24	-	8.50 (3.1-10.7)	9.6	2180 (520-2940)	3.90
	16 + 20 + 20 + 25	1.40	1.75	1.75	2.20	-	7.10 (1.9-8.8)	7.9	1780 (340-2540)	3.99	1.68	2.10	2.10	2.62	-	8.50 (3.1-10.7)	9.6	2180 (520-2940)	3.90
	16 + 20 + 20 + 35	1.25	1.56	1.56	2.73	-	7.10 (1.9-8.8)	7.8	1740 (370-2500)	4.08	1.49	1.87	1.87	3.27	-	8.50 (3.0-10.7)	9.5	2160 (520-2920)	3.94
	16 + 20 + 20 + 42	1.16	1.45	1.45	3.04	-	7.10 (1.9-8.8)	7.8	1740 (370-2500)	4.08	1.39	1.73	1.73	3.65	-	8.50 (3.0-10.7)	9.5	2150 (520-2910)	3.95
	16 + 20 + 20 + 50	1.07	1.34	1.34	3.35	-	7.10 (1.9-8.8)	7.6	1700 (420-2320)	4.18	1.28	1.60	1.60	4.02	-	8.50 (3.0-10.7)	9.4	2120 (590-2810)	4.01
	16 + 20 + 25 + 25	1.33	1.65	2.06	2.06	-	7.10 (1.9-8.8)	7.9	1780 (340-2540)	3.99	1.58	1.98	2.47	2.47	-	8.50 (3.1-10.7)	9.6	2180 (520-2940)	3.90
	16 + 20 + 25 + 35	1.18	1.48	1.85	2.59	-	7.10 (1.9-8.8)	7.8	1740 (370-2500)	4.08	1.42	1.77	2.21	3.10	-	8.50 (3.0-10.7)	9.5	2160 (520-2920)	3.94
	16 + 20 + 25 + 42	1.10	1.38	1.72	2.90	-	7.10 (1.9-8.8)	7.8	1740 (370-2500)	4.08	1.32	1.65	2.06	3.47	-	8.50 (3.0-10.7)	9.5	2150 (520-2910)	3.95
	16 + 20 + 25 + 50	1.02	1.28	1.60	3.20	-	7.10 (1.9-8.8)	7.6	1700 (420-2320)	4.18	1.23	1.53	1.91	3.83	-	8.50 (3.0-10.7)	9.4	2120 (590-2810)	4.01
4 rooms	16 + 20 + 35 + 35	1.07	1.34	2.34	2.35	-	7.10 (1.9-8.8)	7.8	1740 (370-2450)	4.08	1.28	1.60	2.81	2.81	-	8.50 (3.0-10.7)	9.5	2140 (530-2890)	3.97
	16 + 20 + 35 + 42	1.01	1.26	2.20	2.63	-	7.10 (1.9-8.8)	7.8	1740 (370-2450)	4.08	1.20	1.50	2.63	3.17	-	8.50 (3.0-10.7)	9.5	2140 (530-2890)	3.97
	16 + 25 + 25 + 25	1.25	1.95	1.95	1.95	-	7.10 (1.9-8.8)	7.9	1780 (340-2540)	3.99	1.48	2.34	2.34	2.34	-	8.50 (3.1-10.7)	9.6	2180 (520-2940)	3.90
	16 + 25 + 25 + 35	1.12	1.76	1.76	2.46	-	7.10 (1.9-8.8)	7.8	1740 (370-2500)	4.08	1.35	2.10	2.10	2.95	-	8.50 (3.0-10.7)	9.5	2160 (520-2920)	3.94
	16 + 25 + 25 + 42	1.05	1.64	1.64	2.77	-	7.10 (1.9-8.8)	7.8	1740 (370-2500)	4.08	1.25	1.97	1.97	3.31	-	8.50 (3.0-10.7)	9.5	2150 (520-2910)	3.95
	16 + 25 + 35 + 35	1.02	1.60	2.24	2.24	-	7.10 (1.9-8.8)	7.8	1740 (370-2450)	4.08	1.23	1.91	2.68	2.68	-	8.50 (3.0-10.7)	9.5	2140 (530-2890)	3.97
	20 + 20 + 20 + 20	1.77	1.77	1.77	1.77	-	7.08 (1.9-8.8)	7.8	1740 (340-2500)	4.07	2.12	2.12	2.12	2.12	-	8.48 (3.1-10.7)	9.6	2170 (520-2930)	3.91
	20 + 20 + 20 + 25	1.67	1.67	1.67	2.09	-	7.10 (1.9-8.8)	7.9	1780 (340-2500)	3.99	2.00	2.00	2.00	2.50	-	8.50 (3.1-10.7)	9.6	2170 (520-2930)	3.92
	20 + 20 + 20 + 35	1.49	1.49	1.49	2.63	-	7.10 (1.9-8.8)	7.8	1740 (370-2450)	4.08	1.79	1.79	1.79	3.13	-	8.50 (3.0-10.7)	9.5	2150 (520-2910)	3.95
	20 + 20 + 20 + 42	1.39	1.39	1.39	2.93	-	7.10 (1.9-8.8)	7.8	1740 (370-2450)	4.08	1.67	1.67	1.67	3.49	-	8.50 (3.0-10.7)	9.5	2150 (530-2900)	3.95
20 + 20 + 20 + 50	1.29	1.29	1.29	3.23	-	7.10 (1.9-8.8)	7.6	1700 (420-2320)	4.18	1.55	1.55	1.55	3.85	-	8.50 (3.0-10.7)	9.3	2110 (590-2810)	4.03	
20 + 20 + 25 + 25	1.58	1.58	1.97	1.97	-	7.10 (1.9-8.8)	7.9	1780											

CU-4Z71VBR: Free Multi Indoor Combination

Indoor Units Capacity	COOLING OPERATION										HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP	
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E					
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
4 rooms	20 + 25 + 25 + 25	1.49	1.87	1.87	1.87	-	7.10 (1.9-8.8)	7.9	1780 (340-2500)	3.99	1.78	2.24	2.24	2.24	-	8.50 (3.1-10.7)	9.6	2170 (520-2930)	3.92
	20 + 25 + 25 + 35	1.35	1.69	1.69	2.37	-	7.10 (1.9-8.8)	7.8	1740 (370-2450)	4.08	1.62	2.02	2.02	2.84	-	8.50 (3.0-10.7)	9.5	2150 (520-2910)	3.95
	20 + 25 + 25 + 42	1.27	1.58	1.58	2.67	-	7.10 (1.9-8.8)	7.8	1740 (370-2450)	4.08	1.51	1.90	1.90	3.19	-	8.50 (3.0-10.7)	9.5	2150 (530-2900)	3.95
	20 + 25 + 35 + 35	1.24	1.54	2.16	2.16	-	7.10 (1.9-8.8)	7.8	1740 (370-2450)	4.08	1.47	1.85	2.59	2.59	-	8.50 (3.0-10.7)	9.5	2140 (530-2890)	3.97
	25 + 25 + 25 + 25	1.77	1.77	1.77	1.77	-	7.08 (1.9-8.8)	7.8	1740 (340-2500)	4.07	2.12	2.12	2.12	2.12	-	8.48 (3.1-10.7)	9.6	2170 (520-2930)	3.91
	25 + 25 + 25 + 35	1.61	1.61	1.61	2.27	-	7.10 (1.9-8.8)	7.8	1740 (370-2450)	4.08	1.93	1.93	1.93	2.71	-	8.50 (3.0-10.7)	9.5	2150 (520-2910)	3.95

Note: At least two indoor units must be connected. When operating just one unit, minimum connected capacity must still be met, please refer Technical Manual for details.

CU-4Z80VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity	COOLING OPERATION										HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP	
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E					
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
1 room	16	1.60	-	-	-	-	1.60 (1.3-2.3)	2.0	420 (250-660)	3.81	2.60	-	-	-	-	2.60 (1.2-3.2)	3.0	640 (290-1000)	4.06
	20	2.00	-	-	-	-	2.00 (1.8-2.9)	2.5	520 (340-830)	3.85	3.20	-	-	-	-	3.20 (1.2-4.1)	3.7	780 (290-1270)	4.10
	25	2.50	-	-	-	-	2.50 (1.8-2.9)	3.1	650 (340-830)	3.85	3.60	-	-	-	-	3.60 (1.2-4.3)	4.7	980 (290-1270)	3.67
	35	3.50	-	-	-	-	3.50 (1.8-4.1)	4.4	960 (340-1380)	3.65	4.50	-	-	-	-	4.50 (1.2-5.8)	5.9	1270 (290-2140)	3.54
	42	4.20	-	-	-	-	4.20 (1.8-4.5)	6.2	1390 (340-2010)	3.02	5.60	-	-	-	-	5.60 (1.2-6.8)	7.8	1760 (290-2970)	3.18
	50	5.00	-	-	-	-	5.00 (1.9-5.4)	7.3	1630 (340-2150)	3.07	6.80	-	-	-	-	6.80 (1.2-6.9)	10.4	2350 (290-2840)	2.89
	60	6.00	-	-	-	-	6.00 (1.9-6.2)	8.9	2050 (340-2350)	2.93	8.50	-	-	-	-	8.50 (1.3-9.0)	10.8	2440 (320-2590)	3.48
	71	7.10	-	-	-	-	7.10 (2.0-7.2)	11.1	2550 (370-2790)	2.78	8.70	-	-	-	-	8.70 (1.4-9.2)	11.4	2590 (380-2760)	3.36
2 rooms	16+16	1.60	1.60	-	-	-	3.20 (2.3-5.8)	3.7	770 (350-2030)	4.16	2.60	2.60	-	-	-	5.20 (2.2-8.2)	7.5	1640 (430-2920)	3.17
	16+20	1.60	2.00	-	-	-	3.60 (2.3-5.8)	4.3	910 (340-2030)	3.96	2.58	3.22	-	-	-	5.80 (2.2-8.2)	7.9	1760 (430-2910)	3.30
	16+25	1.60	2.50	-	-	-	4.10 (2.3-5.8)	5.2	1110 (340-2030)	3.69	2.42	3.78	-	-	-	6.20 (2.2-8.2)	8.6	1900 (430-2910)	3.26
	16+35	1.60	3.50	-	-	-	5.10 (2.3-5.8)	7.0	1520 (340-1960)	3.36	2.23	4.87	-	-	-	7.10 (2.2-8.6)	9.3	2070 (380-2990)	3.43
	16+42	1.60	4.20	-	-	-	5.80 (2.3-6.7)	8.5	1860 (340-2520)	3.12	2.26	5.94	-	-	-	8.20 (2.2-9.8)	11.0	2450 (370-3520)	3.35
	16+50	1.60	5.00	-	-	-	6.60 (2.3-7.2)	9.6	2100 (320-2520)	3.14	2.28	7.12	-	-	-	9.40 (2.2-10.0)	11.4	2540 (330-3330)	3.70
	16+60	1.60	6.00	-	-	-	7.60 (2.3-8.5)	12.5	2730 (320-3530)	2.78	1.98	7.42	-	-	-	9.40 (2.2-10.0)	11.4	2540 (330-3330)	3.70
	16+71	1.47	6.53	-	-	-	8.00 (2.3-8.5)	13.2	2880 (320-3380)	2.78	1.73	7.67	-	-	-	9.40 (2.2-10.3)	11.2	2480 (320-3500)	3.79
	20+20	2.00	2.00	-	-	-	4.00 (2.3-5.8)	4.9	1050 (340-1970)	3.81	3.20	3.20	-	-	-	6.40 (2.2-8.2)	8.7	1940 (390-2900)	3.30
	20+25	2.00	2.50	-	-	-	4.50 (2.3-5.8)	5.9	1280 (340-1970)	3.52	3.02	3.78	-	-	-	6.80 (2.2-8.2)	9.0	2000 (390-2900)	3.40
	20+35	2.00	3.50	-	-	-	5.50 (2.3-5.8)	7.8	1690 (340-1900)	3.25	2.80	4.90	-	-	-	7.70 (2.2-8.6)	10.1	2250 (370-2930)	3.42
	20+42	2.00	4.20	-	-	-	6.20 (2.3-7.2)	9.7	2110 (340-2940)	2.94	2.84	5.96	-	-	-	8.80 (2.2-10.0)	11.3	2500 (370-3630)	3.52
	20+50	2.00	5.00	-	-	-	7.00 (2.3-8.1)	10.3	2250 (320-3140)	3.11	2.69	6.71	-	-	-	9.40 (2.2-10.0)	11.4	2530 (320-3310)	3.72
	20+60	2.00	6.00	-	-	-	8.00 (2.3-8.5)	13.5	2950 (320-3530)	2.71	2.35	7.05	-	-	-	9.40 (2.2-10.0)	11.4	2530 (320-3310)	3.72
	20+71	1.76	6.24	-	-	-	8.00 (2.3-8.5)	12.9	2810 (350-3380)	2.85	2.07	7.33	-	-	-	9.40 (2.2-10.3)	11.1	2470 (320-3480)	3.81
	25+25	2.50	2.50	-	-	-	5.00 (2.3-5.8)	6.8	1470 (340-1970)	3.40	3.60	3.60	-	-	-	7.20 (2.2-8.6)	9.6	2130 (390-3010)	3.38
	25+35	2.50	3.50	-	-	-	6.00 (2.3-6.7)	9.1	1980 (340-2520)	3.03	3.37	4.73	-	-	-	8.10 (2.2-9.8)	10.8	2400 (370-3520)	3.38
	25+42	2.50	4.20	-	-	-	6.70 (2.3-7.2)	11.2	2450 (340-2940)	2.73	3.43	5.77	-	-	-	9.20 (2.2-10.0)	11.9	2650 (370-3630)	3.47
	25+50	2.50	5.00	-	-	-	7.50 (2.3-8.5)	11.9	2590 (320-3530)	2.90	3.13	6.27	-	-	-	9.40 (2.2-10.0)	11.4	2530 (320-3310)	3.72
	25+60	2.35	5.65	-	-	-	8.00 (2.3-8.5)	13.5	2950 (320-3530)	2.71	2.76	6.64	-	-	-	9.40 (2.2-10.0)	11.4	2530 (320-3310)	3.72
	25+71	2.08	5.92	-	-	-	8.00 (2.3-8.5)	12.9	2810 (350-3380)	2.85	2.45	6.95	-	-	-	9.40 (2.2-10.3)	11.1	2470 (320-3480)	3.81
	35+35	3.50	3.50	-	-	-	7.00 (2.3-8.1)	11.9	2590 (330-3670)	2.70	4.50	4.50	-	-	-	9.00 (2.2-10.0)	11.4	2530 (360-3550)	3.56
	35+42	3.50	4.20	-	-	-	7.70 (2.3-8.5)	14.1	3080 (330-4160)	2.50	4.27	5.13	-	-	-	9.40 (2.2-10.0)	12.0	2670 (350-3540)	3.52
	35+50	3.29	4.71	-	-	-	8.00 (2.3-8.5)	12.9	2810 (320-3380)	2.85	3.87	5.53	-	-	-	9.40 (2.2-10.0)	11.1	2460 (320-3280)	3.82
35+60	2.95	5.05	-	-	-	8.00 (2.3-8.5)	12.9	2810 (320-3380)	2.85	3.46	5.94	-	-	-	9.40 (2.2-10.3)	11.1	2460 (320-3400)	3.82	
35+71	2.64	5.36	-	-	-	8.00 (2.3-8.6)	12.6	2740 (350-3380)	2.92	3.10	6.30	-	-	-	9.40 (2.2-10.5)	11.0	2440 (310-3510)	3.85	
42+42	4.00	4.00	-	-	-	8.00 (2.3-8.5)	15.5	3380 (330-4080)	2.37	4.70	4.70	-	-	-	9.40 (2.2-10.0)	12.0	2660 (350-3530)	3.53	
42+50	3.65	4.35	-	-	-	8.00 (2.3-8.5)	12.9	2810 (320-3380)	2.85	4.29	5.11	-	-	-	9.40 (2.2-10.3)	11.0	2440 (320-3390)	3.85	
42+60	3.29	4.71	-	-	-	8.00 (2.3-8.6)	12.9	2810 (320-3460)	2.85	3.87	5.53	-	-	-	9.40 (2.2-10.3)	11.0	2440 (320-3390)	3.85	
42+71	2.97	5.03	-	-	-	8.00 (2.3-8.6)	12.6	2740 (350-3300)	2.92	3.49	5.91	-	-	-	9.40 (2.2-10.5)	10.9	2430 (310-3500)	3.87	

CU-4Z80VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP	
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
2 rooms	50+50	4.00	4.00	-	-	-	8.00 (2.3-8.6)	11.3	2460 (340-2990)	3.25	4.70	4.70	-	-	-	9.40 (2.2-10.3)	10.3	2280 (310-3170)	4.12
	50+60	3.64	4.36	-	-	-	8.00 (2.3-8.6)	11.3	2460 (340-2990)	3.25	4.27	5.13	-	-	-	9.40 (2.2-10.5)	10.3	2280 (310-3230)	4.12
	50+71	3.31	4.69	-	-	-	8.00 (2.3-8.6)	11.0	2390 (340-2920)	3.35	3.88	5.52	-	-	-	9.40 (2.2-10.5)	10.2	2260 (310-3210)	4.16
	60+60	4.00	4.00	-	-	-	8.00 (2.3-8.6)	11.3	2460 (340-2990)	3.25	4.70	4.70	-	-	-	9.40 (2.2-10.5)	10.3	2280 (310-3230)	4.12
	60+71	3.66	4.34	-	-	-	8.00 (2.3-8.6)	11.0	2390 (340-2920)	3.35	4.31	5.09	-	-	-	9.40 (2.2-10.5)	10.2	2260 (310-3210)	4.16
	71+71	4.00	4.00	-	-	-	8.00 (2.3-8.6)	10.6	2320 (380-2840)	3.45	4.70	4.70	-	-	-	9.40 (2.2-10.5)	10.1	2250 (320-3200)	4.18
	16+16+16	1.60	1.60	1.60	-	-	4.80 (2.3-8.5)	5.3	1140 (350-3170)	4.21	2.60	2.60	2.60	-	-	7.80 (3.0-10.4)	9.0	2000 (440-3460)	3.90
	16+16+20	1.60	1.60	2.00	-	-	5.20 (2.3-8.5)	5.7	1240 (350-3170)	4.19	2.58	2.58	3.24	-	-	8.40 (3.0-10.4)	10.0	2230 (440-3380)	3.77
	16+16+25	1.60	1.60	2.50	-	-	5.70 (2.3-8.5)	6.7	1450 (350-3170)	3.93	2.47	2.47	3.86	-	-	8.80 (3.0-10.4)	10.0	2210 (440-3380)	3.98
	16+16+35	1.60	1.60	3.50	-	-	6.70 (2.3-8.5)	8.1	1770 (340-3090)	3.79	2.24	2.24	4.92	-	-	9.40 (3.0-10.4)	10.7	2370 (440-3350)	3.97
	16+16+42	1.60	1.60	4.20	-	-	7.40 (2.3-8.5)	9.8	2130 (340-3010)	3.47	2.03	2.03	5.34	-	-	9.40 (3.0-10.4)	10.6	2360 (430-3330)	3.98
	16+16+50	1.56	1.56	4.88	-	-	8.00 (2.3-8.6)	9.9	2160 (380-2790)	3.70	1.83	1.83	5.74	-	-	9.40 (3.0-10.4)	10.1	2250 (460-3120)	4.18
	16+16+60	1.39	1.39	5.22	-	-	8.00 (2.3-8.6)	9.9	2160 (380-2790)	3.70	1.63	1.63	6.14	-	-	9.40 (3.0-10.5)	10.1	2250 (460-3180)	4.18
	16+16+71	1.24	1.24	5.52	-	-	8.00 (2.3-8.8)	9.6	2100 (380-2860)	3.81	1.46	1.46	6.48	-	-	9.40 (3.0-10.5)	10.1	2240 (460-3160)	4.20
	16+20+20	1.60	2.00	2.00	-	-	5.60 (2.3-8.5)	6.5	1400 (350-3090)	4.00	2.58	3.21	3.21	-	-	9.00 (3.0-10.4)	10.1	2250 (440-3370)	4.00
	16+20+25	1.60	2.00	2.50	-	-	6.10 (2.3-8.5)	7.5	1610 (350-3090)	3.79	2.47	3.08	3.85	-	-	9.40 (3.0-10.4)	10.8	2390 (440-3370)	3.93
	16+20+35	1.60	2.00	3.50	-	-	7.10 (2.3-8.5)	8.9	1940 (340-3010)	3.66	2.12	2.65	4.63	-	-	9.40 (3.0-10.4)	10.6	2360 (430-3330)	3.98
	16+20+42	1.60	2.00	4.20	-	-	7.80 (2.3-8.5)	10.2	2230 (340-3010)	3.50	1.93	2.41	5.06	-	-	9.40 (3.0-10.4)	10.6	2350 (430-3320)	4.00
	16+20+50	1.49	1.86	4.65	-	-	8.00 (2.3-8.6)	9.9	2160 (380-2790)	3.70	1.75	2.19	5.46	-	-	9.40 (3.0-10.5)	10.1	2240 (460-3170)	4.20
	16+20+60	1.33	1.67	5.00	-	-	8.00 (2.3-8.6)	9.9	2160 (380-2790)	3.70	1.57	1.96	5.87	-	-	9.40 (3.0-10.5)	10.1	2240 (460-3170)	4.20
	16+20+71	1.20	1.50	5.30	-	-	8.00 (2.3-8.8)	9.6	2100 (380-2860)	3.81	1.41	1.76	6.23	-	-	9.40 (3.0-10.5)	10.0	2230 (460-3150)	4.22
	16+25+25	1.60	2.50	2.50	-	-	6.60 (2.3-8.5)	8.5	1850 (350-3090)	3.57	2.28	3.56	3.56	-	-	9.40 (3.0-10.4)	10.8	2390 (440-3370)	3.93
	16+25+35	1.60	2.50	3.50	-	-	7.60 (2.3-8.5)	10.3	2250 (340-3010)	3.38	1.98	3.09	4.33	-	-	9.40 (3.0-10.4)	10.6	2360 (430-3330)	3.98
	16+25+42	1.54	2.41	4.05	-	-	8.00 (2.3-8.6)	10.8	2350 (340-3090)	3.40	1.81	2.83	4.76	-	-	9.40 (3.0-10.4)	10.6	2350 (430-3320)	4.00
	16+25+50	1.41	2.20	4.39	-	-	8.00 (2.3-8.6)	9.9	2160 (380-2790)	3.70	1.65	2.58	5.17	-	-	9.40 (3.0-10.5)	10.1	2240 (460-3170)	4.20
16+25+60	1.27	1.98	4.75	-	-	8.00 (2.3-8.8)	9.9	2160 (380-2860)	3.70	1.49	2.33	5.58	-	-	9.40 (3.0-10.5)	10.1	2240 (460-3170)	4.20	
16+25+71	1.14	1.79	5.07	-	-	8.00 (2.3-8.8)	9.6	2100 (380-2860)	3.81	1.34	2.10	5.96	-	-	9.40 (3.0-10.6)	10.0	2230 (460-3210)	4.22	
16+35+35	1.48	3.26	3.26	-	-	8.00 (2.3-8.6)	10.5	2290 (340-3010)	3.49	1.74	3.83	3.83	-	-	9.40 (3.0-10.5)	10.5	2330 (460-3360)	4.03	
16+35+42	1.38	3.01	3.61	-	-	8.00 (2.3-8.6)	10.5	2290 (340-3010)	3.49	1.62	3.54	4.24	-	-	9.40 (3.0-10.5)	10.4	2320 (460-3280)	4.05	
16+35+50	1.27	2.77	3.96	-	-	8.00 (2.3-8.8)	9.6	2100 (380-2860)	3.81	1.49	3.26	4.65	-	-	9.40 (3.0-10.5)	10.0	2210 (490-3130)	4.25	
16+35+60	1.15	2.52	4.33	-	-	8.00 (2.3-8.8)	9.6	2100 (380-2860)	3.81	1.35	2.96	5.09	-	-	9.40 (3.0-10.6)	10.0	2210 (490-3190)	4.25	
16+35+71	1.05	2.30	4.65	-	-	8.00 (2.3-9.0)	9.6	2100 (380-2930)	3.81	1.23	2.70	5.47	-	-	9.40 (3.0-10.6)	9.9	2200 (490-3180)	4.27	
16+42+42	1.28	3.36	3.36	-	-	8.00 (2.3-8.8)	10.5	2290 (340-3160)	3.49	1.50	3.95	3.95	-	-	9.40 (3.0-10.5)	10.4	2310 (460-3270)	4.07	
16+42+50	1.19	3.11	3.70	-	-	8.00 (2.3-8.8)	9.6	2100 (380-2860)	3.81	1.39	3.66	4.35	-	-	9.40 (3.0-10.5)	10.0	2210 (490-3120)	4.25	
16+42+60	1.08	2.85	4.07	-	-	8.00 (2.3-9.0)	9.6	2100 (380-2930)	3.81	1.27	3.35	4.78	-	-	9.40 (3.0-10.6)	10.0	2210 (490-3180)	4.25	
16+42+71	0.99	2.60	4.41	-	-	8.00 (2.3-9.0)	9.4	2040 (380-2860)	3.92	1.17	3.06	5.17	-	-	9.40 (3.0-10.6)	9.9	2190 (490-3160)	4.29	
3 rooms	16+50+50	1.10	3.45	3.45	-	-	8.00 (2.3-8.8)	9.1	1980 (430-2640)	4.04	1.30	4.05	4.05	-	-	9.40 (3.0-10.6)	9.5	2120 (550-3050)	4.43
	16+50+60	1.02	3.17	3.81	-	-	8.00 (2.3-9.0)	9.1	1980 (430-2710)	4.04	1.19	3.73	4.48	-	-	9.40 (3.0-10.6)	9.5	2120 (550-3050)	4.43
	16+50+71	0.93	2.92	4.15	-	-	8.00 (2.3-9.0)	9.1	1980 (470-2710)	4.04	1.10	3.43	4.87	-	-	9.40 (3.0-10.6)	9.5	2110 (550-3040)	4.45
	16+60+60	0.94	3.53	3.53	-	-	8.00 (2.3-9.0)	9.1	1980 (430-2710)	4.04	1.10	4.15	4.15	-	-	9.40 (3.0-10.6)	9.5	2110 (550-3050)	4.43
	16+60+71	0.87	3.27	3.86	-	-	8.00 (2.3-9.0)	9.1	1980 (470-2710)	4.04	1.02	3.84	4.54	-	-	9.40 (3.0-10.6)	9.5	2110 (550-3040)	4.45
	20+20+20	2.00	2.00	2.00	-	-	6.00 (2.3-8.5)	7.2	1560 (340-3090)	3.85	3.13	3.13	3.13	-	-	9.39 (3.0-10.4)	10.7	2380 (440-3360)	3.95
	20+20+25	2.00	2.00	2.50	-	-	6.50 (2.3-8.5)	8.2	1790 (340-3090)	3.63	2.89	2.89	3.62	-	-	9.40 (3.0-10.4)	10.7	2380 (440-3360)	3.95
	20+20+35	2.00	2.00	3.50	-	-	7.50 (2.3-8.5)	9.7	2120 (340-3010)	3.54	2.51	2.51	4.38	-	-	9.40 (3.0-10.4)	10.6	2350 (430-3320)	4.00
	20+20+42	1.95	1.95	4.10	-	-	8.00 (2.3-8.6)	10.8	2350 (340-3090)	3.40	2.29	2.29	4.82	-	-	9.40 (3.0-10.4)	10.5	2340 (460-3310)	4.02
	20+20+50	1.78	1.78	4.44	-	-	8.00 (2.3-8.6)	9.6	2100 (380-2710)	3.81	2.09	2.09	5.22	-	-	9.40 (3.0-10.5)	10.0	2230 (460-3150)	4.22
	20+20+60	1.60	1.60	4.80	-	-	8.00 (2.3-8.8)	9.6	2100 (380-2860)	3.81	1.88	1.88	5.64	-	-	9.40 (3.0-10.5)	10.0	2230 (460-3150)	4.22
	20+20+71	1.44	1.44	5.12	-	-	8.00 (2.3-8.8)	9.6	2100 (380-2780)	3.81	1.69	1.69	6.02	-	-	9.40 (3.0-10.6)	10.0	2220 (460-3200)	4.23
	20+25+25	2.00	2.50	2.50	-	-	7.00 (2.3-8.5)	8.9	1950 (340-3090)	3.59	2.68	3.36	3.36	-	-	9.40 (3.0-10.4)	10.7	2380 (440-3360)	3.95
	20+25+35	2.00	2.50	3.50	-	-	8.00 (2.3-8.6)	10.8	2350 (340-3090)	3.40	2.35	2.94	4.11	-	-	9.40 (3.0-10.4)	10.6	2350 (430-3320)	4.00
	20+25+42	1.84	2.30	3.86	-	-	8.00 (2.3-8.6)	10.8	2350 (340-3090)	3.40	2.16	2.70	4.54	-	-	9.40 (3.0-10.5)	10.5	2340 (460-3370)	4.02
	20+25+50	1.68	2.11	4.21	-	-	8.00 (2.3-8.6)	9.6	2100 (380-2710)	3.81	1.98	2.47	4.95	-	-	9.40 (3.0-10.5)	10.0	2230 (460-3150)	4.22
	20+25+60	1.52	1.90	4.58	-	-	8.00 (2.3-8.8)	9.6	2100 (380-2860)	3.81	1.79	2.24	5.37	-	-	9.40 (3.0-10.5)	10.0	2230 (460-3150)	4.22
	20+25+71	1.38	1.72	4.90	-	-	8.00 (2.3-8.8)	9.6	2100 (380-2780)	3.81	1.62	2.03	5.75	-	-	9.40 (3.0-10.6)	10.0	2220 (460-3200)	4.23
	20+35+35	1.78	3.11	3.11	-	-	8												

CU-4Z80VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION									
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP		
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				Total	
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	A	W	W/W		
3 rooms	25+35+42	1.96	2.75	3.29	-	-	8.00 [2.3-8.8]	10.5	2290 [340-3160]	3.49	2.30	3.23	3.87	-	-	9.40 [3.0-10.5]	10.4	2310 [460-3270]	4.07
	25+35+50	1.82	2.55	3.63	-	-	8.00 [2.3-8.8]	9.6	2100 [380-2860]	3.81	2.14	2.99	4.27	-	-	9.40 [3.0-10.5]	10.0	2210 [490-3120]	4.25
	25+35+60	1.67	2.33	4.00	-	-	8.00 [2.3-9.0]	9.6	2100 [380-2930]	3.81	1.96	2.74	4.70	-	-	9.40 [3.0-10.6]	10.0	2210 [490-3180]	4.25
	25+35+71	1.53	2.14	4.33	-	-	8.00 [2.3-9.0]	9.4	2040 [380-2860]	3.92	1.79	2.51	5.10	-	-	9.40 [3.0-10.6]	9.9	2190 [490-3160]	4.29
	25+42+42	1.84	3.08	3.08	-	-	8.00 [2.3-8.8]	10.5	2290 [340-3090]	3.49	2.16	3.62	3.62	-	-	9.40 [3.0-10.5]	10.4	2300 [460-3260]	4.09
	25+42+50	1.71	2.87	3.42	-	-	8.00 [2.3-8.8]	9.6	2100 [380-2780]	3.81	2.01	3.37	4.02	-	-	9.40 [3.0-10.6]	9.9	2200 [490-3170]	4.27
	25+42+60	1.57	2.65	3.78	-	-	8.00 [2.3-9.0]	9.6	2100 [380-2930]	3.81	1.85	3.11	4.44	-	-	9.40 [3.0-10.6]	9.9	2200 [490-3170]	4.27
	25+42+71	1.45	2.43	4.12	-	-	8.00 [2.3-9.0]	9.4	2040 [380-2860]	3.92	1.70	2.86	4.84	-	-	9.40 [3.0-10.6]	9.9	2190 [490-3170]	4.29
	25+50+50	1.60	3.20	3.20	-	-	8.00 [2.3-9.0]	9.1	1980 [430-2710]	4.04	1.88	3.76	3.76	-	-	9.40 [3.0-10.6]	9.5	2110 [550-3040]	4.45
	25+50+60	1.48	2.96	3.56	-	-	8.00 [2.3-9.0]	9.1	1980 [430-2710]	4.04	1.74	3.48	4.18	-	-	9.40 [3.0-10.6]	9.5	2110 [550-3040]	4.45
	25+50+71	1.37	2.74	3.89	-	-	8.00 [2.3-9.0]	9.1	1980 [470-2710]	4.04	1.61	3.22	4.57	-	-	9.40 [3.0-10.6]	9.5	2100 [580-3030]	4.48
	25+60+60	1.38	3.31	3.31	-	-	8.00 [2.3-9.0]	9.1	1980 [430-2710]	4.04	1.62	3.89	3.89	-	-	9.40 [3.0-10.6]	9.5	2110 [550-3040]	4.45
	35+35+35	2.66	2.66	2.66	-	-	7.98 [2.3-8.8]	10.2	2230 [340-3090]	3.58	3.13	3.13	3.13	-	-	9.39 [3.0-10.5]	10.4	2300 [460-3250]	4.08
	35+35+42	2.50	2.50	3.00	-	-	8.00 [2.3-8.8]	10.2	2230 [340-3090]	3.59	2.94	2.94	3.52	-	-	9.40 [3.0-10.6]	10.3	2290 [460-3290]	4.10
	35+35+50	2.33	2.33	3.33	-	-	7.99 [2.3-9.0]	9.4	2040 [380-2930]	3.92	2.74	2.74	3.92	-	-	9.40 [3.0-10.6]	9.8	2180 [490-3150]	4.31
	35+35+60	2.15	2.15	3.70	-	-	8.00 [2.3-9.0]	9.4	2040 [380-2930]	3.92	2.53	2.53	4.34	-	-	9.40 [3.0-10.6]	9.8	2180 [490-3150]	4.31
	35+35+71	1.99	1.99	4.02	-	-	8.00 [2.3-9.0]	9.4	2040 [420-2860]	3.92	2.33	2.33	4.74	-	-	9.40 [3.0-10.6]	9.8	2170 [500-3130]	4.33
	35+42+42	2.36	2.82	2.82	-	-	8.00 [2.3-9.0]	10.2	2230 [340-3160]	3.59	2.76	3.32	3.32	-	-	9.40 [3.0-10.6]	10.3	2280 [460-3280]	4.12
	35+42+50	2.20	2.65	3.15	-	-	8.00 [2.3-9.0]	9.4	2040 [380-2860]	3.92	2.59	3.11	3.70	-	-	9.40 [3.0-10.6]	9.8	2170 [500-3140]	4.33
	35+42+60	2.04	2.45	3.51	-	-	8.00 [2.3-9.0]	9.4	2040 [380-2860]	3.92	2.40	2.88	4.12	-	-	9.40 [3.0-10.6]	9.8	2170 [500-3140]	4.33
	35+50+50	2.08	2.96	2.96	-	-	8.00 [2.3-9.0]	9.1	1980 [470-2710]	4.04	2.44	3.48	3.48	-	-	9.40 [3.0-10.6]	9.4	2090 [580-3010]	4.50
	35+50+60	1.93	2.76	3.31	-	-	8.00 [2.3-9.0]	9.1	1980 [470-2710]	4.04	2.27	3.24	3.89	-	-	9.40 [3.0-10.6]	9.4	2090 [580-3010]	4.50
	42+42+42	2.66	2.66	2.66	-	-	7.98 [2.3-9.0]	10.2	2230 [340-3160]	3.58	3.13	3.13	3.13	-	-	9.40 [3.0-10.6]	10.2	2270 [460-3270]	4.14
	42+42+50	2.51	2.51	2.98	-	-	8.00 [2.3-9.0]	9.4	2040 [380-2860]	3.92	2.95	2.95	3.50	-	-	9.40 [3.0-10.6]	9.8	2170 [500-3120]	4.33
	42+42+60	2.33	2.33	3.33	-	-	7.99 [2.3-9.0]	9.4	2040 [380-2860]	3.92	2.74	2.74	3.92	-	-	9.40 [3.0-10.6]	9.8	2170 [500-3120]	4.33
42+50+50	2.36	2.82	2.82	-	-	8.00 [2.3-9.0]	9.1	1980 [470-2710]	4.04	2.78	3.31	3.31	-	-	9.40 [3.0-10.6]	9.4	2090 [590-3000]	4.50	
4 rooms	16+16+16+16	1.60	1.60	1.60	1.60	-	6.40 [2.3-9.2]	6.8	1490 [420-2940]	4.30	2.35	2.35	2.35	2.35	-	9.40 [3.0-11.6]	9.5	2060 [490-3470]	4.56
	16+16+16+20	1.60	1.60	1.60	2.00	-	6.80 [2.3-9.2]	7.3	1600 [420-2870]	4.25	2.21	2.21	2.21	2.77	-	9.40 [3.0-11.6]	9.4	2050 [500-3460]	4.59
	16+16+16+25	1.60	1.60	1.60	2.50	-	7.30 [2.3-9.2]	7.9	1760 [420-2870]	4.15	2.06	2.06	2.06	3.22	-	9.40 [3.0-11.6]	9.4	2050 [500-3460]	4.59
	16+16+16+35	1.54	1.54	1.54	3.38	-	8.00 [2.3-9.2]	8.9	1980 [420-2870]	4.04	1.81	1.81	1.81	3.97	-	9.40 [3.0-11.6]	9.3	2030 [500-3420]	4.63
	16+16+16+42	1.42	1.42	1.42	3.74	-	8.00 [2.3-9.2]	8.9	1980 [420-2870]	4.04	1.67	1.67	1.67	4.39	-	9.40 [3.0-11.6]	9.3	2020 [510-3410]	4.65
	16+16+16+50	1.31	1.31	1.31	4.07	-	8.00 [2.3-9.2]	8.5	1880 [480-2730]	4.26	1.53	1.53	1.53	4.81	-	9.40 [3.0-11.6]	9.2	2000 [600-3340]	4.70
	16+16+16+60	1.19	1.19	1.19	4.43	-	8.00 [2.3-9.2]	8.5	1880 [480-2730]	4.26	1.39	1.39	1.39	5.23	-	9.40 [3.0-11.6]	9.2	2000 [600-3340]	4.70
	16+16+16+71	1.08	1.08	1.08	4.76	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.26	1.26	1.26	5.62	-	9.40 [3.0-11.6]	9.1	1990 [630-3320]	4.72
	16+16+20+20	1.60	1.60	2.00	2.00	-	7.20 [2.3-9.2]	7.8	1710 [420-2870]	4.21	2.09	2.09	2.61	2.61	-	9.40 [3.0-11.6]	9.4	2040 [500-3440]	4.61
	16+16+20+25	1.60	1.60	2.00	2.50	-	7.70 [2.3-9.2]	8.4	1870 [420-2870]	4.12	1.95	1.95	2.44	3.06	-	9.40 [3.0-11.6]	9.4	2040 [500-3440]	4.61
	16+16+20+35	1.47	1.47	1.84	3.22	-	8.00 [2.3-9.2]	8.7	1930 [420-2870]	4.15	1.73	1.73	2.16	3.78	-	9.40 [3.0-11.6]	9.3	2020 [510-3410]	4.65
	16+16+20+42	1.36	1.36	1.70	3.58	-	8.00 [2.3-9.2]	8.7	1930 [420-2870]	4.15	1.60	1.60	2.00	4.20	-	9.40 [3.0-11.6]	9.3	2020 [530-3400]	4.65
	16+16+20+50	1.25	1.25	1.57	3.93	-	8.00 [2.3-9.2]	8.5	1880 [480-2660]	4.26	1.47	1.47	1.84	4.62	-	9.40 [3.0-11.6]	9.1	1990 [620-3330]	4.72
	16+16+20+60	1.14	1.14	1.43	4.29	-	8.00 [2.3-9.2]	8.5	1880 [480-2660]	4.26	1.34	1.34	1.68	5.04	-	9.40 [3.0-11.6]	9.1	1990 [620-3330]	4.72
	16+16+20+71	1.04	1.04	1.30	4.62	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.22	1.22	1.53	5.43	-	9.40 [3.0-11.6]	9.1	1980 [630-3310]	4.75
	16+16+25+25	1.56	1.56	2.44	2.44	-	8.00 [2.3-9.2]	8.9	1980 [420-2870]	4.04	1.83	1.83	2.87	2.87	-	9.40 [3.0-11.6]	9.4	2040 [500-3440]	4.61
	16+16+25+35	1.39	1.39	2.17	3.05	-	8.00 [2.3-9.2]	8.7	1930 [420-2870]	4.15	1.63	1.63	2.55	3.59	-	9.40 [3.0-11.6]	9.3	2020 [510-3410]	4.65
	16+16+25+42	1.29	1.29	2.02	3.40	-	8.00 [2.3-9.2]	8.7	1930 [420-2870]	4.15	1.52	1.52	3.37	3.99	-	9.40 [3.0-11.6]	9.3	2020 [530-3400]	4.65
	16+16+25+50	1.20	1.20	1.87	3.73	-	8.00 [2.3-9.2]	8.5	1880 [480-2660]	4.26	1.41	1.41	2.20	4.38	-	9.40 [3.0-11.6]	9.1	1990 [620-3330]	4.72
	16+16+25+60	1.09	1.09	1.71	4.11	-	8.00 [2.3-9.2]	8.5	1880 [480-2660]	4.26	1.29	1.29	2.01	4.81	-	9.40 [3.0-11.6]	9.1	1990 [620-3330]	4.72
	16+16+25+71	1.00	1.00	1.56	4.44	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.18	1.18	1.84	5.20	-	9.40 [3.0-11.6]	9.1	1980 [630-3310]	4.75
	16+16+35+35	1.25	1.25	2.75	2.75	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.47	1.47	3.23	3.23	-	9.40 [3.0-11.6]	9.2	2010 [540-3380]	4.68
	16+16+35+42	1.17	1.17	2.57	3.09	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.38	1.38	3.02	3.62	-	9.40 [3.0-11.6]	9.2	2000 [540-3360]	4.70
	16+16+35+50	1.09	1.09	2.39	3.43	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.29	1.29	2.81	4.01	-	9.40 [3.0-11.6]	9.1	1980 [640-3300]	4.75
	16+16+35+60	1.01	1.01	2.20	3.78	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.18	1.18	2.59	4.45	-	9.40 [3.0-11.6]	9.1	1980 [640-3300]	4.75
	16+16+35+71	0.93	0.93	2.03	4.11	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.09	1.09	2.38	4.84	-	9.40 [3.0-11.6]	9.0	1970 [650-3290]	4.77
	16+16+42+42	1.10	1.10	2.90	2.90	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.30	1.30	3.40	3.40	-	9.40 [3.0-11.6]	9.1	1990 [550-3350]	4.72
	16+16+42+50	1.03	1.03	2.71	3.23	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.21	1.21	3.18	3.80	-	9.40 [3.0-11.6]	9.0	1970 [650-3290]	4.77
	16+16+42+60	0.96	0.96	2.51	3.57	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.12	1.12	2.95	4.21	-	9.40 [3.0-11.6]	9.0	1970 [650-3290]	4.77
	16+16+42+71	0.88	0.88	2.32	3.92	-	8.00 [2.3-9.2]	8.5	1880 [530-2660]	4.26	1.04	1.04	2.72	4.60	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77
	16+16+50+50	0.97	0.97	3.03	3.03	-	8.00 [2.3-9.2]	8.5	1890 [580-2600]	4.23	1.14	1.14	3.56	3.56	-	9.40 [3.0-11.6]	9.2	2010 [780-3300]	4.68
	16+16+50+60	0.90	0.90	2.82	3.38	-	8.00 [2.3-9.2]	8.5	1890 [580-2600]	4.23	1.06	1.06	3.31	3.97	-	9.40 [3.0-11.6]	9.2	2010 [780-3300]	4.68
	16+20+20+20	1.60	2.00	2.00	2.00														

CU-4Z80VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP	
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				Total
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
16+20+42+42	1.07	1.33	2.80	2.80	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.25	1.57	3.29	3.29	-	9.40 [3.0-11.6]	9.1	1990 [550-3340]	4.72
16+20+42+50	1.00	1.25	2.63	3.12	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.18	1.47	3.08	3.67	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77
16+20+42+60	0.93	1.16	2.43	3.48	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.09	1.36	2.86	4.09	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77
16+20+50+50	0.94	1.18	2.94	2.94	-	8.00 [2.3-9.2]	8.5	1890 [590-2610]	4.23	1.10	1.38	3.46	3.46	-	9.40 [3.0-11.6]	9.2	2010 [790-3300]	4.68
16+20+50+60	0.88	1.10	2.74	3.28	-	8.00 [2.3-9.2]	8.5	1890 [590-2610]	4.23	1.03	1.29	3.22	3.86	-	9.40 [3.0-11.6]	9.2	2010 [790-3300]	4.68
16+25+25+25	1.40	2.20	2.20	2.20	-	8.00 [2.3-9.2]	8.9	1980 [420-2870]	4.04	1.66	2.58	2.58	2.58	-	9.40 [3.0-11.6]	9.4	2040 [500-3430]	4.61
16+25+25+35	1.27	1.98	1.98	2.77	-	8.00 [2.3-9.2]	8.7	1930 [420-2800]	4.15	1.49	2.33	2.33	3.25	-	9.40 [3.0-11.6]	9.3	2020 [530-3400]	4.65
16+25+25+42	1.19	1.85	1.85	3.11	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.39	2.18	2.18	3.65	-	9.40 [3.0-11.6]	9.2	2010 [530-3380]	4.68
16+25+25+50	1.10	1.72	1.72	3.46	-	8.00 [2.3-9.2]	8.5	1880 [480-2660]	4.26	1.30	2.03	2.03	4.04	-	9.40 [3.0-11.6]	9.1	1990 [630-3320]	4.72
16+25+25+60	1.02	1.59	1.59	3.80	-	8.00 [2.3-9.2]	8.5	1880 [480-2660]	4.26	1.19	1.87	1.87	4.47	-	9.40 [3.0-11.6]	9.1	1990 [630-3320]	4.72
16+25+25+71	0.93	1.46	1.46	4.15	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.10	1.72	1.72	4.86	-	9.40 [3.0-11.6]	9.1	1980 [640-3300]	4.75
16+25+35+35	1.15	1.81	2.52	2.52	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.35	2.13	2.96	2.96	-	9.40 [3.0-11.6]	9.2	2000 [540-3360]	4.70
16+25+35+42	1.08	1.69	2.37	2.86	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.27	1.99	2.79	3.35	-	9.40 [3.0-11.6]	9.1	1990 [550-3350]	4.72
16+25+35+50	1.02	1.59	2.22	3.17	-	8.00 [2.3-9.2]	8.5	1880 [480-2660]	4.26	1.19	1.87	2.61	3.73	-	9.40 [3.0-11.6]	9.0	1970 [630-3290]	4.77
16+25+35+60	0.94	1.47	2.06	3.53	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.10	1.73	2.42	4.15	-	9.40 [3.0-11.6]	9.0	1970 [650-3290]	4.77
16+25+35+71	0.87	1.36	1.90	3.87	-	8.00 [2.3-9.2]	8.5	1880 [530-2660]	4.26	1.02	1.60	2.24	4.54	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77
16+25+42+42	1.02	1.60	2.69	2.69	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.20	1.88	3.16	3.16	-	9.40 [3.0-11.6]	9.1	1990 [550-3340]	4.72
16+25+42+50	0.96	1.50	2.53	3.01	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.13	1.77	2.97	3.53	-	9.40 [3.0-11.6]	9.0	1970 [630-3280]	4.77
16+25+42+60	0.90	1.40	2.35	3.35	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.05	1.64	2.76	3.95	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77
16+25+50+50	0.90	1.42	2.84	2.84	-	8.00 [2.3-9.2]	8.5	1890 [590-2610]	4.23	1.07	1.67	3.33	3.33	-	9.40 [3.0-11.6]	9.2	2010 [790-3300]	4.68
16+35+35+35	1.07	2.31	2.31	2.31	-	8.00 [2.3-9.2]	8.7	1930 [470-2800]	4.15	1.24	2.72	2.72	2.72	-	9.40 [3.0-11.6]	9.1	1980 [550-3330]	4.75
16+35+35+42	1.00	2.19	2.19	2.62	-	8.00 [2.3-9.2]	8.7	1930 [470-2730]	4.15	1.18	2.57	2.57	3.08	-	9.40 [3.0-11.6]	9.1	1980 [580-3320]	4.75
16+35+35+50	0.94	2.06	2.06	2.94	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.11	2.42	2.42	3.45	-	9.40 [3.0-11.6]	9.2	2000 [680-3260]	4.70
16+35+35+60	0.88	1.92	1.92	3.28	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.03	2.25	2.25	3.87	-	9.40 [3.0-11.6]	9.2	2000 [680-3260]	4.70
16+35+42+42	0.95	2.07	2.49	2.49	-	8.00 [2.3-9.2]	8.7	1930 [470-2730]	4.15	1.11	2.45	2.92	2.92	-	9.40 [3.0-11.6]	9.0	1970 [580-3370]	4.77
16+35+42+50	0.90	1.96	2.35	2.79	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.05	2.30	2.76	3.29	-	9.40 [3.0-11.6]	9.2	2000 [690-3310]	4.70
16+42+42+42	0.89	2.37	2.37	2.37	-	8.00 [2.3-9.2]	8.7	1930 [470-2730]	4.15	1.06	2.78	2.78	2.78	-	9.40 [3.0-11.6]	9.0	1970 [590-3360]	4.77
20+20+20+20	2.00	2.00	2.00	2.00	-	8.00 [2.3-9.2]	8.9	1980 [420-2870]	4.04	2.35	2.35	2.35	2.35	-	9.40 [3.0-11.6]	9.3	2030 [500-3420]	4.63
20+20+20+25	1.88	1.88	1.88	2.36	-	8.00 [2.3-9.2]	8.9	1980 [420-2870]	4.04	2.21	2.21	2.21	2.77	-	9.40 [3.0-11.6]	9.3	2030 [500-3420]	4.63
20+20+20+35	1.68	1.68	1.68	2.96	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.98	1.98	1.98	3.46	-	9.40 [3.0-11.6]	9.2	2010 [530-3380]	4.68
20+20+20+42	1.57	1.57	1.57	3.29	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.84	1.84	1.84	3.88	-	9.40 [3.0-11.6]	9.2	2000 [540-3370]	4.70
20+20+20+50	1.45	1.45	1.45	3.65	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.71	1.71	1.71	4.27	-	9.40 [3.0-11.6]	9.1	1980 [640-3310]	4.75
20+20+20+60	1.33	1.33	1.33	4.01	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.57	1.57	1.57	4.69	-	9.40 [3.0-11.6]	9.1	1980 [640-3310]	4.75
20+20+20+71	1.22	1.22	1.22	4.34	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.44	1.44	1.44	5.08	-	9.40 [3.0-11.6]	9.0	1970 [640-3290]	4.77
20+20+25+25	1.78	1.78	2.22	2.22	-	8.00 [2.3-9.2]	8.9	1980 [420-2870]	4.04	2.09	2.09	2.61	2.61	-	9.40 [3.0-11.6]	9.3	2030 [500-3420]	4.63
20+20+25+35	1.60	1.60	2.00	2.80	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.88	1.88	2.35	3.29	-	9.40 [3.0-11.6]	9.2	2010 [530-3380]	4.68
20+20+25+42	1.50	1.50	1.87	3.13	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.76	1.76	2.20	3.68	-	9.40 [3.0-11.6]	9.2	2000 [540-3370]	4.70
20+20+25+50	1.39	1.39	1.74	3.48	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.63	1.63	2.04	4.10	-	9.40 [3.0-11.6]	9.1	1980 [640-3310]	4.75
20+20+25+60	1.28	1.28	1.60	3.84	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.50	1.50	1.88	4.52	-	9.40 [3.0-11.6]	9.1	1980 [640-3310]	4.75
20+20+25+71	1.18	1.18	1.47	4.17	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.38	1.38	1.73	4.91	-	9.40 [3.0-11.6]	9.0	1970 [640-3290]	4.77
20+20+35+35	1.45	1.45	2.55	2.55	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.71	1.71	2.99	2.99	-	9.40 [3.0-11.6]	9.1	1990 [550-3350]	4.72
20+20+35+42	1.37	1.37	2.39	2.87	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.61	1.61	2.81	3.37	-	9.40 [3.0-11.6]	9.1	1990 [550-3350]	4.72
20+20+35+50	1.28	1.28	2.24	3.20	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.50	1.50	2.63	3.77	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77
20+20+35+60	1.19	1.19	2.07	3.55	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.39	1.39	2.44	4.18	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77
20+20+35+71	1.10	1.10	1.92	3.88	-	8.00 [2.3-9.2]	8.5	1880 [530-2660]	4.26	1.29	1.29	2.25	4.57	-	9.40 [3.0-11.6]	9.2	2000 [680-3270]	4.70
20+20+42+42	1.29	1.29	2.71	2.71	-	8.00 [2.3-9.2]	8.7	1930 [460-2800]	4.15	1.52	1.52	3.18	3.18	-	9.40 [3.0-11.6]	9.1	1980 [570-3330]	4.75
20+20+42+50	1.21	1.21	2.55	3.03	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.42	1.42	2.99	3.57	-	9.40 [3.0-11.6]	9.2	2000 [680-3270]	4.70
20+20+42+60	1.13	1.13	2.37	3.37	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.32	1.32	2.78	3.98	-	9.40 [3.0-11.6]	9.2	2000 [680-3270]	4.70
20+20+50+50	1.14	1.14	2.86	2.86	-	8.00 [2.3-9.2]	8.5	1890 [590-2610]	4.23	1.34	1.34	3.36	3.36	-	9.40 [3.0-11.6]	9.2	2000 [800-3290]	4.70
20+25+25+25	1.67	2.11	2.11	2.11	-	8.00 [2.3-9.2]	8.9	1980 [420-2870]	4.04	1.99	2.47	2.47	2.47	-	9.40 [3.0-11.6]	9.3	2030 [500-3420]	4.63
20+25+25+35	1.52	1.90	1.90	2.68	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.79	2.24	2.24	3.13	-	9.40 [3.0-11.6]	9.2	2010 [530-3380]	4.68
20+25+25+42	1.43	1.79	1.79	2.99	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.68	2.10	2.10	3.52	-	9.40 [3.0-11.6]	9.2	2000 [540-3370]	4.70
20+25+25+50	1.33	1.67	1.67	3.33	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.57	1.96	1.96	3.91	-	9.40 [3.0-11.6]	9.1	1980 [640-3310]	4.75
20+25+25+60	1.23	1.54	1.54	3.69	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.45	1.81	1.81	4.33	-	9.40 [3.0-11.6]	9.1	1980 [640-3310]	4.75
20+25+25+71	1.13	1.42	1.42	4.03	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.33	1.67	1.67	4.73	-	9.40 [3.0-11.6]	9.0	1970 [640-3290]	4.77
20+25+35+35	1.39	1.75	2.43	2.43	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.63	2.05	2.86	2.86	-	9.40 [3.0-11.6]	9.1	1990 [550-3350]	4.72
20+25+35+42	1.31	1.64	2.30	2.75	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.54	1.93	2.70	3.23	-	9.40 [3.0-11.6]	9.1	1990 [550-3340]	4.72
20+																		

CU-4Z80VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
4 rooms	20+42+42+42	1.10	2.30	2.30	2.30	-	8.00 [2.3-9.2]	8.4	1870 [470-2730]	4.28	1.30	2.70	2.70	2.70	-	9.40 [3.0-11.6]	9.2	2000 [590-3350]	4.70
	25+25+25+25	2.00	2.00	2.00	2.00	-	8.00 [2.3-9.2]	8.9	1980 [420-2870]	4.04	2.35	2.35	2.35	2.35	-	9.40 [3.0-11.6]	9.3	2030 [500-3420]	4.63
	25+25+25+35	1.82	1.82	1.82	2.54	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	2.14	2.14	2.14	2.98	-	9.40 [3.0-11.6]	9.2	2010 [530-3380]	4.68
	25+25+25+42	1.71	1.71	1.71	2.87	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	2.01	2.01	2.01	3.37	-	9.40 [3.0-11.6]	9.2	2000 [540-3370]	4.70
	25+25+25+50	1.60	1.60	1.60	3.20	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.88	1.88	1.88	3.76	-	9.40 [3.0-11.6]	9.1	1980 [640-3310]	4.75
	25+25+25+60	1.48	1.48	1.48	3.56	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.74	1.74	1.74	4.18	-	9.40 [3.0-11.6]	9.1	1980 [640-3310]	4.75
	25+25+25+71	1.37	1.37	1.37	3.89	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.61	1.61	1.61	4.57	-	9.40 [3.0-11.6]	9.0	1970 [640-3290]	4.77
	25+25+35+35	1.67	1.67	2.33	2.33	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.96	1.96	2.74	2.74	-	9.40 [3.0-11.6]	9.1	1990 [550-3350]	4.72
	25+25+35+42	1.57	1.57	2.20	2.66	-	8.00 [2.3-9.2]	8.7	1930 [430-2800]	4.15	1.85	1.85	2.59	3.11	-	9.40 [3.0-11.6]	9.1	1990 [550-3340]	4.72
	25+25+35+50	1.48	1.48	2.07	2.97	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.74	1.74	2.44	3.48	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77
	25+25+35+60	1.38	1.38	1.93	3.31	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.62	1.62	2.27	3.89	-	9.40 [3.0-11.6]	9.0	1970 [670-3280]	4.77
	25+25+42+42	1.49	1.49	2.51	2.51	-	8.00 [2.3-9.2]	8.7	1930 [460-2800]	4.15	1.75	1.75	2.95	2.95	-	9.40 [3.0-11.6]	9.1	1980 [570-3330]	4.75
	25+25+42+50	1.41	1.41	2.37	2.81	-	8.00 [2.3-9.2]	8.5	1880 [520-2660]	4.26	1.65	1.65	2.78	3.32	-	9.40 [3.0-11.6]	9.2	2000 [680-3270]	4.70
	25+35+35+35	1.55	2.15	2.15	2.15	-	8.00 [2.3-9.2]	8.7	1930 [470-2730]	4.15	1.81	2.53	2.53	2.53	-	9.40 [3.0-11.6]	9.1	1980 [580-3320]	4.75
	25+35+35+42	1.46	2.04	2.04	2.46	-	8.00 [2.3-9.2]	8.7	1930 [470-2730]	4.15	1.72	2.40	2.40	2.88	-	9.40 [3.0-11.6]	9.0	1970 [580-3370]	4.77
	25+35+35+50	1.38	1.93	1.93	2.76	-	8.00 [2.3-9.2]	8.5	1880 [530-2660]	4.26	1.62	2.27	2.27	3.24	-	9.40 [3.0-11.6]	9.2	2000 [690-3310]	4.70
	25+35+42+42	1.39	1.95	2.33	2.33	-	8.00 [2.3-9.2]	8.7	1930 [470-2730]	4.15	1.63	2.29	2.74	2.74	-	9.40 [3.0-11.6]	9.0	1970 [590-3360]	4.77
	35+35+35+35	2.00	2.00	2.00	2.00	-	8.00 [2.3-9.2]	8.4	1870 [470-2730]	4.28	2.35	2.35	2.35	2.35	-	9.40 [3.0-11.6]	9.2	2000 [590-3350]	4.70
35+35+35+42	1.90	1.90	1.90	2.30	-	8.00 [2.3-9.2]	8.4	1870 [470-2730]	4.28	2.24	2.24	2.24	2.68	-	9.40 [3.0-11.6]	9.2	2000 [600-3340]	4.70	

Note: At least two indoor units must be connected. When operating just one unit, minimum connected capacity must still be met, please refer Technical Manual for details.

CU-4Z80VBR: Free Multi Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
1 room	16	1.60	-	-	-	-	1.60 [1.3-2.3]	2.2	450 [250-690]	3.56	2.60	-	-	-	-	2.60 [1.2-3.2]	3.2	700 [290-1060]	3.71
	20	2.00	-	-	-	-	2.00 [1.8-2.9]	2.6	550 [340-860]	3.64	3.20	-	-	-	-	3.20 [1.2-4.1]	3.9	840 [290-1330]	3.81
	25	2.50	-	-	-	-	2.50 [1.8-2.9]	3.2	680 [340-860]	3.68	3.60	-	-	-	-	3.60 [1.2-4.3]	4.9	1040 [290-1330]	3.46
	35	3.50	-	-	-	-	3.50 [1.8-4.1]	4.6	990 [340-1410]	3.54	4.50	-	-	-	-	4.50 [1.2-5.8]	6.2	1330 [290-2200]	3.38
	42	4.20	-	-	-	-	4.20 [1.8-4.5]	6.3	1420 [340-2040]	2.96	5.60	-	-	-	-	5.60 [1.2-6.8]	8.0	1820 [290-3030]	3.08
	50	5.00	-	-	-	-	5.00 [1.9-5.4]	7.3	1630 [340-2150]	3.07	6.80	-	-	-	-	6.80 [1.2-6.9]	10.4	2350 [290-2840]	2.89
	60	6.00	-	-	-	-	6.00 [1.9-6.2]	9.0	2080 [340-2380]	2.88	8.50	-	-	-	-	8.50 [1.3-9.0]	11.0	2500 [320-2650]	3.40
2 rooms	71	7.10	-	-	-	-	7.10 [2.0-7.2]	11.2	2580 [370-2820]	2.75	8.70	-	-	-	-	8.70 [1.4-9.2]	11.7	2650 [380-2820]	3.28
	16+16	1.60	1.60	-	-	-	3.20 [2.3-5.8]	4.0	830 [350-2090]	3.86	2.60	2.60	-	-	-	5.20 [2.2-8.2]	7.9	1760 [430-3040]	2.95
	16+20	1.60	2.00	-	-	-	3.60 [2.3-5.8]	4.6	970 [340-2090]	3.71	2.58	3.22	-	-	-	5.80 [2.2-8.2]	8.5	1880 [430-3030]	3.09
	16+25	1.60	2.50	-	-	-	4.10 [2.3-5.8]	5.5	1170 [340-2090]	3.50	2.42	3.78	-	-	-	6.20 [2.2-8.2]	9.1	2020 [430-3030]	3.07
	16+35	1.60	3.50	-	-	-	5.10 [2.3-5.8]	7.3	1580 [340-2020]	3.23	2.23	4.87	-	-	-	7.10 [2.2-8.6]	9.9	2190 [380-3110]	3.24
	16+42	1.60	4.20	-	-	-	5.80 [2.3-6.7]	8.8	1920 [340-2580]	3.02	2.26	5.94	-	-	-	8.20 [2.2-9.8]	11.6	2570 [370-3640]	3.19
	16+50	1.60	5.00	-	-	-	6.60 [2.3-7.2]	9.9	2160 [320-2580]	3.06	2.28	7.12	-	-	-	9.40 [2.2-10.0]	12.0	2660 [330-3450]	3.53
	16+60	1.60	6.00	-	-	-	7.60 [2.3-8.5]	12.8	2790 [320-3590]	2.72	1.98	7.42	-	-	-	9.40 [2.2-10.0]	12.0	2660 [330-3450]	3.53
	16+71	1.47	6.53	-	-	-	8.00 [2.3-8.5]	13.5	2940 [320-3440]	2.72	1.73	7.67	-	-	-	9.40 [2.2-10.3]	11.7	2600 [320-3620]	3.62
	20+20	2.00	2.00	-	-	-	4.00 [2.3-5.8]	5.2	1110 [340-2030]	3.60	3.20	3.20	-	-	-	6.40 [2.2-8.2]	9.3	2060 [390-3020]	3.11
	20+25	2.00	2.50	-	-	-	4.50 [2.3-5.8]	6.2	1340 [340-2030]	3.36	3.02	3.78	-	-	-	6.80 [2.2-8.2]	9.5	2120 [390-3020]	3.21
	20+35	2.00	3.50	-	-	-	5.50 [2.3-5.8]	8.0	1750 [340-1960]	3.14	2.80	4.90	-	-	-	7.70 [2.2-8.6]	10.7	2370 [370-3050]	3.25
	20+42	2.00	4.20	-	-	-	6.20 [2.3-7.2]	10.0	2170 [340-3000]	2.86	2.84	5.96	-	-	-	8.80 [2.2-10.0]	11.8	2620 [370-3750]	3.36
	20+50	2.00	5.00	-	-	-	7.00 [2.3-8.1]	10.6	2310 [320-3200]	3.03	2.69	6.71	-	-	-	9.40 [2.2-10.0]	11.9	2650 [320-3430]	3.55
20+60	2.00	6.00	-	-	-	8.00 [2.3-8.5]	13.8	3010 [320-3590]	2.66	2.35	7.05	-	-	-	9.40 [2.2-10.0]	11.9	2650 [320-3430]	3.55	

CU-4Z80VBR: Free Multi Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
2 rooms	20+71	1.76	6.24	-	-	-	8.00 [2.3-8.5]	13.2	2870 (350-3440)	2.79	2.07	7.33	-	-	-	9.40 [2.2-10.3]	11.7	2590 (320-3600)	3.63
	25+25	2.50	2.50	-	-	-	5.00 [2.3-5.8]	7.1	1530 (340-2030)	3.27	3.60	3.60	-	-	-	7.20 [2.2-8.6]	10.1	2250 (390-3130)	3.20
	25+35	2.50	3.50	-	-	-	6.00 [2.3-6.7]	9.4	2040 (340-2580)	2.94	3.37	4.73	-	-	-	8.10 [2.2-9.8]	11.3	2520 (370-3640)	3.21
	25+42	2.50	4.20	-	-	-	6.70 [2.3-7.2]	11.5	2510 (340-3000)	2.67	3.43	5.77	-	-	-	9.20 [2.2-10.0]	12.5	2770 (370-3750)	3.32
	25+50	2.50	5.00	-	-	-	7.50 [2.3-8.5]	12.2	2650 (320-3590)	2.83	3.13	6.27	-	-	-	9.40 [2.2-10.0]	11.9	2650 (320-3430)	3.55
	25+60	2.35	5.65	-	-	-	8.00 [2.3-8.5]	13.8	3010 (320-3590)	2.66	2.76	6.64	-	-	-	9.40 [2.2-10.0]	11.9	2650 (320-3430)	3.55
	25+71	2.08	5.92	-	-	-	8.00 [2.3-8.5]	13.2	2870 (350-3440)	2.79	2.45	6.95	-	-	-	9.40 [2.2-10.3]	11.7	2590 (320-3600)	3.63
	35+35	3.50	3.50	-	-	-	7.00 [2.3-8.1]	12.2	2650 (330-3730)	2.64	4.50	4.50	-	-	-	9.00 [2.2-10.0]	11.9	2650 (360-3670)	3.40
	35+42	3.50	4.20	-	-	-	7.70 [2.3-8.5]	14.4	3140 (330-4220)	2.45	4.27	5.13	-	-	-	9.40 [2.2-10.0]	12.6	2790 (350-3660)	3.37
	35+50	3.29	4.71	-	-	-	8.00 [2.3-8.5]	13.2	2870 (320-3440)	2.79	3.87	5.53	-	-	-	9.40 [2.2-10.0]	11.6	2580 (320-3400)	3.64
	35+60	2.95	5.05	-	-	-	8.00 [2.3-8.5]	13.2	2870 (320-3440)	2.79	3.46	5.94	-	-	-	9.40 [2.2-10.3]	11.6	2580 (320-3520)	3.64
	35+71	2.64	5.36	-	-	-	8.00 [2.3-8.6]	12.8	2800 (350-3440)	2.86	3.10	6.30	-	-	-	9.40 [2.2-10.5]	11.5	2560 (310-3630)	3.67
	42+42	4.00	4.00	-	-	-	8.00 [2.3-8.5]	15.8	3440 (330-4140)	2.33	4.70	4.70	-	-	-	9.40 [2.2-10.0]	12.5	2780 (350-3650)	3.38
	42+50	3.65	4.35	-	-	-	8.00 [2.3-8.5]	13.2	2870 (320-3440)	2.79	4.29	5.11	-	-	-	9.40 [2.2-10.3]	11.5	2560 (320-3510)	3.67
	42+60	3.29	4.71	-	-	-	8.00 [2.3-8.6]	13.2	2870 (320-3520)	2.79	3.87	5.53	-	-	-	9.40 [2.2-10.3]	11.5	2560 (320-3510)	3.67
	42+71	2.97	5.03	-	-	-	8.00 [2.3-8.6]	12.8	2800 (350-3360)	2.86	3.49	5.91	-	-	-	9.40 [2.2-10.5]	11.5	2550 (310-3620)	3.69
	50+50	4.00	4.00	-	-	-	8.00 [2.3-8.6]	11.6	2520 (340-3050)	3.17	4.70	4.70	-	-	-	9.40 [2.2-10.3]	10.8	2400 (310-3290)	3.92
	50+60	3.64	4.36	-	-	-	8.00 [2.3-8.6]	11.6	2520 (340-3050)	3.17	4.27	5.13	-	-	-	9.40 [2.2-10.5]	10.8	2400 (310-3350)	3.92
	50+71	3.31	4.69	-	-	-	8.00 [2.3-8.6]	11.2	2450 (340-2980)	3.27	3.88	5.52	-	-	-	9.40 [2.2-10.5]	10.7	2380 (310-3330)	3.95
	60+60	4.00	4.00	-	-	-	8.00 [2.3-8.6]	11.6	2520 (340-3050)	3.17	4.70	4.70	-	-	-	9.40 [2.2-10.5]	10.8	2400 (310-3350)	3.92
60+71	3.66	4.34	-	-	-	8.00 [2.3-8.6]	11.2	2450 (340-2980)	3.27	4.31	5.09	-	-	-	9.40 [2.2-10.5]	10.7	2380 (310-3330)	3.95	
71+71	4.00	4.00	-	-	-	8.00 [2.3-8.6]	10.9	2380 (380-2900)	3.36	4.70	4.70	-	-	-	9.40 [2.2-10.5]	10.7	2370 (320-3320)	3.97	
3 rooms	16+16+16	1.60	1.60	1.60	-	-	4.80 [2.3-8.5]	5.7	1230 (350-3260)	3.90	2.60	2.60	2.60	-	-	7.80 (3.0-10.4)	9.8	2180 (440-3640)	3.58
	16+16+20	1.60	1.60	2.00	-	-	5.20 [2.3-8.5]	6.2	1330 (350-3260)	3.91	2.58	2.58	3.24	-	-	8.40 (3.0-10.4)	10.9	2410 (440-3560)	3.49
	16+16+25	1.60	1.60	2.50	-	-	5.70 [2.3-8.5]	7.1	1540 (350-3260)	3.70	2.47	2.47	3.86	-	-	8.80 (3.0-10.4)	10.8	2390 (440-3560)	3.68
	16+16+35	1.60	1.60	3.50	-	-	6.70 [2.3-8.5]	8.5	1860 (340-3180)	3.60	2.24	2.24	4.92	-	-	9.40 (3.0-10.4)	11.5	2550 (440-3530)	3.69
	16+16+42	1.60	1.60	4.20	-	-	7.40 [2.3-8.5]	10.2	2220 (340-3100)	3.33	2.03	2.03	5.34	-	-	9.40 (3.0-10.4)	11.4	2540 (430-3510)	3.70
	16+16+50	1.56	1.56	4.88	-	-	8.00 [2.3-8.6]	10.3	2250 (380-2880)	3.56	1.83	1.83	5.74	-	-	9.40 (3.0-10.4)	10.9	2430 (460-3300)	3.87
	16+16+60	1.39	1.39	5.22	-	-	8.00 [2.3-8.6]	10.3	2250 (380-2880)	3.56	1.63	1.63	6.14	-	-	9.40 (3.0-10.5)	10.9	2430 (460-3360)	3.87
	16+16+71	1.24	1.24	5.52	-	-	8.00 [2.3-8.8]	10.0	2190 (380-2950)	3.65	1.46	1.46	6.48	-	-	9.40 (3.0-10.5)	10.9	2420 (460-3340)	3.88
	16+20+20	1.60	2.00	2.00	-	-	5.60 [2.3-8.5]	6.9	1490 (350-3180)	3.76	2.58	3.21	3.21	-	-	9.00 (3.0-10.4)	10.9	2430 (440-3550)	3.70
	16+20+25	1.60	2.00	2.50	-	-	6.10 [2.3-8.5]	7.9	1700 (350-3180)	3.59	2.47	3.08	3.85	-	-	9.40 (3.0-10.4)	11.6	2570 (440-3550)	3.66
	16+20+35	1.60	2.00	3.50	-	-	7.10 [2.3-8.5]	9.3	2030 (340-3100)	3.50	2.12	2.65	4.63	-	-	9.40 (3.0-10.4)	11.4	2540 (430-3510)	3.70
	16+20+42	1.60	2.00	4.20	-	-	7.80 [2.3-8.5]	10.6	2320 (340-3100)	3.36	1.93	2.41	5.06	-	-	9.40 (3.0-10.4)	11.4	2530 (430-3500)	3.72
	16+20+50	1.49	1.86	4.65	-	-	8.00 [2.3-8.6]	10.3	2250 (380-2880)	3.56	1.75	2.19	5.46	-	-	9.40 (3.0-10.5)	10.9	2420 (460-3350)	3.88
	16+20+60	1.33	1.67	5.00	-	-	8.00 [2.3-8.6]	10.3	2250 (380-2880)	3.56	1.57	1.96	5.87	-	-	9.40 (3.0-10.5)	10.9	2420 (460-3350)	3.88
	16+20+71	1.20	1.50	5.30	-	-	8.00 [2.3-8.8]	10.0	2190 (380-2950)	3.65	1.41	1.76	6.23	-	-	9.40 (3.0-10.5)	10.9	2410 (460-3330)	3.90
	16+25+25	1.60	2.50	2.50	-	-	6.60 [2.3-8.5]	8.9	1940 (350-3180)	3.40	2.28	3.56	3.56	-	-	9.40 (3.0-10.4)	11.6	2570 (440-3550)	3.66
	16+25+35	1.60	2.50	3.50	-	-	7.60 [2.3-8.5]	10.7	2340 (340-3100)	3.25	1.98	3.09	4.33	-	-	9.40 (3.0-10.4)	11.4	2540 (430-3510)	3.70
	16+25+42	1.54	2.41	4.05	-	-	8.00 [2.3-8.6]	11.2	2440 (340-3180)	3.28	1.81	2.83	4.76	-	-	9.40 (3.0-10.4)	11.4	2530 (430-3500)	3.72
	16+25+50	1.41	2.20	4.39	-	-	8.00 [2.3-8.6]	10.3	2250 (380-2880)	3.56	1.65	2.58	5.17	-	-	9.40 (3.0-10.5)	10.9	2420 (460-3350)	3.88
	16+25+60	1.27	1.98	4.75	-	-	8.00 [2.3-8.8]	10.3	2250 (380-2950)	3.56	1.49	2.33	5.58	-	-	9.40 (3.0-10.5)	10.9	2420 (460-3350)	3.88
	16+25+71	1.14	1.79	5.07	-	-	8.00 [2.3-8.8]	10.0	2190 (380-2950)	3.65	1.34	2.10	5.96	-	-	9.40 (3.0-10.6)	10.9	2410 (460-3390)	3.90
	16+35+35	1.48	3.26	3.26	-	-	8.00 [2.3-8.6]	10.9	2380 (340-3100)	3.36	1.74	3.83	3.83	-	-	9.40 (3.0-10.5)	11.3	2510 (460-3540)	3.75
	16+35+42	1.38	3.01	3.61	-	-	8.00 [2.3-8.6]	10.9	2380 (340-3100)	3.36	1.62	3.54	4.24	-	-	9.40 (3.0-10.5)	11.3	2500 (460-3460)	3.76
	16+35+50	1.27	2.77	3.96	-	-	8.00 [2.3-8.8]	10.0	2190 (380-2950)	3.65	1.49	3.26	4.65	-	-	9.40 (3.0-10.5)	10.8	2390 (490-3310)	3.93
	16+35+60	1.15	2.52	4.33	-	-	8.00 [2.3-8.8]	10.0	2190 (380-2950)	3.65	1.35	2.96	5.09	-	-	9.40 (3.0-10.6)	10.8	2390 (490-3370)	3.93
	16+35+71	1.05	2.30	4.65	-	-	8.00 [2.3-9.0]	10.0	2190 (380-3020)	3.65	1.23	2.70	5.47	-	-	9.40 (3.0-10.6)	10.7	2380 (490-3360)	3.95
	16+42+42	1.28	3.36	3.36	-	-	8.00 [2.3-8.8]	10.9	2380 (340-3250)	3.36	1.50	3.95	3.95	-	-	9.40 (3.0-10.5)	11.2	2490 (460-3450)	3.78
	16+42+50	1.19	3.11	3.70	-	-	8.00 [2.3-8.8]	10.0	2190 (380-2950)	3.65	1.39	3.66	4.35	-	-	9.40 (3.0-10.5)	10.8	2390 (490-3300)	3.93
	16+42+60	1.08	2.85	4.07	-	-	8.00 [2.3-9.0]	10.0	2190 (380-3020)	3.65	1.27	3.35	4.78	-	-	9.40 (3.0-10.6)	10.8	2390 (490-3360)	3.93
	16+42+71	0.99	2.60	4.41	-	-	8.00 [2.3-9.0]	9.8	2130 (380-2950)	3.76	1.17	3.06	5.17	-	-	9.40 (3.0-10.6)	10.7	2370 (490-3340)	3.97
	16+50+50	1.10	3.45	3.45	-	-	8.00 [2.3-8.8]	9.5	2070 (430-2730)	3.86	1.30	4.05	4.05	-	-	9.40 (3.0-10.6)	10.4	2300 (550-3230)	4.09
	16+50+60	1.02	3.17	3.81	-	-	8.00 [2.3-9.0]	9.5	2070 (430-2800)	3.86	1.19	3.73	4.48	-	-	9.40 (3.0-10.6)	10.4	2300 (550-3230)	4.09
	16+50+71	0.93	2.92	4.15	-	-	8.00 [2.3-9.0]	9.5	2070 (470-2800)	3.86	1.10	3.43	4.87	-	-	9.40 (3.0-10.6)	10.3	2290 (550-3220)	4.10
	16+60+60	0.94	3.53	3.53	-	-	8.00 [2.3-9.0]	9.5	2070 (430-2800)	3.86	1.10	4.15	4.15	-	-	9.40 (3.0-10.6)	10.4	2300 (550-3230)	4.09
	16+60+71	0.87	3.27	3.86	-	-	8.00 [2.3-9.0]	9.5	2070 (470-2800)	3.86	1.02	3.84	4.54	-	-	9.40 (3.0-10.6)	10.3	2290 (550-3220)	4.10
	20+20+20	2.00	2.00	2.00	-	-	6.00 [2.3-8.5]	7.6	1650 (340-3180)	3.64	3.13	3.13	3.13	-	-	9.39 (3.0-10.4)	11.5	2560 (440-3540)	3.67

CU-4Z80VBR: Free Multi Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP	
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				Total
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
20+20+25	2.00	2.00	2.50	-	-	6.50 (2.3-8.5)	8.6	1880 (340-3180)	3.46	2.89	2.89	3.62	-	-	9.40 (3.0-10.4)	11.5	2560 (440-3540)	3.67
20+20+35	2.00	2.00	3.50	-	-	7.50 (2.3-8.5)	10.1	2210 (340-3100)	3.39	2.51	2.51	4.38	-	-	9.40 (3.0-10.4)	11.4	2530 (430-3500)	3.72
20+20+42	1.95	1.95	4.10	-	-	8.00 (2.3-8.6)	11.2	2440 (340-3180)	3.28	2.29	2.29	4.82	-	-	9.40 (3.0-10.4)	11.3	2520 (460-3490)	3.73
20+20+50	1.78	1.78	4.44	-	-	8.00 (2.3-8.6)	10.0	2190 (380-2800)	3.65	2.09	2.09	5.22	-	-	9.40 (3.0-10.5)	10.9	2410 (460-3330)	3.90
20+20+60	1.60	1.60	4.80	-	-	8.00 (2.3-8.8)	10.0	2190 (380-2950)	3.65	1.88	1.88	5.64	-	-	9.40 (3.0-10.5)	10.9	2410 (460-3330)	3.90
20+20+71	1.44	1.44	5.12	-	-	8.00 (2.3-8.8)	10.0	2190 (380-2870)	3.65	1.69	1.69	6.02	-	-	9.40 (3.0-10.6)	10.8	2400 (460-3380)	3.92
20+25+25	2.00	2.50	2.50	-	-	7.00 (2.3-8.5)	9.4	2040 (340-3180)	3.43	2.68	3.36	3.36	-	-	9.40 (3.0-10.4)	11.5	2560 (440-3540)	3.67
20+25+35	2.00	2.50	3.50	-	-	8.00 (2.3-8.6)	11.2	2440 (340-3180)	3.28	2.35	2.94	4.11	-	-	9.40 (3.0-10.4)	11.4	2530 (430-3500)	3.72
20+25+42	1.84	2.30	3.86	-	-	8.00 (2.3-8.6)	11.2	2440 (340-3180)	3.28	2.16	2.70	4.54	-	-	9.40 (3.0-10.5)	11.3	2520 (460-3550)	3.73
20+25+50	1.68	2.11	4.21	-	-	8.00 (2.3-8.6)	10.0	2190 (380-2800)	3.65	1.98	2.47	4.95	-	-	9.40 (3.0-10.5)	10.9	2410 (460-3330)	3.90
20+25+60	1.52	1.90	4.58	-	-	8.00 (2.3-8.8)	10.0	2190 (380-2950)	3.65	1.79	2.24	5.37	-	-	9.40 (3.0-10.5)	10.9	2410 (460-3330)	3.90
20+25+71	1.38	1.72	4.90	-	-	8.00 (2.3-8.8)	10.0	2190 (380-2870)	3.65	1.62	2.03	5.75	-	-	9.40 (3.0-10.6)	10.8	2400 (460-3380)	3.92
20+35+35	1.78	3.11	3.11	-	-	8.00 (2.3-8.6)	10.9	2380 (340-3100)	3.36	2.08	3.66	3.66	-	-	9.40 (3.0-10.5)	11.3	2500 (460-3460)	3.76
20+35+42	1.65	2.89	3.46	-	-	8.00 (2.3-8.6)	10.9	2380 (340-3100)	3.36	1.94	3.39	4.07	-	-	9.40 (3.0-10.5)	11.2	2490 (460-3450)	3.78
20+35+50	1.52	2.67	3.81	-	-	8.00 (2.3-8.8)	10.0	2190 (380-2950)	3.65	1.79	3.13	4.48	-	-	9.40 (3.0-10.5)	10.8	2390 (490-3300)	3.93
20+35+60	1.39	2.43	4.18	-	-	8.00 (2.3-8.8)	10.0	2190 (380-2950)	3.65	1.63	2.86	4.91	-	-	9.40 (3.0-10.6)	10.8	2390 (490-3360)	3.93
20+35+71	1.27	2.22	4.51	-	-	8.00 (2.3-9.0)	9.8	2130 (380-2950)	3.76	1.49	2.61	5.30	-	-	9.40 (3.0-10.6)	10.7	2370 (490-3340)	3.97
20+42+42	1.54	3.23	3.23	-	-	8.00 (2.3-8.8)	10.9	2380 (340-3180)	3.36	1.80	3.80	3.80	-	-	9.40 (3.0-10.5)	11.2	2480 (460-3440)	3.79
20+42+50	1.43	3.00	3.57	-	-	8.00 (2.3-8.8)	10.0	2190 (380-2870)	3.65	1.68	3.53	4.19	-	-	9.40 (3.0-10.6)	10.7	2380 (490-3350)	3.95
20+42+60	1.31	2.75	3.94	-	-	8.00 (2.3-9.0)	10.0	2190 (380-3020)	3.65	1.54	3.24	4.62	-	-	9.40 (3.0-10.6)	10.7	2380 (490-3350)	3.95
20+42+71	1.20	2.53	4.27	-	-	8.00 (2.3-9.0)	9.8	2130 (380-2950)	3.76	1.41	2.97	5.02	-	-	9.40 (3.0-10.6)	10.7	2370 (490-3330)	3.97
20+50+50	1.33	3.33	3.33	-	-	7.99 (2.3-9.0)	9.5	2070 (430-2800)	3.86	1.56	3.92	3.92	-	-	9.40 (3.0-10.6)	10.3	2290 (550-3220)	4.10
20+50+60	1.23	3.08	3.69	-	-	8.00 (2.3-9.0)	9.5	2070 (430-2800)	3.86	1.45	3.62	4.33	-	-	9.40 (3.0-10.6)	10.3	2290 (550-3220)	4.10
20+50+71	1.13	2.84	4.03	-	-	8.00 (2.3-9.0)	9.5	2070 (470-2800)	3.86	1.33	3.33	4.74	-	-	9.40 (3.0-10.6)	10.3	2280 (580-3210)	4.12
20+60+60	1.14	3.43	3.43	-	-	8.00 (2.3-9.0)	9.5	2070 (430-2800)	3.86	1.34	4.03	4.03	-	-	9.40 (3.0-10.6)	10.3	2290 (550-3220)	4.10
25+25+25	2.50	2.50	2.50	-	-	7.50 (2.3-8.5)	10.5	2280 (340-3180)	3.29	3.13	3.13	3.13	-	-	9.39 (3.0-10.4)	11.5	2560 (440-3540)	3.67
25+25+35	2.35	2.35	3.30	-	-	8.00 (2.3-8.6)	11.2	2440 (340-3180)	3.28	2.76	2.76	3.88	-	-	9.40 (3.0-10.4)	11.4	2530 (430-3500)	3.72
25+25+42	2.17	2.17	3.66	-	-	8.00 (2.3-8.6)	11.2	2440 (340-3180)	3.28	2.55	2.55	4.30	-	-	9.40 (3.0-10.5)	11.3	2520 (460-3550)	3.73
25+25+50	2.00	2.00	4.00	-	-	8.00 (2.3-8.8)	10.0	2190 (380-2950)	3.65	2.35	2.35	4.70	-	-	9.40 (3.0-10.5)	10.9	2410 (460-3330)	3.90
25+25+60	1.82	1.82	4.36	-	-	8.00 (2.3-8.8)	10.0	2190 (380-2950)	3.65	2.14	2.14	5.12	-	-	9.40 (3.0-10.5)	10.9	2410 (460-3330)	3.90
25+25+71	1.65	1.65	4.70	-	-	8.00 (2.3-9.0)	10.0	2190 (380-3020)	3.65	1.94	1.94	5.52	-	-	9.40 (3.0-10.6)	10.8	2400 (460-3380)	3.92
25+35+35	2.10	2.95	2.95	-	-	8.00 (2.3-8.6)	10.9	2380 (340-3100)	3.36	2.48	3.46	3.46	-	-	9.40 (3.0-10.5)	11.3	2500 (460-3460)	3.76
25+35+42	1.96	2.75	3.29	-	-	8.00 (2.3-8.8)	10.9	2380 (340-3250)	3.36	2.30	3.23	3.87	-	-	9.40 (3.0-10.5)	11.2	2490 (460-3450)	3.78
25+35+50	1.82	2.55	3.63	-	-	8.00 (2.3-8.8)	10.0	2190 (380-2950)	3.65	2.14	2.99	4.27	-	-	9.40 (3.0-10.5)	10.8	2390 (490-3300)	3.93
25+35+60	1.67	2.33	4.00	-	-	8.00 (2.3-9.0)	10.0	2190 (380-3020)	3.65	1.96	2.74	4.70	-	-	9.40 (3.0-10.6)	10.8	2390 (490-3360)	3.93
25+35+71	1.53	2.14	4.33	-	-	8.00 (2.3-9.0)	9.8	2130 (380-2950)	3.76	1.79	2.51	5.10	-	-	9.40 (3.0-10.6)	10.7	2370 (490-3340)	3.97
25+42+42	1.84	3.08	3.08	-	-	8.00 (2.3-8.8)	10.9	2380 (340-3180)	3.36	2.16	3.62	3.62	-	-	9.40 (3.0-10.5)	11.2	2480 (460-3440)	3.79
25+42+50	1.71	2.87	3.42	-	-	8.00 (2.3-8.8)	10.0	2190 (380-2870)	3.65	2.01	3.37	4.02	-	-	9.40 (3.0-10.6)	10.7	2380 (490-3350)	3.95
25+42+60	1.57	2.65	3.78	-	-	8.00 (2.3-9.0)	10.0	2190 (380-3020)	3.65	1.85	3.11	4.44	-	-	9.40 (3.0-10.6)	10.7	2380 (490-3350)	3.95
25+42+71	1.45	2.43	4.12	-	-	8.00 (2.3-9.0)	9.8	2130 (380-2950)	3.76	1.70	2.86	4.84	-	-	9.40 (3.0-10.6)	10.7	2370 (490-3330)	3.97
25+50+50	1.60	3.20	3.20	-	-	8.00 (2.3-9.0)	9.5	2070 (430-2800)	3.86	1.88	3.76	3.76	-	-	9.40 (3.0-10.6)	10.3	2290 (550-3220)	4.10
25+50+60	1.48	2.96	3.56	-	-	8.00 (2.3-9.0)	9.5	2070 (430-2800)	3.86	1.74	3.48	4.18	-	-	9.40 (3.0-10.6)	10.3	2290 (550-3220)	4.10
25+50+71	1.37	2.74	3.89	-	-	8.00 (2.3-9.0)	9.5	2070 (470-2800)	3.86	1.61	3.22	4.57	-	-	9.40 (3.0-10.6)	10.3	2280 (580-3210)	4.12
25+60+60	1.38	3.31	3.31	-	-	8.00 (2.3-9.0)	9.5	2070 (430-2800)	3.86	1.62	3.89	3.89	-	-	9.40 (3.0-10.6)	10.3	2290 (550-3220)	4.10
35+35+35	2.66	2.66	2.66	-	-	7.98 (2.3-8.8)	10.6	2320 (340-3180)	3.44	3.13	3.13	3.13	-	-	9.39 (3.0-10.5)	11.2	2480 (460-3430)	3.79
35+35+42	2.50	2.50	3.00	-	-	8.00 (2.3-8.8)	10.6	2320 (340-3180)	3.45	2.94	2.94	3.52	-	-	9.40 (3.0-10.6)	11.1	2470 (460-3470)	3.81
35+35+50	2.33	2.33	3.33	-	-	7.99 (2.3-9.0)	9.8	2130 (380-3020)	3.75	2.74	2.74	3.92	-	-	9.40 (3.0-10.6)	10.6	2360 (490-3330)	3.98
35+35+60	2.15	2.15	3.70	-	-	8.00 (2.3-9.0)	9.8	2130 (380-3020)	3.76	2.53	2.53	4.34	-	-	9.40 (3.0-10.6)	10.6	2360 (490-3330)	3.98
35+35+71	1.99	1.99	4.02	-	-	8.00 (2.3-9.0)	9.8	2130 (420-2950)	3.76	2.33	2.33	4.74	-	-	9.40 (3.0-10.6)	10.6	2350 (500-3310)	4.00
35+42+42	2.36	2.82	2.82	-	-	8.00 (2.3-9.0)	10.6	2320 (340-3250)	3.45	2.76	3.32	3.32	-	-	9.40 (3.0-10.6)	11.1	2460 (460-3460)	3.82
35+42+50	2.20	2.65	3.15	-	-	8.00 (2.3-9.0)	9.8	2130 (380-2950)	3.76	2.59	3.11	3.70	-	-	9.40 (3.0-10.6)	10.6	2350 (500-3320)	4.00
35+42+60	2.04	2.45	3.51	-	-	8.00 (2.3-9.0)	9.8	2130 (380-2950)	3.76	2.40	2.88	4.12	-	-	9.40 (3.0-10.6)	10.6	2350 (500-3320)	4.00
35+50+50	2.08	2.96	2.96	-	-	8.00 (2.3-9.0)	9.5	2070 (470-2800)	3.86	2.44	3.48	3.48	-	-	9.40 (3.0-10.6)	10.2	2270 (580-3190)	4.14
35+50+60	1.93	2.76	3.31	-	-	8.00 (2.3-9.0)	9.5	2070 (470-2800)	3.86	2.27	3.24	3.89	-	-	9.40 (3.0-10.6)	10.2	2270 (580-3190)	4.14
42+42+42	2.66	2.66	2.66	-	-	7.98 (2.3-9.0)	10.6	2320 (340-3250)	3.44	3.13	3.13	3.13	-	-	9.39 (3.0-10.6)	11.0	2450 (460-3450)	3.83
42+42+50	2.51	2.51	2.98	-	-	8.00 (2.3-9.0)	9.8	2130 (380-2950)	3.76	2.95	2.95	3.50	-	-	9.40 (3.0-10.6)	10.6	2350 (500-3300)	4.00
42+42+60	2.33	2.33	3.33	-	-	7.99 (2.3-9.0)	9.8	2130 (380-2950)	3.75	2.74	2.74	3.92	-	-	9.40 (3.0-10.6)	10.6	2350 (500-3300)	4.00
42+50+50	2.36	2.82	2.82	-	-	8.00 (2.3-9.0)	9.5	2070 (470-2800)	3.86	2.78	3.31	3.31	-	-	9.40 (3.0-10.6)	10.2	2270 (590-3180)	4.14

CU-4Z80VBR: Free Multi Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP	
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				Total
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	A	W	W/W	
16+16+16+16	1.60	1.60	1.60	1.60	-	6.40 (2.3-9.2)	7.3	1610 (420-3060)	3.98	2.35	2.35	2.35	2.35	-	9.40 (3.0-11.6)	10.6	2300 (490-3710)	4.09
16+16+16+20	1.60	1.60	1.60	2.00	-	6.80 (2.3-9.2)	7.8	1720 (420-2990)	3.95	2.21	2.21	2.21	2.77	-	9.40 (3.0-11.6)	10.5	2290 (500-3700)	4.10
16+16+16+25	1.60	1.60	1.60	2.50	-	7.30 (2.3-9.2)	8.5	1880 (420-2990)	3.88	2.06	2.06	2.06	3.22	-	9.40 (3.0-11.6)	10.5	2290 (500-3700)	4.10
16+16+16+35	1.54	1.54	1.54	3.38	-	8.00 (2.3-9.2)	9.5	2100 (420-2990)	3.81	1.81	1.81	1.81	3.97	-	9.40 (3.0-11.6)	10.4	2270 (500-3660)	4.14
16+16+16+42	1.42	1.42	1.42	3.74	-	8.00 (2.3-9.2)	9.5	2100 (420-2990)	3.81	1.67	1.67	1.67	4.39	-	9.40 (3.0-11.6)	10.4	2260 (510-3650)	4.16
16+16+16+50	1.31	1.31	1.31	4.07	-	8.00 (2.3-9.2)	9.0	2000 (480-2850)	4.00	1.53	1.53	1.53	4.81	-	9.40 (3.0-11.6)	10.3	2240 (600-3580)	4.20
16+16+16+60	1.19	1.19	1.19	4.43	-	8.00 (2.3-9.2)	9.0	2000 (480-2850)	4.00	1.39	1.39	1.39	5.23	-	9.40 (3.0-11.6)	10.3	2240 (600-3580)	4.20
16+16+16+71	1.08	1.08	1.08	4.76	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.26	1.26	1.26	5.62	-	9.40 (3.0-11.6)	10.2	2230 (630-3560)	4.22
16+16+20+20	1.60	1.60	2.00	2.00	-	7.20 (2.3-9.2)	8.2	1830 (420-2990)	3.93	2.09	2.09	2.61	2.61	-	9.40 (3.0-11.6)	10.5	2280 (500-3680)	4.12
16+16+20+25	1.60	1.60	2.00	2.50	-	7.70 (2.3-9.2)	9.0	1990 (420-2990)	3.87	1.95	1.95	2.44	3.06	-	9.40 (3.0-11.6)	10.5	2280 (500-3680)	4.12
16+16+20+35	1.47	1.47	1.84	3.22	-	8.00 (2.3-9.2)	9.2	2050 (420-2990)	3.90	1.73	1.73	2.16	3.78	-	9.40 (3.0-11.6)	10.4	2260 (510-3650)	4.16
16+16+20+42	1.36	1.36	1.70	3.58	-	8.00 (2.3-9.2)	9.2	2050 (420-2990)	3.90	1.60	1.60	2.00	4.20	-	9.40 (3.0-11.6)	10.4	2260 (530-3640)	4.16
16+16+20+50	1.25	1.25	1.57	3.93	-	8.00 (2.3-9.2)	9.0	2000 (480-2780)	4.00	1.47	1.47	1.84	4.62	-	9.40 (3.0-11.6)	10.2	2230 (620-3570)	4.22
16+16+20+60	1.14	1.14	1.43	4.29	-	8.00 (2.3-9.2)	9.0	2000 (480-2780)	4.00	1.34	1.34	1.68	5.04	-	9.40 (3.0-11.6)	10.2	2230 (620-3570)	4.22
16+16+20+71	1.04	1.04	1.30	4.62	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.22	1.22	1.53	5.43	-	9.40 (3.0-11.6)	10.2	2220 (630-3550)	4.23
16+16+25+25	1.56	1.56	2.44	2.44	-	8.00 (2.3-9.2)	9.5	2100 (420-2990)	3.81	1.83	1.83	2.87	2.87	-	9.40 (3.0-11.6)	10.5	2280 (500-3680)	4.12
16+16+25+35	1.39	1.39	2.17	3.05	-	8.00 (2.3-9.2)	9.2	2050 (420-2990)	3.90	1.63	1.63	2.55	3.59	-	9.40 (3.0-11.6)	10.4	2260 (510-3650)	4.16
16+16+25+42	1.29	1.29	2.02	3.40	-	8.00 (2.3-9.2)	9.2	2050 (420-2990)	3.90	1.52	1.52	2.37	3.99	-	9.40 (3.0-11.6)	10.4	2260 (530-3640)	4.16
16+16+25+50	1.20	1.20	1.87	3.73	-	8.00 (2.3-9.2)	9.0	2000 (480-2780)	4.00	1.41	1.41	2.20	4.38	-	9.40 (3.0-11.6)	10.2	2230 (620-3570)	4.22
16+16+25+60	1.09	1.09	1.71	4.11	-	8.00 (2.3-9.2)	9.0	2000 (480-2780)	4.00	1.29	1.29	2.01	4.81	-	9.40 (3.0-11.6)	10.2	2230 (620-3570)	4.22
16+16+25+71	1.00	1.00	1.56	4.44	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.18	1.18	1.84	5.20	-	9.40 (3.0-11.6)	10.2	2220 (630-3550)	4.23
16+16+35+35	1.25	1.25	2.75	2.75	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.47	1.47	3.23	3.23	-	9.40 (3.0-11.6)	10.3	2250 (540-3620)	4.18
16+16+35+42	1.17	1.17	2.57	3.09	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.38	1.38	3.02	3.62	-	9.40 (3.0-11.6)	10.3	2240 (540-3600)	4.20
16+16+35+50	1.09	1.09	2.39	3.43	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.29	1.29	2.81	4.01	-	9.40 (3.0-11.6)	10.2	2220 (640-3540)	4.23
16+16+35+60	1.01	1.01	2.20	3.78	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.18	1.18	2.59	4.45	-	9.40 (3.0-11.6)	10.2	2220 (640-3540)	4.23
16+16+35+71	0.93	0.93	2.03	4.11	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.09	1.09	2.38	4.84	-	9.40 (3.0-11.6)	10.1	2210 (650-3530)	4.25
16+16+42+42	1.10	1.10	2.90	2.90	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.30	1.30	3.40	3.40	-	9.40 (3.0-11.6)	10.2	2230 (550-3590)	4.22
16+16+42+50	1.03	1.03	2.71	3.23	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.21	1.21	3.18	3.80	-	9.40 (3.0-11.6)	10.1	2210 (650-3530)	4.25
16+16+42+60	0.96	0.96	2.51	3.57	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.12	1.12	2.95	4.21	-	9.40 (3.0-11.6)	10.1	2210 (650-3530)	4.25
16+16+42+71	0.88	0.88	2.32	3.92	-	8.00 (2.3-9.2)	9.0	2000 (530-2780)	4.00	1.04	1.04	2.72	4.60	-	9.40 (3.0-11.6)	10.1	2210 (670-3520)	4.25
16+16+50+50	0.97	0.97	3.03	3.03	-	8.00 (2.3-9.2)	9.1	2010 (580-2720)	3.98	1.14	1.14	3.56	3.56	-	9.40 (3.0-11.6)	10.3	2250 (780-3540)	4.18
16+16+50+60	0.90	0.90	2.82	3.38	-	8.00 (2.3-9.2)	9.1	2010 (580-2720)	3.98	1.06	1.06	3.31	3.97	-	9.40 (3.0-11.6)	10.3	2250 (780-3540)	4.18
16+20+20+20	1.60	2.00	2.00	2.00	-	7.60 (2.3-9.2)	9.0	1990 (420-2990)	3.82	1.99	2.47	2.47	2.47	-	9.40 (3.0-11.6)	10.5	2280 (500-3670)	4.12
16+20+20+25	1.58	1.98	1.98	2.46	-	8.00 (2.3-9.2)	9.5	2100 (420-2990)	3.81	1.86	2.32	2.32	2.90	-	9.40 (3.0-11.6)	10.5	2280 (500-3670)	4.12
16+20+20+35	1.41	1.76	1.76	3.07	-	8.00 (2.3-9.2)	9.2	2050 (420-2920)	3.90	1.65	2.07	2.07	3.61	-	9.40 (3.0-11.6)	10.4	2260 (530-3640)	4.16
16+20+20+42	1.31	1.63	1.63	3.43	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.53	1.92	1.92	4.03	-	9.40 (3.0-11.6)	10.3	2250 (530-3620)	4.18
16+20+20+50	1.21	1.51	1.51	3.77	-	8.00 (2.3-9.2)	9.0	2000 (480-2780)	4.00	1.42	1.77	1.77	4.44	-	9.40 (3.0-11.6)	10.2	2230 (630-3560)	4.22
16+20+20+60	1.10	1.38	1.38	4.14	-	8.00 (2.3-9.2)	9.0	2000 (480-2780)	4.00	1.30	1.62	1.62	4.86	-	9.40 (3.0-11.6)	10.2	2230 (630-3560)	4.22
16+20+20+71	1.01	1.26	1.26	4.47	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.18	1.48	1.48	5.26	-	9.40 (3.0-11.6)	10.2	2220 (640-3540)	4.23
16+20+25+25	1.48	1.86	2.33	2.33	-	8.00 (2.3-9.2)	9.5	2100 (420-2990)	3.81	1.75	2.19	2.73	2.73	-	9.40 (3.0-11.6)	10.5	2280 (500-3670)	4.12
16+20+25+35	1.33	1.67	2.08	2.92	-	8.00 (2.3-9.2)	9.2	2050 (420-2920)	3.90	1.57	1.96	2.45	3.42	-	9.40 (3.0-11.6)	10.4	2260 (530-3640)	4.16
16+20+25+42	1.24	1.55	1.94	3.27	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.46	1.83	2.28	3.83	-	9.40 (3.0-11.6)	10.3	2250 (530-3620)	4.18
16+20+25+50	1.15	1.44	1.80	3.61	-	8.00 (2.3-9.2)	9.0	2000 (480-2780)	4.00	1.35	1.69	2.12	4.24	-	9.40 (3.0-11.6)	10.2	2230 (630-3560)	4.22
16+20+25+60	1.06	1.32	1.65	3.97	-	8.00 (2.3-9.2)	9.0	2000 (480-2780)	4.00	1.24	1.55	1.94	4.67	-	9.40 (3.0-11.6)	10.2	2230 (630-3560)	4.22
16+20+25+71	0.97	1.21	1.52	4.30	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.14	1.42	1.78	5.06	-	9.40 (3.0-11.6)	10.2	2220 (640-3540)	4.23
16+20+35+35	1.21	1.51	2.64	2.64	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.42	1.78	3.10	3.10	-	9.40 (3.0-11.6)	10.3	2240 (540-3600)	4.20
16+20+35+42	1.13	1.42	2.48	2.97	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.33	1.66	2.91	3.50	-	9.40 (3.0-11.6)	10.2	2230 (550-3590)	4.22
16+20+35+50	1.06	1.32	2.31	3.31	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.24	1.55	2.72	3.89	-	9.40 (3.0-11.6)	10.1	2210 (650-3530)	4.25
16+20+35+60	0.98	1.22	2.14	3.66	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.15	1.44	2.51	4.30	-	9.40 (3.0-11.6)	10.1	2210 (650-3530)	4.25
16+20+35+71	0.90	1.13	1.97	4.00	-	8.00 (2.3-9.2)	9.0	2000 (530-2780)	4.00	1.06	1.32	2.32	4.70	-	9.40 (3.0-11.6)	10.1	2210 (670-3520)	4.25
16+20+42+42	1.07	1.33	2.80	2.80	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.25	1.57	3.29	3.29	-	9.40 (3.0-11.6)	10.2	2230 (550-3580)	4.22
16+20+42+50	1.00	1.25	2.63	3.12	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.18	1.47	3.08	3.67	-	9.40 (3.0-11.6)	10.1	2210 (670-3520)	4.25
16+20+42+60	0.93	1.16	2.43	3.48	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.09	1.36	2.86	4.09	-	9.40 (3.0-11.6)	10.1	2210 (670-3520)	4.25
16+20+50+50	0.94	1.18	2.94	2.94	-	8.00 (2.3-9.2)	9.1	2010 (590-2730)	3.98	1.10	1.38	3.46	3.46	-	9.40 (3.0-11.6)	10.3	2250 (790-3540)	4.18
16+20+50+60	0.88	1.10	2.74	3.28	-	8.00 (2.3-9.2)	9.1	2010 (590-2730)	3.98	1.03	1.29	3.22	3.86	-	9.40 (3.0-11.6)	10.3	2250 (790-3540)	4.18
16+25+25+25	1.40	2.20	2.20	2.20	-	8.00 (2.3-9.2)	9.5	2100 (420-2990)	3.81	1.66	2.58	2.58	2.58	-	9.40 (3.0-11.6)	10.5	2280 (500-3670)	4.12
16+25+25+35	1.27	1.98	1.98	2.77	-	8.00 (2.3-9.2)	9.2	2050 (420-2920)	3.90	1.49	2.33	2.33	3.25	-	9.40 (3.0-11.6)			

CU-4Z80VBR: Free Multi Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP	
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				Total
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
16+35+42+50	0.90	1.96	2.35	2.79	-	8.00 (2.3-9.2)	9.0	2000 (530-2780)	4.00	1.05	2.30	2.76	3.29	-	9.40 (3.0-11.6)	10.3	2240 (690-3550)	4.20
16+42+42+42	0.89	2.37	2.37	2.37	-	8.00 (2.3-9.2)	9.2	2050 (470-2850)	3.90	1.06	2.78	2.78	2.78	-	9.40 (3.0-11.6)	10.1	2210 (590-3600)	4.25
20+20+20+20	2.00	2.00	2.00	2.00	-	8.00 (2.3-9.2)	9.5	2100 (420-2990)	3.81	2.35	2.35	2.35	2.35	-	9.40 (3.0-11.6)	10.4	2270 (500-3660)	4.14
20+20+20+25	1.88	1.88	1.88	2.36	-	8.00 (2.3-9.2)	9.5	2100 (420-2990)	3.81	2.21	2.21	2.21	2.77	-	9.40 (3.0-11.6)	10.4	2270 (500-3660)	4.14
20+20+20+35	1.68	1.68	1.68	2.96	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.98	1.98	1.98	3.46	-	9.40 (3.0-11.6)	10.3	2250 (530-3620)	4.18
20+20+20+42	1.57	1.57	1.57	3.29	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.84	1.84	1.84	3.88	-	9.40 (3.0-11.6)	10.3	2240 (540-3610)	4.20
20+20+20+50	1.45	1.45	1.45	3.65	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.71	1.71	1.71	4.27	-	9.40 (3.0-11.6)	10.2	2220 (640-3550)	4.23
20+20+20+60	1.33	1.33	1.33	4.01	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.57	1.57	1.57	4.69	-	9.40 (3.0-11.6)	10.2	2220 (640-3550)	4.23
20+20+20+71	1.22	1.22	1.22	4.34	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.44	1.44	1.44	5.08	-	9.40 (3.0-11.6)	10.1	2210 (640-3530)	4.25
20+20+25+25	1.78	1.78	2.22	2.22	-	8.00 (2.3-9.2)	9.5	2100 (420-2990)	3.81	2.09	2.09	2.61	2.61	-	9.40 (3.0-11.6)	10.4	2270 (500-3660)	4.14
20+20+25+35	1.60	1.60	2.00	2.80	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.88	1.88	2.35	3.29	-	9.40 (3.0-11.6)	10.3	2250 (530-3620)	4.18
20+20+25+42	1.50	1.50	1.87	3.13	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.76	1.76	2.20	3.68	-	9.40 (3.0-11.6)	10.3	2240 (540-3610)	4.20
20+20+25+50	1.39	1.39	1.74	3.48	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.63	1.63	2.04	4.10	-	9.40 (3.0-11.6)	10.2	2220 (640-3550)	4.23
20+20+25+60	1.28	1.28	1.60	3.84	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.50	1.50	1.88	4.52	-	9.40 (3.0-11.6)	10.2	2220 (640-3550)	4.23
20+20+25+71	1.18	1.18	1.47	4.17	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.38	1.38	1.73	4.91	-	9.40 (3.0-11.6)	10.1	2210 (640-3530)	4.25
20+20+35+35	1.45	1.45	2.55	2.55	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.71	1.71	2.99	2.99	-	9.40 (3.0-11.6)	10.2	2230 (550-3590)	4.22
20+20+35+42	1.37	1.37	2.39	2.87	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.61	1.61	2.81	3.37	-	9.40 (3.0-11.6)	10.2	2230 (550-3580)	4.22
20+20+35+50	1.28	1.28	2.24	3.20	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.50	1.50	2.63	3.77	-	9.40 (3.0-11.6)	10.1	2210 (670-3520)	4.25
20+20+35+60	1.19	1.19	2.07	3.55	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.39	1.39	2.44	4.18	-	9.40 (3.0-11.6)	10.1	2210 (670-3520)	4.25
20+20+35+71	1.10	1.10	1.92	3.88	-	8.00 (2.3-9.2)	9.0	2000 (530-2780)	4.00	1.29	1.29	2.25	4.57	-	9.40 (3.0-11.6)	10.3	2240 (680-3510)	4.20
20+20+42+42	1.29	1.29	2.71	2.71	-	8.00 (2.3-9.2)	9.2	2050 (460-2920)	3.90	1.52	1.52	3.18	3.18	-	9.40 (3.0-11.6)	10.2	2220 (570-3570)	4.23
20+20+42+50	1.21	1.21	2.55	3.03	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.42	1.42	2.99	3.57	-	9.40 (3.0-11.6)	10.3	2240 (680-3510)	4.20
20+20+42+60	1.13	1.13	2.37	3.37	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.32	1.32	2.78	3.98	-	9.40 (3.0-11.6)	10.3	2240 (680-3510)	4.20
20+20+50+50	1.14	1.14	2.86	2.86	-	8.00 (2.3-9.2)	9.1	2010 (590-2730)	3.98	1.34	1.34	3.36	3.36	-	9.40 (3.0-11.6)	10.3	2240 (800-3530)	4.20
20+25+25+25	1.67	2.11	2.11	2.11	-	8.00 (2.3-9.2)	9.5	2100 (420-2990)	3.81	1.99	2.47	2.47	2.47	-	9.40 (3.0-11.6)	10.4	2270 (500-3660)	4.14
20+25+25+35	1.52	1.90	1.90	2.68	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.79	2.24	2.24	3.13	-	9.40 (3.0-11.6)	10.3	2250 (530-3620)	4.18
20+25+25+42	1.43	1.79	1.79	2.99	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.68	2.10	2.10	3.52	-	9.40 (3.0-11.6)	10.3	2240 (540-3610)	4.20
20+25+25+50	1.33	1.67	1.67	3.33	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.57	1.96	1.96	3.91	-	9.40 (3.0-11.6)	10.2	2220 (640-3550)	4.23
20+25+25+60	1.23	1.54	1.54	3.69	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.45	1.81	1.81	4.33	-	9.40 (3.0-11.6)	10.2	2220 (640-3550)	4.23
20+25+25+71	1.13	1.42	1.42	4.03	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.33	1.67	1.67	4.73	-	9.40 (3.0-11.6)	10.1	2210 (640-3530)	4.25
20+25+35+35	1.39	1.75	2.43	2.43	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.63	2.05	2.86	2.86	-	9.40 (3.0-11.6)	10.2	2230 (550-3590)	4.22
20+25+35+42	1.31	1.64	2.30	2.75	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.54	1.93	2.70	3.23	-	9.40 (3.0-11.6)	10.2	2230 (550-3580)	4.22
20+25+35+50	1.23	1.54	2.15	3.08	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.45	1.81	2.53	3.61	-	9.40 (3.0-11.6)	10.1	2210 (670-3520)	4.25
20+25+35+60	1.14	1.43	2.00	3.43	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.34	1.68	2.35	4.03	-	9.40 (3.0-11.6)	10.1	2210 (670-3520)	4.25
20+25+42+42	1.24	1.56	2.60	2.60	-	8.00 (2.3-9.2)	9.2	2050 (460-2920)	3.90	1.46	1.82	3.06	3.06	-	9.40 (3.0-11.6)	10.2	2220 (570-3570)	4.23
20+25+42+50	1.17	1.46	2.45	2.92	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.37	1.72	2.88	3.43	-	9.40 (3.0-11.6)	10.3	2240 (680-3510)	4.20
20+25+42+60	1.09	1.36	2.29	3.26	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.28	1.60	2.69	3.83	-	9.40 (3.0-11.6)	10.3	2240 (680-3510)	4.20
20+25+50+50	1.10	1.38	2.76	2.76	-	8.00 (2.3-9.2)	9.1	2010 (590-2730)	3.98	1.30	1.62	3.24	3.24	-	9.40 (3.0-11.6)	10.3	2240 (800-3530)	4.20
20+35+35+35	1.28	2.24	2.24	2.24	-	8.00 (2.3-9.2)	9.2	2050 (470-2850)	3.90	1.51	2.63	2.63	2.63	-	9.40 (3.0-11.6)	10.2	2220 (580-3560)	4.23
20+35+35+42	1.21	2.12	2.12	2.55	-	8.00 (2.3-9.2)	9.2	2050 (470-2850)	3.90	1.42	2.49	2.49	3.00	-	9.40 (3.0-11.6)	10.1	2210 (580-3560)	4.25
20+35+35+50	1.14	2.00	2.00	2.86	-	8.00 (2.3-9.2)	9.0	2000 (530-2780)	4.00	1.34	2.35	2.35	3.36	-	9.40 (3.0-11.6)	10.3	2240 (690-3550)	4.20
20+35+42+42	1.15	2.01	2.42	2.42	-	8.00 (2.3-9.2)	9.2	2050 (470-2850)	3.90	1.35	2.37	2.84	2.84	-	9.40 (3.0-11.6)	10.1	2210 (590-3600)	4.25
20+35+42+50	1.09	1.90	2.29	2.72	-	8.00 (2.3-9.2)	9.0	2000 (530-2780)	4.00	1.28	2.24	2.69	3.19	-	9.40 (3.0-11.6)	10.2	2230 (700-3540)	4.22
20+42+42+42	1.10	2.30	2.30	2.30	-	8.00 (2.3-9.2)	9.0	1990 (470-2850)	4.02	1.30	2.70	2.70	2.70	-	9.40 (3.0-11.6)	10.3	2240 (590-3590)	4.20
25+25+25+25	2.00	2.00	2.00	2.00	-	8.00 (2.3-9.2)	9.5	2100 (420-2990)	3.81	2.35	2.35	2.35	2.35	-	9.40 (3.0-11.6)	10.4	2270 (500-3660)	4.14
25+25+25+35	1.82	1.82	1.82	2.54	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	2.14	2.14	2.14	2.98	-	9.40 (3.0-11.6)	10.3	2250 (530-3620)	4.18
25+25+25+42	1.71	1.71	1.71	2.87	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	2.01	2.01	2.01	3.37	-	9.40 (3.0-11.6)	10.3	2240 (540-3610)	4.20
25+25+25+50	1.60	1.60	1.60	3.20	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.88	1.88	1.88	3.76	-	9.40 (3.0-11.6)	10.2	2220 (640-3550)	4.23
25+25+25+60	1.48	1.48	1.48	3.56	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.74	1.74	1.74	4.18	-	9.40 (3.0-11.6)	10.2	2220 (640-3550)	4.23
25+25+25+71	1.37	1.37	1.37	3.89	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.61	1.61	1.61	4.57	-	9.40 (3.0-11.6)	10.1	2210 (640-3530)	4.25
25+25+35+35	1.67	1.67	2.33	2.33	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.96	1.96	2.74	2.74	-	9.40 (3.0-11.6)	10.2	2230 (550-3590)	4.22
25+25+35+42	1.57	1.57	2.20	2.66	-	8.00 (2.3-9.2)	9.2	2050 (430-2920)	3.90	1.85	1.85	2.59	3.11	-	9.40 (3.0-11.6)	10.2	2230 (550-3580)	4.22
25+25+35+50	1.48	1.48	2.07	2.97	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.74	1.74	2.44	3.48	-	9.40 (3.0-11.6)	10.1	2210 (670-3520)	4.25
25+25+35+60	1.38	1.38	1.93	3.31	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.62	1.62	2.27	3.89	-	9.40 (3.0-11.6)	10.1	2210 (670-3520)	4.25
25+25+42+42	1.49	1.49	2.51	2.51	-	8.00 (2.3-9.2)	9.2	2050 (460-2920)	3.90	1.75	1.75	2.95	2.95	-	9.40 (3.0-11.6)	10.2	2220 (570-3570)	4.23
25+25+42+50	1.41	1.41	2.37	2.81	-	8.00 (2.3-9.2)	9.0	2000 (520-2780)	4.00	1.65	1.65	2.78	3.32	-	9.40 (3.0-11.6)	10.3	2240 (680-3510)	4.20
25+35+35+35	1.55	2.15	2.15	2.15	-	8.00 (2.3-9.2)	9.2	2050 (470-2850)	3.90	1.81	2.53	2.53	2.53	-	9.40 (3.			

CU-5Z100VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION									
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP	
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E					
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W	
2 rooms	16+16	1.60	1.60	-	-	-	3.20 [2.3-5.8]	3.4	700 [260-1780]	4.57	2.60	2.60	-	-	-	5.20 [2.0-8.2]	6.6	1460 [220-2490]	3.56	
	16+20	1.60	2.00	-	-	-	3.60 [2.3-5.8]	4.0	830 [250-1780]	4.34	2.58	3.22	-	-	-	5.80 [2.0-8.2]	7.4	1620 [220-2480]	3.58	
	16+25	1.60	2.50	-	-	-	4.10 [2.3-5.8]	4.7	1000 [250-1780]	4.10	2.42	3.78	-	-	-	6.20 [2.0-8.2]	7.9	1760 [220-2480]	3.52	
	16+35	1.60	3.50	-	-	-	5.10 [2.3-5.8]	6.3	1360 [250-1720]	3.75	2.23	4.87	-	-	-	7.10 [2.0-8.6]	9.0	1990 [210-2560]	3.57	
	16+42	1.60	4.20	-	-	-	5.80 [2.3-6.7]	7.7	1670 [250-2170]	3.47	2.26	5.94	-	-	-	8.20 [2.0-10.1]	10.6	2350 [210-3110]	3.49	
	16+50	1.60	5.00	-	-	-	6.60 [2.3-7.2]	8.6	1880 [240-2170]	3.51	2.28	7.12	-	-	-	9.40 [2.0-11.0]	11.5	2550 [160-3120]	3.69	
	16+60	1.60	6.00	-	-	-	7.60 [2.3-8.6]	11.1	2410 [240-3120]	3.15	2.34	8.76	-	-	-	11.10 [2.0-11.0]	13.4	2970 [160-3120]	3.74	
	16+71	1.60	7.10	-	-	-	8.70 [2.3-9.1]	13.6	2960 [230-3200]	2.94	2.08	9.22	-	-	-	11.30 [2.0-13.0]	13.1	2910 [160-4060]	3.88	
	20+20	2.00	2.00	-	-	-	4.00 [2.3-5.8]	4.5	960 [250-1720]	4.17	3.20	3.20	-	-	-	6.40 [2.0-8.2]	8.1	1790 [220-2470]	3.58	
	20+25	2.00	2.50	-	-	-	4.50 [2.3-5.8]	5.4	1160 [250-1720]	3.88	3.02	3.78	-	-	-	6.80 [2.0-8.2]	8.6	1910 [220-2470]	3.56	
	20+35	2.00	3.50	-	-	-	5.50 [2.3-5.8]	7.0	1510 [250-1670]	3.64	2.80	4.90	-	-	-	7.70 [2.0-8.6]	9.7	2160 [210-2500]	3.56	
	20+42	2.00	4.20	-	-	-	6.20 [2.3-7.2]	8.6	1880 [250-2530]	3.30	2.84	5.96	-	-	-	8.80 [2.0-11.0]	11.3	2500 [200-3310]	3.52	
	20+50	2.00	5.00	-	-	-	7.00 [2.3-8.1]	9.1	1990 [240-2650]	3.52	2.86	7.14	-	-	-	10.00 [2.0-11.0]	12.3	2730 [160-3060]	3.66	
	20+60	2.00	6.00	-	-	-	8.00 [2.3-8.6]	11.9	2590 [240-3050]	3.09	2.93	8.77	-	-	-	11.70 [2.0-11.9]	13.8	3060 [160-3550]	3.82	
	20+71	2.00	7.10	-	-	-	9.10 [2.3-10.0]	14.4	3130 [260-4070]	2.91	2.62	9.28	-	-	-	11.90 [2.0-13.0]	14.1	3140 [160-4050]	3.79	
	25+25	2.50	2.50	-	-	-	5.00 [2.3-5.8]	6.1	1310 [250-1720]	3.82	3.60	3.60	-	-	-	7.20 [2.0-8.6]	9.2	2050 [220-2580]	3.51	
	25+35	2.50	3.50	-	-	-	6.00 [2.3-6.7]	8.1	1770 [250-2170]	3.39	3.38	4.72	-	-	-	8.10 [2.0-10.1]	10.4	2300 [210-3110]	3.52	
	25+42	2.50	4.20	-	-	-	6.70 [2.3-7.2]	10.0	2170 [250-2530]	3.09	3.43	5.77	-	-	-	9.20 [2.0-11.0]	11.9	2650 [200-3310]	3.47	
	25+50	2.50	5.00	-	-	-	7.50 [2.3-8.6]	10.5	2290 [240-3050]	3.28	3.47	6.93	-	-	-	10.40 [2.0-11.0]	12.4	2760 [160-3060]	3.77	
	25+60	2.50	6.00	-	-	-	8.50 [2.3-9.1]	13.7	2980 [240-3330]	2.85	3.53	8.47	-	-	-	12.00 [2.0-13.0]	14.5	3210 [160-4060]	3.74	
	25+71	2.50	7.10	-	-	-	9.60 [2.3-10.1]	16.4	3570 [260-4220]	2.69	3.13	8.87	-	-	-	12.00 [2.0-13.0]	14.4	3190 [160-4050]	3.76	
	35+35	3.50	3.50	-	-	-	7.00 [2.3-8.1]	10.5	2290 [250-3100]	3.06	4.50	4.50	-	-	-	9.00 [2.0-11.0]	11.4	2530 [200-3300]	3.56	
	35+42	3.50	4.20	-	-	-	7.70 [2.3-8.6]	12.4	2710 [250-3590]	2.84	4.59	5.51	-	-	-	10.10 [2.0-11.0]	13.0	2880 [200-3240]	3.51	
	35+50	3.50	5.00	-	-	-	8.50 [2.3-9.1]	13.1	2850 [230-3200]	2.98	4.65	6.65	-	-	-	11.30 [2.0-13.0]	12.8	2840 [160-4040]	3.98	
	35+60	3.50	6.00	-	-	-	9.50 [2.3-10.1]	16.6	3610 [230-4220]	2.63	4.42	7.58	-	-	-	12.00 [2.0-13.0]	14.1	3130 [160-4040]	3.83	
	35+71	3.50	6.70	-	-	-	10.00 [2.3-10.4]	17.7	3860 [260-4380]	2.59	3.96	8.04	-	-	-	12.00 [2.0-13.0]	14.1	3120 [160-4390]	3.85	
	42+42	4.20	4.20	-	-	-	8.40 [2.3-9.1]	15.5	3380 [250-4000]	2.49	5.60	5.60	-	-	-	11.20 [2.0-13.0]	13.6	3020 [190-4230]	3.71	
	42+50	4.20	5.00	-	-	-	9.20 [2.3-10.0]	15.0	3270 [230-4070]	2.81	5.48	6.52	-	-	-	12.00 [2.0-13.0]	14.1	3120 [160-3970]	3.85	
	42+60	4.12	5.88	-	-	-	10.00 [2.3-10.4]	18.7	4070 [230-4370]	2.46	4.94	7.06	-	-	-	12.00 [2.0-13.8]	14.1	3120 [160-4390]	3.85	
	42+71	3.72	6.28	-	-	-	10.00 [2.3-10.4]	17.4	3790 [260-4380]	2.64	4.46	7.54	-	-	-	12.00 [2.0-13.8]	14.0	3110 [160-4380]	3.86	
	50+50	5.00	5.00	-	-	-	10.00 [2.3-10.4]	15.2	3310 [250-3650]	3.02	6.00	6.00	-	-	-	12.00 [2.0-13.8]	13.1	2910 [170-4140]	4.12	
	50+60	4.55	5.45	-	-	-	10.00 [2.3-10.4]	15.2	3310 [250-3650]	3.02	5.45	6.55	-	-	-	12.00 [2.0-13.8]	13.1	2910 [170-4140]	4.12	
	50+71	4.13	5.87	-	-	-	10.00 [2.3-10.4]	14.5	3170 [250-3520]	3.15	4.96	7.04	-	-	-	12.00 [2.0-13.8]	13.0	2890 [170-4120]	4.15	
	60+60	5.00	5.00	-	-	-	10.00 [2.3-10.4]	15.2	3310 [250-3650]	3.02	6.00	6.00	-	-	-	12.00 [2.0-13.8]	13.1	2910 [170-4140]	4.12	
	60+71	4.58	5.42	-	-	-	10.00 [2.3-10.4]	14.5	3170 [250-3520]	3.15	5.50	6.50	-	-	-	12.00 [2.0-13.8]	13.0	2890 [170-4120]	4.15	
	71+71	5.00	5.00	-	-	-	10.00 [2.3-10.4]	13.9	3040 [280-3380]	3.29	6.00	6.00	-	-	-	12.00 [2.0-13.8]	13.0	2880 [180-4100]	4.17	
	16+16+16	1.60	1.60	1.60	-	-	4.80 [2.3-8.5]	4.9	1050 [260-2680]	4.57	2.60	2.60	2.60	-	-	-	7.80 [2.7-12.3]	8.6	1920 [230-3640]	4.06
	16+16+20	1.60	1.60	2.00	-	-	5.20 [2.3-8.5]	5.4	1160 [260-2680]	4.48	2.58	2.58	3.24	-	-	-	8.40 [2.7-12.3]	9.6	2140 [230-3620]	3.93
	16+16+25	1.60	1.60	2.50	-	-	5.70 [2.3-8.5]	6.3	1350 [260-2680]	4.22	2.47	2.47	3.86	-	-	-	8.80 [2.7-12.3]	10.0	2210 [230-3620]	3.98
	16+16+35	1.60	1.60	3.50	-	-	6.70 [2.3-8.5]	7.7	1670 [260-2610]	4.01	2.32	2.32	5.06	-	-	-	9.70 [2.7-12.3]	11.3	2520 [230-3540]	3.85
	16+16+42	1.60	1.60	4.20	-	-	7.40 [2.3-8.5]	9.2	2010 [250-2550]	3.68	2.34	2.34	6.12	-	-	-	10.80 [2.7-12.3]	11.9	2650 [230-3520]	4.08
	16+16+50	1.60	1.60	5.00	-	-	8.20 [2.3-8.7]	10.0	2170 [280-2350]	3.78	2.34	2.34	7.32	-	-	-	12.00 [2.7-12.9]	12.9	2870 [250-3610]	4.18
16+16+60	1.60	1.60	6.00	-	-	9.20 [2.3-10.1]	11.5	2510 [280-3060]	3.67	2.09	2.09	7.82	-	-	-	12.00 [2.7-13.6]	12.9	2870 [250-3970]	4.18	
16+16+71	1.55	1.55	6.90	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	1.86	1.86	8.28	-	-	-	12.00 [2.7-13.6]	12.9	2860 [250-3890]	4.20	
16+20+20	1.60	2.00	2.00	-	-	5.60 [2.3-8.5]	6.0	1300 [260-2610]	4.31	2.58	3.21	3.21	-	-	-	9.00 [2.7-12.3]	10.1	2250 [230-3610]	4.00	
16+20+25	1.60	2.00	2.50	-	-	6.10 [2.3-8.5]	7.0	1510 [260-2610]	4.04	2.47	3.08	3.85	-	-	-	9.40 [2.7-12.3]	10.8	2390 [230-3610]	3.93	
16+20+35	1.60	2.00	3.50	-	-	7.10 [2.3-8.5]	8.4	1840 [250-2550]	3.86	2.32	2.90	5.08	-	-	-	10.30 [2.7-12.3]	11.5	2550 [230-3520]	4.04	
16+20+42	1.60	2.00	4.20	-	-	7.80 [2.3-8.5]	9.7	2120 [250-2550]	3.68	2.34	2.92	6.14	-	-	-	11.40 [2.7-12.9]	12.6	2790 [230-3800]	4.09	
16+20+50	1.60	2.00	5.00	-	-	8.60 [2.3-9.6]	10.8	2360 [280-2680]	3.64	2.23	2.79	6.98	-	-	-	12.00 [2.7-13.6]	12.9	2860 [250-3890]	4.20	
16+20+60	1.60	2.00	6.00	-	-	9.60 [2.3-10.1]	12.3	2680 [280-3000]	3.58	2.00	2.50	7.50	-	-	-	12.00 [2.7-13.6]	12.9	2860 [250-3890]	4.20	
16+20+71	1.50	1.87	6.63	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	1.80	2.24	7.96	-	-	-	12.00 [2.7-13.8]	12.8	2850 [250-4000]	4.21	
16+25+25	1.60	2.50	2.50	-	-	6.60 [2.3-8.5]	8.0	1720 [260-2610]	3.84	2.38	3.71	3.71	-	-	-	9.80 [2.7-12.3]	11.7	2590 [230-3610]	3.78	
16+25+35	1.60	2.50	3.50	-	-	7.60 [2.3-8.5]	9.7	2120 [250-2550]	3.58	2.25	3.52	4.93	-	-	-	10.70 [2.7-12.3]	12.1	2690 [230-3520]	3.98	
16+25+42	1.60	2.50	4.20	-	-	8.30 [2.3-8.7]	11.1	2420 [250-2600]	3.43	2.28	3.55	5.97	-	-	-	11.80 [2.7-12.9]	13.2	2930 [230-3800]	4.03	
16+25+50	1.60	2.50	5.00	-	-	9.10 [2.3-10.1]	11.2	2450 [280-3000]	3.71	2.11	3.30	6.59	-	-	-	12.00 [2.7-13.6]	12.9	2860 [250-3890]	4.20	
16+25+60	1.58	2.48	5.94	-	-	10.00 [2.3-10.7]	13.4	2930 [280-3540]	3.41	1.90	2.97	7.13	-	-	-	12.00 [2.7-13.6]	12.9	2860 [250-3890]	4.20	
16+25+71	1.43	2.23	6.34	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	1.71	2.68	7.61	-	-	-	12.00 [2.7-13.8]	12.8	2850 [250-4000]	4.21	
16+35+35	1.60	3.50	3.50	-	-	8.60 [2.3-9.6]	11.7	2550 [250-2990]	3.37	2.16	4.72	4.72	-	-	-	11.60 [2.7-13.6]	12.7	2820 [230-4140]	4.11	
16+35+42	1.60	3.50	4.20	-	-	9.30 [2.3-10.1]	13.0	2830 [250-3390]	3.29	2.06	4.52	5.42	-	-	-	12.00 [2.7-13.6]	13.3	2950 [240-4130]	4.07	
16+35+50	1.58	3.47	4.95	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	1.90	4.16	5.94	-	-	-	12.00 [2.7-13.6]	12.5	2780 [250-3860]	4.32	
16+35+60	1.44	3.15	5.41	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	1.73	3.78	6.49	-	-	-					

CU-5Z100VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
3 rooms	16+42+60	1.36	3.56	5.08	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	1.63	4.27	6.10	-	-	12.00 [2.7-13.8]	12.5	2770 [270-3970]	4.33
	16+42+71	1.24	3.26	5.50	-	-	10.00 [2.3-10.7]	12.8	2800 [280-3260]	3.57	1.49	3.91	6.60	-	-	12.00 [2.7-14.1]	12.4	2760 [270-4070]	4.35
	16+50+50	1.38	4.31	4.31	-	-	10.00 [2.3-10.7]	12.0	2610 [320-3000]	3.83	1.66	5.17	5.17	-	-	12.00 [2.7-13.8]	12.0	2660 [300-3760]	4.51
	16+50+60	1.27	3.97	4.76	-	-	10.00 [2.3-10.7]	12.0	2610 [320-3000]	3.83	1.53	4.76	5.71	-	-	12.00 [2.7-13.8]	12.0	2660 [300-3760]	4.51
	16+50+71	1.17	3.65	5.18	-	-	10.00 [2.3-10.7]	11.7	2550 [340-2930]	3.92	1.40	4.38	6.22	-	-	12.00 [2.7-14.1]	11.9	2650 [310-3920]	4.53
	16+60+60	1.18	4.41	4.41	-	-	10.00 [2.3-10.7]	12.0	2610 [320-3000]	3.83	1.42	5.29	5.29	-	-	12.00 [2.7-14.1]	12.0	2660 [300-3930]	4.51
	16+60+71	1.09	4.08	4.83	-	-	10.00 [2.3-10.7]	11.7	2550 [340-2930]	3.92	1.31	4.90	5.79	-	-	12.00 [2.7-14.1]	11.9	2650 [310-3920]	4.53
	16+71+71	1.02	4.49	4.49	-	-	10.00 [2.3-10.7]	11.4	2490 [350-2870]	4.02	1.22	5.39	5.39	-	-	12.00 [2.7-14.4]	11.9	2640 [320-4020]	4.55
	20+20+20	2.00	2.00	2.00	-	-	6.00 [2.3-8.5]	6.7	1450 [260-2610]	4.14	3.20	3.20	3.20	-	-	9.60 [2.7-12.3]	11.2	2480 [230-3600]	3.87
	20+20+25	2.00	2.00	2.50	-	-	6.50 [2.3-8.5]	7.7	1660 [260-2610]	3.92	3.08	3.08	3.84	-	-	10.00 [2.7-12.3]	11.8	2630 [230-3600]	3.80
	20+20+35	2.00	2.00	3.50	-	-	7.50 [2.3-8.5]	9.2	2010 [250-2550]	3.73	2.91	2.91	5.08	-	-	10.90 [2.7-12.3]	12.1	2690 [230-3510]	4.05
	20+20+42	2.00	2.00	4.20	-	-	8.20 [2.3-8.7]	10.8	2360 [250-2600]	3.47	2.93	2.93	6.14	-	-	12.00 [2.7-12.9]	13.6	3020 [230-3790]	3.97
	20+20+50	2.00	2.00	5.00	-	-	9.00 [2.3-9.6]	11.3	2470 [280-2680]	3.64	2.67	2.67	6.66	-	-	12.00 [2.7-13.6]	12.8	2850 [250-3880]	4.21
	20+20+60	2.00	2.00	6.00	-	-	10.00 [2.3-10.7]	13.4	2930 [280-3470]	3.41	2.40	2.40	7.20	-	-	12.00 [2.7-13.6]	12.8	2850 [250-3880]	4.21
	20+20+71	1.80	1.80	6.40	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3330]	3.48	2.16	2.16	7.68	-	-	12.00 [2.7-13.8]	12.6	2790 [250-3980]	4.30
	20+25+25	2.00	2.50	2.50	-	-	7.00 [2.3-8.5]	8.4	1840 [260-2610]	3.80	2.98	3.71	3.71	-	-	10.40 [2.7-12.3]	11.8	2610 [230-3600]	3.98
	20+25+35	2.00	2.50	3.50	-	-	8.00 [2.3-8.5]	10.3	2240 [250-2550]	3.57	2.83	3.53	4.94	-	-	11.30 [2.7-12.9]	12.3	2740 [230-3800]	4.12
	20+25+42	2.00	2.50	4.20	-	-	8.70 [2.3-9.6]	11.9	2600 [250-3060]	3.35	2.76	3.45	5.79	-	-	12.00 [2.7-13.6]	13.6	3020 [230-4150]	3.97
	20+25+50	2.00	2.50	5.00	-	-	9.50 [2.3-10.1]	12.4	2700 [280-3000]	3.52	2.53	3.16	6.31	-	-	12.00 [2.7-13.6]	12.8	2850 [250-3880]	4.21
	20+25+60	1.91	2.38	5.71	-	-	10.00 [2.3-10.7]	13.4	2930 [280-3470]	3.41	2.29	2.86	6.85	-	-	12.00 [2.7-13.6]	12.8	2850 [250-4000]	4.21
	20+25+71	1.72	2.16	6.12	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3330]	3.48	2.07	2.59	7.34	-	-	12.00 [2.7-13.8]	12.6	2790 [250-3980]	4.30
	20+35+35	2.00	3.50	3.50	-	-	9.00 [2.3-9.6]	12.5	2720 [250-2990]	3.31	2.66	4.67	4.67	-	-	12.00 [2.7-13.6]	13.3	2950 [240-4130]	4.07
	20+35+42	2.00	3.50	4.20	-	-	9.70 [2.3-10.7]	13.7	2990 [250-3970]	3.24	2.47	4.33	5.20	-	-	12.00 [2.7-13.6]	13.2	2940 [240-4050]	4.08
	20+35+50	1.91	3.33	4.76	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	2.29	4.00	5.71	-	-	12.00 [2.7-13.8]	12.5	2770 [270-3970]	4.33
	20+35+60	1.74	3.04	5.22	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	2.09	3.65	6.26	-	-	12.00 [2.7-13.8]	12.5	2770 [270-3970]	4.33
	20+35+71	1.59	2.78	5.63	-	-	10.00 [2.3-10.7]	12.8	2800 [280-3260]	3.57	1.91	3.33	6.76	-	-	12.00 [2.7-13.8]	12.4	2760 [270-3950]	4.35
	20+42+42	1.92	4.04	4.04	-	-	10.00 [2.3-10.7]	15.0	3260 [250-3970]	3.07	2.30	4.85	4.85	-	-	12.00 [2.7-13.6]	13.2	2930 [240-4040]	4.10
	20+42+50	1.79	3.75	4.46	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3330]	3.48	2.14	4.50	5.36	-	-	12.00 [2.7-13.8]	12.4	2760 [270-3950]	4.35
	20+42+60	1.64	3.44	4.92	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3330]	3.48	1.97	4.13	5.90	-	-	12.00 [2.7-13.8]	12.4	2760 [270-3950]	4.35
	20+42+71	1.50	3.16	5.34	-	-	10.00 [2.3-10.7]	12.6	2740 [280-3260]	3.65	1.80	3.79	6.41	-	-	12.00 [2.7-14.1]	12.4	2750 [270-4060]	4.36
	20+50+50	1.66	4.17	4.17	-	-	10.00 [2.3-10.7]	12.0	2620 [320-3000]	3.82	2.00	5.00	5.00	-	-	12.00 [2.7-13.8]	11.9	2650 [310-3740]	4.53
	20+50+60	1.54	3.85	4.61	-	-	10.00 [2.3-10.7]	12.0	2620 [320-3000]	3.82	1.85	4.62	5.53	-	-	12.00 [2.7-14.1]	11.9	2650 [310-3920]	4.53
	20+50+71	1.42	3.55	5.03	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	1.70	4.26	6.04	-	-	12.00 [2.7-14.1]	11.9	2640 [320-3900]	4.55
	20+60+60	1.42	4.29	4.29	-	-	10.00 [2.3-10.7]	12.0	2620 [320-3000]	3.82	1.72	5.14	5.14	-	-	12.00 [2.7-14.1]	11.9	2650 [310-3920]	4.53
	20+60+71	1.33	3.97	4.70	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	1.59	4.77	5.64	-	-	12.00 [2.7-14.4]	11.9	2640 [320-4020]	4.55
	20+71+71	1.24	4.38	4.38	-	-	10.00 [2.3-10.7]	11.4	2490 [350-2870]	4.02	1.48	5.26	5.26	-	-	12.00 [2.7-14.4]	12.0	2670 [330-4010]	4.49
	25+25+25	2.50	2.50	2.50	-	-	7.50 [2.3-8.5]	9.5	2070 [260-2610]	3.62	3.60	3.60	3.60	-	-	10.80 [2.7-12.3]	12.0	2670 [230-3600]	4.04
	25+25+35	2.50	2.50	3.50	-	-	8.50 [2.3-9.6]	11.7	2550 [250-3060]	3.33	3.44	3.44	4.82	-	-	11.70 [2.7-12.6]	13.0	2880 [230-4160]	4.06
	25+25+42	2.50	2.50	4.20	-	-	9.20 [2.3-10.1]	13.0	2830 [250-3460]	3.25	3.26	3.26	5.48	-	-	12.00 [2.7-13.6]	13.6	3020 [230-4150]	3.97
	25+25+50	2.50	2.50	5.00	-	-	10.00 [2.3-10.7]	13.4	2930 [280-3470]	3.41	3.00	3.00	6.00	-	-	12.00 [2.7-13.6]	12.8	2850 [250-3880]	4.21
	25+25+60	2.27	2.27	5.66	-	-	10.00 [2.3-10.7]	13.4	2930 [280-3470]	3.41	2.73	2.73	6.54	-	-	12.00 [2.7-13.8]	12.8	2850 [250-4000]	4.21
	25+25+71	2.07	2.07	5.86	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3330]	3.48	2.48	2.48	7.04	-	-	12.00 [2.7-13.8]	12.6	2790 [250-3980]	4.30
	25+35+35	2.50	3.50	3.50	-	-	9.50 [2.3-10.1]	13.6	2960 [250-3390]	3.21	3.16	4.42	4.42	-	-	12.00 [2.7-13.6]	13.3	2950 [240-4130]	4.07
	25+35+42	2.45	3.43	4.12	-	-	10.00 [2.3-10.7]	15.0	3260 [250-3970]	3.07	2.94	4.12	4.94	-	-	12.00 [2.7-13.6]	13.2	2940 [240-4050]	4.08
	25+35+50	2.27	3.18	4.55	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	2.73	3.82	5.45	-	-	12.00 [2.7-13.8]	12.5	2770 [270-3970]	4.33
	25+35+60	2.08	2.92	5.00	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3400]	3.48	2.50	3.50	6.00	-	-	12.00 [2.7-13.8]	12.5	2770 [270-3970]	4.33
	25+35+71	1.91	2.67	5.42	-	-	10.00 [2.3-10.7]	12.8	2800 [280-3260]	3.57	2.29	3.21	6.50	-	-	12.00 [2.7-14.1]	12.4	2760 [270-4070]	4.35
	25+42+42	2.30	3.85	3.85	-	-	10.00 [2.3-10.7]	15.0	3260 [250-3970]	3.07	2.76	4.62	4.62	-	-	12.00 [2.7-13.8]	13.2	2930 [240-4160]	4.10
25+42+50	2.14	3.59	4.27	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3330]	3.48	2.56	4.31	5.13	-	-	12.00 [2.7-13.8]	12.4	2760 [270-3950]	4.35	
25+42+60	1.97	3.31	4.72	-	-	10.00 [2.3-10.7]	13.2	2870 [280-3330]	3.48	2.36	3.97	5.67	-	-	12.00 [2.7-14.1]	12.4	2760 [270-4070]	4.35	
25+42+71	1.82	3.04	5.14	-	-	10.00 [2.3-10.7]	12.6	2740 [280-3260]	3.65	2.18	3.65	6.17	-	-	12.00 [2.7-14.1]	12.4	2750 [270-4060]	4.36	
25+50+50	2.00	4.00	4.00	-	-	10.00 [2.3-10.7]	12.0	2620 [320-3000]	3.82	2.40	4.80	4.80	-	-	12.00 [2.7-13.8]	11.9	2650 [310-3740]	4.53	
25+50+60	1.86	3.70	4.44	-	-	10.00 [2.3-10.7]	12.0	2620 [320-3000]	3.82	2.23	4.44	5.33	-	-	12.00 [2.7-14.1]	11.9	2650 [310-3920]	4.53	
25+50+71	1.72	3.42	4.86	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	2.05	4.11	5.84	-	-	12.00 [2.7-14.1]	11.9	2640 [320-3900]	4.55	
25+60+60	1.72	4.14	4.14	-	-	10.00 [2.3-10.7]	12.0	2620 [320-3000]	3.82	2.06	4.97	4.97	-	-	12.00 [2.7-14.1]	11.9	2650 [310-3920]	4.53	
25+60+71	1.60	3.85	4.55	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	1.92	4.62	5.46	-	-	12.00 [2.7-14.4]	11.9	2640 [320-4020]	4.55	
25+71+71	1.50	4.25	4.25	-	-	10.00 [2.3-10.7]	11.4	2490 [350-2870]	4.02	1.80	5.10	5.10	-	-	12.00 [2.7-14.4]	12.0	2670 [330-4010]	4.49	
35+35+35	3.33	3.33	3.33	-	-	9.99 [2.3-10.7]	14.6	3190 [250-3890]	3.13	4.00	4.00	4.00	-	-	12.00 [2.7-13.8]	13.1	2920 [240-4150]	4.11	
35+35+42	3.13	3.13	3.74	-	-	10.00 [2.3-10.7]	14.6	3190 [250-3820]	3.13	3.75	3.75	4.50	-	-	12.00 [2.7-13.8				

CU-5Z100VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION									
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP	
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E					
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W	
3 rooms	35+42+60	2.55	3.07	4.38	-	-	10.00 [2.3-10.7]	12.8	2800 [280-3260]	3.57	3.07	3.68	5.25	-	-	12.00 [2.7-14.1]	12.3	2740 [270-4040]	4.38
	35+42+71	2.36	2.84	4.80	-	-	10.00 [2.3-10.7]	12.6	2740 [310-3200]	3.65	2.84	3.41	5.75	-	-	12.00 [2.7-14.1]	12.2	2720 [280-4020]	4.41
	35+50+50	2.60	3.70	3.70	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	3.12	4.44	4.44	-	-	12.00 [2.7-14.1]	12.0	2670 [330-3890]	4.49
	35+50+60	2.41	3.45	4.14	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	2.90	4.14	4.96	-	-	12.00 [2.7-14.1]	12.0	2670 [330-3890]	4.49
	35+50+71	2.24	3.21	4.55	-	-	10.00 [2.3-10.7]	11.4	2490 [350-2870]	4.02	2.69	3.85	5.46	-	-	12.00 [2.7-14.4]	12.0	2660 [330-3990]	4.51
	35+60+60	2.26	3.87	3.87	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	2.70	4.65	4.65	-	-	12.00 [2.7-14.4]	12.0	2670 [330-4010]	4.49
	35+60+71	2.11	3.61	4.28	-	-	10.00 [2.3-10.7]	11.4	2490 [350-2870]	4.02	2.53	4.34	5.13	-	-	12.00 [2.7-14.4]	12.0	2660 [330-3990]	4.51
	35+71+71	1.98	4.01	4.01	-	-	10.00 [2.3-10.7]	11.5	2500 [350-2870]	4.00	2.38	4.81	4.81	-	-	12.00 [2.7-14.4]	11.9	2650 [340-3970]	4.53
	42+42+42	3.33	3.33	3.33	-	-	9.99 [2.3-10.7]	14.4	3130 [250-3750]	3.19	4.00	4.00	4.00	-	-	12.00 [2.7-13.8]	13.0	2890 [250-4050]	4.15
	42+42+50	3.13	3.13	3.74	-	-	10.00 [2.3-10.7]	12.6	2740 [280-3260]	3.65	3.76	3.76	4.48	-	-	12.00 [2.7-14.1]	12.3	2730 [280-4020]	4.40
	42+42+60	2.92	2.92	4.16	-	-	10.00 [2.3-10.7]	12.6	2740 [280-3260]	3.65	3.50	3.50	5.00	-	-	12.00 [2.7-14.1]	12.3	2730 [280-4020]	4.40
	42+42+71	2.71	2.71	4.58	-	-	10.00 [2.3-10.7]	12.3	2680 [310-3130]	3.73	3.25	3.25	5.50	-	-	12.00 [2.7-14.4]	12.2	2710 [280-4130]	4.43
	42+50+50	2.96	3.52	3.52	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	3.54	4.23	4.23	-	-	12.00 [2.7-14.1]	12.0	2670 [330-3870]	4.49
	42+50+60	2.76	3.29	3.95	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	3.32	3.95	4.73	-	-	12.00 [2.7-14.4]	12.0	2670 [330-3990]	4.49
	42+50+71	2.58	3.07	4.35	-	-	10.00 [2.3-10.7]	11.4	2490 [350-2870]	4.02	3.09	3.68	5.23	-	-	12.00 [2.7-14.4]	11.9	2650 [340-3980]	4.53
	42+60+60	2.60	3.70	3.70	-	-	10.00 [2.3-10.7]	11.7	2550 [350-2930]	3.92	3.12	4.44	4.44	-	-	12.00 [2.7-14.4]	12.0	2670 [330-3990]	4.49
	42+60+71	2.43	3.47	4.10	-	-	10.00 [2.3-10.7]	11.4	2490 [350-2870]	4.02	2.92	4.16	4.92	-	-	12.00 [2.7-14.4]	11.9	2650 [340-3980]	4.53
	50+50+50	3.33	3.33	3.33	-	-	9.99 [2.3-10.7]	10.9	2380 [390-2740]	4.20	4.00	4.00	4.00	-	-	12.00 [2.7-14.4]	11.8	2620 [400-3910]	4.58
	50+50+60	3.13	3.13	3.74	-	-	10.00 [2.3-10.7]	11.2	2440 [390-2740]	4.10	3.75	3.75	4.50	-	-	12.00 [2.7-14.4]	11.8	2620 [400-3910]	4.58
	50+50+71	2.92	2.92	4.16	-	-	10.00 [2.3-10.7]	10.9	2380 [390-2750]	4.20	3.51	3.51	4.98	-	-	12.00 [2.7-14.4]	11.8	2610 [410-3890]	4.60
50+60+60	2.94	3.53	3.53	-	-	10.00 [2.3-10.7]	11.2	2440 [390-2740]	4.10	3.52	4.24	4.24	-	-	12.00 [2.7-14.4]	11.8	2620 [400-3910]	4.58	
50+60+71	2.77	3.31	3.92	-	-	10.00 [2.3-10.7]	10.9	2380 [390-2750]	4.20	3.31	3.98	4.71	-	-	12.00 [2.7-14.4]	11.8	2610 [410-3890]	4.60	
60+60+60	3.33	3.33	3.33	-	-	9.99 [2.3-10.7]	10.9	2380 [390-2740]	4.20	4.00	4.00	4.00	-	-	12.00 [2.7-14.4]	11.8	2620 [400-3910]	4.58	
4 rooms	16+16+16+16	1.60	1.60	1.60	1.60	-	6.40 [2.3-10.6]	6.9	1480 [310-3560]	4.32	2.60	2.60	2.60	2.60	-	10.40 [3.4-14.2]	10.8	2400 [340-4160]	4.33
	16+16+16+20	1.60	1.60	1.60	2.00	-	6.80 [2.3-10.6]	7.5	1620 [310-3560]	4.20	2.59	2.59	2.59	3.23	-	11.00 [3.4-14.2]	11.4	2540 [340-4150]	4.33
	16+16+16+25	1.60	1.60	1.60	2.50	-	7.30 [2.3-10.6]	8.2	1780 [310-3560]	4.10	2.50	2.50	2.50	3.90	-	11.40 [3.4-14.2]	11.7	2600 [340-4150]	4.38
	16+16+16+35	1.60	1.60	1.60	3.50	-	8.30 [2.3-10.6]	10.0	2170 [310-3480]	3.82	2.31	2.31	2.31	5.07	-	12.00 [3.4-14.2]	12.4	2760 [340-4110]	4.35
	16+16+16+42	1.60	1.60	1.60	4.20	-	9.00 [2.3-10.6]	11.3	2460 [310-3480]	3.66	2.13	2.13	2.13	5.61	-	12.00 [3.4-14.2]	12.4	2750 [340-4100]	4.36
	16+16+16+50	1.60	1.60	1.60	5.00	-	9.80 [2.3-10.6]	12.2	2660 [350-3190]	3.68	1.96	1.96	1.96	6.12	-	12.00 [3.4-14.2]	12.1	2690 [390-3950]	4.46
	16+16+16+60	1.48	1.48	1.48	5.56	-	10.00 [2.3-10.6]	12.8	2790 [350-3190]	3.58	1.78	1.78	1.78	6.66	-	12.00 [3.4-14.2]	12.1	2690 [390-3950]	4.46
	16+16+16+71	1.34	1.34	1.34	5.98	-	10.00 [2.3-10.6]	12.5	2730 [380-3120]	3.66	1.61	1.61	1.61	7.17	-	12.00 [3.4-14.2]	12.1	2680 [400-3930]	4.48
	16+16+20+20	1.60	1.60	2.00	2.00	-	7.20 [2.3-10.6]	8.0	1730 [310-3480]	4.16	2.58	2.58	3.22	3.22	-	11.60 [3.4-14.2]	11.8	2630 [340-4130]	4.41
	16+16+20+25	1.60	1.60	2.00	2.50	-	7.70 [2.3-10.6]	8.9	1930 [310-3480]	3.99	2.49	2.49	3.12	3.90	-	12.00 [3.4-14.2]	12.5	2770 [340-4130]	4.33
	16+16+20+35	1.60	1.60	2.00	3.50	-	8.70 [2.3-10.6]	10.7	2330 [310-3410]	3.73	2.21	2.21	2.76	4.82	-	12.00 [3.4-14.2]	12.4	2750 [340-4100]	4.36
	16+16+20+42	1.60	1.60	2.00	4.20	-	9.40 [2.3-10.6]	12.0	2620 [310-3410]	3.59	2.04	2.04	2.56	5.36	-	12.00 [3.4-14.2]	12.3	2740 [340-4080]	4.38
	16+16+20+50	1.57	1.57	1.96	4.90	-	10.00 [2.3-10.6]	12.8	2790 [350-3190]	3.58	1.88	1.88	2.36	5.88	-	12.00 [3.4-14.2]	12.1	2680 [400-3930]	4.48
	16+16+20+60	1.43	1.43	1.79	5.35	-	10.00 [2.3-10.6]	12.8	2790 [350-3190]	3.58	1.71	1.71	2.15	6.43	-	12.00 [3.4-14.2]	12.1	2680 [400-3930]	4.48
	16+16+20+71	1.30	1.30	1.63	5.77	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.56	1.56	1.95	6.93	-	12.00 [3.4-14.2]	12.0	2670 [400-3920]	4.49
	16+16+25+25	1.60	1.60	2.50	2.50	-	8.20 [2.3-10.6]	9.7	2110 [310-3480]	3.89	2.34	2.34	3.66	3.66	-	12.00 [3.4-14.2]	12.5	2770 [340-4130]	4.33
	16+16+25+35	1.60	1.60	2.50	3.50	-	9.20 [2.3-10.6]	11.7	2560 [310-3410]	3.59	2.09	2.09	3.26	4.56	-	12.00 [3.4-14.2]	12.4	2750 [340-4100]	4.36
	16+16+25+42	1.60	1.60	2.50	4.20	-	9.90 [2.3-10.6]	13.4	2920 [310-3410]	3.39	1.94	1.94	3.03	5.09	-	12.00 [3.4-14.2]	12.3	2740 [340-4080]	4.38
	16+16+25+50	1.50	1.50	2.34	4.66	-	10.00 [2.3-10.6]	12.8	2790 [350-3190]	3.58	1.79	1.79	2.81	5.61	-	12.00 [3.4-14.2]	12.1	2680 [400-3930]	4.48
	16+16+25+60	1.37	1.37	2.14	5.12	-	10.00 [2.3-10.6]	12.8	2790 [350-3190]	3.58	1.64	1.64	2.57	6.15	-	12.00 [3.4-14.2]	12.1	2680 [400-3930]	4.48
16+16+25+71	1.25	1.25	1.95	5.55	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.50	1.50	2.34	6.66	-	12.00 [3.4-14.4]	12.0	2670 [400-3980]	4.49	
16+16+35+35	1.57	1.57	3.43	3.43	-	10.00 [2.3-10.6]	13.4	2920 [320-3410]	3.42	1.88	1.88	4.12	4.12	-	12.00 [3.4-14.2]	12.2	2720 [360-4060]	4.41	
16+16+35+42	1.47	1.47	3.21	3.85	-	10.00 [2.3-10.6]	13.4	2920 [320-3330]	3.42	1.76	1.76	3.86	4.62	-	12.00 [3.4-14.2]	12.2	2710 [360-3980]	4.43	
16+16+35+50	1.37	1.37	2.99	4.27	-	10.00 [2.3-10.6]	12.5	2730 [380-3120]	3.66	1.64	1.64	3.59	5.13	-	12.00 [3.4-14.2]	12.0	2660 [420-3900]	4.51	
16+16+35+60	1.26	1.26	2.76	4.72	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.51	1.51	3.31	5.67	-	12.00 [3.4-14.2]	12.0	2660 [420-3900]	4.51	
16+16+35+71	1.16	1.16	2.54	5.14	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.39	1.39	3.05	6.17	-	12.00 [3.4-14.4]	11.9	2650 [420-3940]	4.53	
16+16+42+42	1.38	1.38	3.62	3.62	-	10.00 [2.3-10.6]	13.4	2920 [320-3330]	3.42	1.66	1.66	4.34	4.34	-	12.00 [3.4-14.2]	12.2	2700 [370-3970]	4.44	
16+16+42+50	1.29	1.29	3.39	4.03	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.55	1.55	4.06	4.84	-	12.00 [3.4-14.2]	11.9	2650 [420-3890]	4.53	
16+16+42+60	1.19	1.19	3.14	4.48	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.43	1.43	3.77	5.37	-					

CU-5Z100VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
4 rooms	16+16+50+50	1.21	1.21	3.79	3.79	-	10.00 [2.3-10.8]	12.0	2610 [430-3060]	3.83	1.45	1.45	4.55	4.55	-	12.00 [3.4-14.4]	11.8	2610 [490-3870]	4.60
	16+16+50+60	1.13	1.13	3.52	4.22	-	10.00 [2.3-11.0]	12.0	2610 [430-3200]	3.83	1.35	1.35	4.23	5.07	-	12.00 [3.4-14.4]	11.8	2610 [490-3870]	4.60
	16+16+50+71	1.05	1.05	3.27	4.63	-	10.00 [2.3-11.0]	12.0	2610 [460-3200]	3.83	1.25	1.25	3.93	5.57	-	12.00 [3.4-14.4]	11.9	2650 [510-3860]	4.53
	16+16+60+60	1.05	1.05	3.95	3.95	-	10.00 [2.3-11.0]	12.0	2610 [430-3200]	3.83	1.26	1.26	4.74	4.74	-	12.00 [3.4-14.4]	11.8	2610 [490-3870]	4.60
	16+16+60+71	0.98	0.98	3.68	4.36	-	10.00 [2.3-11.2]	12.0	2610 [460-3280]	3.83	1.18	1.18	4.42	5.22	-	12.00 [3.4-14.4]	11.9	2650 [510-3860]	4.53
	16+16+71+71	0.92	0.92	4.08	4.08	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.10	1.10	4.90	4.90	-	12.00 [3.4-14.4]	11.9	2640 [510-3900]	4.55
	16+20+20+20	1.60	2.00	2.00	2.00	-	7.60 [2.3-10.6]	8.7	1900 [310-3480]	4.00	2.52	3.16	3.16	3.16	-	12.00 [3.4-14.2]	12.4	2760 [340-4120]	4.35
	16+20+20+25	1.60	2.00	2.00	2.50	-	8.10 [2.3-10.6]	9.4	2050 [310-3480]	3.95	2.38	2.96	2.96	3.70	-	12.00 [3.4-14.2]	12.4	2760 [340-4120]	4.35
	16+20+20+35	1.60	2.00	2.00	3.50	-	9.10 [2.3-10.6]	11.4	2490 [310-3410]	3.65	2.11	2.64	2.64	4.61	-	12.00 [3.4-14.2]	12.3	2740 [340-4080]	4.38
	16+20+20+42	1.60	2.00	2.00	4.20	-	9.80 [2.3-10.6]	12.8	2790 [310-3410]	3.51	1.96	2.45	2.45	5.14	-	12.00 [3.4-14.2]	12.3	2730 [350-4070]	4.40
	16+20+20+50	1.51	1.89	1.89	4.71	-	10.00 [2.3-10.6]	12.5	2730 [360-3120]	3.66	1.82	2.26	2.26	5.66	-	12.00 [3.4-14.2]	12.0	2670 [400-3920]	4.49
	16+20+20+60	1.39	1.72	1.72	5.17	-	10.00 [2.3-10.6]	12.5	2730 [360-3120]	3.66	1.66	2.07	2.07	6.20	-	12.00 [3.4-14.2]	12.0	2670 [400-3920]	4.49
	16+20+20+71	1.27	1.57	1.57	5.59	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.51	1.89	1.89	6.71	-	12.00 [3.4-14.2]	12.0	2660 [420-3900]	4.51
	16+20+25+25	1.60	2.00	2.50	2.50	-	8.60 [2.3-10.6]	10.5	2290 [310-3480]	3.76	2.23	2.79	3.49	3.49	-	12.00 [3.4-14.2]	12.4	2760 [340-4120]	4.35
	16+20+25+35	1.60	2.00	2.50	3.50	-	9.60 [2.3-10.6]	12.5	2720 [310-3410]	3.53	2.00	2.50	3.13	4.37	-	12.00 [3.4-14.2]	12.3	2700 [370-3970]	4.44
	16+20+25+42	1.55	1.94	2.43	4.08	-	10.00 [2.3-10.6]	13.4	2920 [310-3410]	3.42	1.87	2.33	2.91	4.89	-	12.00 [3.4-14.2]	12.3	2730 [350-4070]	4.40
	16+20+25+50	1.45	1.80	2.25	4.50	-	10.00 [2.3-10.6]	12.5	2730 [360-3120]	3.66	1.73	2.16	2.70	5.41	-	12.00 [3.4-14.2]	12.0	2670 [400-3920]	4.49
	16+20+25+60	1.32	1.65	2.07	4.96	-	10.00 [2.3-10.8]	12.5	2730 [360-3260]	3.66	1.59	1.98	2.48	5.95	-	12.00 [3.4-14.2]	12.0	2670 [400-3920]	4.49
	16+20+25+71	1.21	1.52	1.89	5.38	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.46	1.82	2.27	6.45	-	12.00 [3.4-14.4]	12.0	2660 [420-3960]	4.51
	16+20+35+35	1.51	1.89	3.30	3.30	-	10.00 [2.3-10.6]	13.4	2920 [320-3330]	3.42	1.82	2.26	3.96	3.96	-	12.00 [3.4-14.2]	12.2	2710 [360-3980]	4.43
	16+20+35+42	1.42	1.77	3.10	3.71	-	10.00 [2.3-10.6]	13.4	2920 [320-3330]	3.42	1.70	2.12	3.72	4.46	-	12.00 [3.4-14.2]	12.2	2700 [370-3970]	4.44
	16+20+35+50	1.33	1.65	2.89	4.13	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.59	1.98	3.47	4.96	-	12.00 [3.4-14.2]	11.9	2650 [420-3890]	4.53
	16+20+35+60	1.22	1.53	2.67	4.58	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.47	1.83	3.21	5.49	-	12.00 [3.4-14.4]	11.9	2650 [420-3950]	4.53
	16+20+35+71	1.13	1.41	2.46	5.00	-	10.00 [2.3-11.0]	12.2	2660 [390-3340]	3.76	1.35	1.69	2.96	6.00	-	12.00 [3.4-14.4]	11.9	2640 [430-3930]	4.55
	16+20+42+42	1.33	1.67	3.50	3.50	-	10.00 [2.3-10.6]	13.1	2860 [320-3330]	3.50	1.60	2.00	4.20	4.20	-	12.00 [3.4-14.2]	12.1	2690 [370-3960]	4.46
	16+20+42+50	1.25	1.56	3.28	3.91	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.50	1.88	3.94	4.68	-	12.00 [3.4-14.4]	11.9	2640 [420-3930]	4.55
	16+20+42+60	1.16	1.45	3.04	4.35	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.39	1.74	3.65	5.22	-	12.00 [3.4-14.4]	11.9	2640 [420-3930]	4.55
	16+20+42+71	1.07	1.34	2.82	4.77	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.29	1.61	3.38	5.72	-	12.00 [3.4-14.4]	11.8	2630 [430-3920]	4.56
	16+20+50+50	1.18	1.47	3.68	3.67	-	10.00 [2.3-10.8]	12.0	2610 [430-3060]	3.83	1.42	1.76	4.41	4.41	-	12.00 [3.4-14.4]	11.9	2650 [500-3860]	4.53
	16+20+50+60	1.10	1.37	3.42	4.11	-	10.00 [2.3-11.0]	12.0	2610 [430-3200]	3.83	1.32	1.64	4.11	4.93	-	12.00 [3.4-14.4]	11.9	2650 [500-3860]	4.53
	16+20+50+71	1.03	1.27	3.18	4.52	-	10.00 [2.3-11.0]	12.0	2610 [470-3130]	3.83	1.22	1.53	3.82	5.43	-	12.00 [3.4-14.4]	11.9	2640 [510-3900]	4.55
	16+20+60+60	1.03	1.27	3.85	3.85	-	10.00 [2.3-11.0]	12.0	2610 [430-3200]	3.83	1.23	1.53	4.62	4.62	-	12.00 [3.4-14.4]	11.9	2650 [500-3860]	4.53
	16+20+60+71	0.96	1.20	3.59	4.25	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.15	1.44	4.31	5.10	-	12.00 [3.4-14.4]	11.9	2640 [510-3900]	4.55
	16+20+71+71	0.90	1.12	3.99	3.99	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.08	1.34	4.79	4.79	-	12.00 [3.4-14.4]	11.8	2630 [520-3890]	4.56
	16+25+25+25	1.60	2.50	2.50	2.50	-	9.10 [2.3-10.6]	11.4	2490 [310-3480]	3.65	2.10	3.30	3.30	3.30	-	12.00 [3.4-14.2]	12.4	2760 [340-4120]	4.35
	16+25+25+35	1.58	2.48	2.48	3.46	-	10.00 [2.3-10.6]	13.4	2920 [310-3410]	3.42	1.90	2.97	2.97	4.16	-	12.00 [3.4-14.2]	12.3	2740 [340-4080]	4.38
	16+25+25+42	1.49	2.31	2.31	3.89	-	10.00 [2.3-10.6]	13.4	2920 [310-3410]	3.42	1.78	2.78	2.78	4.66	-	12.00 [3.4-14.2]	12.3	2730 [350-4070]	4.40
	16+25+25+50	1.38	2.16	2.16	4.30	-	10.00 [2.3-10.6]	12.5	2730 [360-3120]	3.66	1.66	2.59	2.59	5.16	-	12.00 [3.4-14.2]	12.0	2670 [400-3920]	4.49
	16+25+25+60	1.28	1.98	1.98	4.76	-	10.00 [2.3-10.8]	12.5	2730 [360-3260]	3.66	1.53	2.38	2.38	5.71	-	12.00 [3.4-14.2]	12.0	2670 [400-3920]	4.49
	16+25+25+71	1.18	1.82	1.82	5.18	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.40	2.19	2.19	6.22	-	12.00 [3.4-14.4]	12.0	2660 [420-3960]	4.51
	16+25+35+35	1.45	2.25	3.15	3.15	-	10.00 [2.3-10.6]	13.4	2920 [320-3330]	3.42	1.74	2.70	3.78	3.78	-	12.00 [3.4-14.2]	12.2	2710 [360-3980]	4.43
	16+25+35+42	1.36	2.12	2.97	3.55	-	10.00 [2.3-10.6]	13.4	2920 [320-3330]	3.42	1.63	2.54	3.56	4.27	-	12.00 [3.4-14.2]	12.2	2700 [370-3970]	4.44
	16+25+35+50	1.27	1.98	2.78	3.97	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.53	2.38	3.33	4.76	-	12.00 [3.4-14.2]	11.9	2650 [420-3890]	4.53
	16+25+35+60	1.18	1.84	2.57	4.41	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.41	2.21	3.09	5.29	-	12.00 [3.4-14.4]	11.9	2650 [420-3950]	4.53
	16+25+35+71	1.09	1.70	2.38	4.83	-	10.00 [2.3-11.0]	12.2	2660 [390-3340]	3.76	1.31	2.04	2.86	5.79	-	12.00 [3.4-14.4]	11.9	2640 [430-3930]	4.55
	16+25+42+42	1.28	2.00	3.36	3.36	-	10.00 [2.3-10.8]	13.1	2860 [320-3480]	3.50	1.54	2.40	4.03	4.03	-	12.00 [3.4-14.2]	12.1	2690 [370-3960]	4.46
	16+25+42+50	1.20	1.88	3.16	3.76	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.44	2.26	3.79	4.51	-	12.00 [3.4-14.4]	11.9	2640 [420-3930]	4.55
	16+25+42+60	1.12	1.75	2.94	4.19	-	10.00 [2.3-11.0]	12.5	2730 [390-3340]	3.66	1.35	2.10	3.52	5.03	-	12.00 [3.4-14.4]	11.9	2640 [420-3930]	4.55
16+25+42+71	1.04	1.62	2.73	4.61	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.25	1.95	3.27	5.53	-	12.00 [3.4-14.4]	11.8	2630 [430-3920]	4.56	
16+25+50+50	1.13	1.77	3.55	3.55	-	10.00 [2.3-10.8]	12.0	2610 [430-3060]	3.83	1.36	2.12	4.26	4.26	-	12.00 [3.4-14.4]	11.9	2650 [500-3860]	4.53	
16+25+50+60	1.06	1.66	3.31	3.97	-	10.00 [2.3-11.0]	12.0	2610 [430-3200]	3.83	1.27	1.99	3.97	4.77	-	12.00 [3.4-14.4]	11.9	2650 [500-3860]	4.53	
16+25+50+71	0.99	1.54	3.09	4.38	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.19	1.85	3.70	5.26	-	12.00 [3.4-14.4]	11.9	2640 [510-3900]	4.55	
16+25+60+60	0.99	1.55	3.73	3.73	-	10.00 [2.3-11.2]	12.0	2610 [430-3270]	3.83	1.20	1.86	4.47	4.47	-	12.00 [3.4-14.4]	11.9	2650 [500-3860]	4.53	
16+25+60+71	0.93	1.45	3.49	4.13	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.12	1.74	4.19	4.95	-	12.00 [3.4-14.4]	11.9	2640 [510-3900]	4.55	
16+25+71+71	0.87	1.37	3.88	3.88	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.05	1.63	4.66	4.66	-	12.00 [3.4-14.4]	11.8	2630 [520-3890]	4.56	
16+35+35+35	1.33	2.89	2.89	2.89	-	10.00 [2.3-10.8]	13.1	2860 [340-3410]	3.50	1.59	3.47								

CU-5Z100VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
16+35+42+71	0.98	2.13	2.56	4.33	-	10.00 [2.3-11.2]	12.2	2670 [400-3410]	3.75	1.17	2.56	3.07	5.20	-	12.00 [3.4-14.4]	11.9	2650 [450-3940]	4.53
16+35+50+50	1.06	2.32	3.31	3.31	-	10.00 [2.3-11.0]	12.0	2610 [470-3130]	3.83	1.28	2.78	3.97	3.97	-	12.00 [3.4-14.4]	11.8	2630 [520-3890]	4.56
16+35+50+60	0.99	2.17	3.11	3.73	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.19	2.61	3.73	4.47	-	12.00 [3.4-14.4]	11.8	2630 [520-3890]	4.56
16+35+50+71	0.93	2.03	2.91	4.13	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.12	2.44	3.49	4.95	-	12.00 [3.4-14.4]	11.8	2620 [540-3880]	4.58
16+35+60+60	0.93	2.05	3.51	3.51	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.12	2.46	4.21	4.21	-	12.00 [3.4-14.4]	11.8	2630 [520-3890]	4.56
16+35+60+71	0.88	1.92	3.30	3.90	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.05	2.31	3.96	4.68	-	12.00 [3.4-14.4]	11.8	2620 [540-3880]	4.58
16+42+42+42	1.12	2.96	2.96	2.96	-	10.00 [2.3-11.0]	13.1	2860 [350-3560]	3.50	1.35	3.55	3.55	3.55	-	12.00 [3.4-14.4]	12.2	2700 [390-4030]	4.44
16+42+42+50	1.07	2.80	2.80	3.33	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.28	3.36	3.36	4.00	-	12.00 [3.4-14.4]	12.0	2660 [450-3950]	4.51
16+42+42+60	1.00	2.63	2.63	3.74	-	10.00 [2.3-11.2]	12.2	2660 [390-3410]	3.76	1.20	3.15	3.15	4.50	-	12.00 [3.4-14.4]	12.0	2660 [450-3950]	4.51
16+42+42+71	0.94	2.46	2.46	4.14	-	10.00 [2.3-11.2]	12.2	2670 [420-3420]	3.75	1.12	2.95	2.95	4.98	-	12.00 [3.4-14.4]	11.9	2650 [460-3930]	4.53
16+42+50+50	1.02	2.66	3.16	3.16	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.22	3.18	3.80	3.80	-	12.00 [3.4-14.4]	11.8	2630 [530-3880]	4.56
16+42+50+60	0.95	2.50	2.98	3.57	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.14	3.00	3.57	4.29	-	12.00 [3.4-14.4]	11.8	2630 [530-3880]	4.56
16+42+50+71	0.89	2.35	2.79	3.97	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.07	2.82	3.35	4.76	-	12.00 [3.4-14.4]	11.8	2620 [540-3870]	4.58
16+42+60+60	0.90	2.36	3.37	3.37	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.08	2.84	4.04	4.04	-	12.00 [3.4-14.4]	11.8	2630 [530-3880]	4.56
16+50+50+50	0.97	3.01	3.01	3.01	-	10.00 [2.3-11.2]	11.8	2570 [520-3220]	3.89	1.17	3.61	3.61	3.61	-	12.00 [3.4-14.4]	12.0	2660 [420-3880]	4.51
16+50+50+60	0.91	2.84	2.84	3.41	-	10.00 [2.3-11.2]	11.8	2570 [520-3220]	3.89	1.09	3.41	3.41	4.09	-	12.00 [3.4-14.4]	12.0	2660 [630-3880]	4.51
20+20+20+20	2.00	2.00	2.00	2.00	-	8.00 [2.3-10.6]	9.4	2050 [310-3480]	3.90	3.00	3.00	3.00	3.00	-	12.00 [3.4-14.2]	12.4	2750 [340-4110]	4.36
20+20+20+25	2.00	2.00	2.00	2.50	-	8.50 [2.3-10.6]	10.2	2230 [310-3480]	3.81	2.82	2.82	2.82	3.54	-	12.00 [3.4-14.2]	12.4	2750 [340-4110]	4.36
20+20+20+35	2.00	2.00	2.00	3.50	-	9.50 [2.3-10.6]	12.3	2690 [320-3410]	3.53	2.53	2.53	2.53	4.41	-	12.00 [3.4-14.2]	12.3	2730 [350-4070]	4.40
20+20+20+42	1.96	1.96	1.96	4.12	-	10.00 [2.3-10.6]	13.4	2920 [320-3410]	3.42	2.35	2.35	2.35	4.95	-	12.00 [3.4-14.2]	12.2	2720 [360-4050]	4.41
20+20+20+50	1.82	1.82	1.82	4.54	-	10.00 [2.3-10.6]	12.5	2730 [380-3120]	3.66	2.18	2.18	2.18	5.46	-	12.00 [3.4-14.2]	12.0	2660 [420-3910]	4.51
20+20+20+60	1.67	1.67	1.67	4.99	-	10.00 [2.3-10.6]	12.5	2730 [380-3120]	3.66	2.00	2.00	2.00	6.00	-	12.00 [3.4-14.2]	12.0	2660 [420-3910]	4.51
20+20+20+71	1.53	1.53	1.53	5.41	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.83	1.83	1.83	6.51	-	12.00 [3.4-14.4]	11.9	2650 [420-3950]	4.53
20+20+25+25	2.00	2.00	2.50	2.50	-	9.00 [2.3-10.6]	11.3	2460 [310-3480]	3.66	2.67	2.67	3.33	3.33	-	12.00 [3.4-14.2]	12.4	2750 [340-4110]	4.36
20+20+25+35	2.00	2.00	2.50	3.50	-	10.00 [2.3-10.6]	13.4	2920 [320-3410]	3.42	2.40	2.40	3.00	4.20	-	12.00 [3.4-14.2]	12.3	2730 [350-4070]	4.40
20+20+25+42	1.87	1.87	2.34	3.92	-	10.00 [2.3-10.6]	13.4	2920 [320-3410]	3.42	2.24	2.24	2.81	4.71	-	12.00 [3.4-14.2]	12.2	2720 [360-4050]	4.41
20+20+25+50	1.74	1.74	2.17	4.35	-	10.00 [2.3-10.6]	12.5	2730 [380-3120]	3.66	2.09	2.09	2.61	5.21	-	12.00 [3.4-14.2]	12.0	2660 [420-3910]	4.51
20+20+25+60	1.60	1.60	2.00	4.80	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.92	1.92	2.40	5.76	-	12.00 [3.4-14.2]	12.0	2660 [420-3910]	4.51
20+20+25+71	1.47	1.47	1.84	5.22	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.76	1.76	2.22	6.26	-	12.00 [3.4-14.4]	11.9	2650 [420-3950]	4.53
20+20+35+35	1.82	1.82	3.18	3.18	-	10.00 [2.3-10.6]	13.1	2860 [320-3330]	3.50	2.18	2.18	3.82	3.82	-	12.00 [3.4-14.2]	12.2	2700 [370-3970]	4.44
20+20+35+42	1.71	1.71	2.99	3.59	-	10.00 [2.3-10.6]	13.1	2860 [320-3330]	3.50	2.05	2.05	3.59	4.31	-	12.00 [3.4-14.2]	12.1	2690 [370-3960]	4.46
20+20+35+50	1.60	1.60	2.80	4.00	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.92	1.92	3.36	4.80	-	12.00 [3.4-14.2]	11.9	2640 [420-3880]	4.55
20+20+35+60	1.48	1.48	2.60	4.44	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.78	1.78	3.11	5.33	-	12.00 [3.4-14.4]	11.9	2640 [420-3930]	4.55
20+20+35+71	1.37	1.37	2.40	4.86	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.64	1.64	2.88	5.84	-	12.00 [3.4-14.4]	11.8	2630 [430-3920]	4.56
20+20+42+42	1.61	1.61	3.39	3.39	-	10.00 [2.3-10.8]	13.1	2860 [340-3480]	3.50	1.94	1.94	4.06	4.06	-	12.00 [3.4-14.2]	12.1	2680 [370-3950]	4.48
20+20+42+50	1.52	1.52	3.18	3.78	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.82	1.82	3.82	4.54	-	12.00 [3.4-14.4]	11.8	2630 [430-3920]	4.56
20+20+42+60	1.41	1.41	2.96	4.22	-	10.00 [2.3-11.0]	12.5	2730 [390-3340]	3.66	1.69	1.69	3.55	5.07	-	12.00 [3.4-14.4]	11.8	2630 [430-3920]	4.56
20+20+42+71	1.31	1.31	2.75	4.63	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.57	1.57	3.29	5.57	-	12.00 [3.4-14.4]	11.8	2620 [440-3960]	4.58
20+20+50+50	1.43	1.43	3.57	3.57	-	10.00 [2.3-10.8]	12.0	2610 [440-3060]	3.83	1.71	1.71	4.29	4.29	-	12.00 [3.4-14.4]	11.9	2640 [510-3910]	4.55
20+20+50+60	1.33	1.33	3.34	4.00	-	10.00 [2.3-11.0]	12.0	2610 [440-3200]	3.83	1.60	1.60	4.00	4.80	-	12.00 [3.4-14.4]	11.9	2640 [510-3910]	4.55
20+20+50+71	1.24	1.24	3.11	4.41	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.49	1.49	3.73	5.29	-	12.00 [3.4-14.4]	11.8	2630 [520-3890]	4.56
20+20+60+60	1.25	1.25	3.75	3.75	-	10.00 [2.3-11.2]	12.0	2610 [440-3270]	3.83	1.50	1.50	4.50	4.50	-	12.00 [3.4-14.4]	11.9	2640 [510-3910]	4.55
20+20+60+71	1.17	1.17	3.51	4.15	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.40	1.40	4.22	4.98	-	12.00 [3.4-14.4]	11.8	2630 [520-3890]	4.56
20+20+71+71	1.10	1.10	3.90	3.90	-	10.00 [2.3-11.2]	12.0	2620 [480-3210]	3.82	1.32	1.32	4.68	4.68	-	12.00 [3.4-14.4]	11.8	2630 [530-3880]	4.56
20+25+25+25	2.00	2.50	2.50	2.50	-	9.50 [2.3-10.6]	12.3	2690 [310-3480]	3.53	2.52	3.16	3.16	3.16	-	12.00 [3.4-14.2]	12.4	2750 [340-4110]	4.36
20+25+25+35	1.91	2.38	2.38	3.33	-	10.00 [2.3-10.6]	13.4	2920 [320-3410]	3.42	2.29	2.86	2.86	3.99	-	12.00 [3.4-14.2]	12.3	2730 [350-4070]	4.40
20+25+25+42	1.79	2.23	2.23	3.75	-	10.00 [2.3-10.6]	13.4	2920 [320-3410]	3.42	2.14	2.68	2.68	4.50	-	12.00 [3.4-14.2]	12.2	2720 [360-4050]	4.41
20+25+25+50	1.67	2.08	2.08	4.17	-	10.00 [2.3-10.6]	12.5	2730 [380-3120]	3.66	2.00	2.50	2.50	5.00	-	12.00 [3.4-14.2]	12.0	2660 [420-3910]	4.51
20+25+25+60	1.54	1.92	1.92	4.62	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	1.85	2.31	2.31	5.53	-	12.00 [3.4-14.4]	12.0	2660 [420-3970]	4.51
20+25+25+71	1.42	1.77	1.77	5.04	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.70	2.13	2.13	6.04	-	12.00 [3.4-14.4]	11.9	2650 [420-3950]	4.53
20+25+35+35	1.75	2.17	3.04	3.04	-	10.00 [2.3-10.6]	13.1	2860 [320-3330]	3.50	2.09	2.61	3.65	3.65	-	12.00 [3.4-14.2]	12.2	2700 [370-3970]	4.44
20+25+35+42	1.64	2.05	2.87	3.44	-	10.00 [2.3-10.8]	13.1	2860 [320-3480]	3.50	1.97	2.46	3.44	4.13	-	12.00 [3.4-14.2]	12.1	2690 [370-3960]	4.46
20+25+35+50	1.54	1.92	2.69	3.85	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.85	2.31	3.23	4.61	-	12.00 [3.4-14.4]	11.9	2640 [420-3930]	4.55
20+25+35+60	1.43	1.79	2.50	4.28	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	1.72	2.14	3.00	5.14	-	12.00 [3.4-14.4]	11.9	2640 [420-3930]	4.55
20+25+35+71	1.32	1.66	2.32	4.70	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.59	1.99	2.78	5.64	-	12.00 [3.4-14.4]	11.8	2630 [430-3920]	4.56
20+25+42+42	1.55	1.93	3.26	3.26	-	10.00 [2.3-10.8]	13.1	2860 [340-3480]	3.50	1.86	2.32	3.91	3.91					

CU-5Z100VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
20+25+60+71	1.14	1.42	3.41	4.03	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.37	1.70	4.09	4.84	-	12.00 [3.4-14.4]	11.8	2630 [520-3890]	4.56
20+35+35+35	1.60	2.80	2.80	2.80	-	10.00 [2.3-10.8]	13.1	2860 [350-3410]	3.50	1.92	3.36	3.36	3.36	-	12.00 [3.4-14.2]	12.1	2680 [370-3940]	4.48
20+35+35+42	1.52	2.65	2.65	3.18	-	10.00 [2.3-10.8]	13.1	2860 [350-3410]	3.50	1.82	3.18	3.18	3.82	-	12.00 [3.4-14.4]	12.2	2710 [370-4040]	4.43
20+35+35+50	1.43	2.50	2.50	3.57	-	10.00 [2.3-10.8]	12.2	2660 [390-3190]	3.76	1.71	3.00	3.00	4.29	-	12.00 [3.4-14.4]	11.8	2620 [450-3960]	4.58
20+35+35+60	1.34	2.33	2.33	4.00	-	10.00 [2.3-11.0]	12.2	2660 [390-3340]	3.76	1.60	2.80	2.80	4.80	-	12.00 [3.4-14.4]	11.8	2620 [450-3960]	4.58
20+35+35+71	1.25	2.17	2.17	4.41	-	10.00 [2.3-11.2]	12.2	2670 [420-3410]	3.75	1.49	2.61	2.61	5.29	-	12.00 [3.4-14.4]	11.9	2650 [450-3940]	4.53
20+35+42+42	1.44	2.52	3.02	3.02	-	10.00 [2.3-10.8]	13.1	2860 [350-3410]	3.50	1.73	3.01	3.63	3.63	-	12.00 [3.4-14.4]	12.2	2700 [390-4030]	4.44
20+35+42+50	1.36	2.38	2.86	3.40	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.63	2.86	3.43	4.08	-	12.00 [3.4-14.4]	12.0	2660 [450-3950]	4.51
20+35+42+60	1.27	2.23	2.68	3.82	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.53	2.68	3.21	4.58	-	12.00 [3.4-14.4]	12.0	2660 [450-3950]	4.51
20+35+42+71	1.19	2.08	2.50	4.23	-	10.00 [2.3-11.2]	12.2	2670 [420-3420]	3.75	1.43	2.50	3.00	5.07	-	12.00 [3.4-14.4]	11.9	2650 [460-3930]	4.53
20+35+50+50	1.29	2.25	3.23	3.23	-	10.00 [2.3-11.0]	12.0	2610 [470-3130]	3.83	1.55	2.71	3.87	3.87	-	12.00 [3.4-14.4]	11.8	2630 [530-3880]	4.56
20+35+50+60	1.21	2.12	3.03	3.64	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.45	2.55	3.64	4.36	-	12.00 [3.4-14.4]	11.8	2630 [530-3880]	4.56
20+35+50+71	1.14	1.99	2.84	4.03	-	10.00 [2.3-11.2]	12.0	2620 [480-3280]	3.82	1.36	2.39	3.41	4.84	-	12.00 [3.4-14.4]	11.8	2620 [540-3870]	4.58
20+35+60+60	1.14	2.00	3.43	3.43	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.38	2.40	4.11	4.11	-	12.00 [3.4-14.4]	11.8	2630 [530-3880]	4.56
20+42+42+42	1.36	2.88	2.88	2.88	-	10.00 [2.3-11.0]	12.8	2790 [350-3480]	3.58	1.65	3.45	3.45	3.45	-	12.00 [3.4-14.4]	12.2	2700 [390-4020]	4.44
20+42+42+50	1.30	2.73	2.73	3.24	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.56	3.27	3.27	3.90	-	12.00 [3.4-14.4]	11.9	2650 [450-3940]	4.53
20+42+42+60	1.22	2.56	2.56	3.66	-	10.00 [2.3-11.2]	12.2	2660 [390-3410]	3.76	1.47	3.07	3.07	4.39	-	12.00 [3.4-14.4]	11.9	2650 [450-3940]	4.53
20+42+42+71	1.14	2.40	2.40	4.06	-	10.00 [2.3-11.2]	12.2	2670 [420-3340]	3.75	1.37	2.88	2.88	4.87	-	12.00 [3.4-14.4]	11.9	2640 [460-3920]	4.55
20+42+50+50	1.23	2.59	3.09	3.09	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.49	3.11	3.70	3.70	-	12.00 [3.4-14.4]	11.8	2620 [540-3870]	4.58
20+42+50+60	1.16	2.44	2.91	3.49	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.40	2.93	3.49	4.18	-	12.00 [3.4-14.4]	11.8	2620 [540-3870]	4.58
20+42+50+71	1.09	2.30	2.73	3.88	-	10.00 [2.3-11.2]	12.0	2620 [480-3210]	3.82	1.31	2.75	3.28	4.66	-	12.00 [3.4-14.4]	12.0	2660 [550-3860]	4.51
20+42+60+60	1.10	2.30	3.30	3.30	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.32	2.76	3.96	3.96	-	12.00 [3.4-14.4]	11.8	2620 [540-3870]	4.58
20+50+50+50	1.18	2.94	2.94	2.94	-	10.00 [2.3-11.2]	11.8	2570 [550-3220]	3.89	1.41	3.53	3.53	3.53	-	12.00 [3.4-14.4]	12.1	2690 [630-3870]	4.46
20+50+50+60	1.11	2.78	2.78	3.33	-	10.00 [2.3-11.2]	11.8	2570 [550-3220]	3.89	1.34	3.33	3.33	4.00	-	12.00 [3.4-14.4]	12.1	2690 [630-3870]	4.46
25+25+25+25	2.50	2.50	2.50	2.50	-	10.00 [2.3-10.6]	13.7	2990 [310-3480]	3.34	3.00	3.00	3.00	3.00	-	12.00 [3.4-14.2]	12.4	2750 [340-4110]	4.36
25+25+25+35	2.27	2.27	2.27	3.19	-	10.00 [2.3-10.6]	13.4	2920 [320-3410]	3.42	2.73	2.73	2.73	3.81	-	12.00 [3.4-14.2]	12.3	2730 [350-4070]	4.40
25+25+25+42	2.14	2.14	2.14	3.58	-	10.00 [2.3-10.6]	13.4	2920 [320-3410]	3.42	2.56	2.56	2.56	4.32	-	12.00 [3.4-14.2]	12.2	2720 [360-4050]	4.41
25+25+25+50	2.00	2.00	2.00	4.00	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	2.40	2.40	2.40	4.80	-	12.00 [3.4-14.2]	12.0	2660 [420-3910]	4.51
25+25+25+60	1.85	1.85	1.85	4.45	-	10.00 [2.3-10.8]	12.5	2730 [380-3260]	3.66	2.22	2.22	2.22	5.34	-	12.00 [3.4-14.4]	12.0	2660 [420-3970]	4.51
25+25+25+71	1.71	1.71	1.71	4.87	-	10.00 [2.3-11.0]	12.5	2730 [390-3340]	3.66	2.05	2.05	2.05	5.85	-	12.00 [3.4-14.4]	11.9	2650 [420-3950]	4.53
25+25+35+35	2.08	2.08	2.92	2.92	-	10.00 [2.3-10.6]	13.1	2860 [320-3330]	3.50	2.50	2.50	3.50	3.50	-	12.00 [3.4-14.2]	12.2	2700 [370-3970]	4.44
25+25+35+42	1.97	1.97	2.76	3.30	-	10.00 [2.3-10.8]	13.1	2860 [320-3480]	3.50	2.36	2.36	3.31	3.97	-	12.00 [3.4-14.2]	12.1	2690 [370-3960]	4.46
25+25+35+50	1.85	1.85	2.60	3.70	-	10.00 [2.3-10.8]	12.5	2730 [390-3190]	3.66	2.22	2.22	3.12	4.44	-	12.00 [3.4-14.4]	11.9	2640 [420-3930]	4.55
25+25+35+60	1.72	1.72	2.42	4.14	-	10.00 [2.3-11.0]	12.5	2730 [390-3340]	3.66	2.07	2.07	2.90	4.96	-	12.00 [3.4-14.4]	11.9	2640 [420-3930]	4.55
25+25+35+71	1.60	1.60	2.25	4.55	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.92	1.92	2.70	5.46	-	12.00 [3.4-14.4]	11.8	2630 [430-3920]	4.56
25+25+42+42	1.87	1.87	3.13	3.13	-	10.00 [2.3-10.8]	13.1	2860 [340-3480]	3.50	2.24	2.24	3.76	3.76	-	12.00 [3.4-14.4]	12.1	2680 [370-4070]	4.48
25+25+42+50	1.76	1.76	2.96	3.52	-	10.00 [2.3-11.0]	12.5	2730 [390-3340]	3.66	2.11	2.11	3.55	4.23	-	12.00 [3.4-14.4]	11.8	2630 [430-3920]	4.56
25+25+42+60	1.64	1.64	2.77	3.95	-	10.00 [2.3-11.0]	12.5	2730 [390-3340]	3.66	1.97	1.97	3.32	4.74	-	12.00 [3.4-14.4]	11.8	2630 [430-3920]	4.56
25+25+42+71	1.53	1.53	2.58	4.36	-	10.00 [2.3-11.2]	12.2	2660 [390-3410]	3.76	1.84	1.84	3.09	5.23	-	12.00 [3.4-14.4]	11.8	2620 [440-3960]	4.58
25+25+50+50	1.67	1.67	3.33	3.33	-	10.00 [2.3-11.0]	12.0	2610 [440-3200]	3.83	2.00	2.00	4.00	4.00	-	12.00 [3.4-14.4]	11.9	2640 [510-3910]	4.55
25+25+50+60	1.56	1.56	3.13	3.75	-	10.00 [2.3-11.2]	12.0	2610 [440-3270]	3.83	1.88	1.88	3.75	4.49	-	12.00 [3.4-14.4]	11.9	2640 [510-3910]	4.55
25+25+50+71	1.46	1.46	2.93	4.15	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.75	1.75	3.52	4.98	-	12.00 [3.4-14.4]	11.8	2630 [520-3890]	4.56
25+25+60+60	1.47	1.47	3.53	3.53	-	10.00 [2.3-11.2]	12.0	2610 [440-3270]	3.83	1.76	1.76	4.24	4.24	-	12.00 [3.4-14.4]	11.9	2640 [510-3910]	4.55
25+25+60+71	1.38	1.38	3.32	3.92	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.66	1.66	3.98	4.70	-	12.00 [3.4-14.4]	11.8	2630 [520-3890]	4.56
25+35+35+35	1.93	2.69	2.69	2.69	-	10.00 [2.3-10.8]	13.1	2860 [350-3410]	3.50	2.31	3.23	3.23	3.23	-	12.00 [3.4-14.4]	12.1	2680 [370-4060]	4.48
25+35+35+42	1.83	2.55	2.55	3.07	-	10.00 [2.3-10.8]	13.1	2860 [350-3410]	3.50	2.19	3.07	3.07	3.67	-	12.00 [3.4-14.4]	12.2	2710 [370-4040]	4.43
25+35+35+50	1.73	2.41	2.41	3.45	-	10.00 [2.3-11.0]	12.2	2660 [390-3340]	3.76	2.07	2.90	2.90	4.13	-	12.00 [3.4-14.4]	11.8	2620 [450-3960]	4.58
25+35+35+60	1.61	2.26	2.26	3.87	-	10.00 [2.3-11.0]	12.2	2660 [390-3340]	3.76	1.94	2.71	2.71	4.64	-	12.00 [3.4-14.4]	11.8	2620 [450-3960]	4.58
25+35+35+71	1.51	2.11	2.11	4.27	-	10.00 [2.3-11.2]	12.2	2670 [420-3410]	3.75	1.81	2.53	2.53	5.13	-	12.00 [3.4-14.4]	11.9	2650 [450-3940]	4.53
25+35+42+42	1.74	2.42	2.92	2.92	-	10.00 [2.3-11.0]	13.1	2860 [350-3560]	3.50	2.08	2.92	3.50	3.50	-	12.00 [3.4-14.4]	12.2	2700 [390-4030]	4.44
25+35+42+50	1.65	2.30	2.76	3.29	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	1.97	2.76	3.32	3.95	-	12.00 [3.4-14.4]	12.0	2660 [450-3950]	4.51
25+35+42+60	1.55	2.16	2.59	3.70	-	10.00 [2.3-11.2]	12.2	2660 [390-3410]	3.76	1.86	2.59	3.11	4.44	-	12.00 [3.4-14.4]	12.0	2660 [450-3950]	4.51
25+35+42+71	1.45	2.02	2.43	4.10	-	10.00 [2.3-11.2]	12.2	2670 [420-3420]	3.75	1.74	2.43	2.91	4.92	-	12.00 [3.4-14.4]	11.9	2650 [460-3930]	4.53
25+35+50+50	1.56	2.18	3.13	3.13	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.88	2.62	3.75	3.75	-	12.00 [3.4-14.4]	11.8	2630 [530-3880]	4.56
25+35+50+60	1.47	2.06	2.94	3.53	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	1.76	2.47	3.53	4.24	-	12.00 [3.4-14.4]	11.8	2630 [530-3880]	4.56
25+35+50+71	1.39	1.93	2.76	3.92	-	10.00 [2.3-11.2]	12.0	2620 [480-3280]	3.82	1.66	2.32	3.31						

CU-5Z100VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP	
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
4 rooms	25+50+50+50	1.42	2.86	2.86	2.86	-	10.00 [2.3-11.2]	11.8	2570 [550-3220]	3.89	1.71	3.43	3.43	3.43	-	12.00 [3.4-14.4]	12.1	2690 [630-3870]	4.46
	35+35+35+35	2.50	2.50	2.50	2.50	-	10.00 [2.3-10.8]	12.8	2790 [350-3330]	3.58	3.00	3.00	3.00	3.00	-	12.00 [3.4-14.4]	12.2	2700 [390-4020]	4.44
	35+35+35+42	2.38	2.38	2.38	2.86	-	10.00 [2.3-11.0]	12.8	2790 [350-3480]	3.58	2.86	2.86	2.86	3.42	-	12.00 [3.4-14.4]	12.1	2690 [390-4010]	4.46
	35+35+35+50	2.26	2.26	2.26	3.22	-	10.00 [2.3-11.0]	12.2	2660 [390-3270]	3.76	2.71	2.71	2.71	3.87	-	12.00 [3.4-14.4]	11.9	2650 [460-3930]	4.53
	35+35+35+60	2.12	2.12	2.12	3.64	-	10.00 [2.3-11.2]	12.2	2660 [390-3410]	3.76	2.55	2.55	2.55	4.35	-	12.00 [3.4-14.4]	11.9	2650 [460-3930]	4.53
	35+35+35+71	1.99	1.99	1.99	4.03	-	10.00 [2.3-11.2]	12.2	2670 [430-3340]	3.75	2.39	2.39	2.39	4.83	-	12.00 [3.4-14.4]	11.9	2640 [470-3910]	4.55
	35+35+42+42	2.27	2.27	2.73	2.73	-	10.00 [2.3-11.0]	12.8	2790 [350-3480]	3.58	2.73	2.73	3.27	3.27	-	12.00 [3.4-14.4]	12.1	2680 [400-4000]	4.48
	35+35+42+50	2.16	2.16	2.59	3.09	-	10.00 [2.3-11.2]	12.2	2670 [420-3410]	3.75	2.59	2.59	3.12	3.70	-	12.00 [3.4-14.4]	11.9	2640 [470-3920]	4.55
	35+35+42+60	2.03	2.03	2.45	3.49	-	10.00 [2.3-11.2]	12.2	2670 [420-3410]	3.75	2.44	2.44	2.93	4.19	-	12.00 [3.4-14.4]	11.9	2640 [470-3920]	4.55
	35+35+42+71	1.91	1.91	2.30	3.88	-	10.00 [2.3-11.2]	12.2	2670 [430-3340]	3.75	2.30	2.30	2.75	4.65	-	12.00 [3.4-14.4]	11.8	2630 [480-3900]	4.56
	35+35+50+50	2.06	2.06	2.94	2.94	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	2.47	2.47	3.53	3.53	-	12.00 [3.4-14.4]	11.9	2650 [550-3850]	4.53
	35+35+50+60	1.94	1.94	2.79	3.33	-	10.00 [2.3-11.2]	12.0	2610 [470-3280]	3.83	2.33	2.33	3.33	4.01	-	12.00 [3.4-14.4]	11.9	2650 [550-3850]	4.53
	35+42+42+42	2.17	2.61	2.61	2.61	-	10.00 [2.3-11.2]	12.8	2790 [350-3640]	3.58	2.61	3.13	3.13	3.13	-	12.00 [3.4-14.4]	12.0	2670 [400-3980]	4.49
	35+42+42+50	2.07	2.49	2.49	2.95	-	10.00 [2.3-11.2]	12.2	2670 [420-3420]	3.75	2.49	2.98	2.98	3.55	-	12.00 [3.4-14.4]	11.8	2630 [480-3900]	4.56
	35+42+42+60	1.96	2.35	2.35	3.34	-	10.00 [2.3-11.2]	12.2	2670 [420-3420]	3.75	2.35	2.82	2.82	4.01	-	12.00 [3.4-14.4]	11.8	2630 [480-3900]	4.56
	35+42+50+50	1.99	2.37	2.82	2.82	-	10.00 [2.3-11.2]	12.0	2620 [470-3280]	3.82	2.37	2.85	3.39	3.39	-	12.00 [3.4-14.4]	11.9	2650 [560-3840]	4.53
5 rooms	42+42+42+42	2.50	2.50	2.50	2.50	-	10.00 [2.3-11.2]	12.8	2790 [350-3560]	3.58	3.00	3.00	3.00	3.00	-	12.00 [3.4-14.4]	12.0	2660 [400-3970]	4.51
	42+42+42+50	2.39	2.39	2.39	2.83	-	10.00 [2.3-11.2]	12.2	2670 [420-3340]	3.75	2.86	2.86	2.86	3.42	-	12.00 [3.4-14.4]	11.8	2620 [480-3890]	4.58
	16+16+16+16+16	1.60	1.60	1.60	1.60	1.60	8.00 [2.3-11.5]	8.4	1840 [390-3660]	4.35	2.40	2.40	2.40	2.40	2.40	12.00 [3.4-14.5]	12.0	2750 [540-4020]	4.36
	16+16+16+16+20	1.60	1.60	1.60	1.60	2.00	8.40 [2.3-11.5]	8.9	1950 [390-3660]	4.31	2.29	2.29	2.29	2.29	2.84	12.00 [3.4-14.5]	12.0	2740 [560-4010]	4.38
	16+16+16+16+25	1.60	1.60	1.60	1.60	2.50	8.90 [2.3-11.5]	9.6	2120 [390-3660]	4.20	2.16	2.16	2.16	2.16	3.36	12.00 [3.4-14.5]	12.0	2740 [560-4010]	4.38
	16+16+16+16+35	1.60	1.60	1.60	1.60	3.50	9.90 [2.3-11.5]	11.5	2540 [420-3590]	3.90	1.94	1.94	1.94	1.94	4.24	12.00 [3.4-14.5]	12.1	2770 [570-3970]	4.33
	16+16+16+16+42	1.51	1.51	1.51	1.51	3.96	10.00 [2.3-11.5]	11.8	2600 [430-3590]	3.85	1.81	1.81	1.81	1.81	4.76	12.00 [3.4-14.5]	12.1	2760 [580-4020]	4.35
	16+16+16+16+50	1.40	1.40	1.40	1.40	4.40	10.00 [2.3-11.5]	11.6	2550 [480-3450]	3.92	1.68	1.68	1.68	1.68	5.28	12.00 [3.4-14.5]	12.2	2780 [680-3950]	4.32
	16+16+16+16+60	1.29	1.29	1.29	1.29	4.84	10.00 [2.3-11.5]	11.6	2550 [480-3450]	3.92	1.55	1.55	1.55	1.55	5.80	12.00 [3.4-14.5]	12.2	2780 [680-3950]	4.32
	16+16+16+16+71	1.19	1.19	1.19	1.19	5.24	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.42	1.42	1.42	1.42	6.32	12.00 [3.4-14.5]	12.1	2770 [700-3940]	4.33
	16+16+16+20+20	1.60	1.60	1.60	2.00	2.00	8.80 [2.3-11.5]	9.6	2120 [420-3580]	4.15	2.18	2.18	2.18	2.73	2.73	12.00 [3.4-14.5]	12.0	2740 [560-3990]	4.38
	16+16+16+20+25	1.60	1.60	1.60	2.00	2.50	9.30 [2.3-11.5]	10.4	2290 [420-3580]	4.06	2.06	2.06	2.06	2.59	3.23	12.00 [3.4-14.5]	12.0	2740 [560-3990]	4.38
	16+16+16+20+35	1.55	1.55	1.55	1.95	3.40	10.00 [2.3-11.5]	11.8	2600 [430-3590]	3.85	1.86	1.86	1.86	2.34	4.08	12.00 [3.4-14.5]	12.1	2760 [580-4020]	4.35
	16+16+16+20+42	1.45	1.45	1.45	1.83	3.82	10.00 [2.3-11.5]	11.8	2600 [430-3590]	3.85	1.75	1.75	1.75	2.18	4.57	12.00 [3.4-14.5]	12.0	2750 [600-4010]	4.36
	16+16+16+20+50	1.36	1.36	1.36	1.69	4.23	10.00 [2.3-11.5]	11.6	2560 [510-3450]	3.91	1.63	1.63	1.63	2.03	5.08	12.00 [3.4-14.5]	12.1	2770 [700-3940]	4.33
	16+16+16+20+60	1.25	1.25	1.25	1.56	4.69	10.00 [2.3-11.5]	11.6	2560 [510-3450]	3.91	1.50	1.50	1.50	1.88	5.62	12.00 [3.4-14.5]	12.1	2770 [700-3940]	4.33
16+16+16+20+71	1.15	1.15	1.15	1.44	5.11	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.38	1.38	1.38	1.73	6.13	12.00 [3.4-14.5]	12.1	2760 [710-3930]	4.35	
16+16+16+25+25	1.60	1.60	1.60	2.50	2.50	9.80 [2.3-11.5]	11.5	2540 [420-3580]	3.86	1.96	1.96	1.96	3.06	3.06	12.00 [3.4-14.5]	12.0	2740 [560-3990]	4.38	
16+16+16+25+35	1.48	1.48	1.48	2.32	3.24	10.00 [2.3-11.5]	11.8	2600 [430-3590]	3.85	1.78	1.78	1.78	2.78	3.88	12.00 [3.4-14.5]	12.1	2760 [580-4020]	4.35	
16+16+16+25+42	1.39	1.39	1.39	2.18	3.65	10.00 [2.3-11.5]	11.8	2600 [430-3590]	3.85	1.67	1.67	1.67	2.61	4.38	12.00 [3.4-14.5]	12.0	2750 [600-4010]	4.36	
16+16+16+25+50	1.30	1.30	1.30	2.03	4.07	10.00 [2.3-11.5]	11.6	2560 [510-3450]	3.91	1.56	1.56	1.56	2.44	4.88	12.00 [3.4-14.5]	12.1	2770 [700-3940]	4.33	
16+16+16+25+60	1.20	1.20	1.20	1.89	4.51	10.00 [2.3-11.5]	11.6	2560 [510-3450]	3.91	1.44	1.44	1.44	2.27	5.41	12.00 [3.4-14.5]	12.1	2770 [700-3940]	4.33	
16+16+16+25+71	1.11	1.11	1.11	1.74	4.93	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.33	1.33	1.33	2.09	5.92	12.00 [3.4-14.5]	12.1	2760 [710-3930]	4.35	
16+16+16+35+35	1.36	1.36	1.36	2.96	2.96	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.62	1.62	1.62	3.57	3.57	12.00 [3.4-14.5]	12.0	2740 [600-3990]	4.38	
16+16+16+35+42	1.28	1.28	1.28	2.80	3.36	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.54	1.54	1.54	3.36	4.02	12.00 [3.4-14.5]	12.0	2740 [610-3980]	4.38	
16+16+16+35+50	1.20	1.20	1.20	2.64	3.76	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.44	1.44	1.44	3.17	4.51	12.00 [3.4-14.5]	12.1	2760 [720-3970]	4.35	
16+16+16+35+60	1.12	1.12	1.12	2.45	4.19	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.34	1.34	1.34	2.95	5.03	12.00 [3.4-14.5]	12.1	2760 [720-3970]	4.35	
16+16+16+35+71	1.04	1.04	1.04	2.27	4.61	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.25	1.25	1.25	2.73	5.52	12.00 [3.4-14.5]	12.2	2790 [740-3960]	4.30	
16+16+16+42+42	1.22	1.22	1.22	3.17	3.17	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.46	1.46	1.46	3.81	3.81	12.00 [3.4-14.5]	11.9	2730 [630-3970]	4.40	
16+16+16+42+50	1.14	1.14	1.14	3.01	3.57	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.37	1.37	1.37	3.60	4.29	12.00 [3.4-14.5]	12.0	2750 [740-3960]	4.36	
16+16+16+42+60	1.07	1.07	1.07	2.80	3.99	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.28	1.28	1.28	3.36	4.80	12.00 [3.4-14.5]	12.0	2750 [740-3960]	4.36	
16+16+16+42+71	0.99	0.99	0.99	2.62	4.41	10.00 [2.3-11.5]	11.4	2500 [520-3390]	4.00	1.19	1.19	1.19	3.14	5.29	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30	
16+16+16+50+50	1.08	1.08	1.08	3.38	3.38	10.00 [2.3-11.5]	11.5	2520 [600-3330]	3.97	1.30	1.30	1.30	4.05	4.05	12.00 [3.4-14.5]	12.4	2830 [860-3980]	4.24	
16+16+16+50+60	1.01	1.01	1.01	3.17	3.80	10.00 [2.3-11.5]	11.5	2520 [600-3330]	3.97	1.22	1.22	1.22	3.79	4.55	12.00 [3.4-14.5]	12.4	2830 [860-3980]	4.24	
16+16+16+50+71	0.95	0.95	0.95	2.96	4.19	10.00 [2.3-11.5]	11.5	2530 [610-3340]	3.95	1.14	1.14	1.14	3.55	5.03	12.00 [3.4-14.5]	12.4	2830 [890-3960]	4.24	
16+16+16+60+60	0.96	0.96	0.96	3.56	3.56	10.00 [2.3-11.5]	11.5	2520 [600-3330]	3.97	1.14	1.14	1.14	4.29	4.29	12.00 [3.4-14.5]	12.4	2830 [860-3980]	4.24	
16+16+16+60+71	0.89	0.89	0.89	3.36	3.97	10.00 [2.3-11.5]	11.5	2530 [610-3340]	3.95	1.07	1.07	1.07	4.03	4.76	12.00 [3.4-14.5]	12.4	2830 [890-3960]	4.24	

CU-5Z100VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
16+16+20+20+20	1.60	1.60	2.00	2.00	2.00	9.20 [2.3-11.5]	10.2	2240 [420-3590]	4.11	2.10	2.10	2.60	2.60	2.60	12.00 [3.4-14.5]	12.1	2770 [570-3980]	4.33
16+16+20+20+25	1.60	1.60	2.00	2.00	2.50	9.70 [2.3-11.5]	11.3	2480 [420-3590]	3.91	1.98	1.98	2.47	2.47	3.10	12.00 [3.4-14.5]	12.1	2770 [570-3980]	4.33
16+16+20+20+35	1.50	1.50	1.87	1.87	3.26	10.00 [2.3-11.5]	11.8	2600 [430-3590]	3.85	1.79	1.79	2.24	2.24	3.94	12.00 [3.4-14.5]	12.0	2750 [600-4010]	4.36
16+16+20+20+42	1.41	1.41	1.75	1.75	3.68	10.00 [2.3-11.5]	11.8	2600 [430-3510]	3.85	1.68	1.68	2.11	2.11	4.42	12.00 [3.4-14.5]	12.0	2750 [600-4000]	4.36
16+16+20+20+50	1.31	1.31	1.64	1.64	4.10	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.57	1.57	1.97	1.97	4.92	12.00 [3.4-14.5]	12.1	2770 [710-3930]	4.33
16+16+20+20+60	1.21	1.21	1.52	1.52	4.54	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.45	1.45	1.82	1.82	5.46	12.00 [3.4-14.5]	12.1	2770 [710-3930]	4.33
16+16+20+20+71	1.12	1.12	1.40	1.40	4.96	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.34	1.34	1.68	1.68	5.96	12.00 [3.4-14.5]	12.1	2760 [720-3920]	4.35
16+16+20+25+25	1.57	1.57	1.96	2.45	2.45	10.00 [2.3-11.5]	11.8	2600 [420-3590]	3.85	1.88	1.88	2.36	2.94	2.94	12.00 [3.4-14.5]	12.1	2770 [570-3980]	4.33
16+16+20+25+35	1.43	1.43	1.79	2.23	3.12	10.00 [2.3-11.5]	11.8	2600 [430-3590]	3.85	1.71	1.71	2.15	2.68	3.75	12.00 [3.4-14.5]	12.0	2750 [600-4010]	4.36
16+16+20+25+42	1.34	1.34	1.69	2.10	3.53	10.00 [2.3-11.5]	11.8	2600 [430-3510]	3.85	1.61	1.61	2.02	2.52	4.24	12.00 [3.4-14.5]	12.0	2750 [600-4000]	4.36
16+16+20+25+50	1.26	1.26	1.57	1.97	3.94	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.51	1.51	1.90	2.36	4.72	12.00 [3.4-14.5]	12.1	2770 [710-3930]	4.33
16+16+20+25+60	1.17	1.17	1.46	1.82	4.38	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.40	1.40	1.75	2.19	5.26	12.00 [3.4-14.5]	12.1	2770 [710-3930]	4.33
16+16+20+25+71	1.08	1.08	1.35	1.69	4.80	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.30	1.30	1.62	2.03	5.75	12.00 [3.4-14.5]	12.1	2760 [720-3920]	4.35
16+16+20+35+35	1.31	1.31	1.64	2.87	2.87	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.57	1.57	1.98	3.44	3.44	12.00 [3.4-14.5]	12.0	2740 [610-3980]	4.38
16+16+20+35+42	1.24	1.24	1.55	2.71	3.26	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.49	1.49	1.86	3.26	3.90	12.00 [3.4-14.5]	11.9	2730 [630-3970]	4.40
16+16+20+35+50	1.17	1.17	1.46	2.55	3.65	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.40	1.40	1.75	3.07	4.38	12.00 [3.4-14.5]	12.0	2750 [740-3960]	4.36
16+16+20+35+60	1.09	1.09	1.36	2.38	4.08	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.31	1.31	1.63	2.86	4.89	12.00 [3.4-14.5]	12.0	2750 [740-3960]	4.36
16+16+20+35+71	1.01	1.01	1.27	2.22	4.49	10.00 [2.3-11.5]	11.4	2500 [520-3390]	4.00	1.22	1.22	1.52	2.66	5.38	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
16+16+20+42+42	1.18	1.18	1.46	3.09	3.09	10.00 [2.3-11.5]	11.5	2540 [440-3520]	3.94	1.41	1.41	1.76	3.71	3.71	12.00 [3.4-14.5]	12.1	2770 [640-3960]	4.33
16+16+20+42+50	1.11	1.11	1.39	2.92	3.47	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.33	1.33	1.67	3.50	4.17	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
16+16+20+42+60	1.04	1.04	1.30	2.73	3.89	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.25	1.25	1.56	3.27	4.67	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
16+16+20+42+71	0.97	0.97	1.21	2.55	4.30	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.17	1.17	1.45	3.05	5.16	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
16+16+20+50+50	1.05	1.05	1.32	3.29	3.29	10.00 [2.3-11.5]	11.5	2520 [610-3330]	3.97	1.26	1.26	1.58	3.95	3.95	12.00 [3.4-14.5]	12.4	2830 [870-3970]	4.24
16+16+20+50+60	0.99	0.99	1.23	3.09	3.70	10.00 [2.3-11.5]	11.5	2520 [610-3330]	3.97	1.19	1.19	1.48	3.70	4.44	12.00 [3.4-14.5]	12.4	2830 [870-3970]	4.24
16+16+20+50+71	0.92	0.92	1.17	2.89	4.10	10.00 [2.3-11.5]	11.5	2530 [620-3340]	3.95	1.11	1.11	1.39	3.47	4.92	12.00 [3.4-14.5]	12.6	2870 [900-4010]	4.18
16+16+20+60+60	0.93	0.93	1.16	3.49	3.49	10.00 [2.3-11.5]	11.5	2520 [610-3330]	3.97	1.12	1.12	1.40	4.18	4.18	12.00 [3.4-14.5]	12.4	2830 [870-3970]	4.24
16+16+20+60+71	0.87	0.87	1.10	3.28	3.88	10.00 [2.3-11.5]	11.5	2530 [620-3340]	3.95	1.05	1.05	1.31	3.93	4.66	12.00 [3.4-14.5]	12.6	2870 [900-4010]	4.18
16+16+25+25+25	1.49	1.49	2.34	2.34	2.34	10.00 [2.3-11.5]	11.8	2600 [420-3590]	3.85	1.80	1.80	2.80	2.80	2.80	12.00 [3.4-14.5]	12.1	2770 [570-3980]	4.33
16+16+25+25+35	1.37	1.37	2.14	2.14	2.98	10.00 [2.3-11.5]	11.8	2600 [430-3590]	3.85	1.64	1.64	2.56	2.56	3.60	12.00 [3.4-14.5]	12.0	2750 [600-4010]	4.36
16+16+25+25+42	1.29	1.29	2.02	2.02	3.38	10.00 [2.3-11.5]	11.8	2600 [430-3510]	3.85	1.55	1.55	2.42	2.42	4.06	12.00 [3.4-14.5]	12.0	2750 [600-4000]	4.36
16+16+25+25+50	1.21	1.21	1.89	1.89	3.80	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.45	1.45	2.27	2.27	4.56	12.00 [3.4-14.5]	12.1	2770 [710-3930]	4.33
16+16+25+25+60	1.13	1.13	1.76	1.76	4.22	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.35	1.35	2.11	2.11	5.08	12.00 [3.4-14.5]	12.1	2770 [710-3930]	4.33
16+16+25+25+71	1.05	1.05	1.63	1.63	4.64	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.25	1.25	1.96	1.96	5.58	12.00 [3.4-14.5]	12.1	2760 [720-3920]	4.35
16+16+25+35+35	1.26	1.26	1.96	2.76	2.76	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.51	1.51	2.36	3.31	3.31	12.00 [3.4-14.5]	12.0	2740 [610-3980]	4.38
16+16+25+35+42	1.19	1.19	1.88	2.61	3.13	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.43	1.43	2.25	3.13	3.76	12.00 [3.4-14.5]	11.9	2730 [630-3970]	4.40
16+16+25+35+50	1.13	1.13	1.76	2.46	3.52	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.35	1.35	2.11	2.96	4.23	12.00 [3.4-14.5]	12.0	2750 [740-3960]	4.36
16+16+25+35+60	1.05	1.05	1.65	2.30	3.95	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.26	1.26	1.98	2.76	4.74	12.00 [3.4-14.5]	12.0	2750 [740-3960]	4.36
16+16+25+35+71	0.98	0.98	1.53	2.15	4.36	10.00 [2.3-11.5]	11.4	2500 [520-3390]	4.00	1.18	1.18	1.84	2.58	5.22	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
16+16+25+42+42	1.13	1.13	1.78	2.98	2.98	10.00 [2.3-11.5]	11.5	2540 [440-3520]	3.94	1.36	1.36	2.14	3.57	3.57	12.00 [3.4-14.5]	12.1	2770 [640-3960]	4.33
16+16+25+42+50	1.07	1.07	1.68	2.82	3.36	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.29	1.29	2.01	3.38	4.03	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
16+16+25+42+60	1.01	1.01	1.57	2.64	3.77	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.21	1.21	1.89	3.17	4.52	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
16+16+25+42+71	0.94	0.94	1.47	2.47	4.18	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.13	1.13	1.77	2.96	5.01	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
16+16+25+50+50	1.02	1.02	1.60	3.18	3.18	10.00 [2.3-11.5]	11.5	2520 [610-3330]	3.97	1.22	1.22	1.92	3.82	3.82	12.00 [3.4-14.5]	12.4	2830 [870-3970]	4.24
16+16+25+50+60	0.96	0.96	1.50	2.99	3.59	10.00 [2.3-11.5]	11.5	2520 [610-3330]	3.97	1.15	1.15	1.80	3.59	4.31	12.00 [3.4-14.5]	12.4	2830 [870-3970]	4.24
16+16+25+50+71	0.90	0.90	1.40	2.81	3.99	10.00 [2.3-11.5]	11.5	2530 [620-3340]	3.95	1.08	1.08	1.69	3.37	4.78	12.00 [3.4-14.5]	12.6	2870 [900-4010]	4.18
16+16+25+60+60	0.90	0.90	1.42	3.39	3.39	10.00 [2.3-11.5]	11.5	2520 [610-3330]	3.97	1.08	1.08	1.70	4.07	4.07	12.00 [3.4-14.5]	12.4	2830 [870-3970]	4.24
16+16+35+35+35	1.16	1.16	2.56	2.56	2.56	10.00 [2.3-11.5]	11.6	2550 [460-3520]	3.92	1.41	1.41	3.06	3.06	3.06	12.00 [3.4-14.5]	12.1	2760 [640-3950]	4.35
16+16+35+35+42	1.11	1.11	2.43	2.43	2.92	10.00 [2.3-11.5]	11.6	2550 [470-3520]	3.92	1.33	1.33	2.92	2.92	3.50	12.00 [3.4-14.5]	12.1	2760 [650-3940]	4.35
16+16+35+35+50	1.05	1.05	2.30	2.30	3.30	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.26	1.26	2.76	2.76	3.96	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
16+16+35+35+60	0.99	0.99	2.16	2.16	3.70	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.19	1.19	2.59	2.59	4.44	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
16+16+35+35+71	0.93	0.93	2.02	2.02	4.10	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.11	1.11	2.43	2.43	4.92	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32
16+16+35+42+42	1.06	1.06	2.32	2.78	2.78	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.27	1.27	2.78	3.34	3.34	12.00 [3.4-14.5]	12.0	2750 [650-3980]	4.36
16+16+35+42+50	1.01	1.01	2.20	2.64	3.14	10.00 [2.3-11.5]	11.4	2500 [520-3390]	4.00	1.21	1.21	2.64	3.17	3.77	12.00 [3.4-14.5]	12.2	2780 [780-3930]	

CU-5Z100VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
16+20+20+20+25	1.58	1.98	1.98	1.98	2.48	10.00 [2.3-11.5]	11.8	2600 [420-3590]	3.85	1.90	2.38	2.38	2.38	2.96	12.00 [3.4-14.5]	12.1	2770 [570-4030]	4.33
16+20+20+20+35	1.45	1.80	1.80	1.80	3.15	10.00 [2.3-11.5]	11.8	2600 [430-3510]	3.85	1.74	2.16	2.16	2.16	3.78	12.00 [3.4-14.5]	12.0	2750 [600-4000]	4.36
16+20+20+20+42	1.37	1.69	1.69	1.69	3.56	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.64	2.03	2.03	2.03	4.27	12.00 [3.4-14.5]	12.0	2740 [610-3990]	4.38
16+20+20+20+50	1.27	1.59	1.59	1.59	3.96	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.53	1.90	1.90	1.90	4.77	12.00 [3.4-14.5]	12.1	2760 [720-3920]	4.35
16+20+20+20+60	1.18	1.47	1.47	1.47	4.41	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.42	1.76	1.76	1.76	5.30	12.00 [3.4-14.5]	12.1	2760 [720-3920]	4.35
16+20+20+20+71	1.09	1.36	1.36	1.36	4.83	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.31	1.63	1.63	1.63	5.80	12.00 [3.4-14.5]	12.0	2750 [730-3970]	4.36
16+20+20+25+25	1.50	1.89	1.89	2.36	2.36	10.00 [2.3-11.5]	11.8	2600 [420-3590]	3.85	1.82	2.26	2.26	2.83	2.83	12.00 [3.4-14.5]	12.1	2770 [570-4030]	4.33
16+20+20+25+35	1.38	1.72	1.72	2.16	3.02	10.00 [2.3-11.5]	11.8	2600 [430-3510]	3.85	1.66	2.07	2.07	2.59	3.61	12.00 [3.4-14.5]	12.0	2750 [600-4000]	4.36
16+20+20+25+42	1.30	1.63	1.63	2.03	3.41	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.56	1.95	1.95	2.44	4.10	12.00 [3.4-14.5]	12.0	2740 [610-3990]	4.38
16+20+20+25+50	1.22	1.53	1.53	1.91	3.81	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.47	1.83	1.83	2.29	4.58	12.00 [3.4-14.5]	12.1	2760 [720-3920]	4.35
16+20+20+25+60	1.13	1.42	1.42	1.77	4.26	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.36	1.70	1.70	2.13	5.11	12.00 [3.4-14.5]	12.1	2760 [720-3920]	4.35
16+20+20+25+71	1.05	1.32	1.32	1.64	4.67	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.26	1.58	1.58	1.97	5.61	12.00 [3.4-14.5]	12.0	2750 [730-3970]	4.36
16+20+20+35+35	1.26	1.59	1.59	2.78	2.78	10.00 [2.3-11.5]	11.5	2540 [440-3510]	3.94	1.52	1.90	1.90	3.34	3.34	12.00 [3.4-14.5]	11.9	2730 [630-3970]	4.40
16+20+20+35+42	1.21	1.50	1.50	2.63	3.16	10.00 [2.3-11.5]	11.5	2540 [440-3520]	3.94	1.45	1.80	1.80	3.16	3.79	12.00 [3.4-14.5]	12.1	2770 [640-3960]	4.33
16+20+20+35+50	1.13	1.42	1.42	2.48	3.55	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.36	1.70	1.70	2.98	4.26	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.30
16+20+20+35+60	1.07	1.32	1.32	2.32	3.97	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.27	1.59	1.59	2.78	4.77	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
16+20+20+35+71	1.00	1.23	1.23	2.16	4.38	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.19	1.48	1.48	2.59	5.26	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
16+20+20+42+42	1.14	1.43	1.43	3.00	3.00	10.00 [2.3-11.5]	11.6	2550 [460-3520]	3.92	1.38	1.71	1.71	3.60	3.60	12.00 [3.4-14.5]	12.1	2760 [640-3950]	4.35
16+20+20+42+50	1.08	1.35	1.35	2.84	3.38	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.30	1.62	1.62	3.41	4.05	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
16+20+20+42+60	1.01	1.27	1.27	2.66	3.79	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.22	1.52	1.52	3.19	4.55	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
16+20+20+42+71	0.95	1.18	1.18	2.49	4.20	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.14	1.42	1.42	2.98	5.04	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32
16+20+20+50+50	1.02	1.28	1.28	3.21	3.21	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.22	1.54	1.54	3.85	3.85	12.00 [3.4-14.5]	12.6	2870 [890-3960]	4.18
16+20+20+50+60	0.96	1.21	1.21	3.01	3.61	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.16	1.45	1.45	3.61	4.33	12.00 [3.4-14.5]	12.6	2870 [890-3960]	4.18
16+20+20+50+71	0.90	1.13	1.13	2.82	4.02	10.00 [2.3-11.5]	11.5	2530 [650-3340]	3.95	1.08	1.36	1.36	3.39	4.81	12.00 [3.4-14.5]	12.5	2860 [900-4000]	4.20
16+20+20+60+60	0.90	1.14	1.14	3.41	3.41	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.10	1.36	1.36	4.09	4.09	12.00 [3.4-14.5]	12.6	2870 [890-3960]	4.18
16+20+25+25+25	1.45	1.80	2.25	2.25	2.25	10.00 [2.3-11.5]	11.8	2600 [420-3590]	3.85	1.74	2.16	2.70	2.70	2.70	12.00 [3.4-14.5]	12.1	2770 [570-4030]	4.33
16+20+25+25+35	1.32	1.65	2.07	2.07	2.89	10.00 [2.3-11.5]	11.8	2600 [430-3510]	3.85	1.59	1.98	2.48	2.48	3.47	12.00 [3.4-14.5]	12.0	2750 [600-4000]	4.36
16+20+25+25+42	1.26	1.56	1.95	1.95	3.28	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.50	1.88	2.34	2.34	3.94	12.00 [3.4-14.5]	12.0	2740 [610-3990]	4.38
16+20+25+25+50	1.18	1.47	1.84	1.84	3.67	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.41	1.76	2.21	2.21	4.41	12.00 [3.4-14.5]	12.1	2760 [720-3920]	4.35
16+20+25+25+60	1.10	1.37	1.71	1.71	4.11	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.33	1.64	2.05	2.05	4.93	12.00 [3.4-14.5]	12.1	2760 [720-3920]	4.35
16+20+25+25+71	1.03	1.27	1.59	1.59	4.52	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.22	1.53	1.91	1.91	5.43	12.00 [3.4-14.5]	12.0	2750 [730-3970]	4.36
16+20+25+35+35	1.22	1.53	1.91	2.67	2.67	10.00 [2.3-11.5]	11.5	2540 [440-3510]	3.94	1.47	1.83	2.28	3.21	3.21	12.00 [3.4-14.5]	11.9	2730 [630-3970]	4.40
16+20+25+35+42	1.16	1.45	1.81	2.54	3.04	10.00 [2.3-11.5]	11.5	2540 [440-3520]	3.94	1.40	1.74	2.17	3.04	3.65	12.00 [3.4-14.5]	12.1	2770 [640-3960]	4.33
16+20+25+35+50	1.10	1.37	1.71	2.40	3.42	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.32	1.64	2.05	2.88	4.11	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
16+20+25+35+60	1.03	1.28	1.60	2.24	3.85	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.23	1.54	1.92	2.69	4.62	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
16+20+25+35+71	0.96	1.20	1.50	2.10	4.24	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.15	1.44	1.80	2.51	5.10	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
16+20+25+42+42	1.10	1.38	1.72	2.90	2.90	10.00 [2.3-11.5]	11.6	2550 [460-3520]	3.92	1.32	1.66	2.06	3.48	3.48	12.00 [3.4-14.5]	12.1	2760 [640-3950]	4.35
16+20+25+42+50	1.05	1.31	1.63	2.75	3.26	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.26	1.57	1.96	3.29	3.92	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
16+20+25+42+60	0.98	1.23	1.53	2.58	3.68	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.18	1.47	1.84	3.09	4.42	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
16+20+25+42+71	0.92	1.15	1.44	2.41	4.08	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.10	1.38	1.72	2.90	4.90	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32
16+20+25+50+50	0.99	1.24	1.55	3.11	3.11	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.19	1.49	1.86	3.73	3.73	12.00 [3.4-14.5]	12.6	2870 [890-3960]	4.18
16+20+25+50+60	0.94	1.17	1.46	2.92	3.51	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.13	1.40	1.75	3.51	4.21	12.00 [3.4-14.5]	12.6	2870 [890-3960]	4.18
16+20+25+50+71	0.88	1.10	1.37	2.75	3.90	10.00 [2.3-11.5]	11.5	2530 [650-3340]	3.95	1.05	1.32	1.65	3.30	4.68	12.00 [3.4-14.5]	12.5	2860 [900-4000]	4.20
16+20+25+60+60	0.88	1.10	1.38	3.32	3.32	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.06	1.33	1.65	3.98	3.98	12.00 [3.4-14.5]	12.6	2870 [890-3960]	4.18
16+20+35+35+35	1.14	1.42	2.48	2.48	2.48	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.36	1.70	2.98	2.98	2.98	12.00 [3.4-14.5]	12.1	2760 [650-3940]	4.35
16+20+35+35+42	1.09	1.35	2.36	2.36	2.84	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.30	1.62	2.84	2.84	3.40	12.00 [3.4-14.5]	12.0	2750 [650-3980]	4.36
16+20+35+35+50	1.03	1.28	2.24	2.24	3.21	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.23	1.54	2.69	2.69	3.85	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32
16+20+35+35+60	0.97	1.20	2.11	2.11	3.61	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.16	1.45	2.53	2.53	4.33	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32
16+20+35+35+71	0.90	1.13	1.98	1.98	4.01	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.09	1.36	2.37	2.37	4.81	12.00 [3.4-14.5]	12.3	2810 [790-3970]	4.27
16+20+35+42+42	1.03	1.29	2.26	2.71	2.71	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.24	1.55	2.71	3.25	3.25	12.00 [3.4-14.5]	12.0	2740 [670-3970]	4.38
16+20+35+42+50	0.98	1.23	2.15	2.58	3.06	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.18	1.47	2.58	3.09	3.68	12.00 [3.4-14.5]	12.3	2820 [790-3980]	4.26
16+20+35+42+60	0.92	1.16	2.02	2.43	3.47	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.11	1.39	2.43	2.91	4.16	12.00 [3.4-14.5]	12.3	2820 [790-3980]	4.26
16+20+35+50+50	0.94	1.17	2.05	2.92	2.92	10.00 [2.3-11.5]	11.5	2530 [620-3340]	3.95	1.12	1.40	2.46	3.51	3.51	12.00 [3.4-14.5]	12.5	2860 [930-3990	

CU-5Z100VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
16+25+25+25+71	1.00	1.54	1.54	1.54	4.38	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.19	1.85	1.85	1.85	5.26	12.00 [3.4-14.5]	12.0	2750 [730-3970]	4.36
16+25+25+35+35	1.18	1.84	1.84	2.57	2.57	10.00 [2.3-11.5]	11.5	2540 [440-3510]	3.94	1.40	2.21	2.21	3.09	3.09	12.00 [3.4-14.5]	11.9	2730 [630-3970]	4.40
16+25+25+35+42	1.12	1.75	1.75	2.45	2.93	10.00 [2.3-11.5]	11.5	2540 [440-3520]	3.94	1.34	2.10	2.10	2.94	3.52	12.00 [3.4-14.5]	12.1	2770 [640-3960]	4.33
16+25+25+35+50	1.06	1.66	1.66	2.32	3.30	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.27	1.99	1.99	2.78	3.97	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
16+25+25+35+60	1.00	1.55	1.55	2.17	3.73	10.00 [2.3-11.5]	11.6	2560 [520-3380]	3.91	1.20	1.86	1.86	2.61	4.47	12.00 [3.4-14.5]	12.2	2790 [750-3950]	4.30
16+25+25+35+71	0.94	1.45	1.45	2.03	4.13	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.13	1.74	1.74	2.44	4.95	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
16+25+25+42+42	1.06	1.67	1.67	2.80	2.80	10.00 [2.3-11.5]	11.6	2550 [460-3520]	3.92	1.28	2.00	2.00	3.36	3.36	12.00 [3.4-14.5]	12.1	2760 [640-3950]	4.35
16+25+25+42+50	1.02	1.58	1.58	2.66	3.16	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.22	1.90	1.90	3.19	3.79	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
16+25+25+42+60	0.95	1.49	1.49	2.50	3.57	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.14	1.79	1.79	3.00	4.28	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
16+25+25+42+71	0.89	1.40	1.40	2.35	3.96	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.07	1.68	1.68	2.82	4.75	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32
16+25+25+50+50	0.96	1.51	1.51	3.01	3.01	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.16	1.81	1.81	3.61	3.61	12.00 [3.4-14.5]	12.6	2870 [890-3960]	4.18
16+25+25+50+60	0.91	1.42	1.42	2.84	3.41	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.10	1.70	1.70	3.41	4.09	12.00 [3.4-14.5]	12.6	2870 [890-3960]	4.18
16+25+35+35+35	1.10	1.70	2.40	2.40	2.40	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.32	2.04	2.88	2.88	2.88	12.00 [3.4-14.5]	12.1	2760 [650-3940]	4.35
16+25+35+35+42	1.05	1.63	2.29	2.29	2.74	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.25	1.96	2.75	2.75	3.29	12.00 [3.4-14.5]	12.0	2750 [650-3980]	4.36
16+25+35+35+50	1.00	1.55	2.17	2.17	3.11	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.19	1.86	2.61	2.61	3.73	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.32
16+25+35+35+60	0.94	1.46	2.05	2.05	3.50	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.12	1.75	2.46	2.46	4.21	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32
16+25+35+35+71	0.89	1.37	1.92	1.92	3.90	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.05	1.65	2.31	2.31	4.68	12.00 [3.4-14.5]	12.3	2810 [790-3970]	4.27
16+25+35+42+42	1.00	1.56	2.18	2.63	2.63	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.20	1.88	2.62	3.15	3.15	12.00 [3.4-14.5]	12.0	2740 [670-3970]	4.38
16+25+35+42+50	0.95	1.49	2.08	2.50	2.98	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.14	1.79	2.50	3.00	3.57	12.00 [3.4-14.5]	12.3	2820 [790-3980]	4.26
16+25+35+42+60	0.90	1.40	1.97	2.36	3.37	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.08	1.69	2.36	2.83	4.04	12.00 [3.4-14.5]	12.3	2820 [790-3980]	4.26
16+25+35+50+50	0.91	1.42	1.99	2.84	2.84	10.00 [2.3-11.5]	11.5	2530 [620-3340]	3.95	1.09	1.70	2.39	3.41	3.41	12.00 [3.4-14.5]	12.5	2860 [930-3990]	4.20
16+25+42+42+42	0.97	1.50	2.51	2.51	2.51	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.15	1.79	3.02	3.02	3.02	12.00 [3.4-14.5]	12.0	2740 [680-3960]	4.38
16+25+42+42+50	0.91	1.43	2.40	2.40	2.86	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.10	1.71	2.88	2.88	3.43	12.00 [3.4-14.5]	12.3	2810 [800-3970]	4.27
16+25+42+50+50	0.87	1.37	2.30	2.73	2.73	10.00 [2.3-11.5]	11.5	2530 [650-3340]	3.95	1.05	1.64	2.75	3.28	3.28	12.00 [3.4-14.5]	12.7	2900 [940-3990]	4.14
16+35+35+35+35	1.04	2.24	2.24	2.24	2.24	10.00 [2.3-11.5]	11.6	2550 [470-3450]	3.92	1.24	2.69	2.69	2.69	2.69	12.00 [3.4-14.5]	12.0	2740 [680-3970]	4.38
16+35+35+35+42	0.98	2.15	2.15	2.15	2.57	10.00 [2.3-11.5]	11.6	2550 [470-3450]	3.92	1.18	2.58	2.58	2.58	3.08	12.00 [3.4-14.5]	12.2	2760 [680-3960]	4.32
16+35+35+35+50	0.94	2.05	2.05	2.05	2.91	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.12	2.46	2.46	2.46	3.50	12.00 [3.4-14.5]	12.3	2810 [810-3960]	4.27
16+35+35+35+60	0.88	1.94	1.94	1.94	3.30	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.06	2.32	2.32	2.32	3.98	12.00 [3.4-14.5]	12.3	2810 [810-3960]	4.27
16+35+35+42+42	0.94	2.06	2.06	2.47	2.47	10.00 [2.3-11.5]	11.6	2550 [480-3450]	3.92	1.14	2.47	2.47	2.96	2.96	12.00 [3.4-14.5]	12.1	2770 [690-3950]	4.33
16+35+35+42+50	0.90	1.97	1.97	2.36	2.80	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.08	2.36	2.36	2.83	3.37	12.00 [3.4-14.5]	12.3	2810 [820-3950]	4.27
16+35+42+42+42	0.91	1.98	2.37	2.37	2.37	10.00 [2.3-11.5]	11.6	2550 [480-3450]	3.92	1.08	2.37	2.85	2.85	2.85	12.00 [3.4-14.5]	12.1	2770 [710-3940]	4.33
20+20+20+20+20	2.00	2.00	2.00	2.00	2.00	10.00 [2.3-11.5]	11.8	2600 [430-3590]	3.85	2.40	2.40	2.40	2.40	2.40	12.00 [3.4-14.5]	12.1	2760 [580-4020]	4.35
20+20+20+20+25	1.90	1.90	1.90	1.90	2.40	10.00 [2.3-11.5]	11.8	2600 [430-3590]	3.85	2.29	2.29	2.29	2.29	2.84	12.00 [3.4-14.5]	12.1	2760 [580-4020]	4.35
20+20+20+20+35	1.74	1.74	1.74	1.74	3.04	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	2.09	2.09	2.09	2.09	3.64	12.00 [3.4-14.5]	12.0	2740 [610-3990]	4.38
20+20+20+20+42	1.64	1.64	1.64	1.64	3.44	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.97	1.97	1.97	1.97	4.12	12.00 [3.4-14.5]	11.9	2730 [610-3980]	4.40
20+20+20+20+50	1.54	1.54	1.54	1.54	3.84	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.85	1.85	1.85	1.85	4.60	12.00 [3.4-14.5]	12.1	2760 [720-3970]	4.35
20+20+20+20+60	1.43	1.43	1.43	1.43	4.28	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.71	1.71	1.71	1.71	5.16	12.00 [3.4-14.5]	12.1	2760 [720-3970]	4.35
20+20+20+20+71	1.32	1.32	1.32	1.32	4.72	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.59	1.59	1.59	1.59	5.64	12.00 [3.4-14.5]	12.2	2790 [750-3960]	4.30
20+20+20+25+25	1.82	1.82	1.82	2.27	2.27	10.00 [2.3-11.5]	11.8	2600 [430-3590]	3.85	2.18	2.18	2.18	2.73	2.73	12.00 [3.4-14.5]	12.1	2760 [580-4020]	4.35
20+20+20+25+35	1.67	1.67	1.67	2.08	2.91	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	2.00	2.00	2.00	2.50	3.50	12.00 [3.4-14.5]	12.0	2740 [610-3990]	4.38
20+20+20+25+42	1.57	1.57	1.57	1.98	3.31	10.00 [2.3-11.5]	11.5	2540 [430-3510]	3.94	1.89	1.89	1.89	2.36	3.97	12.00 [3.4-14.5]	11.9	2730 [610-3980]	4.40
20+20+20+25+50	1.48	1.48	1.48	1.86	3.70	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.78	1.78	1.78	2.22	4.44	12.00 [3.4-14.5]	12.1	2760 [720-3970]	4.35
20+20+20+25+60	1.38	1.38	1.38	1.72	4.14	10.00 [2.3-11.5]	11.6	2560 [510-3380]	3.91	1.66	1.66	1.66	2.06	4.96	12.00 [3.4-14.5]	12.1	2760 [720-3970]	4.35
20+20+20+25+71	1.28	1.28	1.28	1.61	4.55	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.54	1.54	1.54	1.92	5.64	12.00 [3.4-14.5]	12.2	2790 [750-3960]	4.30
20+20+20+35+35	1.54	1.54	1.54	2.69	2.69	10.00 [2.3-11.5]	11.6	2550 [460-3520]	3.92	1.84	1.84	1.84	3.24	3.24	12.00 [3.4-14.5]	12.1	2770 [640-3960]	4.33
20+20+20+35+42	1.46	1.46	1.46	2.55	3.07	10.00 [2.3-11.5]	11.6	2550 [460-3520]	3.92	1.75	1.75	1.75	3.07	3.68	12.00 [3.4-14.5]	12.1	2760 [640-3950]	4.35
20+20+20+35+50	1.38	1.38	1.38	2.41	3.45	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.66	1.66	1.66	2.89	4.13	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
20+20+20+35+60	1.29	1.29	1.29	2.26	3.87	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.55	1.55	1.55	2.71	4.64	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
20+20+20+35+71	1.20	1.20	1.20	2.12	4.28	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.45	1.45	1.45	2.53	5.12	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32
20+20+20+42+42	1.38	1.38	1.38	2.93	2.93	10.00 [2.3-11.5]	11.6	2550 [470-3520]	3.92	1.66	1.66	1.66	3.51	3.51	12.00 [3.4-14.5]	12.1	2760 [650-3930]	4.35
20+20+20+42+50	1.32	1.32	1.32	2.76	3.28	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.58	1.58	1.58	3.32	3.94	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
20+20+20+42+60	1.23	1.23	1.23	2.61	3.70	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.48	1.48	1.48	3.12	4.44	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
20+20+20+42+71	1.16	1.16	1.16	2.43	4.09	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.39	1.39	1.39	2.91	4.92	12.00 [3.4-14.5]	12.2	2780 [780-3980]</	

CU-5Z100VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP	
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
20+20+25+35+35	1.48	1.48	1.86	2.59	2.59	10.00 [2.3-11.5]	11.6	2550 (460-3520)	3.92	1.78	1.78	2.22	3.11	3.11	12.00 [3.4-14.5]	12.1	2770 (640-3960)	4.33	
20+20+25+35+42	1.41	1.41	1.76	2.46	2.96	10.00 [2.3-11.5]	11.6	2550 (460-3520)	3.92	1.69	1.69	2.11	2.96	3.55	12.00 [3.4-14.5]	12.1	2760 (640-3950)	4.35	
20+20+25+35+50	1.33	1.33	1.68	2.33	3.33	10.00 [2.3-11.5]	11.4	2500 (520-3380)	4.00	1.60	1.60	2.00	2.80	4.00	12.00 [3.4-14.5]	12.2	2790 (760-3950)	4.30	
20+20+25+35+60	1.25	1.25	1.56	2.19	3.75	10.00 [2.3-11.5]	11.4	2500 (520-3380)	4.00	1.50	1.50	1.88	2.63	4.49	12.00 [3.4-14.5]	12.2	2790 (760-3950)	4.30	
20+20+25+35+71	1.17	1.17	1.46	2.05	4.15	10.00 [2.3-11.5]	11.4	2510 (560-3390)	3.98	1.40	1.40	1.76	2.46	4.98	12.00 [3.4-14.5]	12.2	2780 (780-3930)	4.32	
20+20+25+42+42	1.34	1.34	1.68	2.82	2.82	10.00 [2.3-11.5]	11.6	2550 (470-3520)	3.92	1.61	1.61	2.02	3.38	3.38	12.00 [3.4-14.5]	12.1	2760 (650-3930)	4.35	
20+20+25+42+50	1.27	1.27	1.60	2.68	3.18	10.00 [2.3-11.5]	11.4	2500 (520-3380)	4.00	1.53	1.53	1.91	3.21	3.82	12.00 [3.4-14.5]	12.2	2780 (760-3940)	4.32	
20+20+25+42+60	1.20	1.20	1.50	2.51	3.59	10.00 [2.3-11.5]	11.4	2500 (520-3380)	4.00	1.44	1.44	1.80	3.02	4.00	12.00 [3.4-14.5]	12.2	2780 (760-3940)	4.32	
20+20+25+42+71	1.12	1.12	1.41	2.36	3.99	10.00 [2.3-11.5]	11.4	2510 (560-3390)	3.98	1.35	1.35	1.69	2.83	4.78	12.00 [3.4-14.5]	12.2	2780 (780-3980)	4.32	
20+20+25+50+50	1.21	1.21	1.52	3.03	3.03	10.00 [2.3-11.5]	11.5	2530 (610-3330)	3.95	1.45	1.45	1.82	3.64	3.64	12.00 [3.4-14.5]	12.6	2870 (900-4010)	4.18	
20+20+25+50+60	1.14	1.14	1.43	2.86	3.43	10.00 [2.3-11.5]	11.5	2530 (610-3330)	3.95	1.37	1.37	1.72	3.43	4.11	12.00 [3.4-14.5]	12.6	2870 (900-4010)	4.18	
20+20+35+35+35	1.37	1.37	2.42	2.42	2.42	10.00 [2.3-11.5]	11.6	2550 (470-3440)	3.92	1.65	1.65	2.90	2.90	2.90	12.00 [3.4-14.5]	12.0	2750 (650-3980)	4.36	
20+20+35+35+42	1.32	1.32	2.30	2.30	2.76	10.00 [2.3-11.5]	11.6	2550 (470-3440)	3.92	1.58	1.58	2.76	2.76	3.32	12.00 [3.4-14.5]	12.0	2740 (670-3970)	4.38	
20+20+35+35+50	1.25	1.25	2.19	2.19	3.12	10.00 [2.3-11.5]	11.4	2510 (550-3390)	3.98	1.50	1.50	2.63	2.63	3.74	12.00 [3.4-14.5]	12.3	2820 (790-3980)	4.26	
20+20+35+35+60	1.18	1.18	2.06	2.06	3.52	10.00 [2.3-11.5]	11.4	2510 (550-3390)	3.98	1.41	1.41	2.47	2.47	4.24	12.00 [3.4-14.5]	12.3	2820 (790-3980)	4.26	
20+20+35+35+71	1.11	1.11	1.93	1.93	3.92	10.00 [2.3-11.5]	11.4	2510 (560-3390)	3.98	1.33	1.33	2.32	2.32	4.70	12.00 [3.4-14.5]	12.3	2810 (800-3960)	4.27	
20+20+35+42+42	1.26	1.26	2.20	2.64	2.64	10.00 [2.3-11.5]	11.6	2550 (470-3450)	3.92	1.51	1.51	2.64	3.17	3.17	12.00 [3.4-14.5]	12.0	2740 (680-3960)	4.38	
20+20+35+42+50	1.20	1.20	2.10	2.51	2.99	10.00 [2.3-11.5]	11.4	2510 (560-3390)	3.98	1.44	1.44	2.51	3.02	3.59	12.00 [3.4-14.5]	12.3	2810 (800-3970)	4.27	
20+20+35+42+60	1.13	1.13	1.98	2.37	3.39	10.00 [2.3-11.5]	11.4	2510 (560-3390)	3.98	1.36	1.36	2.37	2.85	4.06	12.00 [3.4-14.5]	12.3	2810 (800-3970)	4.27	
20+20+35+50+50	1.14	1.14	2.00	2.86	2.86	10.00 [2.3-11.5]	11.5	2540 (650-3340)	3.94	1.37	1.37	2.40	3.43	3.43	12.00 [3.4-14.5]	12.7	2900 (940-3990)	4.14	
20+20+42+42+42	1.19	1.19	2.54	2.54	2.54	10.00 [2.3-11.5]	11.6	2550 (470-3450)	3.92	1.44	1.44	3.04	3.04	3.04	12.00 [3.4-14.5]	12.2	2780 (680-3950)	4.32	
20+20+42+42+50	1.15	1.15	2.41	2.41	2.88	10.00 [2.3-11.5]	11.4	2510 (560-3390)	3.98	1.38	1.38	2.90	2.90	3.44	12.00 [3.4-14.5]	12.3	2810 (810-3960)	4.27	
20+20+42+50+50	1.10	1.10	2.30	2.75	2.75	10.00 [2.3-11.5]	11.5	2540 (650-3340)	3.94	1.32	1.32	2.76	3.30	3.30	12.00 [3.4-14.5]	12.7	2900 (950-4030)	4.14	
20+25+25+25+25	1.68	2.08	2.08	2.08	2.08	10.00 [2.3-11.5]	11.8	2600 (430-3590)	3.85	2.00	2.50	2.50	2.50	2.50	12.00 [3.4-14.5]	12.1	2760 (580-4020)	4.35	
20+25+25+25+35	1.55	1.92	1.92	1.92	2.69	10.00 [2.3-11.5]	11.5	2540 (430-3510)	3.94	1.85	2.31	2.31	2.31	3.22	12.00 [3.4-14.5]	12.0	2740 (610-3990)	4.38	
20+25+25+25+42	1.47	1.82	1.82	1.82	3.07	10.00 [2.3-11.5]	11.5	2540 (430-3510)	3.94	1.75	2.19	2.19	2.19	3.68	12.00 [3.4-14.5]	11.9	2730 (610-3980)	4.40	
20+25+25+25+50	1.39	1.72	1.72	1.72	3.45	10.00 [2.3-11.5]	11.6	2560 (510-3380)	3.91	1.66	2.07	2.07	2.07	4.13	12.00 [3.4-14.5]	12.1	2760 (720-3970)	4.35	
20+25+25+25+60	1.30	1.61	1.61	1.61	3.87	10.00 [2.3-11.5]	11.6	2560 (510-3380)	3.91	1.54	1.94	1.94	1.94	4.64	12.00 [3.4-14.5]	12.1	2760 (720-3970)	4.35	
20+25+25+25+71	1.20	1.51	1.51	1.51	4.27	10.00 [2.3-11.5]	11.4	2500 (520-3380)	4.00	1.45	1.81	1.81	1.81	5.12	12.00 [3.4-14.5]	12.2	2790 (750-3960)	4.30	
20+25+25+35+35	1.42	1.79	1.79	2.50	2.50	10.00 [2.3-11.5]	11.6	2550 (460-3520)	3.92	1.72	2.14	2.14	3.00	3.00	12.00 [3.4-14.5]	12.1	2770 (640-3960)	4.33	
20+25+25+35+42	1.36	1.70	1.70	2.38	2.86	10.00 [2.3-11.5]	11.6	2550 (460-3520)	3.92	1.63	2.04	2.04	2.86	3.43	12.00 [3.4-14.5]	12.1	2760 (640-3950)	4.35	
20+25+25+35+50	1.29	1.61	1.61	2.26	3.23	10.00 [2.3-11.5]	11.4	2500 (520-3380)	4.00	1.55	1.94	1.94	2.71	3.86	12.00 [3.4-14.5]	12.2	2790 (760-3950)	4.30	
20+25+25+35+60	1.21	1.52	1.52	2.12	3.63	10.00 [2.3-11.5]	11.4	2500 (520-3380)	4.00	1.45	1.82	1.82	2.55	4.36	12.00 [3.4-14.5]	12.2	2790 (760-3950)	4.30	
20+25+25+35+71	1.14	1.42	1.42	1.99	4.03	10.00 [2.3-11.5]	11.4	2510 (560-3390)	3.98	1.37	1.70	1.70	2.39	4.84	12.00 [3.4-14.5]	12.2	2780 (780-3930)	4.32	
20+25+25+42+42	1.30	1.62	1.62	2.73	2.73	10.00 [2.3-11.5]	11.6	2550 (470-3520)	3.92	1.56	1.95	1.95	3.27	3.27	12.00 [3.4-14.5]	12.1	2760 (650-3930)	4.35	
20+25+25+42+50	1.24	1.54	1.54	2.59	3.09	10.00 [2.3-11.5]	11.4	2500 (520-3380)	4.00	1.49	1.85	1.85	3.11	3.70	12.00 [3.4-14.5]	12.2	2780 (760-3940)	4.32	
20+25+25+42+60	1.17	1.45	1.45	2.44	3.49	10.00 [2.3-11.5]	11.4	2500 (520-3380)	4.00	1.40	1.74	1.74	2.93	4.19	12.00 [3.4-14.5]	12.2	2780 (760-3940)	4.32	
20+25+25+42+71	1.09	1.37	1.37	2.30	3.87	10.00 [2.3-11.5]	11.4	2510 (560-3390)	3.98	1.31	1.64	1.64	2.75	4.66	12.00 [3.4-14.5]	12.2	2780 (780-3980)	4.32	
20+25+25+50+50	1.18	1.47	1.47	2.94	2.94	10.00 [2.3-11.5]	11.5	2530 (610-3330)	3.95	1.42	1.76	1.76	3.53	3.53	12.00 [3.4-14.5]	12.6	2870 (900-4010)	4.18	
20+25+25+50+60	1.11	1.39	1.39	2.78	3.33	10.00 [2.3-11.5]	11.5	2530 (610-3330)	3.95	1.33	1.67	1.67	3.33	4.00	12.00 [3.4-14.5]	12.6	2870 (900-4010)	4.18	
20+25+35+35+35	1.34	1.67	2.33	2.33	2.33	10.00 [2.3-11.5]	11.6	2550 (470-3440)	3.92	1.60	2.00	2.80	2.80	2.80	12.00 [3.4-14.5]	12.0	2750 (650-3980)	4.36	
20+25+35+35+42	1.27	1.59	2.23	2.23	2.68	10.00 [2.3-11.5]	11.6	2550 (470-3440)	3.92	1.53	1.91	2.68	2.68	3.20	12.00 [3.4-14.5]	12.0	2740 (670-3970)	4.38	
20+25+35+35+50	1.21	1.52	2.12	2.12	3.03	10.00 [2.3-11.5]	11.4	2510 (550-3390)	3.98	1.45	1.82	2.55	2.55	3.63	12.00 [3.4-14.5]	12.3	2820 (790-3980)	4.26	
20+25+35+35+60	1.14	1.43	2.00	2.00	3.43	10.00 [2.3-11.5]	11.4	2510 (550-3390)	3.98	1.38	1.71	2.40	2.40	4.11	12.00 [3.4-14.5]	12.3	2820 (790-3980)	4.26	
20+25+35+42+42	1.23	1.52	2.13	2.56	2.56	10.00 [2.3-11.5]	11.6	2550 (470-3450)	3.92	1.47	1.83	2.56	3.07	3.07	12.00 [3.4-14.5]	12.0	2740 (680-3960)	4.38	
20+25+35+42+50	1.17	1.45	2.03	2.44	2.91	10.00 [2.3-11.5]	11.4	2510 (560-3390)	3.98	1.40	1.74	2.44	2.93	3.49	12.00 [3.4-14.5]	12.3	2810 (800-3970)	4.27	
20+25+35+42+60	1.10	1.37	1.92	2.31	3.30	10.00 [2.3-11.5]	11.4	2510 (560-3390)	3.98	1.32	1.65	2.31	2.77	3.95	12.00 [3.4-14.5]	12.3	2810 (800-3970)	4.27	
20+25+35+50+50	1.11	1.39	1.94	2.78	2.78	10.00 [2.3-11.5]	11.5	2540 (650-3340)	3.94	1.34	1.67	2.33	3.33	3.33	12.00 [3.4-14.5]	12.7	2900 (940-3990)	4.14	
20+25+42+42+42	1.17	1.45	2.46	2.46	2.46	10.00 [2.3-11.5]	11.6	2550 (470-3450)	3.92	1.40	1.75	2.95	2.95	2.95	12.00 [3.4-14.5]	12.2	2780 (680-3950)	4.32	
20+25+42+42+50	1.12	1.40	2.35	2.35	2.78	10.00 [2.3-11.5]	11.4	2510 (560-3390)	3.98	1.34	1.68	2.82	2.82	3.34	12.00 [3.4-14.5]	12.3	2810 (810-3960)	4.27	
20+35+35+35+35	1.24	2.19	2.19	2.19	2.19	10.00 [2.3-11.5]	11.6	2550 (470-3450)	3.92	1.48	2.63	2.63	2.63	2.63	12.00 [3.4-14.5]	12.2	2780 (680-3960)	4.32	
20+35+35+35+42	1.20	2.10	2.10	2.10	2.50	10.00 [2.3-11.5]	11.6	2550 (480-3450)	3.92	1.45	2.51	2.51	2.51	3.02	12.00 [3.4-14.5]	12.1	2770 (690-3950)	4.33	
20+35+35+35+50	1.14	2.00	2.00	2.00	2.86	10.00 [2.3-11.5]	11.4	2510 (560-3390)	3.98	1.37	2.40	2.40	2.40	3.43	12.00 [3.4-14.5]	12.3	2810 (820-395		

CU-5Z100VBR: Only Wall-Mounted Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
5 rooms	25+25+25+35+42	1.64	1.64	1.64	2.31	2.77	10.00 [2.3-11.5]	11.6	2550 [460-3520]	3.92	1.97	1.97	1.97	2.77	3.32	12.00 [3.4-14.5]	12.1	2760 [640-3950]	4.35
	25+25+25+35+50	1.56	1.56	1.56	2.19	3.13	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.88	1.88	1.88	2.62	3.74	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
	25+25+25+35+60	1.47	1.47	1.47	2.06	3.53	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.76	1.76	1.76	2.48	4.24	12.00 [3.4-14.5]	12.2	2790 [760-3950]	4.30
	25+25+25+35+71	1.38	1.38	1.38	1.93	3.93	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.66	1.66	1.66	2.32	4.70	12.00 [3.4-14.5]	12.2	2780 [780-3930]	4.32
	25+25+25+42+42	1.58	1.58	1.58	2.63	2.63	10.00 [2.3-11.5]	11.6	2550 [470-3520]	3.92	1.88	1.88	1.88	3.18	3.18	12.00 [3.4-14.5]	12.1	2760 [650-3930]	4.35
	25+25+25+42+50	1.50	1.50	1.50	2.51	2.99	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.80	1.80	1.80	3.02	3.58	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
	25+25+25+42+60	1.41	1.41	1.41	2.38	3.39	10.00 [2.3-11.5]	11.4	2500 [520-3380]	4.00	1.69	1.69	1.69	2.86	4.07	12.00 [3.4-14.5]	12.2	2780 [760-3940]	4.32
	25+25+25+50+50	1.42	1.42	1.42	2.87	2.87	10.00 [2.3-11.5]	11.5	2530 [610-3330]	3.95	1.72	1.72	1.72	3.42	3.42	12.00 [3.4-14.5]	12.6	2870 [900-4010]	4.18
	25+25+35+35+35	1.61	1.61	2.26	2.26	2.26	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.95	1.95	2.70	2.70	2.70	12.00 [3.4-14.5]	12.0	2750 [650-3980]	4.36
	25+25+35+35+42	1.54	1.54	2.16	2.16	2.60	10.00 [2.3-11.5]	11.6	2550 [470-3440]	3.92	1.85	1.85	2.59	2.59	3.12	12.00 [3.4-14.5]	12.0	2740 [670-3970]	4.38
	25+25+35+35+50	1.47	1.47	2.06	2.06	2.94	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.76	1.76	2.47	2.47	3.54	12.00 [3.4-14.5]	12.3	2820 [790-3980]	4.26
	25+25+35+35+60	1.39	1.39	1.94	1.94	3.34	10.00 [2.3-11.5]	11.4	2510 [550-3390]	3.98	1.67	1.67	2.33	2.33	4.00	12.00 [3.4-14.5]	12.3	2820 [790-3980]	4.26
	25+25+35+42+42	1.48	1.48	2.06	2.49	2.49	10.00 [2.3-11.5]	11.6	2550 [470-3450]	3.92	1.78	1.78	2.48	2.98	2.98	12.00 [3.4-14.5]	12.0	2740 [680-3960]	4.38
	25+25+35+42+50	1.41	1.41	1.99	2.37	2.82	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.69	1.69	2.37	2.85	3.40	12.00 [3.4-14.5]	12.3	2810 [800-3970]	4.27
	25+25+42+42+42	1.43	1.43	2.38	2.38	2.38	10.00 [2.3-11.5]	11.6	2550 [470-3450]	3.92	1.71	1.71	2.86	2.86	2.86	12.00 [3.4-14.5]	12.2	2780 [680-3950]	4.32
	25+35+35+35+35	1.52	2.12	2.12	2.12	2.12	10.00 [2.3-11.5]	11.6	2550 [470-3450]	3.92	1.80	2.55	2.55	2.55	2.55	12.00 [3.4-14.5]	12.2	2780 [680-3960]	4.32
	25+35+35+35+42	1.46	2.03	2.03	2.03	2.45	10.00 [2.3-11.5]	11.6	2550 [480-3450]	3.92	1.75	2.44	2.44	2.44	2.93	12.00 [3.4-14.5]	12.1	2770 [690-3950]	4.33
	25+35+35+35+50	1.40	1.94	1.94	1.94	2.78	10.00 [2.3-11.5]	11.4	2510 [560-3390]	3.98	1.68	2.33	2.33	2.33	3.33	12.00 [3.4-14.5]	12.3	2810 [820-3950]	4.27
	25+35+35+42+42	1.40	1.96	1.96	2.34	2.34	10.00 [2.3-11.5]	11.6	2550 [480-3450]	3.92	1.68	2.35	2.35	2.81	2.81	12.00 [3.4-14.5]	12.1	2770 [710-3940]	4.33
	35+35+35+35+35	2.00	2.00	2.00	2.00	2.00	10.00 [2.3-11.5]	11.6	2550 [510-3450]	3.92	2.40	2.40	2.40	2.40	2.40	12.00 [3.4-14.5]	12.1	2760 [710-3930]	4.35
35+35+35+35+42	1.92	1.92	1.92	1.92	2.32	10.00 [2.3-11.5]	11.6	2560 [510-3450]	3.91	2.31	2.31	2.31	2.31	2.76	12.00 [3.4-14.5]	12.1	2760 [720-3980]	4.35	

Note: At least two indoor units must be connected. When operating just one unit, minimum connected capacity must still be met, please refer Technical Manual for details.

CU-5Z100VBR: Free Multi Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W		
1 room	16	1.60	-	-	-	-	1.60 [1.3-2.3]	2.2	450 [250-690]	3.56	2.60	-	-	-	-	2.60 [1.2-3.2]	3.2	700 [290-1060]	3.71
	20	2.00	-	-	-	-	2.00 [1.8-2.9]	2.6	550 [340-860]	3.64	3.20	-	-	-	-	3.20 [1.2-4.1]	3.9	840 [290-1330]	3.81
	25	2.50	-	-	-	-	2.50 [1.8-2.9]	3.2	680 [340-860]	3.68	3.60	-	-	-	-	3.60 [1.2-4.3]	4.9	1040 [290-1330]	3.46
	35	3.50	-	-	-	-	3.50 [1.8-4.1]	4.6	990 [340-1410]	3.54	4.50	-	-	-	-	4.50 [1.2-5.8]	6.2	1330 [290-2200]	3.38
	42	4.20	-	-	-	-	4.20 [1.8-4.5]	6.3	1420 [340-2040]	2.96	5.60	-	-	-	-	5.60 [1.2-6.8]	8.0	1820 [290-3030]	3.08
	50	5.00	-	-	-	-	5.00 [1.9-5.4]	7.3	1630 [340-2150]	3.07	6.80	-	-	-	-	6.80 [1.2-6.9]	10.4	2350 [290-2840]	2.89
	60	6.00	-	-	-	-	6.00 [1.9-6.2]	9.0	2080 [340-2380]	2.88	8.50	-	-	-	-	8.50 [1.3-9.0]	11.0	2500 [320-2650]	3.40
71	7.10	-	-	-	-	7.10 [2.0-7.2]	11.2	2580 [370-2820]	2.75	8.70	-	-	-	-	8.70 [1.4-9.2]	11.7	2650 [380-2820]	3.28	
2 rooms	16+16	1.60	1.60	-	-	-	3.20 [2.3-5.8]	3.7	760 [260-1840]	4.21	2.60	2.60	-	-	-	5.20 [2.0-8.2]	7.2	1580 [220-2610]	3.29
	16+20	1.60	2.00	-	-	-	3.60 [2.3-5.8]	4.3	890 [250-1840]	4.04	2.58	3.22	-	-	-	5.80 [2.0-8.2]	7.9	1740 [220-2600]	3.33
	16+25	1.60	2.50	-	-	-	4.10 [2.3-5.8]	5.0	1060 [250-1840]	3.87	2.42	3.78	-	-	-	6.20 [2.0-8.2]	8.5	1880 [220-2600]	3.30
	16+35	1.60	3.50	-	-	-	5.10 [2.3-5.8]	6.6	1420 [250-1780]	3.59	2.23	4.87	-	-	-	7.10 [2.0-8.6]	9.5	2110 [210-2680]	3.36
	16+42	1.60	4.20	-	-	-	5.80 [2.3-6.7]	8.0	1730 [250-2230]	3.35	2.26	5.94	-	-	-	8.20 [2.0-10.1]	11.1	2470 [210-3230]	3.32
	16+50	1.60	5.00	-	-	-	6.60 [2.3-7.2]	8.9	1940 [240-2230]	3.40	2.28	7.12	-	-	-	9.40 [2.0-11.0]	12.0	2670 [160-3240]	3.52
	16+60	1.60	6.00	-	-	-	7.60 [2.3-8.6]	11.3	2470 [240-3180]	3.08	2.34	8.76	-	-	-	11.10 [2.0-11.0]	13.9	3090 [160-3240]	3.59
	16+71	1.60	7.10	-	-	-	8.70 [2.3-9.1]	13.9	3020 [230-3260]	2.88	2.08	9.22	-	-	-	11.30 [2.0-13.0]	13.6	3030 [160-4180]	3.73
	20+20	2.00	2.00	-	-	-	4.00 [2.3-5.8]	4.8	1020 [250-1780]	3.92	3.20	3.20	-	-	-	6.40 [2.0-8.2]	8.6	1910 [220-2590]	3.35
	20+25	2.00	2.50	-	-	-	4.50 [2.3-5.8]	5.7	1220 [250-1780]	3.69	3.02	3.78	-	-	-	6.80 [2.0-8.2]	9.1	2030 [220-2590]	3.35
	20+35	2.00	3.50	-	-	-	5.50 [2.3-5.8]	7.3	1570 [250-1730]	3.50	2.80	4.90	-	-	-	7.70 [2.0-8.6]	10.3	2280 [210-2620]	3.38
	20+42	2.00	4.20	-	-	-	6.20 [2.3-7.2]	8.9	1940 [250-2590]	3.20	2.84	5.96	-	-	-	8.80 [2.0-11.0]	11.8	2620 [200-3430]	3.36
	20+50	2.00	5.00	-	-	-	7.00 [2.3-8.1]	9.4	2050 [240-2710]	3.41	2.86	7.14	-	-	-	10.00 [2.0-11.0]	12.8	2850 [160-3180]	3.51
	20+60	2.00	6.00	-	-	-	8.00 [2.3-8.6]	12.2	2650 [240-3110]	3.02	2.93	8.77	-	-	-	11.70 [2.0-11.9]	14.3	3180 [160-3670]	3.68
	20+71	2.00	7.10	-	-	-	9.10 [2.3-10.0]	14.6	3190 [260-4130]	2.85	2.62	9.28	-	-	-	11.90 [2.0-13.0]	14.7	3260 [160-4170]	3.65
	25+25	2.50	2.50	-	-	-	5.00 [2.3-5.8]	6.3	1370 [250-1780]	3.65	3.60	3.60	-	-	-	7.20 [2.0-8.6]	9.8	2170 [220-2700]	3.32
	25+35	2.50	3.50	-	-	-	6.00 [2.3-6.7]	8.4	1830 [250-2230]	3.28	3.38	4.72	-	-	-	8.10 [2.0-10.1]	10.9	2420 [210-3230]	3.35
	25+42	2.50	4.20	-	-	-	6.70 [2.3-7.2]	10.2	2230 [250-2590]	3.00	3.43	5.77	-	-	-	9.20 [2.0-11.0]	12.5	2770 [200-3430]	3.32
	25+50	2.50	5.00	-	-	-	7.50 [2.3-8.6]	10.8	2350 [240-3110]	3.19	3.47	6.93	-	-	-	10.40 [2.0-11.0]	13.0	2880 [160-3180]	3.61
	25+60	2.50	6.00	-	-	-	8.50 [2.3-9.1]	13.9	3040 [240-3390]	2.80	3.53	8.47	-	-	-	12.00 [2.0-13.0]	15.0	3330 [160-4180]	3.60
25+71	2.50	7.10	-	-	-	9.60 [2.3-10.1]	16.7	3630 [260-4280]	2.64	3.13	8.87	-	-	-	12.00 [2.0-13.0]	14.9	3310 [160-4170]	3.63	
35+35	3.50	3.50	-	-	-	7.00 [2.3-8.1]	10.8	2350 [250-3160]	2.98	4.50	4.50	-	-	-	9.00 [2.0-11.0]	11.9	2650 [200-3420]	3.40	
35+42	3.50	4.20	-	-	-	7.70 [2.3-8.6]	12.7	2770 [250-3650]	2.78	4.59	5.51	-	-	-	10.10 [2.0-11.0]	13.5	3000 [200-3360]	3.37	
35+50	3.50	5.00	-	-	-	8.50 [2.3-9.1]	13.3	2910 [230-3260]	2.92	4.65	6.65	-	-	-	11.30 [2.0-13.0]	13.3	2960 [160-4160]	3.82	
35+60	3.50	6.00	-	-	-	9.50 [2.3-10.1]	16.8	3670 [230-4280]	2.59	4.42	7.58	-	-	-	12.00 [2.0-13.0]	14.6	3250 [160-4160]	3.69	
35+71	3.30	6.70	-	-	-	10.00 [2.3-10.4]	18.0	3920 [260-4440]	2.55	3.96	8.04	-	-	-	12.00 [2.0-13.8]	14.6	3240 [160-4510]	3.70	
42+42	4.20	4.20	-	-	-	8.40 [2.3-9.1]	15.8	3440 [250-4060]	2.44	5.60	5.60	-	-	-	11.20 [2.0-13.0]	14.1	3140 [190-4350]	3.57	
42+50	4.20	5.00	-	-	-	9.20 [2.3-10.0]	15.3	3330 [230-4130]	2.76	5.48									

CU-5Z100VBR: Free Multi Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
2 rooms	42+60	4.12	5.88	-	-	-	10.00 [2.3 -10.4]	18.9	4130 [230-4430]	2.42	4.94	7.06	-	-	-	12.00 [2.0-13.8]	14.6	3240 [160-4510]	3.70
	42+71	3.72	6.28	-	-	-	10.00 [2.3 -10.4]	17.7	3850 [260-4440]	2.60	4.46	7.54	-	-	-	12.00 [2.0-13.8]	14.5	3230 [160-4500]	3.72
	50+50	5.00	5.00	-	-	-	10.00 [2.3 -10.4]	15.5	3370 [250-3710]	2.97	6.00	6.00	-	-	-	12.00 [2.0-13.8]	13.6	3030 [170-4260]	3.96
	50+60	4.55	5.45	-	-	-	10.00 [2.3 -10.4]	15.5	3370 [250-3710]	2.97	5.45	6.55	-	-	-	12.00 [2.0-13.8]	13.6	3030 [170-4260]	3.96
	50+71	4.13	5.87	-	-	-	10.00 [2.3 -10.4]	14.8	3230 [250-3580]	3.10	4.96	7.04	-	-	-	12.00 [2.0-13.8]	13.6	3010 [170-4240]	3.99
	60+60	5.00	5.00	-	-	-	10.00 [2.3 -10.4]	15.5	3370 [250-3710]	2.97	6.00	6.00	-	-	-	12.00 [2.0-13.8]	13.6	3030 [170-4260]	3.96
	60+71	4.58	5.42	-	-	-	10.00 [2.3 -10.4]	14.8	3230 [250-3580]	3.10	5.50	6.50	-	-	-	12.00 [2.0-13.8]	13.6	3010 [170-4240]	3.99
3 rooms	71+71	5.00	5.00	-	-	-	10.00 [2.3 -10.4]	14.2	3100 [280-3440]	3.23	6.00	6.00	-	-	-	12.00 [2.0-13.8]	13.5	3000 [180-4220]	4.00
	16+16+16	1.60	1.60	1.60	-	-	4.80 [2.3 -8.5]	5.3	1140 [260-2770]	4.21	2.60	2.60	2.60	-	-	7.80 [2.7-12.3]	9.5	2100 [230-3820]	3.71
	16+16+20	1.60	1.60	2.00	-	-	5.20 [2.3 -8.5]	5.8	1250 [260-2770]	4.16	2.58	2.58	3.24	-	-	8.40 [2.7-12.3]	10.4	2320 [230-3800]	3.62
	16+16+25	1.60	1.60	2.50	-	-	5.70 [2.3 -8.5]	6.7	1440 [260-2770]	3.96	2.47	2.47	3.86	-	-	8.80 [2.7-12.3]	10.8	2390 [230-3800]	3.68
	16+16+35	1.60	1.60	3.50	-	-	6.70 [2.3 -8.5]	8.1	1760 [260-2700]	3.81	2.32	2.32	5.06	-	-	9.70 [2.7-12.3]	12.2	2700 [230-3720]	3.59
	16+16+42	1.60	1.60	4.20	-	-	7.40 [2.3 -8.5]	9.6	2100 [250-2640]	3.52	2.34	2.34	6.12	-	-	10.80 [2.7-12.3]	12.7	2830 [230-3700]	3.82
	16+16+50	1.60	1.60	5.00	-	-	8.20 [2.3 -8.7]	10.4	2260 [280-2440]	3.63	2.34	2.34	7.32	-	-	12.00 [2.7-12.9]	13.7	3050 [250-3790]	3.93
	16+16+60	1.60	1.60	6.00	-	-	9.20 [2.3 -10.1]	11.9	2600 [280-3150]	3.54	2.09	2.09	7.82	-	-	12.00 [2.7-13.6]	13.7	3050 [250-4150]	3.93
	16+16+71	1.55	1.55	6.90	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3490]	3.38	1.86	1.86	8.28	-	-	12.00 [2.7-13.6]	13.7	3040 [250-4070]	3.95
	16+20+20	1.60	2.00	2.00	-	-	5.60 [2.3 -8.5]	6.4	1390 [260-2700]	4.03	2.58	3.21	3.21	-	-	9.00 [2.7-12.3]	10.9	2430 [230-3790]	3.70
	16+20+25	1.60	2.00	2.50	-	-	6.10 [2.3 -8.5]	7.4	1600 [260-2700]	3.81	2.47	3.08	3.85	-	-	9.40 [2.7-12.3]	11.6	2570 [230-3790]	3.66
	16+20+35	1.60	2.00	3.50	-	-	7.10 [2.3 -8.5]	8.9	1930 [250-2640]	3.68	2.32	2.90	5.08	-	-	10.30 [2.7-12.3]	12.3	2730 [230-3700]	3.77
	16+20+42	1.60	2.00	4.20	-	-	7.80 [2.3 -8.5]	10.1	2210 [250-2640]	3.53	2.34	2.92	6.14	-	-	11.40 [2.7-12.9]	13.4	2970 [230-3980]	3.84
	16+20+50	1.60	2.00	5.00	-	-	8.60 [2.3 -9.6]	11.2	2450 [280-2770]	3.51	2.23	2.79	6.98	-	-	12.00 [2.7-13.6]	13.7	3040 [250-4070]	3.95
	16+20+60	1.60	2.00	6.00	-	-	9.60 [2.3 -10.1]	12.7	2770 [280-3090]	3.47	2.00	2.50	7.50	-	-	12.00 [2.7-13.6]	13.7	3040 [250-4070]	3.95
	16+20+71	1.50	1.87	6.63	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3490]	3.38	1.80	2.24	7.96	-	-	12.00 [2.7-13.8]	13.6	3030 [250-4180]	3.96
	16+25+25	1.60	2.50	2.50	-	-	6.60 [2.3 -8.5]	8.3	1810 [260-2700]	3.65	2.38	3.71	3.71	-	-	9.80 [2.7-12.3]	12.5	2770 [230-3790]	3.54
	16+25+35	1.60	2.50	3.50	-	-	7.60 [2.3 -8.5]	10.1	2210 [250-2640]	3.44	2.25	3.52	4.93	-	-	10.70 [2.7-12.3]	12.9	2870 [230-3700]	3.73
	16+25+42	1.60	2.50	4.20	-	-	8.30 [2.3 -8.7]	11.5	2510 [250-2690]	3.31	2.28	3.55	5.97	-	-	11.80 [2.7-12.9]	14.0	3110 [230-3980]	3.79
	16+25+50	1.60	2.50	5.00	-	-	9.10 [2.3 -10.1]	11.7	2540 [280-3090]	3.58	2.11	3.30	6.59	-	-	12.00 [2.7-13.6]	13.7	3040 [250-4070]	3.95
	16+25+60	1.58	2.48	5.94	-	-	10.00 [2.3 -10.7]	13.9	3020 [280-3630]	3.31	1.90	2.97	7.13	-	-	12.00 [2.7-13.6]	13.7	3040 [250-4070]	3.95
	16+25+71	1.43	2.23	6.34	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3490]	3.38	1.71	2.68	7.61	-	-	12.00 [2.7-13.8]	13.6	3030 [250-4180]	3.96
	16+35+35	1.60	3.50	3.50	-	-	8.60 [2.3 -9.6]	12.1	2640 [250-3080]	3.26	2.16	4.72	4.72	-	-	11.60 [2.7-13.6]	13.5	3000 [230-4320]	3.87
	16+35+42	1.60	3.50	4.20	-	-	9.30 [2.3 -10.1]	13.4	2920 [250-3480]	3.18	2.06	4.52	5.42	-	-	12.00 [2.7-13.6]	14.1	3130 [240-4310]	3.83
	16+35+50	1.58	3.47	4.95	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3490]	3.38	1.90	4.16	5.94	-	-	12.00 [2.7-13.6]	13.3	2960 [250-4040]	4.05
	16+35+60	1.44	3.15	5.41	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3490]	3.38	1.73	3.78	6.49	-	-	12.00 [2.7-13.8]	13.3	2960 [250-4160]	4.05
	16+35+71	1.31	2.87	5.82	-	-	10.00 [2.3 -10.7]	13.3	2890 [280-3350]	3.46	1.58	3.44	6.98	-	-	12.00 [2.7-13.8]	13.3	2950 [270-4140]	4.07
	16+42+42	1.60	4.20	4.20	-	-	10.00 [2.3 -10.7]	15.4	3350 [250-4060]	2.99	1.92	5.04	5.04	-	-	12.00 [2.7-13.6]	14.1	3120 [240-4230]	3.85
	16+42+50	1.48	3.89	4.63	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3490]	3.38	1.78	4.67	5.55	-	-	12.00 [2.7-13.8]	13.3	2950 [270-4150]	4.07
	16+42+60	1.36	3.56	5.08	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3490]	3.38	1.63	4.27	6.10	-	-	12.00 [2.7-13.8]	13.3	2950 [270-4150]	4.07
	16+42+71	1.24	3.26	5.50	-	-	10.00 [2.3 -10.7]	13.3	2890 [280-3350]	3.46	1.49	3.91	6.60	-	-	12.00 [2.7-14.1]	13.2	2940 [270-4250]	4.08
	16+50+50	1.38	4.31	4.31	-	-	10.00 [2.3 -10.7]	12.4	2700 [320-3090]	3.70	1.66	5.17	5.17	-	-	12.00 [2.7-13.8]	12.8	2840 [300-3940]	4.23
	16+50+60	1.27	3.97	4.76	-	-	10.00 [2.3 -10.7]	12.4	2700 [320-3090]	3.70	1.53	4.76	5.71	-	-	12.00 [2.7-13.8]	12.8	2840 [300-3940]	4.23
	16+50+71	1.17	3.65	5.18	-	-	10.00 [2.3 -10.7]	12.1	2640 [340-3020]	3.79	1.40	4.38	6.22	-	-	12.00 [2.7-14.1]	12.7	2830 [310-4100]	4.24
	16+60+60	1.18	4.41	4.41	-	-	10.00 [2.3 -10.7]	12.4	2700 [320-3090]	3.70	1.42	5.29	5.29	-	-	12.00 [2.7-14.1]	12.8	2840 [300-4110]	4.23
	16+60+71	1.09	4.08	4.83	-	-	10.00 [2.3 -10.7]	12.1	2640 [340-3020]	3.79	1.31	4.90	5.79	-	-	12.00 [2.7-14.1]	12.7	2830 [310-4100]	4.24
	16+71+71	1.02	4.49	4.49	-	-	10.00 [2.3 -10.7]	11.8	2580 [350-2960]	3.88	1.22	5.39	5.39	-	-	12.00 [2.7-14.4]	12.7	2820 [320-4200]	4.26
	20+20+20	2.00	2.00	2.00	-	-	6.00 [2.3 -8.5]	7.1	1540 [260-2700]	3.90	3.20	3.20	3.20	-	-	9.60 [2.7-12.3]	12.0	2660 [230-3780]	3.61
	20+20+25	2.00	2.00	2.50	-	-	6.50 [2.3 -8.5]	8.0	1750 [260-2700]	3.71	3.08	3.08	3.84	-	-	10.00 [2.7-12.3]	12.7	2810 [230-3780]	3.56
	20+20+35	2.00	2.00	3.50	-	-	7.50 [2.3 -8.5]	9.6	2100 [250-2640]	3.57	2.91	2.91	5.08	-	-	10.90 [2.7-12.3]	12.9	2870 [230-3690]	3.80
	20+20+42	2.00	2.00	4.20	-	-	8.20 [2.3 -8.7]	11.2	2450 [250-2690]	3.35	2.93	2.93	6.14	-	-	12.00 [2.7-12.9]	14.4	3200 [230-3970]	3.75
	20+20+50	2.00	2.00	5.00	-	-	9.00 [2.3 -9.6]	11.7	2560 [280-2770]	3.52	2.67	2.67	6.66	-	-	12.00 [2.7-13.6]	13.6	3030 [250-4060]	3.96
20+20+60	2.00	2.00	6.00	-	-	10.00 [2.3 -10.7]	13.9	3020 [280-3560]	3.31	2.40	2.40	7.20	-	-	12.00 [2.7-13.6]	13.6	3030 [250-4060]	3.96	
20+20+71	1.80	1.80	6.40	-	-	10.00 [2.3 -10.7]	13.6	2960 [280-3420]	3.38	2.16	2.16	7.68	-	-	12.00 [2.7-13.8]	13.4	2970 [250-4160]	4.04	
20+25+25	2.00	2.50	2.50	-	-	7.00 [2.3 -8.5]	8.9	1930 [260-2700]	3.63	2.98	3.71	3.71	-	-	10.40 [2.7-12.3]	12.6	2790 [230-3780]	3.73	
20+25+35	2.00	2.50	3.50	-	-	8.00 [2.3 -8.5]	10.7	2330 [250-2640]	3.43	2.83	3.53	4.94	-	-	11.30 [2.7-12.9]	13.1	2920 [230-3980]	3.87	
20+25+42	2.00	2.50	4.20	-	-	8.70 [2.3 -9.6]	12.3	2690 [250-3150]	3.23	2.76	3.45	5.79	-	-	12.00 [2.7				

CU-5Z100VBR: Free Multi Indoor Combination

Indoor Units Capacity	COOLING OPERATION										HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input		EER	Heating Capacity					Running Current	Power Input		COP
	Room A	Room B	Room C	Room D	Room E			kW	W		W/W	Room A	Room B	Room C	Room D		Room E	kW	
	kW	kW	kW	kW	kW	kW	kW			kW		kW	kW	kW	kW	kW	kW		
20+42+50	1.79	3.75	4.46	-	-	10.00 [2.3-10.7]	13.6	2960 [280-3420]	3.38	2.14	4.50	5.36	-	-	12.00 [2.7-13.8]	13.2	2940 [270-4130]	4.08	
20+42+60	1.64	3.44	4.92	-	-	10.00 [2.3-10.7]	13.6	2960 [280-3420]	3.38	1.97	4.13	5.90	-	-	12.00 [2.7-13.8]	13.2	2940 [270-4130]	4.08	
20+42+71	1.50	3.16	5.34	-	-	10.00 [2.3-10.7]	13.0	2830 [280-3350]	3.53	1.80	3.79	6.41	-	-	12.00 [2.7-14.1]	13.2	2930 [270-4240]	4.10	
20+50+50	1.66	4.17	4.17	-	-	10.00 [2.3-10.7]	12.4	2710 [320-3090]	3.69	2.00	5.00	5.00	-	-	12.00 [2.7-13.8]	12.7	2830 [310-3920]	4.24	
20+50+60	1.54	3.85	4.61	-	-	10.00 [2.3-10.7]	12.4	2710 [320-3090]	3.69	1.85	4.62	5.53	-	-	12.00 [2.7-14.1]	12.7	2830 [310-4100]	4.24	
20+50+71	1.42	3.55	5.03	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	1.70	4.26	6.04	-	-	12.00 [2.7-14.1]	12.7	2820 [320-4080]	4.26	
20+60+60	1.42	4.29	4.29	-	-	10.00 [2.3-10.7]	12.4	2710 [320-3090]	3.69	1.72	5.14	5.14	-	-	12.00 [2.7-14.1]	12.7	2830 [310-4100]	4.24	
20+60+71	1.33	3.97	4.70	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	1.59	4.77	5.64	-	-	12.00 [2.7-14.4]	12.7	2820 [320-4200]	4.26	
20+71+71	1.24	4.38	4.38	-	-	10.00 [2.3-10.7]	11.8	2580 [350-2960]	3.88	1.48	5.26	5.26	-	-	12.00 [2.7-14.4]	12.8	2850 [330-4190]	4.21	
25+25+25	2.50	2.50	2.50	-	-	7.50 [2.3-8.5]	9.9	2160 [260-2700]	3.47	3.60	3.60	3.60	-	-	10.80 [2.7-12.3]	12.8	2850 [230-3780]	3.79	
25+25+35	2.50	2.50	3.50	-	-	8.50 [2.3-9.6]	12.1	2640 [250-3150]	3.22	3.44	3.44	4.82	-	-	11.70 [2.7-13.6]	13.8	3060 [230-4340]	3.82	
25+25+42	2.50	2.50	4.20	-	-	9.20 [2.3-10.1]	13.4	2920 [250-3550]	3.15	3.26	3.26	5.48	-	-	12.00 [2.7-13.6]	14.4	3200 [230-4330]	3.75	
25+25+50	2.50	2.50	5.00	-	-	10.00 [2.3-10.7]	13.9	3020 [280-3560]	3.31	3.00	3.00	6.00	-	-	12.00 [2.7-13.6]	13.6	3030 [250-4060]	3.96	
25+25+60	2.27	2.27	5.46	-	-	10.00 [2.3-10.7]	13.9	3020 [280-3560]	3.31	2.73	2.73	6.54	-	-	12.00 [2.7-13.8]	13.6	3030 [250-4180]	3.96	
25+25+71	2.07	2.07	5.86	-	-	10.00 [2.3-10.7]	13.6	2960 [280-3420]	3.38	2.48	2.48	7.04	-	-	12.00 [2.7-13.8]	13.4	2970 [250-4160]	4.04	
25+35+35	2.50	3.50	3.50	-	-	9.50 [2.3-10.1]	14.0	3050 [250-3480]	3.11	3.16	4.42	4.42	-	-	12.00 [2.7-13.6]	14.1	3130 [240-4310]	3.83	
25+35+42	2.45	3.43	4.12	-	-	10.00 [2.3-10.7]	15.4	3350 [250-4060]	2.99	2.94	4.12	4.94	-	-	12.00 [2.7-13.6]	14.1	3120 [240-4230]	3.85	
25+35+50	2.27	3.18	4.55	-	-	10.00 [2.3-10.7]	13.6	2960 [280-3490]	3.38	2.73	3.82	5.45	-	-	12.00 [2.7-13.8]	13.3	2950 [270-4150]	4.07	
25+35+60	2.08	2.92	5.00	-	-	10.00 [2.3-10.7]	13.6	2960 [280-3490]	3.38	2.50	3.50	6.00	-	-	12.00 [2.7-13.8]	13.3	2950 [270-4150]	4.07	
25+35+71	1.91	2.67	5.42	-	-	10.00 [2.3-10.7]	13.3	2890 [280-3350]	3.46	2.29	3.21	6.50	-	-	12.00 [2.7-14.1]	13.2	2940 [270-4250]	4.08	
25+42+42	2.30	3.85	3.85	-	-	10.00 [2.3-10.7]	15.4	3350 [250-4060]	2.99	2.76	4.62	4.62	-	-	12.00 [2.7-13.8]	14.0	3110 [240-4340]	3.86	
25+42+50	2.14	3.59	4.27	-	-	10.00 [2.3-10.7]	13.6	2960 [280-3420]	3.38	2.56	4.31	5.13	-	-	12.00 [2.7-13.8]	13.2	2940 [270-4130]	4.08	
25+42+60	1.97	3.31	4.72	-	-	10.00 [2.3-10.7]	13.6	2960 [280-3420]	3.38	2.36	3.97	5.67	-	-	12.00 [2.7-14.1]	13.2	2940 [270-4250]	4.08	
25+42+71	1.82	3.04	5.14	-	-	10.00 [2.3-10.7]	13.0	2830 [280-3350]	3.53	2.18	3.65	6.17	-	-	12.00 [2.7-14.1]	13.2	2930 [270-4240]	4.10	
25+50+50	2.00	4.00	4.00	-	-	10.00 [2.3-10.7]	12.4	2710 [320-3090]	3.69	2.40	4.80	4.80	-	-	12.00 [2.7-13.8]	12.7	2830 [310-3920]	4.24	
25+50+60	1.86	3.70	4.44	-	-	10.00 [2.3-10.7]	12.4	2710 [320-3090]	3.69	2.23	4.44	5.33	-	-	12.00 [2.7-14.1]	12.7	2830 [310-4100]	4.24	
25+50+71	1.72	3.42	4.86	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	2.05	4.11	5.84	-	-	12.00 [2.7-14.1]	12.7	2820 [320-4080]	4.26	
25+60+60	1.72	4.14	4.14	-	-	10.00 [2.3-10.7]	12.4	2710 [320-3090]	3.69	2.06	4.97	4.97	-	-	12.00 [2.7-14.1]	12.7	2830 [310-4100]	4.24	
25+60+71	1.60	3.85	4.55	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	1.92	4.62	5.46	-	-	12.00 [2.7-14.4]	12.7	2820 [320-4200]	4.26	
25+71+71	1.50	4.25	4.25	-	-	10.00 [2.3-10.7]	11.8	2580 [350-2960]	3.88	1.80	5.10	5.10	-	-	12.00 [2.7-14.4]	12.8	2850 [330-4190]	4.21	
35+35+35	3.33	3.33	3.33	-	-	9.99 [2.3-10.7]	15.0	3280 [250-3980]	3.05	4.00	4.00	4.00	-	-	12.00 [2.7-13.8]	14.0	3100 [240-4330]	3.87	
35+35+42	3.13	3.13	3.74	-	-	10.00 [2.3-10.7]	15.0	3280 [250-3910]	3.05	3.75	3.75	4.50	-	-	12.00 [2.7-13.8]	13.9	3090 [240-4320]	3.88	
35+35+50	2.92	2.92	4.16	-	-	10.00 [2.3-10.7]	13.3	2890 [280-3350]	3.46	3.50	3.50	5.00	-	-	12.00 [2.7-13.8]	13.2	2930 [270-4110]	4.10	
35+35+60	2.69	2.69	4.62	-	-	10.00 [2.3-10.7]	13.3	2890 [280-3350]	3.46	3.23	3.23	5.54	-	-	12.00 [2.7-14.1]	13.2	2930 [270-4230]	4.10	
35+35+71	2.48	2.48	5.04	-	-	10.00 [2.3-10.7]	13.0	2830 [310-3290]	3.53	2.98	2.98	6.04	-	-	12.00 [2.7-14.1]	13.1	2910 [270-4210]	4.12	
35+42+42	2.94	3.53	3.53	-	-	10.00 [2.3-10.7]	14.8	3220 [250-3910]	3.11	3.52	4.24	4.24	-	-	12.00 [2.7-13.8]	13.9	3080 [250-4310]	3.90	
35+42+50	2.76	3.31	3.93	-	-	10.00 [2.3-10.7]	13.3	2890 [280-3350]	3.46	3.31	3.97	4.72	-	-	12.00 [2.7-14.1]	13.1	2920 [270-4220]	4.11	
35+42+60	2.55	3.07	4.38	-	-	10.00 [2.3-10.7]	13.3	2890 [280-3350]	3.46	3.07	3.68	5.25	-	-	12.00 [2.7-14.1]	13.1	2920 [270-4220]	4.11	
35+42+71	2.36	2.84	4.80	-	-	10.00 [2.3-10.7]	13.0	2830 [310-3290]	3.53	2.84	3.41	5.75	-	-	12.00 [2.7-14.1]	13.1	2900 [280-4200]	4.14	
35+50+50	2.60	3.70	3.70	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	3.12	4.44	4.44	-	-	12.00 [2.7-14.1]	12.8	2850 [330-4070]	4.21	
35+50+60	2.41	3.45	4.14	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	2.90	4.14	4.96	-	-	12.00 [2.7-14.1]	12.8	2850 [330-4070]	4.21	
35+50+71	2.24	3.21	4.55	-	-	10.00 [2.3-10.7]	11.8	2580 [350-2960]	3.88	2.69	3.85	5.46	-	-	12.00 [2.7-14.4]	12.8	2840 [330-4170]	4.23	
35+60+60	2.26	3.87	3.87	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	2.70	4.65	4.65	-	-	12.00 [2.7-14.4]	12.8	2850 [330-4190]	4.21	
35+60+71	2.11	3.61	4.28	-	-	10.00 [2.3-10.7]	11.8	2580 [350-2960]	3.88	2.53	4.34	5.13	-	-	12.00 [2.7-14.4]	12.8	2840 [330-4170]	4.23	
35+71+71	1.98	4.01	4.01	-	-	10.00 [2.3-10.7]	11.9	2590 [350-2960]	3.86	2.38	4.81	4.81	-	-	12.00 [2.7-14.4]	12.7	2830 [340-4150]	4.24	
42+42+42	3.33	3.33	3.33	-	-	9.99 [2.3-10.7]	14.8	3220 [250-3840]	3.10	4.00	4.00	4.00	-	-	12.00 [2.7-13.8]	13.8	3070 [250-4230]	3.91	
42+42+50	3.13	3.13	3.74	-	-	10.00 [2.3-10.7]	13.0	2830 [280-3350]	3.53	3.76	3.76	4.48	-	-	12.00 [2.7-14.1]	13.1	2910 [280-4200]	4.12	
42+42+60	2.92	2.92	4.16	-	-	10.00 [2.3-10.7]	13.0	2830 [280-3350]	3.53	3.50	3.50	5.00	-	-	12.00 [2.7-14.1]	13.1	2910 [280-4200]	4.12	
42+42+71	2.71	2.71	4.58	-	-	10.00 [2.3-10.7]	12.7	2770 [310-3220]	3.61	3.25	3.25	5.50	-	-	12.00 [2.7-14.4]	13.0	2890 [280-4310]	4.15	
42+50+50	2.96	3.52	3.52	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	3.54	4.23	4.23	-	-	12.00 [2.7-14.1]	12.8	2850 [330-4050]	4.21	
42+50+60	2.76	3.29	3.95	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	3.32	3.95	4.73	-	-	12.00 [2.7-14.4]	12.8	2850 [330-4170]	4.21	
42+50+71	2.58	3.07	4.35	-	-	10.00 [2.3-10.7]	11.8	2580 [350-2960]	3.88	3.09	3.68	5.23	-	-	12.00 [2.7-14.4]	12.7	2830 [340-4160]	4.24	
42+60+60	2.60	3.70	3.70	-	-	10.00 [2.3-10.7]	12.1	2640 [350-3020]	3.79	3.12	4.44	4.44	-	-	12.00 [2.7-14.4]	12.8	2850 [330-4170]	4.21	
42+60+71	2.43	3.47	4.10	-	-	10.00 [2.3-10.7]	11.8	2580 [350-2960]	3.88	2.92	4.16	4.92	-	-	12.00 [2.7-14.4]	12.7	2830 [340-4160]	4.24	
50+50+50	3.33	3.33	3.33	-	-	9.99 [2.3-10.7]	11.3	2470 [390-2830]	4.04	4.00	4.00	4.00	-	-	12.00 [2.7-14.4]	12.6	2800 [400-4090]	4.29	
50+50+60	3.13	3.13	3.74	-	-	10.00 [2.3-10.7]	11.6	2530 [390-2830]	3.95	3.75	3.75	4.50	-	-	12.00 [2.7-14.4]	12.6	2800 [400-4090]	4.29	
50+50+71	2.92	2.92	4.16	-	-	10.00 [2.3-10.7]	11.3	2470 [390-2840]	4.05	3.51	3.51	4.98	-	-	12.00 [2.7-14.4]	12.6	2790 [410-4070]	4.30	
50+60+60	2.94	3.53	3.53	-	-	10.00 [2.3-10.7]	11.6	2530 [390-2830]	3.95	3.52	4.24	4.24	-	-	12.00 [2.7-14.4]	12.6	2800 [400-4090]	4.29	
50+60+71	2.77	3.31	3.92	-	-	10.00 [2.3-10.7]	11.3	2470 [390-2840]	4.05	3.31	3.								

CU-5Z100VBR: Free Multi Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	A	W	W/W	
4 rooms	16+16+16+16	1.60	1.60	1.60	1.60	-	6.40 (2.3-10.6)	7.4	1600 (310-3680)	4.00	2.60	2.60	2.60	2.60	-	10.40 (3.4-14.2)	11.9	2640 (340-4400)	3.94
	16+16+16+20	1.60	1.60	1.60	2.00	-	6.80 (2.3-10.6)	8.1	1740 (310-3680)	3.91	2.59	2.59	2.59	3.23	-	11.00 (3.4-14.2)	12.5	2780 (340-4390)	3.96
	16+16+16+25	1.60	1.60	1.60	2.50	-	7.30 (2.3-10.6)	8.7	1900 (310-3680)	3.84	2.50	2.50	2.50	3.90	-	11.40 (3.4-14.2)	12.8	2840 (340-4390)	4.01
	16+16+16+35	1.60	1.60	1.60	3.50	-	8.30 (2.3-10.6)	10.5	2290 (310-3600)	3.62	2.31	2.31	2.31	5.07	-	12.00 (3.4-14.2)	13.5	3000 (340-4350)	4.00
	16+16+16+42	1.60	1.60	1.60	4.20	-	9.00 (2.3-10.6)	11.8	2580 (310-3600)	3.49	2.13	2.13	2.13	5.61	-	12.00 (3.4-14.2)	13.5	2990 (340-4340)	4.01
	16+16+16+50	1.60	1.60	1.60	5.00	-	9.80 (2.3-10.6)	12.8	2780 (350-3310)	3.53	1.96	1.96	1.96	6.12	-	12.00 (3.4-14.2)	13.2	2930 (390-4190)	4.10
	16+16+16+60	1.48	1.48	1.48	5.56	-	10.00 (2.3-10.6)	13.3	2910 (350-3310)	3.44	1.78	1.78	1.78	6.66	-	12.00 (3.4-14.2)	13.2	2930 (390-4190)	4.10
	16+16+16+71	1.34	1.34	1.34	5.98	-	10.00 (2.3-10.6)	13.1	2850 (380-3240)	3.51	1.61	1.61	1.61	7.17	-	12.00 (3.4-14.2)	13.1	2920 (400-4170)	4.11
	16+16+20+20	1.60	1.60	2.00	2.00	-	7.20 (2.3-10.6)	8.5	1850 (310-3600)	3.89	2.58	2.58	3.22	3.22	-	11.60 (3.4-14.2)	12.9	2870 (340-4370)	4.04
	16+16+20+25	1.60	1.60	2.00	2.50	-	7.70 (2.3-10.6)	9.4	2050 (310-3600)	3.76	2.49	2.49	3.12	3.90	-	12.00 (3.4-14.2)	13.6	3010 (340-4370)	3.99
	16+16+20+35	1.60	1.60	2.00	3.50	-	8.70 (2.3-10.6)	11.2	2450 (310-3530)	3.55	2.21	2.21	2.76	4.82	-	12.00 (3.4-14.2)	13.5	2990 (340-4340)	4.01
	16+16+20+42	1.60	1.60	2.00	4.20	-	9.40 (2.3-10.6)	12.6	2740 (310-3530)	3.43	2.04	2.04	2.56	5.36	-	12.00 (3.4-14.2)	13.4	2980 (340-4320)	4.03
	16+16+20+50	1.57	1.57	1.96	4.90	-	10.00 (2.3-10.6)	13.3	2910 (350-3310)	3.44	1.88	1.88	2.36	5.88	-	12.00 (3.4-14.2)	13.1	2920 (400-4170)	4.11
	16+16+20+60	1.43	1.43	1.79	5.35	-	10.00 (2.3-10.6)	13.3	2910 (350-3310)	3.44	1.71	1.71	2.15	6.43	-	12.00 (3.4-14.2)	13.1	2920 (400-4170)	4.11
	16+16+20+71	1.30	1.30	1.63	5.77	-	10.00 (2.3-10.8)	13.1	2850 (380-3380)	3.51	1.56	1.56	1.95	6.93	-	12.00 (3.4-14.2)	13.1	2910 (400-4160)	4.12
	16+16+25+25	1.60	1.60	2.50	2.50	-	8.20 (2.3-10.6)	10.2	2230 (310-3600)	3.68	2.34	2.34	3.66	3.66	-	12.00 (3.4-14.2)	13.6	3010 (340-4370)	3.99
	16+16+25+35	1.60	1.60	2.50	3.50	-	9.20 (2.3-10.6)	12.3	2680 (310-3530)	3.43	2.09	2.09	3.26	4.56	-	12.00 (3.4-14.2)	13.5	2990 (340-4340)	4.01
	16+16+25+42	1.60	1.60	2.50	4.20	-	9.90 (2.3-10.6)	13.9	3040 (310-3530)	3.26	1.94	1.94	3.03	5.09	-	12.00 (3.4-14.2)	13.4	2980 (340-4320)	4.03
	16+16+25+50	1.50	1.50	2.34	4.66	-	10.00 (2.3-10.6)	13.3	2910 (350-3310)	3.44	1.79	1.79	2.81	5.61	-	12.00 (3.4-14.2)	13.1	2920 (400-4170)	4.11
	16+16+25+60	1.37	1.37	2.14	5.12	-	10.00 (2.3-10.6)	13.3	2910 (350-3310)	3.44	1.64	1.64	2.57	6.15	-	12.00 (3.4-14.2)	13.1	2920 (400-4170)	4.11
	16+16+25+71	1.25	1.25	1.95	5.55	-	10.00 (2.3-10.8)	13.1	2850 (380-3380)	3.51	1.50	1.50	2.34	6.66	-	12.00 (3.4-14.4)	13.1	2910 (400-4220)	4.12
	16+16+35+35	1.57	1.57	3.43	3.43	-	10.00 (2.3-10.6)	13.9	3040 (320-3530)	3.29	1.88	1.88	4.12	4.12	-	12.00 (3.4-14.2)	13.3	2960 (360-4300)	4.05
	16+16+35+42	1.47	1.47	3.21	3.85	-	10.00 (2.3-10.6)	13.9	3040 (320-3450)	3.29	1.76	1.76	3.86	4.62	-	12.00 (3.4-14.2)	13.3	2950 (360-4220)	4.07
	16+16+35+50	1.37	1.37	2.99	4.27	-	10.00 (2.3-10.6)	13.1	2850 (380-3240)	3.51	1.64	1.64	3.59	5.13	-	12.00 (3.4-14.2)	13.1	2900 (420-4140)	4.14
	16+16+35+60	1.26	1.26	2.76	4.72	-	10.00 (2.3-10.8)	13.1	2850 (380-3380)	3.51	1.51	1.51	3.31	5.67	-	12.00 (3.4-14.2)	13.1	2900 (420-4140)	4.14
	16+16+35+71	1.16	1.16	2.54	5.14	-	10.00 (2.3-10.8)	13.1	2850 (390-3310)	3.51	1.39	1.39	3.05	6.17	-	12.00 (3.4-14.4)	13.0	2890 (420-4180)	4.15
	16+16+42+42	1.38	1.38	3.62	3.62	-	10.00 (2.3-10.6)	13.9	3040 (320-3450)	3.29	1.66	1.66	4.34	4.34	-	12.00 (3.4-14.2)	13.2	2940 (370-4210)	4.08
	16+16+42+50	1.29	1.29	3.39	4.03	-	10.00 (2.3-10.8)	13.1	2850 (380-3380)	3.51	1.55	1.55	4.06	4.84	-	12.00 (3.4-14.2)	13.0	2890 (420-4130)	4.15
	16+16+42+60	1.19	1.19	3.14	4.48	-	10.00 (2.3-10.8)	13.1	2850 (380-3380)	3.51	1.43	1.43	3.77	5.37	-	12.00 (3.4-14.4)	13.0	2890 (420-4190)	4.15
	16+16+42+71	1.10	1.10	2.90	4.90	-	10.00 (2.3-11.0)	13.1	2850 (390-3460)	3.51	1.32	1.32	3.48	5.88	-	12.00 (3.4-14.4)	13.0	2880 (430-4170)	4.17
	16+16+50+50	1.21	1.21	3.79	3.79	-	10.00 (2.3-10.8)	12.5	2730 (430-3180)	3.66	1.45	1.45	4.55	4.55	-	12.00 (3.4-14.4)	12.8	2850 (490-4110)	4.21
	16+16+50+60	1.13	1.13	3.52	4.22	-	10.00 (2.3-11.0)	12.5	2730 (430-3320)	3.66	1.35	1.35	4.23	5.07	-	12.00 (3.4-14.4)	12.8	2850 (490-4110)	4.21
	16+16+50+71	1.05	1.05	3.27	4.63	-	10.00 (2.3-11.0)	12.5	2730 (460-3320)	3.66	1.25	1.25	3.93	5.57	-	12.00 (3.4-14.4)	13.0	2890 (510-4100)	4.15
	16+16+60+60	1.05	1.05	3.95	3.95	-	10.00 (2.3-11.0)	12.5	2730 (430-3320)	3.66	1.26	1.26	4.74	4.74	-	12.00 (3.4-14.4)	12.8	2850 (490-4110)	4.21
	16+16+60+71	0.98	0.98	3.68	4.36	-	10.00 (2.3-11.2)	12.5	2730 (460-3400)	3.66	1.18	1.18	4.42	5.22	-	12.00 (3.4-14.4)	13.0	2890 (510-4100)	4.15
	16+16+71+71	0.92	0.92	4.08	4.08	-	10.00 (2.3-11.2)	12.5	2730 (470-3400)	3.66	1.10	1.10	4.90	4.90	-	12.00 (3.4-14.4)	13.0	2880 (510-4140)	4.17
	16+20+20+20	1.60	2.00	2.00	2.00	-	7.60 (2.3-10.6)	9.3	2020 (310-3600)	3.76	2.52	3.10	3.16	3.16	-	12.00 (3.4-14.2)	13.5	3000 (340-4360)	4.00
	16+20+20+25	1.60	2.00	2.00	2.50	-	8.10 (2.3-10.6)	10.0	2170 (310-3600)	3.73	2.38	2.96	2.96	3.70	-	12.00 (3.4-14.2)	13.5	3000 (340-4360)	4.00
	16+20+20+35	1.60	2.00	2.00	3.50	-	9.10 (2.3-10.6)	12.0	2610 (310-3530)	3.49	2.11	2.64	2.64	4.61	-	12.00 (3.4-14.2)	13.4	2980 (340-4320)	4.03
	16+20+20+42	1.60	2.00	2.00	4.20	-	9.80 (2.3-10.6)	13.3	2910 (310-3530)	3.37	1.96	2.45	2.45	5.14	-	12.00 (3.4-14.2)	13.4	2970 (350-4310)	4.04
16+20+20+50	1.51	1.89	1.89	4.71	-	10.00 (2.3-10.6)	13.1	2850 (360-3240)	3.51	1.82	2.26	2.26	5.66	-	12.00 (3.4-14.2)	13.1	2910 (400-4160)	4.12	
16+20+20+60	1.39	1.72	1.72	5.17	-	10.00 (2.3-10.6)	13.1	2850 (360-3240)	3.51	1.66	2.07	2.07	6.20	-	12.00 (3.4-14.2)	13.1	2910 (400-4160)	4.12	
16+20+20+71	1.27	1.57	1.57	5.59	-	10.00 (2.3-10.8)	13.1	2850 (390-3310)	3.51	1.51	1.89	1.89	6.71	-	12.00 (3.4-14.2)	13.1	2900 (420-4140)	4.14	
16+20+25+25	1.60	2.00	2.50	2.50	-	8.60 (2.3-10.6)	11.1	2410 (310-3600)	3.57	2.23	2.79	3.49	3.49	-	12.00 (3.4-14.2)	13.5	3000 (340-4360)	4.00	
16+20+25+35	1.60	2.00	2.50	3.50	-	9.60 (2.3-10.6)	13.0	2840 (310-3530)	3.38	2.00	2.50	3.13	4.37	-	12.00 (3.4-14.2)	13.4	2980 (340-4320)	4.03	
16+20+25+42	1.55	1.94	2.43	4.08	-	10.00 (2.3-10.6)	13.9	3040 (310-3530)	3.29	1.87	2.33	2.91	4.89	-	12.00 (3.4-14.2)	13.4	2970 (350-4310)	4.04	
16+20+25+50	1.45	1.80	2.25	4.50	-	10.00 (2.3-10.6)	13.1	2850 (360-3240)	3.51	1.73	2.16	2.70	5.41	-	12.00 (3.4-14.2)	13.1	2910 (400-4160)	4.12	
16+20+25+60	1.32	1.65	2.07	4.96	-	10.00 (2.3-10.8)	13.1	2850 (360-3380)	3.51	1.59	1.98	2.48	5.95	-	12.00 (3.4-14.2)	13.1	2910 (400-4160)	4.12	
16+20+25+71	1.21	1.52	1.89	5.38	-	10.00 (2.3-10.8)	13.1	2850 (390-3310)	3.51	1.46	1.82	2.27	6.45	-	12.00 (3.4-14.4)	13.1	2900 (420-4200)	4.14	
16+20+35+35	1.51	1.89	3.30	3.30	-	10.00 (2.3-10.6)	13.9	3040 (320-3450)	3.29	1.82	2.26	3.96	3.96	-	12.00 (3.4-14.2)	13.3	2950 (360-4220)	4.07	
16+20+35+42	1.42	1.77	3.10	3.71	-	10.00 (2.3-10.6)	13.9	3040 (320-3450)	3.29	1.70	2.12	3.72	4.46	-	12.00 (3.4-14.2)	13.2	2940 (370-4210)	4.08	
16+20+35+50	1.33	1.65	2.89	4.13	-	10.00 (2.3-10.8)	13.1	2850 (380-3380)	3.51	1.59	1.98	3.47	4.96	-	12.00 (3.4-14.2)	13.0	2890 (420-4130)	4.15	
16+20+35+60	1.22	1.53	2.67	4.58	-	10.00 (2.3-10.8)	13.1	2850 (380-3380)	3.51	1.47	1.83	3.21	5.49	-	12.00 (3.4-14.4)	13.0	2890 (420-4190)	4.15	
16+20+35+71	1.13	1.41	2.46	5.00	-	10.00 (2.3-11.0)	12.8	2780 (390-3460)	3.60	1.35	1.69	2.96	6.00	-	12.00 (3.4-14.4)	13.0	2880 (430-4170)	4.17	
16+20+42+42	1.33	1.67	3.50	3.50	-	10.00 (2.3-10.6)	13.7	2980 (320-3450)	3.36	1.60	2.00	4.20	4.20	-	12.00 (3.4-14.2)	13.2	2930 (370-4200)	4.10	
16+20+42+50	1.25	1.56	3.28	3.91	-	10.00 (2.3-10.8)	13.1	2850 (390-3310)	3.51	1.50	1.88	3.94	4.68	-	12.00 (

CU-5Z100VBR: Free Multi Indoor Combination

Indoor Units Capacity		COOLING OPERATION									HEATING OPERATION								
		Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP	
		Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				Total
		kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	A	W	W/W	
4 rooms	16+20+71+71	0.90	1.12	3.99	3.99	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.08	1.34	4.79	4.79	-	12.00 [3.4-14.4]	12.9	2870 [520-4130]	4.18
	16+25+25+25	1.60	2.50	2.50	2.50	-	9.10 [2.3-10.6]	12.0	2610 [310-3600]	3.49	2.10	3.30	3.30	3.30	-	12.00 [3.4-14.2]	13.5	3000 [340-4360]	4.00
	16+25+25+35	1.58	2.48	2.48	3.46	-	10.00 [2.3-10.6]	13.9	3040 [310-3530]	3.29	1.90	2.97	2.97	4.16	-	12.00 [3.4-14.2]	13.4	2980 [340-4320]	4.03
	16+25+25+42	1.49	2.31	2.31	3.89	-	10.00 [2.3-10.6]	13.9	3040 [310-3530]	3.29	1.78	2.78	2.78	4.66	-	12.00 [3.4-14.2]	13.4	2970 [350-4310]	4.04
	16+25+25+50	1.38	2.16	2.16	4.30	-	10.00 [2.3-10.6]	13.1	2850 [360-3240]	3.51	1.66	2.59	2.59	5.16	-	12.00 [3.4-14.2]	13.1	2910 [400-4160]	4.12
	16+25+25+60	1.28	1.98	1.98	4.76	-	10.00 [2.3-10.8]	13.1	2850 [360-3380]	3.51	1.53	2.38	2.38	5.71	-	12.00 [3.4-14.2]	13.1	2910 [400-4160]	4.12
	16+25+25+71	1.18	1.82	1.82	5.18	-	10.00 [2.3-10.8]	13.1	2850 [390-3310]	3.51	1.40	2.19	2.19	6.22	-	12.00 [3.4-14.4]	13.1	2900 [420-4200]	4.14
	16+25+35+35	1.45	2.25	3.15	3.15	-	10.00 [2.3-10.6]	13.9	3040 [320-3450]	3.29	1.74	2.70	3.78	3.78	-	12.00 [3.4-14.2]	13.3	2950 [360-4220]	4.07
	16+25+35+42	1.36	2.12	2.97	3.55	-	10.00 [2.3-10.6]	13.9	3040 [320-3450]	3.29	1.63	2.54	3.56	4.27	-	12.00 [3.4-14.2]	13.2	2940 [370-4210]	4.08
	16+25+35+50	1.27	1.98	2.78	3.97	-	10.00 [2.3-10.8]	13.1	2850 [380-3380]	3.51	1.53	2.38	3.33	4.76	-	12.00 [3.4-14.2]	13.0	2890 [420-4130]	4.15
	16+25+35+60	1.18	1.84	2.57	4.41	-	10.00 [2.3-10.8]	13.1	2850 [380-3380]	3.51	1.41	2.21	3.09	5.29	-	12.00 [3.4-14.4]	13.0	2890 [420-4190]	4.15
	16+25+35+71	1.09	1.70	2.38	4.83	-	10.00 [2.3-11.0]	12.8	2780 [390-3460]	3.60	1.31	2.04	2.86	5.79	-	12.00 [3.4-14.4]	13.0	2880 [430-4170]	4.17
	16+25+42+42	1.28	2.00	3.36	3.36	-	10.00 [2.3-10.8]	13.7	2980 [320-3600]	3.36	1.54	2.40	4.03	4.03	-	12.00 [3.4-14.2]	13.2	2930 [370-4200]	4.10
	16+25+42+50	1.20	1.88	3.16	3.76	-	10.00 [2.3-10.8]	13.1	2850 [390-3310]	3.51	1.44	2.26	3.79	4.51	-	12.00 [3.4-14.4]	13.0	2880 [420-4170]	4.17
	16+25+42+60	1.12	1.75	2.94	4.19	-	10.00 [2.3-11.0]	13.1	2850 [390-3460]	3.51	1.35	2.10	3.52	5.03	-	12.00 [3.4-14.4]	13.0	2880 [420-4170]	4.17
	16+25+42+71	1.04	1.62	2.73	4.61	-	10.00 [2.3-11.0]	12.8	2780 [390-3390]	3.60	1.25	1.95	3.27	5.53	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18
	16+25+50+50	1.13	1.77	3.55	3.55	-	10.00 [2.3-10.8]	12.5	2730 [430-3180]	3.66	1.36	2.12	4.26	4.26	-	12.00 [3.4-14.4]	13.0	2890 [500-4100]	4.15
	16+25+50+60	1.06	1.66	3.31	3.97	-	10.00 [2.3-11.0]	12.5	2730 [430-3320]	3.66	1.27	1.99	3.97	4.77	-	12.00 [3.4-14.4]	13.0	2890 [500-4100]	4.15
	16+25+50+71	0.99	1.54	3.09	4.38	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.19	1.85	3.70	5.26	-	12.00 [3.4-14.4]	13.0	2880 [510-4140]	4.17
	16+25+60+60	0.99	1.55	3.73	3.73	-	10.00 [2.3-11.2]	12.5	2730 [430-3390]	3.66	1.20	1.86	4.47	4.47	-	12.00 [3.4-14.4]	13.0	2890 [500-4100]	4.15
	16+25+60+71	0.93	1.45	3.49	4.13	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.12	1.74	4.19	4.95	-	12.00 [3.4-14.4]	13.0	2880 [510-4140]	4.17
	16+25+71+71	0.87	1.37	3.88	3.88	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.05	1.63	4.66	4.66	-	12.00 [3.4-14.4]	12.9	2870 [520-4130]	4.18
	16+35+35+35	1.33	2.89	2.89	2.89	-	10.00 [2.3-10.8]	13.7	2980 [340-3530]	3.36	1.59	3.47	3.47	3.47	-	12.00 [3.4-14.2]	13.2	2930 [370-4190]	4.10
	16+35+35+42	1.26	2.73	2.73	3.28	-	10.00 [2.3-10.8]	13.7	2980 [350-3530]	3.36	1.50	3.28	3.28	3.94	-	12.00 [3.4-14.4]	13.1	2920 [370-4300]	4.11
	16+35+35+50	1.18	2.57	2.57	3.68	-	10.00 [2.3-10.8]	13.1	2850 [390-3310]	3.51	1.41	3.09	3.09	4.41	-	12.00 [3.4-14.4]	12.9	2870 [430-4150]	4.18
	16+35+35+60	1.10	2.40	2.40	4.10	-	10.00 [2.3-11.0]	13.1	2850 [390-3460]	3.51	1.32	2.88	2.88	4.92	-	12.00 [3.4-14.4]	12.9	2870 [430-4150]	4.18
	16+35+35+71	1.02	2.23	2.23	4.52	-	10.00 [2.3-11.0]	12.8	2780 [390-3390]	3.60	1.22	2.68	2.68	5.42	-	12.00 [3.4-14.4]	12.9	2860 [450-4200]	4.20
	16+35+42+42	1.19	2.59	3.11	3.11	-	10.00 [2.3-10.8]	13.7	2980 [350-3530]	3.36	1.43	3.11	3.73	3.73	-	12.00 [3.4-14.4]	13.3	2950 [370-4280]	4.07
	16+35+42+50	1.12	2.45	2.94	3.49	-	10.00 [2.3-11.0]	12.8	2780 [390-3460]	3.60	1.34	2.94	3.52	4.20	-	12.00 [3.4-14.4]	12.9	2860 [450-4200]	4.20
	16+35+42+60	1.05	2.29	2.75	3.91	-	10.00 [2.3-11.0]	12.8	2780 [390-3460]	3.60	1.25	2.75	3.29	4.71	-	12.00 [3.4-14.4]	12.9	2860 [450-4200]	4.20
	16+35+42+71	0.98	2.13	2.56	4.33	-	10.00 [2.3-11.2]	12.8	2790 [400-3530]	3.58	1.17	2.56	3.07	5.20	-	12.00 [3.4-14.4]	13.0	2890 [450-4180]	4.15
	16+35+50+50	1.06	2.32	3.31	3.31	-	10.00 [2.3-11.0]	12.5	2730 [470-3250]	3.66	1.28	2.78	3.97	3.97	-	12.00 [3.4-14.4]	12.9	2870 [520-4130]	4.18
	16+35+50+60	0.99	2.17	3.11	3.73	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.19	2.61	3.73	4.47	-	12.00 [3.4-14.4]	12.9	2870 [520-4130]	4.18
	16+35+50+71	0.93	2.03	2.91	4.13	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.12	2.44	3.49	4.95	-	12.00 [3.4-14.4]	12.9	2860 [540-4120]	4.20
	16+35+60+60	0.93	2.05	3.51	3.51	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.12	2.46	4.21	4.21	-	12.00 [3.4-14.4]	12.9	2870 [520-4130]	4.18
	16+35+60+71	0.88	1.92	3.30	3.90	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.05	2.31	3.96	4.68	-	12.00 [3.4-14.4]	12.9	2860 [540-4120]	4.20
	16+42+42+42	1.12	2.96	2.96	2.96	-	10.00 [2.3-11.0]	13.7	2980 [350-3680]	3.36	1.35	3.55	3.55	3.55	-	12.00 [3.4-14.4]	13.2	2940 [390-4270]	4.08
	16+42+42+50	1.07	2.80	2.80	3.33	-	10.00 [2.3-11.0]	12.8	2780 [390-3390]	3.60	1.28	3.36	3.36	4.00	-	12.00 [3.4-14.4]	13.1	2900 [450-4190]	4.14
	16+42+42+60	1.00	2.63	2.63	3.74	-	10.00 [2.3-11.2]	12.8	2780 [390-3530]	3.60	1.20	3.15	3.15	4.50	-	12.00 [3.4-14.4]	13.1	2900 [450-4190]	4.14
	16+42+42+71	0.94	2.46	2.46	4.14	-	10.00 [2.3-11.2]	12.8	2790 [420-3540]	3.58	1.12	2.95	2.95	4.98	-	12.00 [3.4-14.4]	13.0	2890 [460-4170]	4.15
16+42+50+50	1.02	2.66	3.16	3.16	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.22	3.18	3.80	3.80	-	12.00 [3.4-14.4]	12.9	2870 [530-4120]	4.18	
16+42+50+60	0.95	2.50	2.98	3.57	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.14	3.00	3.57	4.29	-	12.00 [3.4-14.4]	12.9	2870 [530-4120]	4.18	
16+42+50+71	0.89	2.35	2.79	3.97	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.07	2.82	3.35	4.76	-	12.00 [3.4-14.4]	12.9	2860 [540-4110]	4.20	
16+42+60+60	0.90	2.36	3.37	3.37	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.08	2.84	4.04	4.04	-	12.00 [3.4-14.4]	12.9	2870 [530-4120]	4.18	
16+50+50+50	0.97	3.01	3.01	3.01	-	10.00 [2.3-11.2]	12.3	2690 [520-3340]	3.72	1.17	3.61	3.61	3.61	-	12.00 [3.4-14.4]	13.1	2900 [630-4120]	4.14	
16+50+50+60	0.91	2.84	2.84	3.41	-	10.00 [2.3-11.2]	12.3	2690 [520-3340]	3.72	1.09	3.41	3.41	4.09	-	12.00 [3.4-14.4]	13.1	2900 [630-4120]	4.14	
20+20+20+20	2.00	2.00	2.00	2.00	-	8.00 [2.3-10.6]	10.0	2170 [310-3600]	3.69	3.00	3.00	3.00	3.00	-	12.00 [3.4-14.2]	13.5	2990 [340-4350]	4.01	
20+20+20+25	2.00	2.00	2.00	2.50	-	8.50 [2.3-10.6]	10.8	2350 [310-3600]	3.62	2.82	2.82	2.82	3.54	-	12.00 [3.4-14.2]	13.5	2990 [340-4350]	4.01	
20+20+20+35	2.00	2.00	2.00	3.50	-	9.50 [2.3-10.6]	12.9	2810 [320-3530]	3.38	2.53	2.53	2.53	4.41	-	12.00 [3.4-14.2]	13.4	2970 [350-4310]	4.04	
20+20+20+42	1.96	1.96	1.96	4.12	-	10.00 [2.3-10.6]	13.9	3040 [320-3530]	3.29	2.35	2.35	2.35	4.95	-	12.00 [3.4-14.2]	13.3	2960 [360-4290]	4.05	
20+20+20+50	1.82	1.82	1.82	4.54	-	10.00 [2.3-10.6]	13.1	2850 [380-3240]	3.51	2.18	2.18	2.18	5.46	-	12.00 [3.4-14.2]	13.1	2900 [420-4150]	4.14	
20+20+20+60	1.67	1.67	1.67	4.99	-	10.00 [2.3-10.6]	13.1	2850 [380-3240]	3.51	2.00	2.00	2.00	6.00	-	12.00 [3.4-14.2]	13.1	2900 [420-4150]	4.14	
20+20+20+71	1.53	1.53	1.53	5.41	-	10.00 [2.3-10.8]	13.1	2850 [390-3310]	3.51	1.83	1.83	1.83	6.51	-	12.00 [3.4-14.4]	13.0	2890 [420-4190]	4.15	
20+20+25+25	2.00	2.00	2.50	2.50	-	9.00 [2.3-10.6]	11.8	2580 [310-3600]	3.49	2.67	2.67	3.33	3.33	-	12.00 [3.4-14.2]	13.5	2990 [340-4350]	4.01	
20+20+25+35	2.00	2.00	2.50	3.50	-	10.00 [2.3-10.6]	13.9	3040 [320-3530]	3.29	2.40	2.40	3.00	4.20	-	12.00 [3.4-14.2]	13.4	2970 [350-4310]	4.04	
20+20+25+42	1.87	1.87	2.34	3.92	-	10.00 [2.3-10.6]	13.9	3040 [320-3530]	3.29	2.24	2.24	2.81	4.71						

CU-5Z100VBR: Free Multi Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
20+20+35+71	1.37	1.37	2.40	4.86	-	10.00 [2.3-11.0]	12.8	2780 [390-3390]	3.60	1.64	1.64	2.88	5.84	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18
20+20+42+42	1.61	1.61	3.39	3.39	-	10.00 [2.3-10.8]	13.7	2980 [340-3600]	3.36	1.94	1.94	4.06	4.06	-	12.00 [3.4-14.2]	13.1	2920 [370-4190]	4.11
20+20+42+50	1.52	1.52	3.18	3.78	-	10.00 [2.3-10.8]	13.1	2850 [390-3310]	3.51	1.82	1.82	3.82	4.54	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18
20+20+42+60	1.41	1.41	2.96	4.22	-	10.00 [2.3-11.0]	13.1	2850 [390-3460]	3.51	1.69	1.69	3.55	5.07	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18
20+20+42+71	1.31	1.31	2.75	4.63	-	10.00 [2.3-11.0]	12.8	2780 [390-3390]	3.60	1.57	1.57	3.29	5.57	-	12.00 [3.4-14.4]	12.9	2860 [440-4200]	4.20
20+20+50+50	1.43	1.43	3.57	3.57	-	10.00 [2.3-10.8]	12.5	2730 [440-3180]	3.66	1.71	1.71	4.29	4.29	-	12.00 [3.4-14.4]	13.0	2880 [510-4150]	4.17
20+20+50+60	1.33	1.33	3.34	4.00	-	10.00 [2.3-11.0]	12.5	2730 [440-3320]	3.66	1.60	1.60	4.00	4.80	-	12.00 [3.4-14.4]	13.0	2880 [510-4150]	4.17
20+20+50+71	1.24	1.24	3.14	4.41	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.49	1.49	3.73	5.29	-	12.00 [3.4-14.4]	12.9	2870 [520-4130]	4.18
20+20+60+60	1.25	1.25	3.75	3.75	-	10.00 [2.3-11.2]	12.5	2730 [440-3390]	3.66	1.50	1.50	4.50	4.50	-	12.00 [3.4-14.4]	13.0	2880 [510-4150]	4.17
20+20+60+71	1.17	1.17	3.51	4.15	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.40	1.40	4.22	4.98	-	12.00 [3.4-14.4]	12.9	2870 [520-4130]	4.18
20+20+71+71	1.10	1.10	3.90	3.90	-	10.00 [2.3-11.2]	12.6	2740 [480-3330]	3.65	1.32	1.32	4.68	4.68	-	12.00 [3.4-14.4]	12.9	2870 [530-4120]	4.18
20+25+25+25	2.00	2.50	2.50	2.50	-	9.50 [2.3-10.6]	12.9	2810 [310-3600]	3.38	2.52	3.16	3.16	3.16	-	12.00 [3.4-14.2]	13.5	2990 [340-4350]	4.01
20+25+25+35	1.91	2.38	2.38	3.33	-	10.00 [2.3-10.6]	13.9	3040 [320-3530]	3.29	2.29	2.86	2.86	3.99	-	12.00 [3.4-14.2]	13.4	2970 [350-4310]	4.04
20+25+25+42	1.79	2.23	2.23	3.75	-	10.00 [2.3-10.6]	13.9	3040 [320-3530]	3.29	2.14	2.68	2.68	4.50	-	12.00 [3.4-14.2]	13.3	2960 [360-4290]	4.05
20+25+25+50	1.67	2.08	2.08	4.17	-	10.00 [2.3-10.6]	13.1	2850 [380-3240]	3.51	2.00	2.50	2.50	5.00	-	12.00 [3.4-14.2]	13.1	2900 [420-4150]	4.14
20+25+25+60	1.54	1.92	1.92	4.62	-	10.00 [2.3-10.8]	13.1	2850 [380-3380]	3.51	1.85	2.31	2.31	5.53	-	12.00 [3.4-14.4]	13.1	2900 [420-4210]	4.14
20+25+25+71	1.42	1.77	1.77	5.04	-	10.00 [2.3-10.8]	13.1	2850 [390-3310]	3.51	1.70	2.13	2.13	6.04	-	12.00 [3.4-14.4]	13.0	2890 [420-4190]	4.15
20+25+35+35	1.75	2.17	3.04	3.04	-	10.00 [2.3-10.6]	13.7	2980 [320-3450]	3.36	2.09	2.61	3.65	3.65	-	12.00 [3.4-14.2]	13.2	2940 [370-4210]	4.08
20+25+35+42	1.64	2.05	2.87	3.44	-	10.00 [2.3-10.8]	13.7	2980 [320-3600]	3.36	1.97	2.46	3.44	4.13	-	12.00 [3.4-14.2]	13.2	2930 [370-4200]	4.10
20+25+35+50	1.54	1.92	2.69	3.85	-	10.00 [2.3-10.8]	13.1	2850 [390-3310]	3.51	1.85	2.31	3.23	4.61	-	12.00 [3.4-14.4]	13.0	2880 [420-4170]	4.17
20+25+35+60	1.43	1.79	2.50	4.28	-	10.00 [2.3-10.8]	13.1	2850 [390-3310]	3.51	1.72	2.14	3.00	5.14	-	12.00 [3.4-14.4]	13.0	2880 [420-4170]	4.17
20+25+35+71	1.32	1.66	2.32	4.70	-	10.00 [2.3-11.0]	12.8	2780 [390-3390]	3.60	1.59	1.99	2.78	5.64	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18
20+25+42+42	1.55	1.93	3.26	3.26	-	10.00 [2.3-10.8]	13.7	2980 [340-3600]	3.36	1.86	2.32	3.91	3.91	-	12.00 [3.4-14.4]	13.1	2920 [370-4310]	4.11
20+25+42+50	1.46	1.82	3.07	3.65	-	10.00 [2.3-10.8]	13.1	2850 [390-3310]	3.51	1.75	2.19	3.68	4.38	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18
20+25+42+60	1.36	1.70	2.86	4.08	-	10.00 [2.3-11.0]	13.1	2850 [390-3460]	3.51	1.63	2.04	3.43	4.90	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18
20+25+42+71	1.27	1.58	2.66	4.49	-	10.00 [2.3-11.2]	12.8	2780 [390-3530]	3.60	1.52	1.90	3.19	5.39	-	12.00 [3.4-14.4]	12.9	2860 [440-4200]	4.20
20+25+50+50	1.38	1.72	3.45	3.45	-	10.00 [2.3-11.0]	12.5	2730 [440-3320]	3.66	1.66	2.06	4.14	4.14	-	12.00 [3.4-14.4]	13.0	2880 [510-4150]	4.17
20+25+50+60	1.29	1.61	3.23	3.87	-	10.00 [2.3-11.0]	12.5	2730 [440-3320]	3.66	1.55	1.94	3.87	4.64	-	12.00 [3.4-14.4]	13.0	2880 [510-4150]	4.17
20+25+50+71	1.20	1.51	3.01	4.28	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.45	1.81	3.61	5.13	-	12.00 [3.4-14.4]	12.9	2870 [520-4130]	4.18
20+25+60+60	1.21	1.51	3.64	3.64	-	10.00 [2.3-11.2]	12.5	2730 [440-3390]	3.66	1.46	1.82	4.36	4.36	-	12.00 [3.4-14.4]	13.0	2880 [510-4150]	4.17
20+25+60+71	1.14	1.42	3.41	4.03	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.37	1.70	4.09	4.84	-	12.00 [3.4-14.4]	12.9	2870 [520-4130]	4.18
20+35+35+35	1.60	2.80	2.80	2.80	-	10.00 [2.3-10.8]	13.7	2980 [350-3530]	3.36	1.92	3.36	3.36	3.36	-	12.00 [3.4-14.2]	13.1	2920 [370-4180]	4.11
20+35+35+42	1.52	2.65	2.65	3.18	-	10.00 [2.3-10.8]	13.7	2980 [350-3530]	3.36	1.82	3.18	3.18	3.82	-	12.00 [3.4-14.4]	13.3	2950 [370-4280]	4.07
20+35+35+50	1.43	2.50	2.50	3.57	-	10.00 [2.3-10.8]	12.8	2780 [390-3310]	3.60	1.71	3.00	3.00	4.29	-	12.00 [3.4-14.4]	12.9	2860 [450-4200]	4.20
20+35+35+60	1.34	2.33	2.33	4.00	-	10.00 [2.3-11.0]	12.8	2780 [390-3460]	3.60	1.60	2.80	2.80	4.80	-	12.00 [3.4-14.4]	12.9	2860 [450-4200]	4.20
20+35+35+71	1.25	2.17	2.17	4.41	-	10.00 [2.3-11.2]	12.8	2790 [420-3530]	3.58	1.49	2.61	2.61	5.29	-	12.00 [3.4-14.4]	13.0	2890 [450-4180]	4.15
20+35+42+42	1.44	2.52	3.02	3.02	-	10.00 [2.3-10.8]	13.7	2980 [350-3530]	3.36	1.73	3.01	3.63	3.63	-	12.00 [3.4-14.4]	13.2	2940 [390-4270]	4.08
20+35+42+50	1.36	2.38	2.86	3.40	-	10.00 [2.3-11.0]	12.8	2780 [390-3390]	3.60	1.63	2.86	3.43	4.08	-	12.00 [3.4-14.4]	13.1	2900 [450-4190]	4.14
20+35+42+60	1.27	2.23	2.68	3.82	-	10.00 [2.3-11.0]	12.8	2780 [390-3390]	3.60	1.53	2.68	3.21	4.58	-	12.00 [3.4-14.4]	13.1	2900 [450-4190]	4.14
20+35+42+71	1.19	2.08	2.50	4.23	-	10.00 [2.3-11.2]	12.8	2790 [420-3540]	3.58	1.43	2.50	3.00	5.07	-	12.00 [3.4-14.4]	13.0	2890 [460-4170]	4.15
20+35+50+50	1.29	2.25	3.23	3.23	-	10.00 [2.3-11.0]	12.5	2730 [470-3250]	3.66	1.55	2.71	3.87	3.87	-	12.00 [3.4-14.4]	12.9	2870 [530-4120]	4.18
20+35+50+60	1.21	2.12	3.03	3.64	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.45	2.55	3.64	4.36	-	12.00 [3.4-14.4]	12.9	2870 [530-4120]	4.18
20+35+50+71	1.14	1.99	2.84	4.03	-	10.00 [2.3-11.2]	12.6	2740 [480-3400]	3.65	1.36	2.39	3.41	4.84	-	12.00 [3.4-14.4]	12.9	2860 [540-4110]	4.20
20+35+60+60	1.14	2.00	3.43	3.43	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.38	2.40	4.11	4.11	-	12.00 [3.4-14.4]	12.9	2870 [530-4120]	4.18
20+42+42+42	1.36	2.88	2.88	2.88	-	10.00 [2.3-11.0]	13.3	2910 [350-3600]	3.44	1.65	3.45	3.45	3.45	-	12.00 [3.4-14.4]	13.2	2940 [390-4260]	4.08
20+42+42+50	1.30	2.73	2.73	3.24	-	10.00 [2.3-11.0]	12.8	2780 [390-3390]	3.60	1.56	3.27	3.27	3.90	-	12.00 [3.4-14.4]	13.0	2890 [450-4180]	4.15
20+42+42+60	1.22	2.56	2.56	3.66	-	10.00 [2.3-11.2]	12.8	2780 [390-3530]	3.60	1.47	3.07	3.07	4.39	-	12.00 [3.4-14.4]	13.0	2890 [450-4180]	4.15
20+42+42+71	1.14	2.40	2.40	4.06	-	10.00 [2.3-11.2]	12.8	2790 [420-3460]	3.58	1.37	2.88	2.88	4.87	-	12.00 [3.4-14.4]	13.0	2880 [460-4160]	4.17
20+42+50+50	1.23	2.59	3.09	3.09	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.49	3.11	3.70	3.70	-	12.00 [3.4-14.4]	12.9	2860 [540-4110]	4.20
20+42+50+60	1.16	2.44	2.91	3.49	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.40	2.93	3.49	4.18	-	12.00 [3.4-14.4]	12.9	2860 [540-4110]	4.20
20+42+50+71	1.09	2.30	2.73	3.88	-	10.00 [2.3-11.2]	12.6	2740 [480-3330]	3.65	1.31	2.75	3.28	4.66	-	12.00 [3.4-14.4]	13.1	2900 [550-4100]	4.14
20+42+60+60	1.10	2.30	3.30	3.30	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.32	2.76	3.96	3.96	-	12.00 [3.4-14.4]	12.9	2860 [540-4110]	4.20
20+50+50+50	1.18	2.94	2.94	2.94	-	10.00 [2.3-11.2]	12.3	2690 [550-3340]	3.72	1.41	3.53	3.53	3.53	-	12.00 [3.4-14.4]	13.2	2930 [630-4110]	4.10
20+50+50+60	1.11	2.78	2.78	3.33	-	10.00 [2.3-11.2]	12.3	2690 [550-3340]	3.72	1.34	3.33	3.33	4.00	-	12.00 [3.4-14.4]	13.2	2930 [630-4110]	4.10
25+25+25+25	2.50	2.50	2.50	2.50	-	10.00 [2.3-10.6]	14.3	3110 [310-3600]	3.22	3.00	3.00	3.00	3.00	-	12.00 [3.4-14.2]	13.5	2990 [340-4350]	4.01
25+25+25+35	2.27	2.27	2.27	3.19	-	10.00 [2.3-10.6]	13.9	3040 [320-3530]	3.29	2.73	2.73	2.73	3.81					

CU-5Z100VBR: Free Multi Indoor Combination

Indoor Units Capacity	COOLING OPERATION										HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP	
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E					
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W	
25+25+35+60	1.72	1.72	2.42	4.14	-	10.00 [2.3-11.0]	13.1	2850 [390-3460]	3.51	2.07	2.07	2.90	4.96	-	12.00 [3.4-14.4]	13.0	2880 [420-4170]	4.17	
25+25+35+71	1.60	1.60	2.25	4.55	-	10.00 [2.3-11.0]	12.8	2780 [390-3390]	3.60	1.92	1.92	2.70	5.46	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18	
25+25+42+42	1.87	1.87	3.13	3.13	-	10.00 [2.3-10.8]	13.7	2980 [340-3600]	3.36	2.24	2.24	3.76	3.76	-	12.00 [3.4-14.4]	13.1	2920 [370-4310]	4.11	
25+25+42+50	1.76	1.76	2.96	3.52	-	10.00 [2.3-11.0]	13.1	2850 [390-3460]	3.51	2.11	2.11	3.55	4.23	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18	
25+25+42+60	1.64	1.64	2.77	3.95	-	10.00 [2.3-11.0]	13.1	2850 [390-3460]	3.51	1.97	1.97	3.32	4.74	-	12.00 [3.4-14.4]	12.9	2870 [430-4160]	4.18	
25+25+42+71	1.53	1.53	2.58	4.36	-	10.00 [2.3-11.2]	12.8	2780 [390-3530]	3.60	1.84	1.84	3.09	5.23	-	12.00 [3.4-14.4]	12.9	2860 [440-4200]	4.20	
25+25+50+50	1.67	1.67	3.33	3.33	-	10.00 [2.3-11.0]	12.5	2730 [440-3320]	3.66	2.00	2.00	4.00	4.00	-	12.00 [3.4-14.4]	13.0	2880 [510-4150]	4.17	
25+25+50+60	1.56	1.56	3.13	3.75	-	10.00 [2.3-11.2]	12.5	2730 [440-3390]	3.66	1.88	1.88	3.75	4.49	-	12.00 [3.4-14.4]	13.0	2880 [510-4150]	4.17	
25+25+50+71	1.46	1.46	2.93	4.15	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.75	1.75	3.52	4.98	-	12.00 [3.4-14.4]	12.9	2870 [520-4130]	4.18	
25+25+60+60	1.47	1.47	3.53	3.53	-	10.00 [2.3-11.2]	12.5	2730 [440-3390]	3.66	1.76	1.76	4.24	4.24	-	12.00 [3.4-14.4]	13.0	2880 [510-4150]	4.17	
25+25+60+71	1.38	1.38	3.32	3.92	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.66	1.66	3.98	4.70	-	12.00 [3.4-14.4]	12.9	2870 [520-4130]	4.18	
25+35+35+35	1.93	2.69	2.69	2.69	-	10.00 [2.3-10.8]	13.7	2980 [350-3530]	3.36	2.31	3.23	3.23	3.23	-	12.00 [3.4-14.4]	13.1	2920 [370-4300]	4.11	
25+35+35+42	1.83	2.55	2.55	3.07	-	10.00 [2.3-10.8]	13.7	2980 [350-3530]	3.36	2.19	3.07	3.07	3.67	-	12.00 [3.4-14.4]	13.3	2950 [370-4280]	4.07	
25+35+35+50	1.73	2.41	2.41	3.45	-	10.00 [2.3-11.0]	12.8	2780 [390-3460]	3.60	2.07	2.90	2.90	4.13	-	12.00 [3.4-14.4]	12.9	2860 [450-4200]	4.20	
25+35+35+60	1.61	2.26	2.26	3.87	-	10.00 [2.3-11.0]	12.8	2780 [390-3460]	3.60	1.94	2.71	2.71	4.64	-	12.00 [3.4-14.4]	12.9	2860 [450-4200]	4.20	
25+35+35+71	1.51	2.11	2.11	4.27	-	10.00 [2.3-11.2]	12.8	2790 [420-3530]	3.58	1.81	2.53	2.53	5.13	-	12.00 [3.4-14.4]	13.0	2890 [450-4180]	4.15	
25+35+42+42	1.74	2.42	2.92	2.92	-	10.00 [2.3-11.0]	13.7	2980 [350-3680]	3.36	2.08	2.92	3.50	3.50	-	12.00 [3.4-14.4]	13.2	2940 [390-4270]	4.08	
25+35+42+50	1.65	2.30	2.76	3.29	-	10.00 [2.3-11.0]	12.8	2780 [390-3390]	3.60	1.97	2.76	3.32	3.95	-	12.00 [3.4-14.4]	13.1	2900 [450-4190]	4.14	
25+35+42+60	1.55	2.16	2.59	3.70	-	10.00 [2.3-11.2]	12.8	2780 [390-3530]	3.60	1.86	2.59	3.11	4.44	-	12.00 [3.4-14.4]	13.1	2900 [450-4190]	4.14	
25+35+42+71	1.45	2.02	2.43	4.10	-	10.00 [2.3-11.2]	12.8	2790 [420-3540]	3.58	1.74	2.43	2.91	4.92	-	12.00 [3.4-14.4]	13.0	2890 [460-4170]	4.15	
25+35+50+50	1.56	2.18	3.13	3.13	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.88	2.62	3.75	3.75	-	12.00 [3.4-14.4]	12.9	2870 [530-4120]	4.18	
25+35+50+60	1.47	2.06	2.94	3.53	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.76	2.47	3.53	4.24	-	12.00 [3.4-14.4]	12.9	2870 [530-4120]	4.18	
25+35+50+71	1.39	1.93	2.76	3.92	-	10.00 [2.3-11.2]	12.6	2740 [480-3400]	3.65	1.66	2.32	3.31	4.71	-	12.00 [3.4-14.4]	12.9	2860 [540-4110]	4.20	
25+35+60+60	1.40	1.94	3.33	3.33	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.67	2.33	4.00	4.00	-	12.00 [3.4-14.4]	12.9	2870 [530-4120]	4.18	
25+42+42+42	1.66	2.78	2.78	2.78	-	10.00 [2.3-11.0]	13.3	2910 [350-3600]	3.44	1.98	3.34	3.34	3.34	-	12.00 [3.4-14.4]	13.2	2940 [390-4260]	4.08	
25+42+42+50	1.58	2.64	2.64	3.14	-	10.00 [2.3-11.2]	12.8	2780 [390-3530]	3.60	1.89	3.17	3.17	3.77	-	12.00 [3.4-14.4]	13.0	2890 [450-4180]	4.15	
25+42+42+60	1.48	2.49	2.49	3.54	-	10.00 [2.3-11.2]	12.8	2780 [390-3530]	3.60	1.78	2.98	2.98	4.26	-	12.00 [3.4-14.4]	13.0	2890 [450-4180]	4.15	
25+42+42+71	1.40	2.33	2.33	3.94	-	10.00 [2.3-11.2]	12.8	2790 [420-3460]	3.58	1.67	2.80	2.80	4.73	-	12.00 [3.4-14.4]	13.0	2880 [460-4160]	4.17	
25+42+50+50	1.51	2.51	2.99	2.99	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.80	3.02	3.59	3.59	-	12.00 [3.4-14.4]	12.9	2860 [540-4110]	4.20	
25+42+50+60	1.42	2.37	2.82	3.39	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	1.69	2.85	3.39	4.07	-	12.00 [3.4-14.4]	12.9	2860 [540-4110]	4.20	
25+50+50+50	1.42	2.86	2.86	2.86	-	10.00 [2.3-11.2]	12.3	2690 [550-3340]	3.72	1.71	3.43	3.43	3.43	-	12.00 [3.4-14.4]	13.2	2930 [630-4110]	4.10	
35+35+35+35	2.50	2.50	2.50	2.50	-	10.00 [2.3-10.8]	13.3	2910 [350-3450]	3.44	3.00	3.00	3.00	3.00	-	12.00 [3.4-14.4]	13.2	2940 [390-4260]	4.08	
35+35+35+42	2.38	2.38	2.38	2.86	-	10.00 [2.3-11.0]	13.3	2910 [350-3600]	3.44	2.86	2.86	2.86	3.42	-	12.00 [3.4-14.4]	13.2	2930 [390-4250]	4.10	
35+35+35+50	2.26	2.26	2.26	3.22	-	10.00 [2.3-11.0]	12.8	2780 [390-3390]	3.60	2.71	2.71	2.71	3.87	-	12.00 [3.4-14.4]	13.0	2890 [460-4170]	4.15	
35+35+35+60	2.12	2.12	2.12	3.64	-	10.00 [2.3-11.2]	12.8	2780 [390-3530]	3.60	2.55	2.55	2.55	4.35	-	12.00 [3.4-14.4]	13.0	2890 [460-4170]	4.15	
35+35+35+71	1.99	1.99	1.99	4.03	-	10.00 [2.3-11.2]	12.8	2790 [430-3460]	3.58	2.39	2.39	2.39	4.83	-	12.00 [3.4-14.4]	13.0	2880 [470-4150]	4.17	
35+35+42+42	2.27	2.27	2.73	2.73	-	10.00 [2.3-11.0]	13.3	2910 [350-3600]	3.44	2.73	2.73	3.27	3.27	-	12.00 [3.4-14.4]	13.1	2920 [400-4240]	4.11	
35+35+42+50	2.16	2.16	2.59	3.09	-	10.00 [2.3-11.2]	12.8	2790 [420-3530]	3.58	2.59	2.59	3.12	3.70	-	12.00 [3.4-14.4]	13.0	2880 [470-4160]	4.17	
35+35+42+60	2.03	2.03	2.45	3.49	-	10.00 [2.3-11.2]	12.8	2790 [420-3530]	3.58	2.44	2.44	2.93	4.19	-	12.00 [3.4-14.4]	13.0	2880 [470-4160]	4.17	
35+35+42+71	1.91	1.91	2.30	3.88	-	10.00 [2.3-11.2]	12.8	2790 [430-3460]	3.58	2.30	2.30	2.75	4.65	-	12.00 [3.4-14.4]	12.9	2870 [480-4140]	4.18	
35+35+50+50	2.06	2.06	2.94	2.94	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	2.47	2.47	3.53	3.53	-	12.00 [3.4-14.4]	13.0	2890 [550-4090]	4.15	
35+35+50+60	1.94	1.94	2.79	3.33	-	10.00 [2.3-11.2]	12.5	2730 [470-3400]	3.66	2.33	2.33	3.33	4.01	-	12.00 [3.4-14.4]	13.0	2890 [550-4090]	4.15	
35+42+42+42	2.17	2.61	2.61	2.61	-	10.00 [2.3-11.2]	13.3	2910 [350-3760]	3.44	2.61	3.13	3.13	3.13	-	12.00 [3.4-14.4]	13.1	2910 [400-4220]	4.12	
35+42+42+50	2.07	2.49	2.49	2.95	-	10.00 [2.3-11.2]	12.8	2790 [420-3540]	3.58	2.49	2.98	2.98	3.55	-	12.00 [3.4-14.4]	12.9	2870 [480-4140]	4.18	
35+42+42+60	1.96	2.35	2.35	3.34	-	10.00 [2.3-11.2]	12.8	2790 [420-3540]	3.58	2.35	2.82	2.82	4.01	-	12.00 [3.4-14.4]	12.9	2870 [480-4140]	4.18	
35+42+50+50	1.99	2.37	2.82	2.82	-	10.00 [2.3-11.2]	12.6	2740 [470-3400]	3.65	2.37	2.85	3.39	3.39	-	12.00 [3.4-14.4]	13.0	2890 [560-4080]	4.15	
42+42+42+42	2.50	2.50	2.50	2.50	-	10.00 [2.3-11.2]	13.3	2910 [350-3680]	3.44	3.00	3.00	3.00	3.00	-	12.00 [3.4-14.4]	13.1	2900 [400-4210]	4.14	
42+42+42+50	2.39	2.39	2.39	2.83	-	10.00 [2.3-11.2]	12.8	2790 [420-3460]	3.58	2.86	2.86	2.86	3.42	-	12.00 [3.4-14.4]	12.9	2860 [480-4130]	4.20	

CU-5Z100VBR: Free Multi Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Running Current	Power Input	COP	
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				Total
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
16+16+16+16+16	1.60	1.60	1.60	1.60	1.60	8.00 [2.3-11.5]	9.0	1990 [390-3810]	4.02	2.40	2.40	2.40	2.40	2.40	12.00 [3.4-14.5]	13.4	3050 [540-4320]	3.93
16+16+16+16+20	1.60	1.60	1.60	1.60	2.00	8.40 [2.3-11.5]	9.5	2100 [390-3810]	4.00	2.29	2.29	2.29	2.29	2.84	12.00 [3.4-14.5]	13.3	3040 [560-4310]	3.95
16+16+16+16+25	1.60	1.60	1.60	1.60	2.50	8.90 [2.3-11.5]	10.3	2270 [390-3810]	3.92	2.16	2.16	2.16	2.16	3.36	12.00 [3.4-14.5]	13.3	3040 [560-4310]	3.95
16+16+16+16+35	1.60	1.60	1.60	1.60	3.50	9.90 [2.3-11.5]	12.2	2690 [420-3740]	3.68	1.94	1.94	1.94	1.94	4.24	12.00 [3.4-14.5]	13.4	3070 [570-4270]	3.91
16+16+16+16+42	1.51	1.51	1.51	1.51	3.96	10.00 [2.3-11.5]	12.5	2750 [430-3740]	3.64	1.81	1.81	1.81	1.81	4.76	12.00 [3.4-14.5]	13.4	3060 [580-4320]	3.92
16+16+16+16+50	1.40	1.40	1.40	1.40	4.40	10.00 [2.3-11.5]	12.3	2700 [480-3600]	3.70	1.68	1.68	1.68	1.68	5.28	12.00 [3.4-14.5]	13.5	3080 [680-4250]	3.90
16+16+16+16+60	1.29	1.29	1.29	1.29	4.84	10.00 [2.3-11.5]	12.3	2700 [480-3600]	3.70	1.55	1.55	1.55	1.55	5.80	12.00 [3.4-14.5]	13.5	3080 [680-4250]	3.90
16+16+16+16+71	1.19	1.19	1.19	1.19	5.24	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.42	1.42	1.42	1.42	6.32	12.00 [3.4-14.5]	13.4	3070 [700-4240]	3.91
16+16+16+20+20	1.60	1.60	1.60	2.00	2.00	8.80 [2.3-11.5]	10.3	2270 [420-3730]	3.88	2.18	2.18	2.18	2.73	2.73	12.00 [3.4-14.5]	13.3	3040 [560-4290]	3.95
16+16+16+20+25	1.60	1.60	1.60	2.00	2.50	9.30 [2.3-11.5]	11.1	2440 [420-3730]	3.81	2.06	2.06	2.06	2.59	3.23	12.00 [3.4-14.5]	13.3	3040 [560-4290]	3.95
16+16+16+20+35	1.55	1.55	1.55	1.95	3.40	10.00 [2.3-11.5]	12.5	2750 [430-3740]	3.64	1.86	1.86	1.86	2.34	4.08	12.00 [3.4-14.5]	13.4	3060 [580-4320]	3.92
16+16+16+20+42	1.45	1.45	1.45	1.83	3.82	10.00 [2.3-11.5]	12.5	2750 [430-3740]	3.64	1.75	1.75	1.75	2.18	4.57	12.00 [3.4-14.5]	13.4	3050 [600-4310]	3.93
16+16+16+20+50	1.36	1.36	1.36	1.69	4.23	10.00 [2.3-11.5]	12.3	2710 [510-3600]	3.69	1.63	1.63	1.63	2.03	5.08	12.00 [3.4-14.5]	13.4	3070 [700-4240]	3.91
16+16+16+20+60	1.25	1.25	1.25	1.56	4.69	10.00 [2.3-11.5]	12.3	2710 [510-3600]	3.69	1.50	1.50	1.50	1.88	5.62	12.00 [3.4-14.5]	13.4	3070 [700-4240]	3.91
16+16+16+20+71	1.15	1.15	1.15	1.44	5.11	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.38	1.38	1.38	1.73	6.13	12.00 [3.4-14.5]	13.4	3060 [710-4230]	3.92
16+16+16+25+25	1.60	1.60	1.60	2.50	2.50	9.80 [2.3-11.5]	12.2	2690 [420-3730]	3.64	1.96	1.96	1.96	3.06	3.06	12.00 [3.4-14.5]	13.3	3040 [560-4290]	3.95
16+16+16+25+35	1.48	1.48	1.48	2.32	3.24	10.00 [2.3-11.5]	12.5	2750 [430-3740]	3.64	1.78	1.78	1.78	2.78	3.88	12.00 [3.4-14.5]	13.4	3060 [580-4320]	3.92
16+16+16+25+42	1.39	1.39	1.39	2.18	3.65	10.00 [2.3-11.5]	12.5	2750 [430-3740]	3.64	1.67	1.67	1.67	2.61	4.38	12.00 [3.4-14.5]	13.4	3050 [600-4310]	3.93
16+16+16+25+50	1.30	1.30	1.30	2.03	4.07	10.00 [2.3-11.5]	12.3	2710 [510-3600]	3.69	1.56	1.56	1.56	2.44	4.88	12.00 [3.4-14.5]	13.4	3070 [700-4240]	3.91
16+16+16+25+60	1.20	1.20	1.20	1.89	4.51	10.00 [2.3-11.5]	12.3	2710 [510-3600]	3.69	1.44	1.44	1.44	2.27	5.41	12.00 [3.4-14.5]	13.4	3070 [700-4240]	3.91
16+16+16+25+71	1.11	1.11	1.11	1.74	4.93	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.33	1.33	1.33	2.09	5.92	12.00 [3.4-14.5]	13.4	3060 [710-4230]	3.92
16+16+16+35+35	1.36	1.36	1.36	2.96	2.96	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	1.62	1.62	1.62	3.57	3.57	12.00 [3.4-14.5]	13.3	3040 [600-4290]	3.95
16+16+16+35+42	1.28	1.28	1.28	2.80	3.36	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	1.54	1.54	1.54	3.36	4.02	12.00 [3.4-14.5]	13.3	3040 [610-4280]	3.95
16+16+16+35+50	1.20	1.20	1.20	2.64	3.76	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.44	1.44	1.44	3.17	4.51	12.00 [3.4-14.5]	13.4	3060 [720-4270]	3.92
16+16+16+35+60	1.12	1.12	1.12	2.45	4.19	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.34	1.34	1.34	2.95	5.03	12.00 [3.4-14.5]	13.4	3060 [720-4270]	3.92
16+16+16+35+71	1.04	1.04	1.04	2.27	4.61	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.25	1.25	1.25	2.73	5.52	12.00 [3.4-14.5]	13.5	3090 [740-4260]	3.88
16+16+16+42+42	1.22	1.22	1.22	3.17	3.17	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	1.46	1.46	1.46	3.81	3.81	12.00 [3.4-14.5]	13.3	3030 [630-4270]	3.96
16+16+16+42+50	1.14	1.14	1.14	3.01	3.57	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.37	1.37	1.37	3.60	4.29	12.00 [3.4-14.5]	13.4	3050 [740-4260]	3.93
16+16+16+42+60	1.07	1.07	1.07	2.80	3.99	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.28	1.28	1.28	3.36	4.80	12.00 [3.4-14.5]	13.4	3050 [740-4260]	3.93
16+16+16+42+71	0.99	0.99	0.99	2.62	4.41	10.00 [2.3-11.5]	12.0	2650 [520-3540]	3.77	1.19	1.19	1.19	3.14	5.29	12.00 [3.4-14.5]	13.5	3090 [750-4250]	3.88
16+16+16+50+50	1.08	1.08	1.08	3.38	3.38	10.00 [2.3-11.5]	12.1	2670 [600-3480]	3.75	1.30	1.30	1.30	4.05	4.05	12.00 [3.4-14.5]	13.7	3130 [860-4280]	3.83
16+16+16+50+60	1.01	1.01	1.01	3.17	3.80	10.00 [2.3-11.5]	12.1	2680 [600-3480]	3.75	1.22	1.22	1.22	3.79	4.55	12.00 [3.4-14.5]	13.7	3130 [860-4280]	3.83
16+16+16+50+71	0.95	0.95	0.95	2.96	4.19	10.00 [2.3-11.5]	12.2	2680 [610-3490]	3.73	1.14	1.14	1.14	3.55	5.03	12.00 [3.4-14.5]	13.7	3130 [890-4260]	3.83
16+16+16+60+60	0.96	0.96	0.96	3.56	3.56	10.00 [2.3-11.5]	12.1	2670 [600-3480]	3.75	1.14	1.14	1.14	4.29	4.29	12.00 [3.4-14.5]	13.7	3130 [860-4280]	3.83
16+16+16+60+71	0.89	0.89	0.89	3.36	3.97	10.00 [2.3-11.5]	12.2	2680 [610-3490]	3.73	1.07	1.07	1.07	4.03	4.76	12.00 [3.4-14.5]	13.7	3130 [890-4260]	3.83
16+16+20+20+20	1.60	1.60	2.00	2.00	2.00	9.20 [2.3-11.5]	10.9	2390 [420-3740]	3.85	2.10	2.10	2.60	2.60	2.60	12.00 [3.4-14.5]	13.4	3070 [570-4280]	3.91
16+16+20+20+25	1.60	1.60	2.00	2.00	2.50	9.70 [2.3-11.5]	12.0	2630 [420-3740]	3.69	1.98	1.98	2.47	2.47	3.10	12.00 [3.4-14.5]	13.4	3070 [570-4280]	3.91
16+16+20+20+35	1.50	1.50	1.87	1.87	3.26	10.00 [2.3-11.5]	12.5	2750 [430-3740]	3.64	1.79	1.79	2.24	2.24	3.94	12.00 [3.4-14.5]	13.4	3050 [600-4310]	3.93
16+16+20+20+42	1.41	1.41	1.75	1.75	3.68	10.00 [2.3-11.5]	12.5	2750 [430-3660]	3.64	1.68	1.68	2.11	2.11	4.42	12.00 [3.4-14.5]	13.4	3050 [600-4300]	3.93
16+16+20+20+50	1.31	1.31	1.64	1.64	4.10	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.57	1.57	1.97	1.97	4.92	12.00 [3.4-14.5]	13.4	3070 [710-4230]	3.91
16+16+20+20+60	1.21	1.21	1.52	1.52	4.54	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.45	1.45	1.82	1.82	5.66	12.00 [3.4-14.5]	13.4	3070 [710-4230]	3.91
16+16+20+20+71	1.12	1.12	1.40	1.40	4.96	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.34	1.34	1.68	1.68	5.96	12.00 [3.4-14.5]	13.4	3060 [720-4220]	3.92
16+16+20+25+25	1.57	1.57	1.96	2.45	2.45	10.00 [2.3-11.5]	12.5	2750 [420-3740]	3.64	1.88	1.88	2.36	2.94	2.94	12.00 [3.4-14.5]	13.4	3070 [570-4280]	3.91
16+16+20+25+35	1.43	1.43	1.79	2.23	3.12	10.00 [2.3-11.5]	12.5	2750 [430-3740]	3.64	1.71	1.71	2.15	2.68	3.75	12.00 [3.4-14.5]	13.4	3050 [600-4310]	3.93
16+16+20+25+42	1.34	1.34	1.69	2.10	3.53	10.00 [2.3-11.5]	12.5	2750 [430-3660]	3.64	1.61	1.61	2.02	2.52	4.24	12.00 [3.4-14.5]	13.4	3050 [600-4300]	3.93
16+16+20+25+50	1.26	1.26	1.57	1.97	3.94	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.51	1.51	1.90	2.36	4.72	12.00 [3.4-14.5]	13.4	3070 [710-4230]	3.91
16+16+20+25+60	1.17	1.17	1.46	1.82	4.38	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.40	1.40	1.75	2.19	5.26	12.00 [3.4-14.5]	13.4	3070 [710-4230]	3.91
16+16+20+25+71	1.08	1.08	1.35	1.69	4.80	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.30	1.30	1.62	2.03	5.75	12.00 [3.4-14.5]	13.4	3060 [720-4220]	3.92
16+16+20+35+35	1.31	1.31	1.64	2.87	2.87	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	1.57	1.57	1.98	3.44	3.44	12.00 [3.4-14.5]	13.3	3040 [610-4280]	3.95
16+16+20+35+42	1.24	1.24	1.55	2.71	3.26	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	1.49	1.49	1.86	3.26	3.90	12.00 [3.4-14.5]	13.3	3030 [630-4270]	3.96
16+16+20+35+50	1.17	1.17	1.46	2.55	3.65	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.40	1.40	1.75	3.07	4.38	12.00 [3.4-14.5]	13.4	3050 [740-4260]	3.93
16+16+20+35+60	1.09	1.09	1.36	2.38	4.08	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.31	1.31	1.63	2.86	4.89	12.00 [3.4-14.5]	13.4	3050 [740-4260]	3.93
16+16+20+35+71	1.01	1.01	1.27	2.22	4.49	10.00 [2.3-11.5]	12.0	2650 [520-3540]	3.77	1.22	1.22	1.52	2.66	5.38	12.00 [3.4-14.5]	13.5	3090 [750-4250]	3.88

CU-5Z100VBR: Free Multi Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
16+16+25+25+35	1.37	1.37	2.14	2.14	2.98	10.00 [2.3-11.5]	12.5	2750 [430-3740]	3.64	1.64	1.64	2.56	2.56	3.60	12.00 [3.4-14.5]	13.4	3050 [600-4310]	3.93
16+16+25+25+42	1.29	1.29	2.02	2.02	3.38	10.00 [2.3-11.5]	12.5	2750 [430-3660]	3.64	1.55	1.55	2.42	2.42	4.06	12.00 [3.4-14.5]	13.4	3050 [600-4300]	3.93
16+16+25+25+50	1.21	1.21	1.89	1.89	3.80	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.45	1.45	2.27	2.27	4.56	12.00 [3.4-14.5]	13.4	3070 [710-4230]	3.91
16+16+25+25+60	1.13	1.13	1.76	1.76	4.22	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.35	1.35	2.11	2.11	5.08	12.00 [3.4-14.5]	13.4	3070 [710-4230]	3.91
16+16+25+25+71	1.05	1.05	1.63	1.63	4.64	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.25	1.25	1.96	1.96	5.58	12.00 [3.4-14.5]	13.4	3060 [720-4220]	3.92
16+16+25+35+35	1.26	1.26	1.96	2.76	2.76	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	1.51	1.51	2.36	3.31	3.31	12.00 [3.4-14.5]	13.3	3040 [610-4280]	3.95
16+16+25+35+42	1.19	1.19	1.88	2.61	3.13	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	1.43	1.43	2.25	3.13	3.76	12.00 [3.4-14.5]	13.3	3030 [630-4270]	3.96
16+16+25+35+50	1.13	1.13	1.76	2.46	3.52	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.35	1.35	2.11	2.96	4.23	12.00 [3.4-14.5]	13.4	3050 [740-4260]	3.93
16+16+25+35+60	1.05	1.05	1.65	2.30	3.95	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.26	1.26	1.98	2.76	4.74	12.00 [3.4-14.5]	13.4	3050 [740-4260]	3.93
16+16+25+35+71	0.98	0.98	1.53	2.15	4.36	10.00 [2.3-11.5]	12.0	2650 [520-3540]	3.77	1.18	1.18	1.84	2.58	5.22	12.00 [3.4-14.5]	13.5	3090 [750-4250]	3.88
16+16+25+42+42	1.13	1.13	1.78	2.98	2.98	10.00 [2.3-11.5]	12.2	2690 [440-3670]	3.72	1.36	1.36	2.14	3.57	3.57	12.00 [3.4-14.5]	13.4	3070 [640-4260]	3.91
16+16+25+42+50	1.07	1.07	1.68	2.82	3.36	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.29	1.29	2.01	3.38	4.03	12.00 [3.4-14.5]	13.5	3090 [750-4250]	3.88
16+16+25+42+60	1.01	1.01	1.57	2.64	3.77	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.21	1.21	1.89	3.17	4.52	12.00 [3.4-14.5]	13.5	3090 [750-4250]	3.88
16+16+25+42+71	0.94	0.94	1.47	2.47	4.18	10.00 [2.3-11.5]	12.1	2660 [550-3540]	3.76	1.13	1.13	1.77	2.96	5.01	12.00 [3.4-14.5]	13.5	3080 [760-4240]	3.90
16+16+25+50+50	1.02	1.02	1.60	3.18	3.18	10.00 [2.3-11.5]	12.1	2670 [610-3480]	3.75	1.22	1.22	1.92	3.82	3.82	12.00 [3.4-14.5]	13.7	3130 [870-4270]	3.83
16+16+25+50+60	0.96	0.96	1.50	2.99	3.59	10.00 [2.3-11.5]	12.1	2670 [610-3480]	3.75	1.15	1.15	1.80	3.59	4.31	12.00 [3.4-14.5]	13.7	3130 [870-4270]	3.83
16+16+25+50+71	0.90	0.90	1.40	2.81	3.99	10.00 [2.3-11.5]	12.2	2680 [620-3490]	3.73	1.08	1.08	1.69	3.37	4.78	12.00 [3.4-14.5]	13.9	3170 [900-4310]	3.79
16+16+25+60+60	0.90	0.90	1.42	3.39	3.39	10.00 [2.3-11.5]	12.1	2670 [610-3480]	3.75	1.08	1.08	1.70	4.07	4.07	12.00 [3.4-14.5]	13.7	3130 [870-4270]	3.83
16+16+35+35+35	1.16	1.16	2.56	2.56	2.56	10.00 [2.3-11.5]	12.3	2700 [460-3670]	3.70	1.41	1.41	3.06	3.06	3.06	12.00 [3.4-14.5]	13.4	3060 [640-4250]	3.92
16+16+35+35+42	1.11	1.11	2.43	2.43	2.92	10.00 [2.3-11.5]	12.3	2700 [470-3670]	3.70	1.33	1.33	2.92	2.92	3.50	12.00 [3.4-14.5]	13.4	3060 [650-4240]	3.92
16+16+35+35+50	1.05	1.05	2.30	2.30	3.30	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.26	1.26	2.76	2.76	3.96	12.00 [3.4-14.5]	13.5	3080 [760-4240]	3.90
16+16+35+35+60	0.99	0.99	2.16	2.16	3.70	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.19	1.19	2.59	2.59	4.44	12.00 [3.4-14.5]	13.5	3080 [760-4240]	3.90
16+16+35+35+71	0.93	0.93	2.02	2.02	4.10	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.11	1.11	2.43	2.43	4.92	12.00 [3.4-14.5]	13.5	3080 [780-4230]	3.90
16+16+35+42+42	1.06	1.06	2.32	2.78	2.78	10.00 [2.3-11.5]	12.3	2700 [470-3590]	3.70	1.27	1.27	2.78	3.34	3.34	12.00 [3.4-14.5]	13.4	3050 [650-4280]	3.93
16+16+35+42+50	1.01	1.01	2.20	2.64	3.14	10.00 [2.3-11.5]	12.0	2650 [520-3540]	3.77	1.21	1.21	2.64	3.17	3.77	12.00 [3.4-14.5]	13.5	3080 [780-4230]	3.90
16+16+35+42+60	0.95	0.95	2.07	2.49	3.54	10.00 [2.3-11.5]	12.0	2650 [520-3540]	3.77	1.14	1.14	2.49	2.98	4.25	12.00 [3.4-14.5]	13.5	3080 [780-4230]	3.90
16+16+35+42+71	0.89	0.89	1.95	2.33	3.94	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.07	1.07	2.33	2.80	4.73	12.00 [3.4-14.5]	13.6	3110 [790-4270]	3.86
16+16+35+50+50	0.96	0.96	2.10	2.99	2.99	10.00 [2.3-11.5]	12.2	2680 [620-3490]	3.73	1.15	1.15	2.52	3.59	3.59	12.00 [3.4-14.5]	13.8	3160 [910-4300]	3.80
16+16+35+50+60	0.90	0.90	1.99	2.82	3.39	10.00 [2.3-11.5]	12.2	2680 [620-3490]	3.73	1.08	1.08	2.38	3.39	4.07	12.00 [3.4-14.5]	13.8	3160 [910-4300]	3.80
16+16+42+42+42	1.01	1.01	2.66	2.66	2.66	10.00 [2.3-11.5]	12.3	2700 [470-3590]	3.70	1.23	1.23	3.18	3.18	3.18	12.00 [3.4-14.5]	13.3	3040 [670-4270]	3.95
16+16+42+42+50	0.96	0.96	2.53	2.53	3.02	10.00 [2.3-11.5]	12.1	2660 [550-3540]	3.76	1.16	1.16	3.04	3.04	3.60	12.00 [3.4-14.5]	13.7	3120 [790-4280]	3.85
16+16+42+42+60	0.91	0.91	2.39	2.39	3.40	10.00 [2.3-11.5]	12.1	2660 [550-3540]	3.76	1.09	1.09	2.86	2.86	4.10	12.00 [3.4-14.5]	13.7	3120 [790-4280]	3.85
16+16+42+50+50	0.92	0.92	2.42	2.87	2.87	10.00 [2.3-11.5]	12.2	2680 [620-3490]	3.73	1.10	1.10	2.90	3.45	4.45	12.00 [3.4-14.5]	13.8	3160 [930-4290]	3.80
16+16+50+50+50	0.89	0.89	2.74	2.74	2.74	10.00 [2.3-11.5]	12.6	2780 [720-3520]	3.60	1.05	1.05	3.30	3.30	3.30	12.00 [3.4-14.5]	14.4	3300 [1080-4380]	3.64
16+20+20+20+20	1.60	2.00	2.00	2.00	2.00	9.60 [2.3-11.5]	11.7	2570 [420-3740]	3.74	2.00	2.50	2.50	2.50	2.50	12.00 [3.4-14.5]	13.4	3070 [570-4330]	3.91
16+20+20+20+25	1.58	1.98	1.98	1.98	2.48	10.00 [2.3-11.5]	12.5	2750 [420-3740]	3.64	1.90	2.38	2.38	2.38	2.96	12.00 [3.4-14.5]	13.4	3070 [570-4330]	3.91
16+20+20+20+35	1.45	1.80	1.80	1.80	3.15	10.00 [2.3-11.5]	12.5	2750 [430-3660]	3.64	1.74	2.16	2.16	2.16	3.78	12.00 [3.4-14.5]	13.4	3050 [600-4300]	3.93
16+20+20+20+42	1.37	1.69	1.69	1.69	3.56	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	1.64	2.03	2.03	2.03	4.27	12.00 [3.4-14.5]	13.3	3040 [610-4290]	3.95
16+20+20+20+50	1.27	1.59	1.59	1.59	3.96	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.53	1.90	1.90	1.90	4.77	12.00 [3.4-14.5]	13.4	3060 [720-4220]	3.92
16+20+20+20+60	1.18	1.47	1.47	1.47	4.41	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.42	1.76	1.76	1.76	5.30	12.00 [3.4-14.5]	13.4	3060 [720-4220]	3.92
16+20+20+20+71	1.09	1.36	1.36	1.36	4.83	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.31	1.63	1.63	1.63	5.80	12.00 [3.4-14.5]	13.4	3050 [730-4270]	3.93
16+20+20+25+25	1.50	1.89	1.89	2.36	2.36	10.00 [2.3-11.5]	12.5	2750 [420-3740]	3.64	1.82	2.26	2.26	2.83	2.83	12.00 [3.4-14.5]	13.4	3070 [570-4330]	3.91
16+20+20+25+35	1.38	1.72	1.72	2.16	3.02	10.00 [2.3-11.5]	12.5	2750 [430-3660]	3.64	1.66	2.07	2.07	2.59	3.61	12.00 [3.4-14.5]	13.4	3050 [600-4300]	3.93
16+20+20+25+42	1.30	1.63	1.63	2.03	3.41	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	1.56	1.95	1.95	2.44	4.10	12.00 [3.4-14.5]	13.3	3040 [610-4290]	3.95
16+20+20+25+50	1.22	1.53	1.53	1.91	3.81	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.47	1.83	1.83	2.29	4.58	12.00 [3.4-14.5]	13.4	3060 [720-4220]	3.92
16+20+20+25+60	1.13	1.42	1.42	1.77	4.26	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.36	1.70	1.70	2.13	5.11	12.00 [3.4-14.5]	13.4	3060 [720-4220]	3.92
16+20+20+25+71	1.05	1.32	1.32	1.64	4.67	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.26	1.58	1.58	1.97	5.61	12.00 [3.4-14.5]	13.4	3050 [730-4270]	3.93
16+20+20+35+35	1.26	1.59	1.59	2.78	2.78	10.00 [2.3-11.5]	12.2	2690 [440-3660]	3.72	1.52	1.90	1.90	3.34	3.34	12.00 [3.4-14.5]	13.3	3030 [630-4270]	3.96
16+20+20+35+42	1.21	1.50	1.50	2.63	3.16	10.00 [2.3-11.5]	12.2	2690 [440-3670]	3.72	1.45	1.80	1.80	3.16	3.79	12.00 [3.4-14.5]	13.4	3070 [640-4260]	3.91
16+20+20+35+50	1.13	1.42	1.42	2.48	3.55	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.36	1.70	1.70	2.98	4.26	12.00 [3.4-14.5]	13.5	3090 [750-4250]	3.88
16+20+20+35+60	1.07	1.32	1.32	2.32	3.97	10.00 [2.3-11.5]	12.3	2710 [520-3530]	3.69	1.27	1.59	1.59	2.78	4.77	12.00 [3.4-14.5]	13.5	3090 [750-4250]	3.88
16+20+20+35+71	1.00	1.23	1.23	2.16	4.38	10.00 [2.3-11.5]	12.1	2660 [550-3540]	3.76	1.19	1.48	1.48	2.59	5.26	12.00 [3.4-14.5]	13.5	3080 [760-4240]	3.90
16+20+20+42+42	1.14	1.43	1.43	3.00	3.00	10.00 [2.3-11.5]	12.3	2700 [460-3670]	3.70	1.38	1.71	1.71	3.60	3.60	12.00 [3.4-14.5]	13.4	3060 [640-4250]	

CU-5Z100VBR: Free Multi Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
16+20+25+25+50	1.18	1.47	1.84	1.84	3.67	10.00 (2.3-11.5)	12.3	2710 (510-3530)	3.69	1.41	1.76	2.21	2.21	4.41	12.00 (3.4-14.5)	13.4	3060 (720-4220)	3.92
16+20+25+25+60	1.10	1.37	1.71	1.71	4.11	10.00 (2.3-11.5)	12.3	2710 (510-3530)	3.69	1.33	1.64	2.05	2.05	4.93	12.00 (3.4-14.5)	13.4	3060 (720-4220)	3.92
16+20+25+25+71	1.03	1.27	1.59	1.59	4.52	10.00 (2.3-11.5)	12.0	2650 (520-3530)	3.77	1.22	1.53	1.91	1.91	5.43	12.00 (3.4-14.5)	13.4	3050 (730-4270)	3.93
16+20+25+35+35	1.22	1.53	1.91	2.67	2.67	10.00 (2.3-11.5)	12.2	2690 (440-3660)	3.72	1.47	1.83	2.28	3.21	3.21	12.00 (3.4-14.5)	13.3	3030 (630-4270)	3.96
16+20+25+35+42	1.16	1.45	1.81	2.54	3.04	10.00 (2.3-11.5)	12.2	2690 (440-3670)	3.72	1.40	1.74	2.17	3.04	3.65	12.00 (3.4-14.5)	13.4	3070 (640-4260)	3.91
16+20+25+35+50	1.10	1.37	1.71	2.40	3.42	10.00 (2.3-11.5)	12.3	2710 (520-3530)	3.69	1.32	1.64	2.05	2.88	4.11	12.00 (3.4-14.5)	13.5	3090 (750-4250)	3.88
16+20+25+35+60	1.03	1.28	1.60	2.24	3.85	10.00 (2.3-11.5)	12.3	2710 (520-3530)	3.69	1.23	1.54	1.92	2.69	4.62	12.00 (3.4-14.5)	13.5	3090 (750-4250)	3.88
16+20+25+35+71	0.96	1.20	1.50	2.10	4.24	10.00 (2.3-11.5)	12.1	2660 (550-3540)	3.76	1.15	1.44	1.80	2.51	5.10	12.00 (3.4-14.5)	13.5	3080 (760-4240)	3.90
16+20+25+42+42	1.10	1.38	1.72	2.90	2.90	10.00 (2.3-11.5)	12.3	2700 (460-3670)	3.70	1.32	1.66	2.06	3.48	3.48	12.00 (3.4-14.5)	13.4	3060 (640-4250)	3.92
16+20+25+42+50	1.05	1.31	1.63	2.75	3.26	10.00 (2.3-11.5)	12.0	2650 (520-3530)	3.77	1.26	1.57	1.96	3.29	3.92	12.00 (3.4-14.5)	13.5	3090 (760-4250)	3.88
16+20+25+42+60	0.98	1.23	1.53	2.58	3.68	10.00 (2.3-11.5)	12.0	2650 (520-3530)	3.77	1.18	1.47	1.84	3.09	4.42	12.00 (3.4-14.5)	13.5	3090 (760-4250)	3.88
16+20+25+42+71	0.92	1.15	1.44	2.41	4.08	10.00 (2.3-11.5)	12.1	2660 (560-3540)	3.76	1.10	1.38	1.72	2.90	4.90	12.00 (3.4-14.5)	13.5	3080 (780-4230)	3.90
16+20+25+50+50	0.99	1.24	1.55	3.11	3.11	10.00 (2.3-11.5)	12.2	2680 (610-3480)	3.73	1.19	1.49	1.86	3.73	3.73	12.00 (3.4-14.5)	13.9	3170 (890-4260)	3.79
16+20+25+50+60	0.94	1.17	1.46	2.92	3.51	10.00 (2.3-11.5)	12.2	2680 (610-3480)	3.73	1.13	1.40	1.75	3.51	4.21	12.00 (3.4-14.5)	13.9	3170 (890-4260)	3.79
16+20+25+50+71	0.88	1.10	1.37	2.75	3.90	10.00 (2.3-11.5)	12.2	2680 (650-3490)	3.73	1.05	1.32	1.65	3.30	4.68	12.00 (3.4-14.5)	13.8	3160 (900-4300)	3.80
16+20+25+60+60	0.88	1.10	1.38	3.32	3.32	10.00 (2.3-11.5)	12.2	2680 (610-3480)	3.73	1.06	1.33	1.65	3.98	3.98	12.00 (3.4-14.5)	13.9	3170 (890-4260)	3.79
16+20+35+35+35	1.14	1.42	2.48	2.48	2.48	10.00 (2.3-11.5)	12.3	2700 (470-3590)	3.70	1.36	1.70	2.98	2.98	2.98	12.00 (3.4-14.5)	13.4	3060 (650-4240)	3.92
16+20+35+35+42	1.09	1.35	2.36	2.36	2.84	10.00 (2.3-11.5)	12.3	2700 (470-3590)	3.70	1.30	1.62	2.84	2.84	3.40	12.00 (3.4-14.5)	13.4	3050 (650-4280)	3.93
16+20+35+35+50	1.03	1.28	2.24	2.24	3.21	10.00 (2.3-11.5)	12.1	2660 (550-3540)	3.76	1.23	1.54	2.69	2.69	3.85	12.00 (3.4-14.5)	13.5	3080 (780-4230)	3.90
16+20+35+35+60	0.97	1.20	2.11	2.11	3.61	10.00 (2.3-11.5)	12.1	2660 (550-3540)	3.76	1.16	1.45	2.53	2.53	4.33	12.00 (3.4-14.5)	13.5	3080 (780-4230)	3.90
16+20+35+35+71	0.90	1.13	1.98	1.98	4.01	10.00 (2.3-11.5)	12.1	2660 (560-3540)	3.76	1.09	1.36	2.37	2.37	4.81	12.00 (3.4-14.5)	13.6	3110 (790-4270)	3.86
16+20+35+42+42	1.03	1.29	2.26	2.71	2.71	10.00 (2.3-11.5)	12.3	2700 (470-3590)	3.70	1.24	1.55	2.71	3.25	3.25	12.00 (3.4-14.5)	13.3	3040 (670-4270)	3.95
16+20+35+42+50	0.98	1.23	2.15	2.58	3.06	10.00 (2.3-11.5)	12.1	2660 (550-3540)	3.76	1.18	1.47	2.58	3.09	3.68	12.00 (3.4-14.5)	13.7	3120 (790-4280)	3.85
16+20+35+42+60	0.92	1.16	2.02	2.43	3.47	10.00 (2.3-11.5)	12.1	2660 (550-3540)	3.76	1.11	1.39	2.43	2.91	4.16	12.00 (3.4-14.5)	13.7	3120 (790-4280)	3.85
16+20+35+50+50	0.94	1.17	2.05	2.92	2.92	10.00 (2.3-11.5)	12.2	2680 (620-3490)	3.73	1.12	1.40	2.46	3.51	3.51	12.00 (3.4-14.5)	13.8	3160 (930-4290)	3.80
16+20+35+50+60	0.89	1.11	1.93	2.76	3.31	10.00 (2.3-11.5)	12.2	2680 (620-3490)	3.73	1.06	1.33	2.32	3.31	3.98	12.00 (3.4-14.5)	13.8	3160 (930-4290)	3.80
16+20+42+42+42	1.00	1.23	2.59	2.59	2.59	10.00 (2.3-11.5)	12.3	2700 (470-3590)	3.70	1.19	1.48	3.11	3.11	3.11	12.00 (3.4-14.5)	13.3	3040 (680-4260)	3.95
16+20+42+42+50	0.94	1.18	2.47	2.47	2.94	10.00 (2.3-11.5)	12.1	2660 (560-3540)	3.76	1.14	1.41	2.96	2.96	3.53	12.00 (3.4-14.5)	13.6	3110 (800-4270)	3.86
16+20+42+42+60	0.90	1.11	2.33	2.33	3.33	10.00 (2.3-11.5)	12.1	2660 (560-3540)	3.76	1.07	1.33	2.80	2.80	4.00	12.00 (3.4-14.5)	13.6	3110 (800-4270)	3.86
16+20+42+50+50	0.90	1.12	2.36	2.81	2.81	10.00 (2.3-11.5)	12.2	2680 (650-3490)	3.73	1.08	1.35	2.83	3.37	3.37	12.00 (3.4-14.5)	14.0	3200 (940-4290)	3.75
16+25+25+25+25	1.36	2.16	2.16	2.16	2.16	10.00 (2.3-11.5)	12.5	2750 (420-3740)	3.64	1.64	2.59	2.59	2.59	2.59	12.00 (3.4-14.5)	13.4	3070 (570-4330)	3.91
16+25+25+25+35	1.28	1.98	1.98	1.98	2.78	10.00 (2.3-11.5)	12.5	2750 (430-3660)	3.64	1.53	2.38	2.38	2.38	3.33	12.00 (3.4-14.5)	13.4	3050 (600-4300)	3.93
16+25+25+25+42	1.20	1.88	1.88	1.88	3.16	10.00 (2.3-11.5)	12.2	2690 (430-3660)	3.72	1.44	2.26	2.26	2.26	3.78	12.00 (3.4-14.5)	13.3	3040 (610-4290)	3.95
16+25+25+25+50	1.14	1.77	1.77	1.77	3.55	10.00 (2.3-11.5)	12.3	2710 (510-3530)	3.69	1.36	2.13	2.13	2.13	4.25	12.00 (3.4-14.5)	13.4	3060 (720-4220)	3.92
16+25+25+25+60	1.06	1.66	1.66	1.66	3.96	10.00 (2.3-11.5)	12.3	2710 (510-3530)	3.69	1.27	1.99	1.99	1.99	4.76	12.00 (3.4-14.5)	13.4	3060 (720-4220)	3.92
16+25+25+25+71	1.00	1.54	1.54	1.54	4.38	10.00 (2.3-11.5)	12.0	2650 (520-3530)	3.77	1.19	1.85	1.85	1.85	5.26	12.00 (3.4-14.5)	13.4	3050 (730-4270)	3.93
16+25+25+35+35	1.18	1.84	1.84	2.57	2.57	10.00 (2.3-11.5)	12.2	2690 (440-3660)	3.72	1.40	2.21	2.21	3.09	3.09	12.00 (3.4-14.5)	13.3	3030 (630-4270)	3.96
16+25+25+35+42	1.12	1.75	1.75	2.45	2.93	10.00 (2.3-11.5)	12.2	2690 (440-3670)	3.72	1.34	2.10	2.10	2.94	3.52	12.00 (3.4-14.5)	13.4	3070 (640-4260)	3.91
16+25+25+35+50	1.06	1.66	1.66	2.32	3.30	10.00 (2.3-11.5)	12.3	2710 (520-3530)	3.69	1.27	1.99	1.99	2.78	3.97	12.00 (3.4-14.5)	13.5	3090 (750-4250)	3.88
16+25+25+35+60	1.00	1.55	1.55	2.17	3.73	10.00 (2.3-11.5)	12.3	2710 (520-3530)	3.69	1.20	1.86	1.86	2.61	4.47	12.00 (3.4-14.5)	13.5	3090 (750-4250)	3.88
16+25+25+35+71	0.94	1.45	1.45	2.03	4.13	10.00 (2.3-11.5)	12.1	2660 (550-3540)	3.76	1.13	1.74	1.74	2.44	4.95	12.00 (3.4-14.5)	13.5	3080 (760-4240)	3.90
16+25+25+42+42	1.06	1.67	1.67	2.80	2.80	10.00 (2.3-11.5)	12.3	2700 (460-3670)	3.70	1.28	2.00	2.00	3.36	3.36	12.00 (3.4-14.5)	13.4	3060 (640-4250)	3.92
16+25+25+42+50	1.02	1.58	1.58	2.66	3.16	10.00 (2.3-11.5)	12.0	2650 (520-3530)	3.77	1.22	1.90	1.90	3.19	3.79	12.00 (3.4-14.5)	13.5	3090 (760-4250)	3.88
16+25+25+42+60	0.95	1.49	1.49	2.50	3.57	10.00 (2.3-11.5)	12.0	2650 (520-3530)	3.77	1.14	1.79	1.79	3.00	4.28	12.00 (3.4-14.5)	13.5	3090 (760-4250)	3.88
16+25+25+42+71	0.89	1.40	1.40	2.35	3.96	10.00 (2.3-11.5)	12.1	2660 (560-3540)	3.76	1.07	1.68	1.68	2.82	4.75	12.00 (3.4-14.5)	13.5	3080 (780-4230)	3.90
16+25+25+50+50	0.96	1.51	1.51	3.01	3.01	10.00 (2.3-11.5)	12.2	2680 (610-3480)	3.73	1.16	1.81	1.81	3.61	3.61	12.00 (3.4-14.5)	13.9	3170 (890-4260)	3.79
16+25+25+50+60	0.91	1.42	1.42	2.84	3.41	10.00 (2.3-11.5)	12.2	2680 (610-3480)	3.73	1.10	1.70	1.70	3.41	4.09	12.00 (3.4-14.5)	13.9	3170 (890-4260)	3.79
16+25+35+35+35	1.10	1.70	2.40	2.40	2.40	10.00 (2.3-11.5)	12.3	2700 (470-3590)	3.70	1.32	2.04	2.88	2.88	2.88	12.00 (3.4-14.5)	13.4	3060 (650-4240)	3.92
16+25+35+35+42	1.05	1.63	2.29	2.29	2.74	10.00 (2.3-11.5)	12.3	2700 (470-3590)	3.70	1.25	1.96	2.75	2.75	3.29	12.00 (3.4-14.5)	13.4	3050 (650-4280)	3.93
16+25+35+35+50	1.00	1.55	2.17	2.17	3.11	10.00 (2.3-11.5)	12.1	2660 (550-3540)	3.76	1.19	1.86	2.61	2.61	3.73	12.00 (3.4-14.5)	13.5	3080 (780-4230)	3.90
16+25+35+35+60	0.94	1.46	2.05	2.05	3.50	10.00 (2.3-11.5)	12.1	2660 (550-3540)	3.76	1.12	1.75	2.46	2.46	4.21	12.00 (3.4-14.5)	13.5	3080 (780-4230)	3.90
16+25+35+35+71	0.89	1.37	1.92	1.92	3.90	10.00 (2.3-11.5)	12.1	2660 (560-3540)	3.76	1.05	1.65	2.31	2.31	4.68	12.00 (3.4-14.5)	13.6	3110 (790-4270)	3.86
16+25+35+42+42	1.00	1.56	2.18	2.63	2.63	10.00 (2.3-11.5)	12.3	2700 (470-3590)	3.70	1.20	1.88	2.62	3.15	3.15	12.00 (3.4-14.5)	13.3	3040 (670-4270)	

CU-5Z100VBR: Free Multi Indoor Combination

Indoor Units Capacity	COOLING OPERATION									HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E				
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W
16+35+35+42+42	0.94	2.06	2.06	2.47	2.47	10.00 [2.3-11.5]	12.3	2700 [480-3600]	3.70	1.14	2.47	2.47	2.96	2.96	12.00 [3.4-14.5]	13.4	3070 [690-4250]	3.91
16+35+35+42+50	0.90	1.97	1.97	2.36	2.80	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.08	2.36	2.36	2.83	3.37	12.00 [3.4-14.5]	13.6	3110 [820-4250]	3.86
16+35+42+42+42	0.91	1.98	2.37	2.37	2.37	10.00 [2.3-11.5]	12.3	2700 [480-3600]	3.70	1.08	2.37	2.85	2.85	2.85	12.00 [3.4-14.5]	13.4	3070 [710-4240]	3.91
20+20+20+20+20	2.00	2.00	2.00	2.00	2.00	10.00 [2.3-11.5]	12.5	2750 [430-3740]	3.64	2.40	2.40	2.40	2.40	2.40	12.00 [3.4-14.5]	13.4	3060 [580-4320]	3.92
20+20+20+20+25	1.90	1.90	1.90	1.90	2.40	10.00 [2.3-11.5]	12.5	2750 [430-3740]	3.64	2.29	2.29	2.29	2.29	2.84	12.00 [3.4-14.5]	13.4	3060 [580-4320]	3.92
20+20+20+20+35	1.74	1.74	1.74	1.74	3.04	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	2.09	2.09	2.09	2.09	3.64	12.00 [3.4-14.5]	13.3	3040 [610-4290]	3.95
20+20+20+20+42	1.64	1.64	1.64	1.64	3.44	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	1.97	1.97	1.97	1.97	4.12	12.00 [3.4-14.5]	13.3	3030 [610-4280]	3.96
20+20+20+20+50	1.54	1.54	1.54	1.54	3.84	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.85	1.85	1.85	1.85	4.60	12.00 [3.4-14.5]	13.4	3060 [720-4270]	3.92
20+20+20+20+60	1.43	1.43	1.43	1.43	4.28	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.71	1.71	1.71	1.71	5.16	12.00 [3.4-14.5]	13.4	3060 [720-4270]	3.92
20+20+20+20+71	1.32	1.32	1.32	1.32	4.72	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.59	1.59	1.59	1.59	5.64	12.00 [3.4-14.5]	13.5	3090 [750-4260]	3.88
20+20+20+25+25	1.82	1.82	1.82	2.27	2.27	10.00 [2.3-11.5]	12.5	2750 [430-3740]	3.64	2.18	2.18	2.18	2.73	2.73	12.00 [3.4-14.5]	13.4	3060 [580-4320]	3.92
20+20+20+25+35	1.67	1.67	1.67	2.08	2.91	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	2.00	2.00	2.00	2.50	3.50	12.00 [3.4-14.5]	13.3	3040 [610-4290]	3.95
20+20+20+25+42	1.57	1.57	1.57	1.98	3.31	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	1.89	1.89	1.89	2.36	3.97	12.00 [3.4-14.5]	13.3	3030 [610-4280]	3.96
20+20+20+25+50	1.48	1.48	1.48	1.86	3.70	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.78	1.78	1.78	2.22	4.44	12.00 [3.4-14.5]	13.4	3060 [720-4270]	3.92
20+20+20+25+60	1.38	1.38	1.38	1.72	4.14	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.66	1.66	1.66	2.06	4.96	12.00 [3.4-14.5]	13.4	3060 [720-4270]	3.92
20+20+20+25+71	1.28	1.28	1.28	1.61	4.55	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.54	1.54	1.54	1.92	5.46	12.00 [3.4-14.5]	13.5	3090 [750-4260]	3.88
20+20+20+35+35	1.54	1.54	1.54	2.69	2.69	10.00 [2.3-11.5]	12.3	2700 [460-3670]	3.70	1.84	1.84	1.84	3.24	3.24	12.00 [3.4-14.5]	13.4	3070 [640-4260]	3.91
20+20+20+35+42	1.46	1.46	1.46	2.55	3.07	10.00 [2.3-11.5]	12.3	2700 [460-3670]	3.70	1.75	1.75	1.75	3.07	3.68	12.00 [3.4-14.5]	13.4	3060 [640-4250]	3.92
20+20+20+35+50	1.38	1.38	1.38	2.41	3.45	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.66	1.66	1.66	2.89	4.13	12.00 [3.4-14.5]	13.5	3090 [760-4250]	3.88
20+20+20+35+60	1.29	1.29	1.29	2.26	3.87	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.55	1.55	1.55	2.71	4.64	12.00 [3.4-14.5]	13.5	3090 [760-4250]	3.88
20+20+20+35+71	1.20	1.20	1.20	2.12	4.28	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.45	1.45	1.45	2.53	5.12	12.00 [3.4-14.5]	13.5	3080 [780-4230]	3.90
20+20+20+42+42	1.38	1.38	1.38	2.93	2.93	10.00 [2.3-11.5]	12.3	2700 [470-3670]	3.70	1.66	1.66	1.66	3.51	3.51	12.00 [3.4-14.5]	13.4	3060 [650-4230]	3.92
20+20+20+42+50	1.32	1.32	1.32	2.76	3.28	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.58	1.58	1.58	3.32	3.94	12.00 [3.4-14.5]	13.5	3080 [760-4240]	3.90
20+20+20+42+60	1.23	1.23	1.23	2.61	3.70	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.48	1.48	1.48	3.12	4.44	12.00 [3.4-14.5]	13.5	3080 [760-4240]	3.90
20+20+20+42+71	1.16	1.16	1.16	2.43	4.09	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.39	1.39	1.39	2.91	4.92	12.00 [3.4-14.5]	13.5	3080 [780-4280]	3.90
20+20+20+50+50	1.24	1.24	1.24	3.14	3.14	10.00 [2.3-11.5]	12.2	2680 [610-3480]	3.73	1.50	1.50	1.50	3.75	3.75	12.00 [3.4-14.5]	13.9	3170 [900-4310]	3.79
20+20+20+50+60	1.18	1.18	1.18	2.94	3.52	10.00 [2.3-11.5]	12.2	2680 [610-3480]	3.73	1.41	1.41	1.41	3.53	4.24	12.00 [3.4-14.5]	13.9	3170 [900-4310]	3.79
20+20+20+50+71	1.10	1.10	1.10	2.78	3.92	10.00 [2.3-11.5]	12.2	2690 [650-3490]	3.72	1.33	1.33	1.33	3.31	4.70	12.00 [3.4-14.5]	13.8	3160 [920-4300]	3.80
20+20+20+60+60	1.12	1.12	1.12	3.32	3.32	10.00 [2.3-11.5]	12.2	2680 [610-3480]	3.73	1.34	1.34	1.34	3.99	3.99	12.00 [3.4-14.5]	13.9	3170 [900-4310]	3.79
20+20+25+25+25	1.73	1.73	2.18	2.18	2.18	10.00 [2.3-11.5]	12.5	2750 [430-3740]	3.64	2.10	2.10	2.60	2.60	2.60	12.00 [3.4-14.5]	13.4	3060 [580-4320]	3.92
20+20+25+25+35	1.60	1.60	2.00	2.00	2.80	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	1.92	1.92	2.40	2.40	3.36	12.00 [3.4-14.5]	13.3	3040 [610-4290]	3.95
20+20+25+25+42	1.52	1.52	1.89	1.89	3.18	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	1.82	1.82	2.27	2.27	3.82	12.00 [3.4-14.5]	13.3	3030 [610-4280]	3.96
20+20+25+25+50	1.43	1.43	1.79	1.79	3.56	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.71	1.71	2.14	2.14	4.30	12.00 [3.4-14.5]	13.4	3060 [720-4270]	3.92
20+20+25+25+60	1.33	1.33	1.67	1.67	4.00	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.60	1.60	2.00	2.00	4.80	12.00 [3.4-14.5]	13.4	3060 [720-4270]	3.92
20+20+25+25+71	1.24	1.24	1.55	1.55	4.42	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.49	1.49	1.86	1.86	5.30	12.00 [3.4-14.5]	13.5	3090 [750-4260]	3.88
20+20+25+35+35	1.48	1.48	1.86	2.59	2.59	10.00 [2.3-11.5]	12.3	2700 [460-3670]	3.70	1.78	1.78	2.22	3.11	3.11	12.00 [3.4-14.5]	13.4	3070 [640-4260]	3.91
20+20+25+35+42	1.41	1.41	1.76	2.46	2.96	10.00 [2.3-11.5]	12.3	2700 [460-3670]	3.70	1.69	1.69	2.11	2.96	3.55	12.00 [3.4-14.5]	13.4	3060 [640-4250]	3.92
20+20+25+35+50	1.33	1.33	1.68	2.33	3.33	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.60	1.60	2.00	2.80	4.00	12.00 [3.4-14.5]	13.5	3090 [760-4250]	3.88
20+20+25+35+60	1.25	1.25	1.56	2.19	3.75	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.50	1.50	1.88	2.63	4.49	12.00 [3.4-14.5]	13.5	3090 [760-4250]	3.88
20+20+25+35+71	1.17	1.17	1.46	2.05	4.15	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.40	1.40	1.76	2.46	4.98	12.00 [3.4-14.5]	13.5	3080 [780-4230]	3.90
20+20+25+42+42	1.34	1.34	1.68	2.82	2.82	10.00 [2.3-11.5]	12.3	2700 [470-3670]	3.70	1.61	1.61	2.02	3.38	3.38	12.00 [3.4-14.5]	13.4	3060 [650-4230]	3.92
20+20+25+42+50	1.27	1.27	1.60	2.68	3.18	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.53	1.53	1.91	3.21	3.82	12.00 [3.4-14.5]	13.5	3080 [760-4240]	3.90
20+20+25+42+60	1.20	1.20	1.50	2.51	3.59	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.44	1.44	1.80	3.02	4.30	12.00 [3.4-14.5]	13.5	3080 [760-4240]	3.90
20+20+25+42+71	1.12	1.12	1.41	2.36	3.99	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.35	1.35	1.69	2.83	4.78	12.00 [3.4-14.5]	13.5	3080 [780-4280]	3.90
20+20+25+50+50	1.21	1.21	1.52	3.03	3.03	10.00 [2.3-11.5]	12.2	2680 [610-3480]	3.73	1.45	1.45	1.82	3.64	3.64	12.00 [3.4-14.5]	13.9	3170 [900-4310]	3.79
20+20+25+50+60	1.14	1.14	1.43	2.86	3.43	10.00 [2.3-11.5]	12.2	2680 [610-3480]	3.73	1.37	1.37	1.72	3.43	4.11	12.00 [3.4-14.5]	13.9	3170 [900-4310]	3.79
20+20+35+35+35	1.37	1.37	2.42	2.42	2.42	10.00 [2.3-11.5]	12.3	2700 [470-3590]	3.70	1.65	1.65	2.90	2.90	2.90	12.00 [3.4-14.5]	13.4	3050 [650-4280]	3.93
20+20+35+35+42	1.32	1.32	2.30	2.30	2.76	10.00 [2.3-11.5]	12.3	2700 [470-3590]	3.70	1.58	1.58	2.76	2.76	3.32	12.00 [3.4-14.5]	13.3	3040 [670-4270]	3.95
20+20+35+35+50	1.25	1.25	2.19	2.19	3.12	10.00 [2.3-11.5]	12.1	2660 [550-3540]	3.76	1.50	1.50	2.63	2.63	3.74	12.00 [3.4-14.5]	13.7	3120 [790-4280]	3.85
20+20+35+35+60	1.18	1.18	2.06	2.06	3.52	10.00 [2.3-11.5]	12.1	2660 [550-3540]	3.76	1.41	1.41	2.47	2.47	4.24	12.00 [3.4-14.5]	13.7	3120 [790-4280]	3.85
20+20+35+35+71	1.11	1.11	1.93	1.93	3.92	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.33	1.33	2.32	2.32	4.70	12.00 [3.4-14.5]	13.6	3110 [800-4260]	3.86
20+20+35+42+42	1.26	1.26	2.20	2.64	2.64	10.00 [2.3-11.5]	12.3	2700 [470-3600]	3.70	1.51	1.51	2.64	3.17	3.17	12.00 [3.4-14.5]	13.3	3040 [680-4260]	3.95
20+20+35+42+50	1.20	1.20	2.10	2.51	2.99	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.44	1.44	2.51	3.02	3.59	12.00 [3.4-14.5]	13.6	3110 [800-4270]	

CU-5Z100VBR: Free Multi Indoor Combination

Indoor Units Capacity	COOLING OPERATION										HEATING OPERATION								
	Cooling Capacity					Total	Running Current	Power Input	EER	Heating Capacity					Total	Running Current	Power Input	COP	
	Room A	Room B	Room C	Room D	Room E					Room A	Room B	Room C	Room D	Room E					
	kW	kW	kW	kW	kW	kW	A	W	W/W	kW	kW	kW	kW	kW	kW	A	W	W/W	
20+25+25+25+71	1.20	1.51	1.51	1.51	4.27	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.45	1.81	1.81	1.81	5.12	12.00 [3.4-14.5]	13.5	3090 [750-4260]	3.88	
20+25+25+35+35	1.42	1.79	1.79	2.50	2.50	10.00 [2.3-11.5]	12.3	2700 [460-3670]	3.70	1.72	2.14	2.14	3.00	3.00	12.00 [3.4-14.5]	13.4	3070 [640-4260]	3.91	
20+25+25+35+42	1.36	1.70	1.70	2.38	2.86	10.00 [2.3-11.5]	12.3	2700 [460-3670]	3.70	1.63	2.04	2.04	2.86	3.43	12.00 [3.4-14.5]	13.4	3060 [640-4250]	3.92	
20+25+25+35+50	1.29	1.61	1.61	2.26	3.23	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.55	1.94	1.94	2.71	3.86	12.00 [3.4-14.5]	13.5	3090 [760-4250]	3.88	
20+25+25+35+60	1.21	1.52	1.52	2.12	3.63	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.45	1.82	1.82	2.55	4.36	12.00 [3.4-14.5]	13.5	3090 [760-4250]	3.88	
20+25+25+35+71	1.14	1.42	1.42	1.99	4.03	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.37	1.70	1.70	2.39	4.84	12.00 [3.4-14.5]	13.5	3080 [780-4230]	3.90	
20+25+25+42+42	1.30	1.62	1.62	2.73	2.73	10.00 [2.3-11.5]	12.3	2700 [470-3670]	3.70	1.56	1.95	1.95	3.27	3.27	12.00 [3.4-14.5]	13.4	3060 [650-4230]	3.92	
20+25+25+42+50	1.24	1.54	1.54	2.59	3.09	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.49	1.85	1.85	3.11	3.70	12.00 [3.4-14.5]	13.5	3080 [760-4240]	3.90	
20+25+25+42+60	1.17	1.45	1.45	2.44	3.49	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.40	1.74	1.74	2.93	4.19	12.00 [3.4-14.5]	13.5	3080 [760-4240]	3.90	
20+25+25+42+71	1.09	1.37	1.37	2.30	3.87	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.31	1.64	1.64	2.75	4.66	12.00 [3.4-14.5]	13.5	3080 [780-4280]	3.90	
20+25+25+50+50	1.18	1.47	1.47	2.94	2.94	10.00 [2.3-11.5]	12.2	2680 [610-3480]	3.73	1.42	1.76	1.76	3.53	3.53	12.00 [3.4-14.5]	13.9	3170 [900-4310]	3.79	
20+25+25+50+60	1.11	1.39	1.39	2.78	3.33	10.00 [2.3-11.5]	12.2	2680 [610-3480]	3.73	1.33	1.67	1.67	3.33	4.00	12.00 [3.4-14.5]	13.9	3170 [900-4310]	3.79	
20+25+35+35+35	1.34	1.67	2.33	2.33	2.33	10.00 [2.3-11.5]	12.3	2700 [470-3590]	3.70	1.60	2.00	2.80	2.80	2.80	12.00 [3.4-14.5]	13.4	3050 [650-4280]	3.93	
20+25+35+35+42	1.27	1.59	2.23	2.23	2.68	10.00 [2.3-11.5]	12.3	2700 [470-3590]	3.70	1.53	1.91	2.68	2.68	3.20	12.00 [3.4-14.5]	13.3	3040 [670-4270]	3.95	
20+25+35+35+50	1.21	1.52	2.12	2.12	3.03	10.00 [2.3-11.5]	12.1	2660 [550-3540]	3.76	1.45	1.82	2.55	2.55	3.63	12.00 [3.4-14.5]	13.7	3120 [790-4280]	3.85	
20+25+35+35+60	1.14	1.43	2.00	2.00	3.43	10.00 [2.3-11.5]	12.1	2660 [550-3540]	3.76	1.38	1.71	2.40	2.40	4.11	12.00 [3.4-14.5]	13.7	3120 [790-4280]	3.85	
20+25+35+42+42	1.23	1.52	2.13	2.56	2.56	10.00 [2.3-11.5]	12.3	2700 [470-3600]	3.70	1.47	1.83	2.56	3.07	3.07	12.00 [3.4-14.5]	13.3	3040 [680-4260]	3.95	
20+25+35+42+50	1.17	1.45	2.03	2.44	2.91	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.40	1.74	2.44	2.93	3.49	12.00 [3.4-14.5]	13.6	3110 [800-4270]	3.86	
20+25+35+42+60	1.10	1.37	1.92	2.31	3.30	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.32	1.65	2.31	2.77	3.95	12.00 [3.4-14.5]	13.6	3110 [800-4270]	3.86	
20+25+35+50+50	1.11	1.39	1.94	2.78	2.78	10.00 [2.3-11.5]	12.2	2690 [650-3490]	3.72	1.34	1.67	2.33	3.33	3.33	12.00 [3.4-14.5]	14.0	3200 [940-4290]	3.75	
20+25+42+42+42	1.17	1.45	2.46	2.46	2.46	10.00 [2.3-11.5]	12.3	2700 [470-3600]	3.70	1.40	1.75	2.95	2.95	2.95	12.00 [3.4-14.5]	13.5	3080 [680-4250]	3.90	
20+25+42+42+50	1.12	1.40	2.35	2.35	2.78	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.34	1.68	2.82	2.82	3.34	12.00 [3.4-14.5]	13.6	3110 [810-4260]	3.86	
20+35+35+35+35	1.24	2.19	2.19	2.19	2.19	10.00 [2.3-11.5]	12.3	2700 [470-3600]	3.70	1.48	2.63	2.63	2.63	2.63	12.00 [3.4-14.5]	13.5	3080 [680-4260]	3.90	
20+35+35+35+42	1.20	2.10	2.10	2.10	2.50	10.00 [2.3-11.5]	12.3	2700 [480-3600]	3.70	1.45	2.51	2.51	2.51	3.02	12.00 [3.4-14.5]	13.4	3070 [690-4250]	3.91	
20+35+35+35+50	1.14	2.00	2.00	2.00	2.86	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.37	2.40	2.40	2.40	3.43	12.00 [3.4-14.5]	13.6	3110 [820-4250]	3.86	
20+35+35+42+42	1.16	2.01	2.01	2.41	2.41	10.00 [2.3-11.5]	12.3	2700 [480-3600]	3.70	1.38	2.41	2.41	2.90	2.90	12.00 [3.4-14.5]	13.4	3070 [710-4240]	3.91	
20+35+35+42+50	1.10	1.92	1.92	2.31	2.75	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.32	2.31	2.31	2.77	3.29	12.00 [3.4-14.5]	13.6	3100 [830-4240]	3.87	
20+35+42+42+42	1.11	1.93	2.32	2.32	2.32	10.00 [2.3-11.5]	12.3	2700 [480-3600]	3.70	1.34	2.32	2.78	2.78	2.78	12.00 [3.4-14.5]	13.4	3060 [710-4230]	3.92	
25+25+25+25+25	2.00	2.00	2.00	2.00	2.00	10.00 [2.3-11.5]	12.5	2750 [430-3740]	3.64	2.40	2.40	2.40	2.40	2.40	12.00 [3.4-14.5]	13.4	3060 [580-4320]	3.92	
25+25+25+25+35	1.85	1.85	1.85	1.85	2.60	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	2.22	2.22	2.22	2.22	3.12	12.00 [3.4-14.5]	13.3	3040 [610-4290]	3.95	
25+25+25+25+42	1.76	1.76	1.76	1.76	2.96	10.00 [2.3-11.5]	12.2	2690 [430-3660]	3.72	2.11	2.11	2.11	2.11	3.56	12.00 [3.4-14.5]	13.3	3030 [610-4280]	3.96	
25+25+25+25+50	1.67	1.67	1.67	1.67	3.32	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	2.00	2.00	2.00	2.00	4.00	12.00 [3.4-14.5]	13.4	3060 [720-4270]	3.92	
25+25+25+25+60	1.56	1.56	1.56	1.56	3.76	10.00 [2.3-11.5]	12.3	2710 [510-3530]	3.69	1.88	1.88	1.88	1.88	4.48	12.00 [3.4-14.5]	13.4	3060 [720-4270]	3.92	
25+25+25+25+71	1.46	1.46	1.46	1.46	4.16	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.75	1.75	1.75	1.75	5.00	12.00 [3.4-14.5]	13.5	3090 [750-4260]	3.88	
25+25+25+35+35	1.72	1.72	1.72	2.42	2.42	10.00 [2.3-11.5]	12.3	2700 [460-3670]	3.70	2.06	2.06	2.06	2.91	2.91	12.00 [3.4-14.5]	13.4	3070 [640-4260]	3.91	
25+25+25+35+42	1.64	1.64	1.64	2.31	2.77	10.00 [2.3-11.5]	12.3	2700 [460-3670]	3.70	1.97	1.97	1.97	2.77	3.32	12.00 [3.4-14.5]	13.4	3060 [640-4250]	3.92	
25+25+25+35+50	1.56	1.56	1.56	2.19	3.13	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.88	1.88	1.88	2.62	3.74	12.00 [3.4-14.5]	13.5	3090 [760-4250]	3.88	
25+25+25+35+60	1.47	1.47	1.47	2.06	3.53	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.76	1.76	1.76	2.48	4.24	12.00 [3.4-14.5]	13.5	3090 [760-4250]	3.88	
25+25+25+35+71	1.38	1.38	1.38	1.93	3.93	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.66	1.66	1.66	2.32	4.70	12.00 [3.4-14.5]	13.5	3080 [780-4230]	3.90	
25+25+25+42+42	1.58	1.58	1.58	2.63	2.63	10.00 [2.3-11.5]	12.3	2700 [470-3670]	3.70	1.88	1.88	1.88	3.18	3.18	12.00 [3.4-14.5]	13.4	3060 [650-4230]	3.92	
25+25+25+42+50	1.50	1.50	1.50	2.51	2.99	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.80	1.80	1.80	3.02	3.58	12.00 [3.4-14.5]	13.5	3080 [760-4240]	3.90	
25+25+25+42+60	1.41	1.41	1.41	2.38	3.39	10.00 [2.3-11.5]	12.0	2650 [520-3530]	3.77	1.69	1.69	1.69	2.86	4.07	12.00 [3.4-14.5]	13.5	3080 [760-4240]	3.90	
25+25+25+50+50	1.42	1.42	1.42	2.87	2.87	10.00 [2.3-11.5]	12.2	2680 [610-3480]	3.73	1.72	1.72	1.72	3.42	3.42	12.00 [3.4-14.5]	13.9	3170 [900-4310]	3.79	
25+25+35+35+35	1.61	1.61	2.26	2.26	2.26	10.00 [2.3-11.5]	12.3	2700 [470-3590]	3.70	1.95	1.95	2.70	2.70	2.70	12.00 [3.4-14.5]	13.4	3050 [650-4280]	3.93	
25+25+35+35+42	1.54	1.54	2.16	2.16	2.60	10.00 [2.3-11.5]	12.3	2700 [470-3590]	3.70	1.85	1.85	2.59	2.59	3.12	12.00 [3.4-14.5]	13.3	3040 [670-4270]	3.95	
25+25+35+35+50	1.47	1.47	2.06	2.06	2.94	10.00 [2.3-11.5]	12.1	2660 [550-3540]	3.76	1.76	1.76	2.47	2.47	3.54	12.00 [3.4-14.5]	13.7	3120 [790-4280]	3.85	
25+25+35+35+60	1.39	1.39	1.94	1.94	3.34	10.00 [2.3-11.5]	12.1	2660 [550-3540]	3.76	1.67	1.67	2.33	2.33	4.00	12.00 [3.4-14.5]	13.7	3120 [790-4280]	3.85	
25+25+35+42+42	1.48	1.48	2.06	2.49	2.49	10.00 [2.3-11.5]	12.3	2700 [470-3600]	3.70	1.78	1.78	2.48	2.98	3.98	12.00 [3.4-14.5]	13.3	3040 [680-4260]	3.95	
25+25+35+42+50	1.41	1.41	1.99	2.37	2.82	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.69	1.69	2.37	2.85	3.40	12.00 [3.4-14.5]	13.6	3110 [800-4270]	3.86	
25+25+42+42+42	1.43	1.43	2.38	2.38	2.38	10.00 [2.3-11.5]	12.3	2700 [470-3600]	3.70	1.71	1.71	2.86	2.86	2.86	12.00 [3.4-14.5]	13.5	3080 [680-4250]	3.90	
25+35+35+35+35	1.52	2.12	2.12	2.12	2.12	10.00 [2.3-11.5]	12.3	2700 [470-3600]	3.70	1.80	2.55	2.55	2.55	2.55	12.00 [3.4-14.5]	13.5	3080 [680-4260]	3.90	
25+35+35+35+42	1.46	2.03	2.03	2.03	2.45	10.00 [2.3-11.5]	12.3	2700 [480-3600]	3.70	1.75	2.44	2.44	2.44	2.93	12.00 [3.4-14.5]	13.4	3070 [690-4250]	3.91	
25+35+35+35+50	1.40	1.94	1.94	1.94	2.78	10.00 [2.3-11.5]	12.1	2660 [560-3540]	3.76	1.68	2.33	2.33	2.33	3.33	12.00 [3.4-14.5]	13.6	3110 [820-4250]		